

Computer Systems Fundamentals

[integer_types.c](#)

Print size and min and max values of integer types

```
#include <stdio.h>
#include <limits.h>

int main(void) {

    char c;
    printf("char          %lu bytes min=%20d, max=%20d\n", sizeof c, CHAR_MIN, CHAR_MAX);
    signed char sc;
    printf("signed char      %lu bytes min=%20d, max=%20d\n", sizeof sc, SCHAR_MIN, SCHAR_MAX);
    unsigned char uc;
    printf("unsigned char    %lu bytes min=%20d, max=%20d\n", sizeof uc, 0, UCHAR_MAX);

    short s;
    printf("short           %lu bytes min=%20d, max=%20d\n", sizeof s, SHRT_MIN, SHRT_MAX);
    unsigned short us;
    printf("unsigned short  %lu bytes min=%20d, max=%20d\n", sizeof us, 0, USHRT_MAX);

    int i;
    printf("int             %lu bytes min=%20d, max=%20d\n", sizeof i, INT_MIN, INT_MAX);
    unsigned int ui;
    printf("unsigned int    %lu bytes min=%20d, max=%20d\n", sizeof ui, 0, UINT_MAX);

    long l;
    printf("long            %lu bytes min=%20ld, max=%20ld\n", sizeof l, LONG_MIN, LONG_MAX);
    unsigned long ul;
    printf("unsigned long   %lu bytes min=%20d, max=%20lu\n", sizeof ul, 0, ULONG_MAX);

    long long ll;
    printf("long long       %lu bytes min=%20lld, max=%20lld\n", sizeof ll, LLONG_MIN, LLONG_MAX);
    unsigned long long ull;
    printf("unsigned long long %lu bytes min=%20d, max=%20llu\n", sizeof ull, 0, ULLONG_MAX);

    return 0;
}
```

[stdint.c](#)

example declarations of the most commonly used fixed width integer types found in stdint.h

```
#include <stdint.h>

int main(void) {

    // range of values for type
    //          minimum          maximum
    int8_t  i1; //          -128          127
    uint8_t i2; //           0          255
    int16_t i3; //        -32768         32767
    uint16_t i4; //           0         65535
    int32_t i5; //    -2147483648     2147483647
    uint32_t i6; //           0     4294967295
    int64_t i7; // -9223372036854775808  9223372036854775807
    uint64_t i8; //           0 18446744073709551615

    return 0;
}
```

[char_bug.c](#)

```

#include <stdio.h>

int main(void){
    // common C bug.
    //
    // char may be signed (e.g. x86) or unsigned (powerpc).
    //
    // if char is signed (-128..127).
    // loop will incorrect exit for a byte containing 0xFF
    //
    // if char is unsigned (0..255).
    // loop will never exit
    //
    // fix bug by making c int
    //

    char c;
    while ((c = getchar()) != EOF){
        putchar(c);
    }.

    return 0;
}

```

[print bits.h](#)

```

// header file so we use print bits in several examples
#ifndef PRINT_BITS_H

#include <stdint.h>
void print_bits(uint64_t value, int how_many_bits);

#endif

```

[print bits.c](#)

two useful functions that we will use in a number of following programs

```

#include <stdio.h>
#include <stdint.h>

#include "print_bits.h"

// extract the nth bit from a value
int get_nth_bit(uint64_t value, int n) {
    // shift the bit right n bits
    // this leaves the n-th bit as the least significant bit
    uint64_t shifted_value = value >> n;

    // zero all bits except the the least significant bit
    int bit = shifted_value & 1;

    return bit;
}

// print the bottom how_many_bits bits of value
void print_bits(uint64_t value, int how_many_bits) {
    // print bits from most significant to least significant

    for (int i = how_many_bits - 1; i >= 0; i--) {
        int bit = get_nth_bit(value, i);
        printf("%d", bit);
    }
}

```

[print bits of int.c](#)

print the bits of an int, for example:

[illegible]

```
#include <stdio.h>  
#include <stdint.h>  
#include "print_bits.h"  
  
int main(void){  
  
    int a = 0;  
    printf("Enter an int: ");  
    scanf("%d", &a);  
  
    // sizeof returns number of bytes, a byte has 8 bits  
    int n_bits = 8 * sizeof a;  
  
    print_bits(a, n_bits);  
    printf("\n");  
  
    return 0;  
}
```

[eight bit twos complement.c](#)

print the twos-complement representation of 8 bit signed integers essentially all modern machines represent integers in

```
$ gcc eight_bit_twos_complement.c print_bits.c -o eight_bit_twos_complement
$ ./eight_bit_twos_complement
-128 10000000
-127 10000001
-126 10000010
-125 10000011
-124 10000100
-123 10000101
-122 10000110
-121 10000111
-120 10001000
-119 10001001
-118 10001010
-117 10001011
-116 10001100
-115 10001101
-114 10001110
-113 10001111
-112 10010000
-111 10010001
-110 10010010
-109 10010011
-108 10010100
-107 10010101
-106 10010110
-105 10010111
-104 10011000
-103 10011001
-102 10011010
-101 10011011
-100 10011100
-99 10011101
-98 10011110
-97 10011111
-96 10100000
-95 10100001
-94 10100010
-93 10100011
-92 10100100
-91 10100101
-90 10100110
-89 10100111
-88 10101000
-87 10101001
-86 10101010
-85 10101011
-84 10101100
-83 10101101
-82 10101110
-81 10101111
-80 10110000
-79 10110001
-78 10110010
-77 10110011
-76 10110100
-75 10110101
-74 10110110
-73 10110111
-72 10111000
-71 10111001
-70 10111010
-69 10111011
-68 10111100
-67 10111101
-66 10111110
-65 10111111
-64 11000000
-63 11000001
-62 11000010
-61 11000011
-60 11000100
```

<u>-59</u>	<u>11000101</u>
<u>-58</u>	<u>11000110</u>
<u>-57</u>	<u>11000111</u>
<u>-56</u>	<u>11001000</u>
<u>-55</u>	<u>11001001</u>
<u>-54</u>	<u>11001010</u>
<u>-53</u>	<u>11001011</u>
<u>-52</u>	<u>11001100</u>
<u>-51</u>	<u>11001101</u>
<u>-50</u>	<u>11001110</u>
<u>-49</u>	<u>11001111</u>
<u>-48</u>	<u>11010000</u>
<u>-47</u>	<u>11010001</u>
<u>-46</u>	<u>11010010</u>
<u>-45</u>	<u>11010011</u>
<u>-44</u>	<u>11010100</u>
<u>-43</u>	<u>11010101</u>
<u>-42</u>	<u>11010110</u>
<u>-41</u>	<u>11010111</u>
<u>-40</u>	<u>11011000</u>
<u>-39</u>	<u>11011001</u>
<u>-38</u>	<u>11011010</u>
<u>-37</u>	<u>11011011</u>
<u>-36</u>	<u>11011100</u>
<u>-35</u>	<u>11011101</u>
<u>-34</u>	<u>11011110</u>
<u>-33</u>	<u>11011111</u>
<u>-32</u>	<u>11100000</u>
<u>-31</u>	<u>11100001</u>
<u>-30</u>	<u>11100010</u>
<u>-29</u>	<u>11100011</u>
<u>-28</u>	<u>11100100</u>
<u>-27</u>	<u>11100101</u>
<u>-26</u>	<u>11100110</u>
<u>-25</u>	<u>11100111</u>
<u>-24</u>	<u>11101000</u>
<u>-23</u>	<u>11101001</u>
<u>-22</u>	<u>11101010</u>
<u>-21</u>	<u>11101011</u>
<u>-20</u>	<u>11101100</u>
<u>-19</u>	<u>11101101</u>
<u>-18</u>	<u>11101110</u>
<u>-17</u>	<u>11101111</u>
<u>-16</u>	<u>11110000</u>
<u>-15</u>	<u>11110001</u>
<u>-14</u>	<u>11110010</u>
<u>-13</u>	<u>11110011</u>
<u>-12</u>	<u>11110100</u>
<u>-11</u>	<u>11110101</u>
<u>-10</u>	<u>11110110</u>
<u>-9</u>	<u>11110111</u>
<u>-8</u>	<u>11111000</u>
<u>-7</u>	<u>11111001</u>
<u>-6</u>	<u>11111010</u>
<u>-5</u>	<u>11111011</u>
<u>-4</u>	<u>11111100</u>
<u>-3</u>	<u>11111101</u>
<u>-2</u>	<u>11111110</u>
<u>-1</u>	<u>11111111</u>
<u>0</u>	<u>00000000</u>
<u>1</u>	<u>00000001</u>
<u>2</u>	<u>00000010</u>
<u>3</u>	<u>00000011</u>
<u>4</u>	<u>00000100</u>
<u>5</u>	<u>00000101</u>
<u>6</u>	<u>00000110</u>
<u>7</u>	<u>00000111</u>
<u>8</u>	<u>00001000</u>
<u>9</u>	<u>00001001</u>
<u>10</u>	<u>00001010</u>
<u>11</u>	<u>00001011</u>

<u>12</u>	<u>00001100</u>
<u>13</u>	<u>00001101</u>
<u>14</u>	<u>00001110</u>
<u>15</u>	<u>00001111</u>
<u>16</u>	<u>00010000</u>
<u>17</u>	<u>00010001</u>
<u>18</u>	<u>00010010</u>
<u>19</u>	<u>00010011</u>
<u>20</u>	<u>00010100</u>
<u>21</u>	<u>00010101</u>
<u>22</u>	<u>00010110</u>
<u>23</u>	<u>00010111</u>
<u>24</u>	<u>00011000</u>
<u>25</u>	<u>00011001</u>
<u>26</u>	<u>00011010</u>
<u>27</u>	<u>00011011</u>
<u>28</u>	<u>00011100</u>
<u>29</u>	<u>00011101</u>
<u>30</u>	<u>00011110</u>
<u>31</u>	<u>00011111</u>
<u>32</u>	<u>00100000</u>
<u>33</u>	<u>00100001</u>
<u>34</u>	<u>00100010</u>
<u>35</u>	<u>00100011</u>
<u>36</u>	<u>00100100</u>
<u>37</u>	<u>00100101</u>
<u>38</u>	<u>00100110</u>
<u>39</u>	<u>00100111</u>
<u>40</u>	<u>00101000</u>
<u>41</u>	<u>00101001</u>
<u>42</u>	<u>00101010</u>
<u>43</u>	<u>00101011</u>
<u>44</u>	<u>00101100</u>
<u>45</u>	<u>00101101</u>
<u>46</u>	<u>00101110</u>
<u>47</u>	<u>00101111</u>
<u>48</u>	<u>00110000</u>
<u>49</u>	<u>00110001</u>
<u>50</u>	<u>00110010</u>
<u>51</u>	<u>00110011</u>
<u>52</u>	<u>00110100</u>
<u>53</u>	<u>00110101</u>
<u>54</u>	<u>00110110</u>
<u>55</u>	<u>00110111</u>
<u>56</u>	<u>00111000</u>
<u>57</u>	<u>00111001</u>
<u>58</u>	<u>00111010</u>
<u>59</u>	<u>00111011</u>
<u>60</u>	<u>00111100</u>
<u>61</u>	<u>00111101</u>
<u>62</u>	<u>00111110</u>
<u>63</u>	<u>00111111</u>
<u>64</u>	<u>01000000</u>
<u>65</u>	<u>01000001</u>
<u>66</u>	<u>01000010</u>
<u>67</u>	<u>01000011</u>
<u>68</u>	<u>01000100</u>
<u>69</u>	<u>01000101</u>
<u>70</u>	<u>01000110</u>
<u>71</u>	<u>01000111</u>
<u>72</u>	<u>01001000</u>
<u>73</u>	<u>01001001</u>
<u>74</u>	<u>01001010</u>
<u>75</u>	<u>01001011</u>
<u>76</u>	<u>01001100</u>
<u>77</u>	<u>01001101</u>
<u>78</u>	<u>01001110</u>
<u>79</u>	<u>01001111</u>
<u>80</u>	<u>01010000</u>
<u>81</u>	<u>01010001</u>
<u>82</u>	<u>01010010</u>

```

83 01010011
84 01010100
85 01010101
86 01010110
87 01010111
88 01011000
89 01011001
90 01011010
91 01011011
92 01011100
93 01011101
94 01011110
95 01011111
96 01100000
97 01100001
98 01100010
99 01100011
100 01100100
101 01100101
102 01100110
103 01100111
104 01101000
105 01101001
106 01101010
107 01101011
108 01101100
109 01101101
110 01101110
111 01101111
112 01110000
113 01110001
114 01110010
115 01110011
116 01110100
117 01110101
118 01110110
119 01110111
120 01111000
121 01111001
122 01111010
123 01111011
124 01111100
125 01111101
126 01111110
127 01111111
$

```

```

#include <stdio.h>
#include <stdint.h>
#include "print_bits.h"

int main(void) {
    for (int i = -128; i < 128; i++) {
        printf("%4d ", i);
        print_bits(i, 8);
        printf("\n");
    }

    return 0;
}

```

COMP1521 20T2: Computer Systems Fundamentals is brought to you by
the [School of Computer Science and Engineering](#)
at the [University of New South Wales](#), Sydney.

For all enquiries, please email the class account at cs1521@cse.unsw.edu.au

