

# 2-3-4 Trees

---

- Search Cost
- 2-3-4 Trees
- Node splitting
- Data Structure
- Search Cost Analysis
- Insertion into 2-3-4 Trees
- 2-3-4 Variations

## ❖ Search Cost

---

Critical factor determining search cost in BSTs

- worst case: length of longest path
- average case: < average path length (not all searches end at leaves)

Either way, path length (tree depth) is a critical factor

In a perfectly balanced tree, max path length =  $\log_2 n$

The 2 in the path length is the branching factor (*binary* search tree)


What if branching factor > 2?

- $\log_2 4096 = 12$ ,  $\log_4 4096 = 6$ ,  $\log_8 4096 = 4$

## ❖ 2-3-4 Trees


2-3-4 trees have three kinds of nodes

- 2-nodes, with two children (same as normal BSTs)
- 3-nodes, two values and three children
- 4-nodes, three values and four children



## ❖ ... 2-3-4 Trees

2-3-4 trees are ordered similarly to BSTs



In a **balanced 2-3-4 tree**:


- all leaves are at same distance from the root

2-3-4 trees grow "upwards" from the leaves, via **node splitting**.

## ❖ Node splitting

Insertion into a full node causes a split


- middle value propagated to parent node
- values in original node split across original node and new node



COMP2521 20T2 ♦ 2-3-4 Trees [4/16]

## ❖ ... Node splitting

Intermediate stage of insert-split:



## ❖ ... Node splitting

Searching in 2-3-4 trees:

**Search(tree,item):**

**Input** tree, item

**Output** address of item if found in 2-3-4 tree  
NULL otherwise

**if** tree is empty **then**  
    **return** NULL

**else**

    scan tree.data to find i such that

$\text{tree.data}[i-1] < \text{item} \leq \text{tree.data}[i]$

**if** item=tree.data[i] **then**     // item found

**return** address of tree.data[i]

**else**             // keep looking in relevant subtree

**return** Search(tree.child[i],item)


**end if**

**end if**

## ❖ Data Structure

Possible concrete 2-3-4 tree data structure:

```
typedef struct node {  
    int          order;      // 2, 3 or 4  
    int          data[3];    // items in node  
    struct node *child[4];   // links to subtrees  
} node;
```





COMP2521 20T2 ♦ 2-3-4 Trees [7/16]



## ❖ ... Data Structure

Finding which branch to follow

```
// n is a pointer to a (struct node)
int i;
for (i = 0; i < n->order-1; i++) {
    if (item <= n->data[i]) break;
}
// go to the ith subtree, unless item == n->data[i]
```



COMP2521 20T2 ♦ 2-3-4 Trees [8/16]

## ❖ Search Cost Analysis

---

2-3-4 tree searching cost analysis:

- as for other trees, worst case determined by height  $h$
- 2-3-4 trees are always balanced  $\Rightarrow$  height is  $O(\log n)$
- worst case for height: all nodes are 2-nodes  
(same case as for balanced BSTs, i.e.  $h \cong \log_2 n$ )
- best case for height: all nodes are 4-nodes  
(balanced tree with branching factor 4, i.e.  $h \cong \log_4 n$ )

## ❖ Insertion into 2-3-4 Trees



---

Insertion algorithm:


- find leaf node where Item belongs (via search)
- if not full (i.e. order  $< 4$ )
  - insert Item in this node, order++
- if node is full (i.e. contains 3 items)
  - split into two 2-nodes as leaves
  - promote middle element to parent
  - insert item into appropriate leaf 2-node
  - if parent is a 4-node
    - continue split/promote upwards
  - if promote to root, and root is a 4-node
    - split root node and add new root

## ❖ ... Insertion into 2-3-4 Trees

Insertion into a 2-node or 3-node:




Insertion into a 4-node (requires a split):



## ❖ ... Insertion into 2-3-4 Trees


Splitting the root:



COMP2521 20T2 ♦ 2-3-4 Trees [12/16]

## ❖ ... Insertion into 2-3-4 Trees

Building a 2-3-4 tree ... 7 insertions:



COMP2521 20T2 ♦ 2-3-4 Trees [13/16]

## ❖ ... Insertion into 2-3-4 Trees

Insertion algorithm:

```

insert(tree,item):
    Input  2-3-4 tree, item
    Output tree with item inserted

    if tree is empty then
        return new node containing item
    end if
    node=Search(tree,item)
    parent=parent of node
    if node.order < 4 then
        insert item into node
        increment node.order
    else
        promote = node.data[1]      // middle value
        nodeL    = new node containing data[0]
        nodeR    = new node containing data[2]
        delete node
        if item < promote then
            insert(nodeL,item)
        else
            insert(nodeR,item)
        end if
        insert(parent,promote)
        while parent.order=4 do
            continue promote/split upwards
        end while
        if parent is root ^ parent.order=4 then
            split root, making new root
        end if
    end if
end if

```

## ❖ ... Insertion into 2-3-4 Trees

---

Insertion cost (remembering that 2-3-4 trees are balanced  $\Rightarrow h = \log_4 n$ )

- search for leaf node in which to insert =  $O(\log n)$
- if node not full, insert item into node =  $O(1)$
- if node full, promote middle, create two new nodes =  $O(1)$
- if promotion propagates ...
  - best case: update parent =  $O(1)$
  - worst case: propagate to root =  $O(\log n)$

Overall insertion cost =  $O(\log n)$



## ❖ 2-3-4 Variations

---

Variations on 2-3-4 trees ...

Variation #1: why stop at 4? why not 2-3-4-5 trees? or  $M$ -way trees?

- allow nodes to hold between  $M/2$  and  $M-1$  items
- if each node is a disk-page, then we have a **B-tree** (databases)
- for B-trees, depending on **Item** size,  $M > 100/200/400$

Variation #2: don't have "variable-sized" nodes

- use standard BST nodes, augmented with one extra piece of data
- implement similar strategy as 2-3-4 trees → red-black trees.

Produced: 17 Jun 2020