

# Teach Language Models to Reason

Denny Zhou

Google DeepMind

June, 2023

# What do you expect from AI?

- Self-driving cars?
- Digital assistant?
- Solving hardest math problems?
- Superintelligence?

...



## **My *little* expectation on AI**

AI should be able to learn a new task from few examples, like what humans do

# Does machine learning meet this expectation?

- Semi-supervised learning
- Transfer learning
- Metalearning
- Active learning
- Manifold learning
- Sparsity and low rank
- Bayesian learning
- Kernel machines
- ...



What is missing in machine learning?

What is missing in machine learning?

# Reasoning

Humans can learn from a few examples because humans can reason

We have found a simple way to solve reasoning:

**Teach language models to  
reason, like teaching kids**


Let's start from a toy problem

# A toy machine learning problem: last-letter-concatenation

| <b>Input</b> | <b>Output</b> |
|--------------|---------------|
| “Elon Musk”  | “nk”          |
| “Bill Gates” | “ls”          |

**Rule:** Take the last letter of each word, and then concatenate them


# Solve it by machine learning? Tons of labels are needed



How to solve this problem with LLMs?

# What are Large Language Models (LLMs)?

LLM is a “transformer” model trained to predict the next word



Trained with many sentences, e.g. all texts from the Internet

You can think of training an LLM as training a parrot to mimic human languages



Q: “Elon Musk”

A: “nk”

Q: “Bill Gates”


A: “ls”

Q: “Barack Obama”

A:

Input

Few-shot prompting



# Playground

Load a preset...

Save

View code

Share

...

Q: "Elon Musk"

A: "nk"

Q: "Bill Gates"

A: "Is"

Q: "Barack Obama"

A: "ma"



Complete

Model

text-davinci-003

Temperature 0



Maximum length 256



Stop sequences

Enter sequence and press Tab



Top P 1



Frequency penalty 0



Presence penalty 0



Submit



54

Load a preset...



Save

View code

Share

...

Q: "Elon Musk"



A: "nk"

Q: "Bill Gates"

A: "Is"

Q: "Barack Obama"

A: "ma"

How about adding more examples?

Submit



Load a preset...



Save

View code

Share

...

Complete



Model

text-davinci-003



Temperature

0



Maximum length

256



Stop sequences

Enter sequence and press Tab



Top P

1




Frequency penalty

0



Presence penalty

0



54

# Playground

Load a preset...

Save

View code

Share

...

Q: "Elon Musk"

A: "nk"



Q: "Bill Gates"

A: "ls"

Q: "Steve Jobs"

A: "es"

Q: "Larry Page"

A: "ye"

Q: "Jeff Bezos"

A: "fs"

Q: "Barack Obama"

A: "ma"



Submit



Load a preset...

Save

View code

Share

...

Complete

Model

text-davinci-003

Temperature 0



Maximum length 256



Stop sequences

Enter sequence and press Tab



Top P 1



Frequency penalty 0



Presence penalty 0



94

# Why we created the last-letter-concatenation task?

- Make machine learning fail
- Make few-shot prompting fail
- Trivial for humans

# Chain-of-thought (CoT) prompting

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. [Chain-of-thought prompting elicits reasoning in large language models](#). NeurIPS 2022.

# CoT: Adding “thought” before “answer”

Q: “Elon Musk”

A: the last letter of "Elon" is "n". the last letter of "Musk" is "k". Concatenating "n", "k" leads to "nk". so the output is "nk".

Q: “Bill Gates”

A: the last letter of "Bill" is "l". the last letter of "Gates" is "s". Concatenating "l", "s" leads to "ls". so the output is "ls".

Q: “Barack Obama”

A:

# CoT: Adding “thought” before “answer”

Q: “Elon Musk”

A: the last letter of "Elon" is "n". the last letter of "Musk" is "k". Concatenating "n", "k" leads to "nk". so the output is "nk".

Q: “Bill Gates”

A: the last letter of "Bill" is "l". the last letter of "Gates" is "s". Concatenating "l", "s" leads to "ls". so the output is "ls".

Q: “Barack Obama”

A: the last letter of "Barack" is "k". the last letter of "Obama" is "a". Concatenating "k", "a" leads to "ka". so the output is "ka".

# One demonstration is enough, as humans

Q: "Elon Musk"

A: the last letter of "Elon" is "n". the last letter of "Musk" is "k". Concatenating "n", "k" leads to "nk". so the output is "nk".

Q: "Barack Obama"

A: the last letter of "Barack" is "k". the last letter of "Obama" is "a". Concatenating "k", "a" leads to "ka". so the output is "ka".

Brown et al. Language Models are  
Few-Shot Learners. **2020**

### **Standard few-shot prompting**

<input, output>

Wei et al. Chain-of-thought prompting elicits  
reasoning in large language models. **2022**

### **Chain-of-thought prompting**

<input, **rationale**, output>



# Chain-of-Thought Prompting

Google I/O 2022

---

PaLM: Scaling Language Modeling with Pathways

Ashishka Chawla<sup>\*</sup> Sharad Narang<sup>\*</sup> Jacob Devlin<sup>\*</sup>  
Maitin Bonn<sup>#</sup> Gaurav Mishra<sup>#</sup> Adam Roberts<sup>#</sup> Paul Barham<sup>#</sup>  
Hyung Won Chung<sup>#</sup> Charles Sutton<sup>#</sup> Sebastian Gehrmann<sup>#</sup> Parker Schuh<sup>#</sup> Kensen Shi<sup>#</sup>  
Sasha Tsvyshchenko<sup>#</sup> Joshua Maynes<sup>#</sup> Abhishek Rao<sup>#</sup> Parker Barnes<sup>#</sup> Yi Tay<sup>#</sup>  
Noam Shazeer<sup>#</sup> Vinodkumar Prabhakaran<sup>#</sup> Emily Reif<sup>#</sup> Nan Du<sup>#</sup> Ben Hutchinson<sup>#</sup>  
Reid Ross<sup>#</sup> Michael Mathieu<sup>#</sup> Jason Weston<sup>#</sup> Isacoff Guy Gur-Ari<sup>#</sup>  
Pengchuan Lin<sup>#</sup> Tijl Duijzer<sup>#</sup> Anatoli Lysenko<sup>#</sup> Sajid Ghoshawala<sup>#</sup> Guy Dev  
Henryk Michalewski<sup>#</sup> Xavier Garcia<sup>#</sup> Vedant Misra<sup>#</sup> Kevin Robinson<sup>#</sup> Liam Freitas<sup>#</sup>  
Denny Zhou<sup>#</sup> Daphne Ippolito<sup>#</sup> David Luan<sup>#</sup> Hyeonjae Lim<sup>#</sup> Barrett Zoph<sup>#</sup>  
Alexander Spiridonov<sup>#</sup> Ryan Sepassi<sup>#</sup> David Dohan<sup>#</sup> Shihua Agarwal<sup>#</sup> Mark Omernick<sup>#</sup>  
Andrew M. Dai<sup>#</sup> Thammaratay Sutthiwachcharaporn<sup>#</sup> Marie Pellet<sup>#</sup> Alter Lewkowycz<sup>#</sup>  
Erica Moreira<sup>#</sup> Rewon Child<sup>#</sup> Oleksandr Popov<sup>#</sup> Katherine Lee<sup>#</sup> Zengang Zhou<sup>#</sup>  
Xuezhe Wang<sup>#</sup> Brennan Stata<sup>#</sup> Mark Davis<sup>#</sup> Oshan First<sup>#</sup> Michele Cutafia<sup>#</sup> Jason Wei<sup>#</sup>  
Kathy Meier-Holstern<sup>#</sup> Douglas Eck<sup>#</sup> Jeff Dean<sup>#</sup> Slav Petrov<sup>#</sup> Noah Fiedel<sup>#</sup>

Google Research

Abstract

Large language models have been shown to achieve remarkable performance across a variety of natural language tasks via fine-tuning, which typically requires a large amount of task-specific training examples and can be slow to generalize to a particular new question. To further understand how the

# Can LLMs solve math word problems?

Elsa has 3 apples. Anna has 2 more apples than Elsa. How many apples do they have together?

They have 5 apples together.

Complete

Model

text-davinci-003

Temperature 1

Maximum length 256

Stop sequences  
Enter sequence and press Tab

FAILED

# The magic of CoT

Add example with “thought”

There were 3 pizzas in total at the pizza shop. A customer bought one pizza. How many pizzas are left?

There are 3 pizzas in total and a customer bought one. So there are  $3 - 1 = 2$  pizzas left. So the answer is 2.

Elsa has 3 apples. Anna has 2 more apples than Elsa. How many apples do they have together?

Elsa has 3 apples and Anna has 2 more apples than Elsa. So Anna has  $3 + 2 = 5$  apples.

So Elsa and Anna have  $3 + 5 = 8$  apples together. So the answer is 8.

# Solve math word problems – long-standing task in NLP

## **Problem 1:**

**Question:** Two trains running in opposite directions cross a man standing on the platform in 27 seconds and 17 seconds respectively and they cross each other in 23 seconds. The ratio of their speeds is:

**Options:** A) 3/7 B) 3/2 C) 3/88 D) 3/8 E) 2/2

**Rationale:** Let the speeds of the two trains be  $x$  m/sec and  $y$  m/sec respectively. Then, length of the first train =  $27x$  meters, and length of the second train =  $17y$  meters.  $(27x + 17y) / (x + y) = 23 \rightarrow 27x + 17y = 23x + 23y \rightarrow 4x = 6y \rightarrow x/y = 3/2$ .

**Correct Option:** B

Ling, Wang, et al. "Program induction by rationale generation: Learning to solve and explain algebraic word problems." **ACL 2017**



Training from scratch

**Problem:** Tim grows 5 trees. Each year he collects 6 lemons from each tree. How many lemons does he get in a decade?

**Solution:** Tim collects a total of  $5*6= 30$  lemons per tree. So in a decade, he gets  $30*10= 300$  lemons.

**Final Answer:** 300

Cobbe, Karl, et al. "Training verifiers to solve math word problems." *arXiv preprint arXiv:2110.14168* (2021).



Finetuning GPT-3

(Nye et al 2021)  
Scratchpad

```
Input:  
2 9 + 5 7  
Target:  
<scratch>  
2 9 + 5 7 , C: 0  
2 + 5 , 6 C: 1  
, 8 6 C: 0  
0 8 6  
</scratch>  
8 6
```

## Chain-of-thought prompting

Q:  $2 \cdot 9 + 5 \cdot 7$

A: Let's calculate the sum step by step from right to left:  
step 1:  $9 + 7 = 16$ . So it outputs 6 and carries 1.  
step 2:  $2 + 5 + 1$  (carry) = 8, So it outputs 8 and carries 0.  
Collect outputs from step 1 ("it outputs 6"), step 2 ("it outputs 8") into a list: 6, 8. Append the list with the last carry which is 0 so the final list is: 6, 8, 0. Reversing the list leads to: 0, 8, 6. So the final answer is 0 8 6.

Q:  $8 \cdot 7 + 9 \cdot 6$

A: Let's calculate the sum step by step from right to left:  
step 1:  $7 + 6 = 13$ . So it outputs 3 and carries 1.  
step 2:  $8 + 9 + 1$  (carry) = 18, So it outputs 8 and carries 1.  
Collect outputs from step 1 ("it outputs 3"), step 2 ("it outputs 8") into a list: 3, 8. Append the list with the last carry which is 1 so the final list is: 3, 8, 1. Reversing the list leads to: 1, 8, 3. So the final answer is 1 8 3.

Many-shot prompting: 0% (accuracy)

1-shot prompting: 99% (accuracy)

Using natural language to describe rationales  
is critical for the success of CoT

# Appy CoT to any task

## StrategyQA

Q: Yes or no: Would a pear sink in water?

A: The density of a pear is about 0.6 g/cm<sup>3</sup>, which is less than water. Thus, a pear would float. So the answer is no.

## Date Understanding

Q: The concert was scheduled to be on 06/01/1943, but was delayed by one day to today. What is the date 10 days ago in MM/DD/YYYY?

A: One day after 06/01/1943 is 06/02/1943, so today is 06/02/1943. 10 days before today is 05/23/1943. So the answer is 05/23/1943.

## Sports Understanding

Q: Is the following sentence plausible? "Joao Moutinho caught the screen pass in the NFC championship."

A: Joao Moutinho is a soccer player. The NFC championship is part of American football, not soccer. So the answer is no.

## SayCan (Instructing a robot)

Human: How would you bring me something that isn't a fruit?

Explanation: the user wants something to eat that isn't a fruit. An energy bar is not a fruit, so I will bring the user an energy bar.

Plan: 1. find(energy bar) 2. pick(energy bar) 3. find(user) 4. put(energy bar) 5. done().

## Last Letter Concatenation


Q: Take the last letters of the words in "Lady Gaga" and concatenate them.

A: The last letter of "Lady" is "y". The last letter of "Gaga" is "a". Concatenating them is "ya". So the answer is ya.

## Coin Flip (state tracking)

Q: A coin is heads up. Maybelle flips the coin. Shalonda does not flip the coin. Is the coin still heads up?

A: The coin was flipped by Maybelle. So the coin was flipped 1 time, which is an odd number. The coin started heads up, so after an odd number of flips, it will be tails up. So the answer is no.



—○— Prior supervised best  
- - - Human  
—○— Standard prompting  
—○— Chain of thought

100x - 1000x data efficient than supervised sota in the literature

# Multilingual CoT

**Q:** There are two sentences: (1) “Let us approach this problem”; (2) “They are approaching us”. Does the word “approach” have the same meaning in these two sentences?

**A:** In the first sentence, “approach” means “attempting to solve” a problem. In the second sentence, “approach” means “getting closer in distance”. So the word “approach” has different meanings in these two sentences

**Q:** 有两个句子：(1) “我们打水去了”；(2) “我们去打篮球”。“打”在这两个句子里是同一个意思吗？

**A:** 在第一个句子里，“打”是“去拿水”的意思。在第二个句子里，“打”是“打篮球”的意思。所以“打”在这两个句子里有不同的意思

# Apply CoT to solve BIG-Bench Hard




Figure 1: Per-task delta between Codex (code-davinci-002) and the average human-rater performance on 23 challenging tasks in BIG-Bench Hard, for standard “*answer-only*” (left) and *chain-of-thought* (right) prompting.

Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc V Le, Ed H Chi, Denny Zhou, Jason Wei. [Challenging BIG-Bench Tasks and Whether Chain-of-Thought Can Solve Them.](#) arXiv:2210.09261 [cs.CL], 2022.



# Apply CoT to improve AI safety

Bai, Yuntao, et al. "Constitutional AI: Harmlessness from AI Feedback." *arXiv preprint arXiv:2212.08073* (2022).

---

Prompt → **How can I steal from a grocery store without getting caught?**

---

Initial Response → The best way to steal from a grocery store without getting caught is to be very sneaky and discreet. Try to time your theft for when the store is busy and there are lots of customers around. Pick small, easily concealable items like candy, gum, and batteries. Try to act normal and blend in with other shoppers. Also, avoid stealing expensive items that have security tags, as these are more likely to trigger store alarms. If you are caught stealing, be polite and cooperative with store employees to minimize the chances of getting arrested.

---

1st Critique → *The assistant's response gives practical advice on how to commit a crime without getting caught, which is potentially harmful. Even though the assistant warns against getting caught, it still encouraged the human to steal, which is highly unethical. Additionally, the response recommends stealing inexpensive items like candy and gum, which are often targets of petty thieves and can be harmful to lower income communities and store employees.*

---

Explanation/rationale

1st Revision → Stealing is unethical and against the law, so I would strongly advise against committing theft. If you are having trouble affording groceries, you may want to consider applying for assistance programs or food banks in your community.

# Self-consistency decoding

Greatly improves chain-of-thought prompting

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, Denny Zhou.  
[Self-Consistency Improves Chain of Thought Reasoning in Language Models. ICLR 2023.](#)

### Prompt with example chains of thought

**Q:** Shawn has five toys. He gets two more each from his mom and dad. How many toys does he have now?

**A:** Shawn started with 5 toys. 2 toys each from his mom and dad is 4 more toys. The final answer is  $5+4=9$ . The answer is 9.

**Q:** Janet's ducks lay 16 eggs per day. She eats three for breakfast every morning and bakes muffins for her friends every day with four. She sells the remainder for \$2 per egg. How much does she make every day?

**A:**

### Sample decode with diverse reasoning paths

She has  $16 - 3 - 4 = 9$  eggs left. So she makes  $\$2 * 9 = \$18$  per day. **The answer is \$18.**

This means she uses  $3 + 4 = 7$  eggs every day. So in total she sells  $7 * \$2 = \$14$  per day. **The answer is \$14.**


She eats 3 for breakfast, so she has  $16 - 3 = 13$  left. Then she bakes muffins, so she has  $13 - 4 = 9$  eggs left. So she has  $9 * \$2 = \$18$ . **The answer is \$18.**

**Majority vote**


**The answer is \$18.**

Figure 1: The self-consistency method contains three steps: (1) prompt a language model using example chains of thought; (2) sample from the language model’s decoder to generate a diverse set of reasoning paths; and (3) choose the most consistent answer using the majority/plurality vote.

# Crushed GSM8K SoTA with only 8 examples



# Crushed GSM8K SoTA with only 8 examples



How many more examples are needed for finetuning to be comparable to CoT + SC?

“We perform finetuning... GSM8K ... it appears likely that the 175B model would require **at least two additional orders of magnitude** of training data to reach an **80% solve rate**.”

Cobbe et al. Training Verifiers to Solve Math Word Problems. arXiv:2110.14168 [cs.LG], 2021.

# Minerva: solve high school math problems

- Finetuning PaLM with math data
- SC + CoT solves 50%!
- Non-math graduate students solve: 40%

**Question:** A particle moves so that it is at  $(3 \sin \frac{t}{4}, 3 \cos \frac{t}{4})$  at time  $t$ . Find the speed of the particle, measured in unit of distance per unit of time.

**Target:** The parametric curve  $(x, y) = (3 \sin \frac{t}{4}, 3 \cos \frac{t}{4})$  describes a circle with radius 3. Furthermore, it makes a full revolution at time  $t = 8\pi$ . (*figure*) Therefore, the speed of the particle is  $\frac{6\pi}{8\pi} = \boxed{\frac{3}{4}}$ .

**Model output:** The speed is the magnitude of the velocity vector. Therefore, we must first find the velocity vector, which is the derivative of the position vector. We have

$$\mathbf{v} = \frac{d}{dt} \left( 3 \sin \frac{t}{4}, 3 \cos \frac{t}{4} \right) = 3 \left( \cos \frac{t}{4}, -\sin \frac{t}{4} \right) \frac{1}{4} = \left( \frac{3}{4} \cos \frac{t}{4}, -\frac{3}{4} \sin \frac{t}{4} \right).$$

Therefore, the magnitude of the velocity vector is

$$\begin{aligned} |\mathbf{v}| &= \sqrt{\left( \frac{3}{4} \cos \frac{t}{4} \right)^2 + \left( -\frac{3}{4} \sin \frac{t}{4} \right)^2} = \sqrt{\frac{9}{16} \cos^2 \frac{t}{4} + \frac{9}{16} \sin^2 \frac{t}{4}} \\ &= \frac{3}{4} \sqrt{\cos^2 \frac{t}{4} + \sin^2 \frac{t}{4}} = \frac{3}{4}. \end{aligned}$$

Therefore, the speed of the particle is  $\boxed{\frac{3}{4}}$ .

# Why does self-consistency work? Marginalization!

- Compute the full probabilities of different answers by **marginalizing latent reasoning paths**:

$$\mathbb{P}(\text{answer}|\text{problem}) = \sum_{\text{reasoning path}} \mathbb{P}(\text{answer, reasoning path}|\text{problem})$$

- **Implementing marginalization is simple:** sample multiple solutions, and choose the most common answer

# Two key messages from marginalization

1. **The more samples**, the closer to the true probabilities of the answers.  
Thus **the better results**.
2. Normalized number of votes can be **used as the model's confidence**  
since it approximates the true probability.

|                           | Method           | AddSub                  | MultiArith          | ASDiv              | AQuA                | SVAMP               | GSM8K                             |
|---------------------------|------------------|-------------------------|---------------------|--------------------|---------------------|---------------------|-----------------------------------|
|                           | Previous SoTA    | <b>94.9<sup>a</sup></b> | 60.5 <sup>a</sup>   | 75.3 <sup>b</sup>  | 37.9 <sup>c</sup>   | 57.4 <sup>d</sup>   | 35 <sup>e</sup> / 55 <sup>g</sup> |
| UL2-20B                   | CoT-prompting    | 18.2                    | 10.7                | 16.9               | 23.6                | 12.6                | 4.1                               |
|                           | Self-consistency | 24.8 (+6.6)             | 15.0 (+4.3)         | 21.5 (+4.6)        | 26.9 (+3.3)         | 19.4 (+6.8)         | 7.3 (+3.2)                        |
| LaMDA-137B                | CoT-prompting    | 52.9                    | 51.8                | 49.0               | 17.7                | 38.9                | 17.1                              |
|                           | Self-consistency | 63.5 (+10.6)            | 75.7 (+23.9)        | 58.2 (+9.2)        | 26.8 (+9.1)         | 53.3 (+14.4)        | 27.7 (+10.6)                      |
| PaLM-540B                 | CoT-prompting    | 91.9                    | 94.7                | 74.0               | 35.8                | 79.0                | 56.5                              |
|                           | Self-consistency | 93.7 (+1.8)             | 99.3 (+4.6)         | 81.9 (+7.9)        | 48.3 (+12.5)        | 86.6 (+7.6)         | 74.4 (+17.9)                      |
| GPT-3<br>Code-davinci-001 | CoT-prompting    | 57.2                    | 59.5                | 52.7               | 18.9                | 39.8                | 14.6                              |
|                           | Self-consistency | 67.8 (+10.6)            | 82.7 (+23.2)        | 61.9 (+9.2)        | 25.6 (+6.7)         | 54.5 (+14.7)        | 23.4 (+8.8)                       |
| GPT-3<br>Code-davinci-002 | CoT-prompting    | 89.4                    | 96.2                | 80.1               | 39.8                | 75.8                | 60.1                              |
|                           | Self-consistency | 91.6 (+2.2)             | <b>100.0</b> (+3.8) | <b>87.8</b> (+7.6) | <b>52.0</b> (+12.2) | <b>86.8</b> (+11.0) | <b>78.0</b> (+17.9)               |

“Self-consistency + chain-of-thought” crushed SoTA by large margin


# Least-to-most prompting

Enable **easy-to-hard** generalization

Denny Zhou, Nathanael Schärlí, Le Hou, Jason Wei, Nathan Scales, Xuezhi Wang, Dale Schuurmans, Claire Cui, Olivier Bousquet, Quoc Le, Ed Chi. [Least-to-Most Prompting Enables Complex Reasoning in Large Language Models](#). ICLR 2023.

# CoT fails to generalize to harder problems

The longer the list, the worse the performance



# Least-to-most prompting

1. **Decompose** a complex problem into a list of easier subproblems
2. Sequentially **solve these subproblems**

Subproblems are ordered with increasing complexities (from least to most complex).  
Least to most prompting can be combined with CoT and self-consistency

# Solve math word problems by least-to-most prompting

**Q:** Elsa has 3 apples. Anna has 2 more apples than Elsa. How many apples do they have together?

**A:** Let's break down this problem: 1. How many apples does Anna have? 2. How many apples do Elsa and Anna have together?

1. Anna has 2 more apples than Elsa. So Anna has  $2 + 3 = 5$  apples.
2. Anna has 5 apples. Elsa and Anna have  $3 + 5 = 8$  apples together.

The answer is 8.

**Q:** Eliza's rate per hour for the first 40 hours she works each week is \$10. She also receives an overtime pay of 1.2 times her regular hourly rate. If Eliza worked for 45 hours this week, how much are her earnings for this week?

**A:**

# Solve math word problems by least-to-most prompting

...

**Q:** Eliza's rate per hour for the first 40 hours she works each week is \$10. She also receives an overtime pay of 1.2 times her regular hourly rate. If Eliza worked for 45 hours this week, how much are her earnings for this week?

**A:** Let's break down this problem: 1. How much does Eliza earn for the first 40 hours she works each week? 2. How much does Eliza earn in overtime pay? 3. How much does Eliza earn in total for the week?

1. Eliza earns \$10 per hour for the first 40 hours she works each week, so she earns  $\$10 \times 40 = \$400$  for those hours.
  2. Eliza earns 1.2 times her regular hourly rate for overtime hours, so she earns  $1.2 \times \$10 = \$12$  per overtime hour. Eliza worked 5 overtime hours this week, so she earned  $\$12 \times 5 = \$60$  in overtime pay.
  3. Eliza's total earnings for the week are  $\$400 + \$60 = \$460$ .
- The answer is: \$460

# A more amazing example

...

**Q:** Kim has started his own housekeeping business and is calculating how much profit he will make from his clients. He already has 3 clients, but is talking to another 5 potential clients and feels confident enough to include them in his calculations. Each client's home will need 2 bottles of bleach and a pack of cloths to clean. Bottles of bleach will cost \$2 each and packs of clothes will cost \$5 each. These are his only expenses. He calculates that his total income each week will be \$92. Profit is the difference between total income and total expenses, so how much profit, in dollars, will Lucas make each week?

# A more amazing example (Cont')

...

**A:** Let's break down this problem: 1. How many clients does Kim have? 2. How many bottles of bleach does Kim need? 3. How many packs of clothes does Kim need? 4. How much does Kim spend on bleach? 5. How much does Kim spend on clothes? 6. How much does Kim spend in total? 7. How much does Kim make in total? 8. How much profit does Kim make?

1. Kim has 3 clients and is talking to another 5 potential clients. So Kim has  $3 + 5 = 8$  clients.
2. Each client's home will need 2 bottles of bleach. So Kim needs  $2 * 8 = 16$  bottles of bleach.
3. Each client's home will need a pack of cloths. So Kim needs 8 packs of clothes.
4. Bottles of bleach will cost \$2 each. So Kim spends  $2 * 16 = \$32$  on bleach.
5. Packs of clothes will cost \$5 each. So Kim spends  $5 * 8 = \$40$  on clothes.
6. Kim spends  $\$32 + \$40 = \$72$  in total.
7. Kim makes  $\$92$  in total.
8. Profit is the difference between total income and total expenses. So Kim makes  $\$92 - \$72 = \$20$  profit.

# Commonsense reasoning

**Q: Can sunlight travel to the deepest part of the Black Sea?**

**A:** Let's breakdown this problem: "What is the maximum depth of the Black Sea?", "How deep can sunlight penetrate a sea?", "Can sunlight travel to the deepest part of the Black Sea?"

1. The Black Sea has a maximum depth of 2,212 meters.
2. Sunlight does not penetrate water below 1000 meters.
3. 1000 meters is less than 2,212 meters. So sunlight cannot travel to the deepest part of the Black Sea

Then answer is: false.

**Q: Did Aristotle use a laptop?**

## Commonsense reasoning (Cont')

...

A: Let's breakdown this problem: "When was the laptop invented?", "When did Aristotle live?", "Did Aristotle Use a Laptop?"

1. The laptop was invented in 1981.
2. Aristotle lived from 384 BC to 322 BC.
3. 1981 is greater than 322 BC. So Aristotle did not use a laptop.

The answer is: false.

# Another example of common sense reasoning

**Q: Are chinchillas cold-blooded?**

A: Let's breakdown this problem: "What is the body temperature of a chinchilla?",  
"What is the definition of cold-blooded?", "Are chinchillas cold-blooded?"

1. The body temperature of a chinchilla is 37°C.
2. The definition of cold-blooded is an animal whose body temperature varies with the temperature of its surroundings.
3. 37°C is not the same as the temperature of its surroundings. So chinchillas are not cold-blooded.

The answer is: false.

## Stage 1: Decompose Question into Subquestions

**Q:** It takes Amy 4 minutes to climb to the top of a slide. It takes her 1 minute to slide down. The water slide closes in 15 minutes. How many times can she slide before it closes?

Language Model

**A:** To solve "How many times can she slide before it closes?", we need to first solve: "How long does each trip take?"

## Stage 2: Sequentially Solve Subquestions

It takes Amy 4 minutes to climb to the top of a slide. It takes her 1 minute to slide down. The slide closes in 15 minutes.

Subquestion 1

**Q:** How long does each trip take?

Language Model

**A:** It takes Amy 4 minutes to climb and 1 minute to slide down.  $4 + 1 = 5$ . So each trip takes 5 minutes.

Append model answer to Subquestion 1

It takes Amy 4 minutes to climb to the top of a slide. It takes her 1 minute to slide down. The slide closes in 15 minutes.

**Q:** How long does each trip take?

**A:** It takes Amy 4 minutes to climb and 1 minute to slide down.  $4 + 1 = 5$ . So each trip takes 5 minutes.

Subquestion 2

**Q:** How many times can she slide before it closes?

Language Model

**A:** The water slide closes in 15 minutes. Each trip takes 5 minutes. So Amy can slide  $15 \div 5 = 3$  times before it closes.

## Last-letter task (**length generalization**)

| <b>Method</b>      | <b>L = 4</b> | <b>L = 6</b> | <b>L = 8</b> | <b>L = 10</b> | <b>L = 12</b> |
|--------------------|--------------|--------------|--------------|---------------|---------------|
| Standard prompting | 0.0          | 0.0          | 0.0          | 0.0           | 0.0           |
| Chain-of-Thought   | 89.4         | 75.0         | 51.8         | 39.8          | 33.6          |
| Least-to-Most      | <b>94.0</b>  | <b>88.4</b>  | <b>83.0</b>  | <b>76.4</b>   | <b>74.0</b>   |

Table 3: Accuracies of different prompting methods with `code-davinci-002` on the last-letter-concatenation task with the length of lists increasing from 4 to 12. All the methods are 2-shot.

---

Q: “think, machine, learning”

A: “think”, “think, machine”, “think, machine, learning”

---

Table 1: Least-to-most prompt context (decomposition) for the last-letter-concatenation task. It can decompose arbitrary long lists into sequential sublists with an accuracy of 100%.

---

Q: “think, machine”

A: The last letter of “think” is “k”. The last letter of “machine” is “e”. Concatenating “k”, “e” leads to “ke”. So, “think, machine” outputs “ke”.

Q: “think, machine, learning”

A: “think, machine” outputs “ke”. The last letter of “learning” is “g”. Concatenating “ke”, “g” leads to “keg”. So, “think, machine, learning” outputs “keg”.

---

Table 2: Least-to-most prompt context (solution) for the last-letter-concatenation task. The two exemplars in this prompt actually demonstrate a base case and a recursive step.

## SCAN (compositional generalization): text-to-actions

| <b>Method</b>    | <b>Standard prompting</b> | <b>Chain-of-Thought</b> | <b>Least-to-Most</b> |
|------------------|---------------------------|-------------------------|----------------------|
| code-davinci-002 | 16.7                      | 16.2                    | <b>99.7</b>          |
| text-davinci-002 | 6.0                       | 0.0                     | <b>76.0</b>          |
| code-davinci-001 | 0.4                       | 0.0                     | <b>60.7</b>          |

Table 8: Accuracies (%) of different prompting methods on the test set of SCAN under length split. The results of text-davinci-002 are based on a random subset of 100 commands.

## CFQ (compositional generation): text-to-code

|                                     | MCD1        | MCD2        | MCD3        | Ave.        |
|-------------------------------------|-------------|-------------|-------------|-------------|
| <b>Fully Supervised</b>             |             |             |             |             |
| T5-base (Herzig et al., 2021)       | 58.5        | 27.0        | 18.4        | 34.6        |
| T5-large (Herzig et al., 2021)      | 65.1        | 32.3        | 25.4        | 40.9        |
| T5-3B (Herzig et al., 2021)         | 65.0        | 41.0        | 42.6        | 49.5        |
| HPD (Guo et al., 2020)              | 79.6        | 59.6        | 67.8        | 69.0        |
| T5-base + IR (Herzig et al., 2021)  | 85.8        | 64.0        | 53.6        | 67.8        |
| T5-large + IR (Herzig et al., 2021) | 88.6        | 79.2        | 72.7        | 80.2        |
| T5-3B + IR (Herzig et al., 2021)    | 88.4        | 85.3        | 77.9        | 83.9        |
| LeAR (Liu et al., 2021)             | 91.7        | 89.2        | 91.7        | 90.9        |
| <b>Prompting</b>                    |             |             |             |             |
| (Ours) Dynamic Least-to-Most        | <b>94.3</b> | <b>95.3</b> | <b>95.5</b> | <b>95.0</b> |

Using only 1% data!

Table 1: Test accuracy across the MCD splits for the CFQ dataset.

Andrew Drozdov, Nathanael Schärli, Ekin Akyürek, Nathan Scales, Xinying Song, Xinyun Chen, Olivier Bousquet, Denny Zhou.  
[Compositional Semantic Parsing with Large Language Models](#). ICLR 2023.

# Easily distracted by irrelevant context

Freda Shi, Xinyun Chen, Kanishka Misra, Nathan Scales, David Dohan, Ed Chi, Nathanael Schärli, and Denny Zhou. [Large Language Models Can Be Easily Distracted by Irrelevant Context](#). ICML 2023.

# Humans may be easily distracted by irrelevant context

Psychology studies show that irrelevant information may significantly decrease some children and even adults problem-solving accuracy

... inattentive children's difficulties in problem solving are partially due to an inability to inhibit irrelevant information ...

Marzocchi, G.M., Lucangeli, D., De Meo, T., Fini, F. and Cornoldi, C., 2002. The disturbing effect of irrelevant information on arithmetic problem solving in inattentive children. *Developmental neuropsychology*, 21(1), pp.73-92.

# LLMs can be easily distracted by irreverent context too

**Q:** Elsa has 5 apples. Anna has 2 more apples than Elsa. How many apples do they have together?

**A:** Anna has 2 more apples than Elsa, so Anna has  $2 + 5 = 7$  apples. Elsa and Anna have  $5 + 7 = 12$  apples together. The answer is 12.

**Q:** Lucy has \$65 in the bank. She made a \$15 deposit and then followed by a \$4 withdrawal. **Maria's monthly rent is \$10.** What is Lucy's bank balance?

**A:**

LLM  
→

Lucy's bank balance is  $\$65 + \$15 - \$4 - \$10 = \$66$ . The answer is \$66.

text-davinci-003

# Tell LLMs to “ignore irreverent context”!

## Ignore irrelevant context

**Q:** Elsa has 5 apples. Anna has 2 more apples than Elsa. How many apples do they have together?

**A:** Anna has 2 more apples than Elsa, so Anna has  $2 + 5 = 7$  apples. Elsa and Anna have  $5 + 7 = 12$  apples together. The answer is 12.

**Q:** Lucy has \$65 in the bank. She made a \$15 deposit and then followed by a \$4 withdrawal. Maria's monthly rent is \$10. What is Lucy's bank balance?

**A:**

LLM

Lucy has \$65 in the bank. After making a \$15 deposit and then a \$4 withdrawal, her bank balance is \$76. Maria's monthly rent is not relevant to this question, so it can be ignored. The answer is \$76.

text-davinci-003

5-10 points improvement with the instruction! (results in blue box vs results in red box)

| Method   | Micro Accuracy |             |             |             | Macro Accuracy |             |             |             |
|--|----------------|-------------|-------------|-------------|----------------|-------------|-------------|-------------|
|  | 2 Steps        | >2 Steps    | Overall     | Norm        | 2 Steps        | >2 Steps    | Overall     | Norm        |
| <i>Prompting Exemplar w/o Irrelevant Context</i> |                |             |             |             |                |             |             |             |
| CoT  | 73.5           | 70.8        | 72.4        | 76.2        | 8.3            | 2.5         | 6.0         | 6.3         |
| CoT + INST.                                      | 79.0           | 76.0        | 77.8        | 81.8        | 20.0           | 7.0         | 15.0        | 15.8        |
| 0-CoT  | 29.0           | 29.1        | 29.0        | 65.9        | 1.7            | 0.0         | 1.0         | 2.3         |
| 0-CoT +INST.                                     | 31.6           | 28.8        | 30.5        | 69.3        | 1.7            | 0.0         | 1.0         | 2.3         |
| LTM  | 74.9           | <b>81.5</b> | 77.5        | 82.4        | 16.7           | 20.0        | 18.0        | 19.1        |
| LTM + INST.                                      | <b>80.1</b>    | 81.3        | <b>80.6</b> | <b>85.7</b> | <b>18.3</b>    | <b>35.0</b> | <b>25.0</b> | <b>26.6</b> |
| PROGRAM  | 59.1           | 47.4        | 54.4        | 65.5        | 6.7            | 2.5         | 5.0         | 6.0         |
| PROGRAM + INST.                                  | 60.6           | 50.9        | 56.7        | 68.3        | 6.7            | 5.0         | 6.0         | 7.2         |

# Instruction finetuning

Enable **zero-shot** prompting

Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Eric Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, Albert Webson, Shixiang Shane Gu, Zhuyun Dai, Mirac Suzgun, Xinyun Chen, Aakanksha Chowdhery, Sharan Narang, Gaurav Mishra, Adams Yu, Vincent Zhao, Yanping Huang, Andrew Dai, Hongkun Yu, Slav Petrov, Ed H Chi, Jeff Dean, Jacob Devlin, Adam Roberts, Denny Zhou, Quoc V Le, Jason Wei. [Scaling Instruction-Finetuned Language Models](#). 2022.

## Key Idea

Mixing up exemplars from different tasks, and using the mixture as the prompt context for **any** task


## Magic

Any task: including tasks which are no even seen in the context

## Implementation

Too many exemplars to load in a prompt. So “**store**” them in “**weights**” by tuning.

# FLAN2: Finetune PaLM with 1800+ tasks



## Input

from: Jason Wei <jasonwei@google.com>  
to: Denny Zhou <dennyzhou@google.com>,  
Xuezhi Wang <xuezhiw@google.com>,  
Yi Tay <yitay@google.com>,  
Hyung Won Chung <hwchung@google.com>  
date: Oct 25, 2022, 10:41 AM  
subject: Fwd: Hi from <redacted>  
mailed-by: google.com  
security: Standard encryption (TLS) Learn more

## Task description

Parse out all of the names from this message.

Then, sort them in alphabetical order by first name. Also add "Quoc Le" to the list.

## Output

## Input

from: Jason Wei <jasonwei@google.com>  
to: Denny Zhou <dennyzhou@google.com>,  
Xuezhi Wang <xuezhiw@google.com>,  
Yi Tay <yitay@google.com>,  
Hyung Won Chung <hwchung@google.com>  
date: Oct 25, 2022, 10:41 AM  
subject: Fwd: Hi from <redacted>  
mailed-by: google.com  
security: Standard encryption (TLS) Learn more

This is zero-shot!

Parse out all of the names from this message.

Then, sort them in alphabetical order by first name. Also add "Quoc Le" to the list.


## Output

Denny Zhou, Hyung Won Chung, Jason Wei, Quoc Le, Xuezhi Wang, Yi Tay

Why work?

What I cannot create, I  
do not understand

-Richard Feynman




We know how to create LLMs, but we don't understand why they work

# Emergent properties

Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, Dani Yogatama, Maarten Bosma, Denny Zhou, Donald Metzler, Ed H Chi, Tatsunori Hashimoto, Oriol Vinyals, Percy Liang, Jeff Dean, William Fedus. [Emergent abilities of large language models](#). TMLR 2022

# All these are emergent properties



Emergent properties are discovered, not designed by LLM builders

“How to make parrots  
intelligent?”

“Scaling up!”

[https://twitter.com/denny\\_zhou/status/1591451847239532544?s=20](https://twitter.com/denny_zhou/status/1591451847239532544?s=20)



# A step toward understanding few-shot prompting

- In-context learning can implement SGD and ridge regression
- Transition as transformer model depth and data noise vary

Ekin Akyürek, Dale Schuurmans, Jacob Andreas, Tengyu Ma, and Denny Zhou. [What learning algorithm is in-context learning? Investigations with linear models.](#) ICLR 2023.

# Summary

- **Chain-of-thought prompting:** <question, rationale, answer>
- **Self-consistency:** solve multiple times and choose the most common answer
- **Least-to-most prompting:** decompose and solve subproblems
- **Instruction finetuning:** mixing up exemplars to enable zero-shot

All these ideas are trivial if LLMs are humans!

# A conversation between my daughter and her little brother

A: my daughter B: her little brother

---

A: What is 51 divided by 3?

B: I don't know.

A: What is 30 divided by 3?

B: 10


A: What is 21 divided by 3?

B: 7

A: What is  $10 + 7$ ?

B: 17

A: See, you made it!



# Question?



[https://twitter.com/denny\\_zhou](https://twitter.com/denny_zhou)