

Running a Platform for CNFs in 2023

The Good, the Bad and the Ugly

Marcel Fest | DT Technik GmbH | November 15, 2023



Who am I?



Located in Wesel, Germany



Coffee drinker



Adventuresome, Casual cycling



Amateur snowboarder



Gardening

You can find me on:



Marcel Fest
Cloud Architect
**Deutsche Telekom
Technik GmbH**

The Mission

1. Reliable Kubernetes Clusters with well defined API Contract for internal customers

The Mission

1. Reliable Kubernetes Clusters with well defined API Contract for internal customers
2. Telco Grade Network Integration for Cloud Native Network Functions (CNFs)

The Mission

1. Reliable Kubernetes Clusters with well defined API Contract for internal customers
2. Telco Grade Network Integration for Cloud Native Network Functions (CNFs)
3. Contribute to Upstream OpenSource projects to provide enhancements for our niche use-cases

01

The Narrative



Running NF on Kubernetes in a Telco





Figure 1: Hosting a NF (Network Function) on vanilla Kubernetes!^[1]

What is a CNF or VNF or PNF? Really what's an NF



History Lesson about NFs

- Everything started with **PNF's**
 - normally it is a proprietary hardware chassis or black-box with labeled network ports
 - support and maintenance was done by the vendor and the updatecycle was around once/twice a year
- Than **VNFs** came around
 - These network functions are deployed in a VM (Virtual Machine)
 - First approach to consolidate on commodity hardware
 - The main NFVI (Network Function and Virtualization Infrastructure) is OpenStack
- The newest incarnation of a network function is the **CNF**
 - These network functions are deployed as a Container with 12-factors
 - Second approach to consolidate on commodity hardware
 - The main *NFCO (Network Function and Container Orchestrator)* is Kubernetes

Lets hydronate and drink some VRF!





Figure 2: Glass with water getting empty.



Lets hydronate and drink some VRF!





Figure 2: Glass with water getting empty.



Lets hydronate and drink some VRF!







Figure 2: Glass with water getting empty.



The Good CNF




The Bad & Ugly CNF



02 Conclusion



Conclusion

- Vendors like L2  but we want to enforce **L3**
- Linux VRFs are a pain but can work if used with caution
- Vendors don't like Kubernetes CNI approach
- Vendors should standardize around AF_XDP or memif (of VPP) instead of legacy SR-IOV for the fast-datapath
- Vendors ❤️ interfaces instead of using multiple IPs (3GPP 🙄)
- DPUs might be an option to offload the VRF peering on the network card for our platform

END



END

**Two years of
BGP-EVPN to the
host**



References I

[1] Hannah Fest. Telco in a cloudnative world. Private handdrawn Picture under Creative Commons v2 License, May 2022. Accessed on 2022-05-03.