Fast startup and low latency: pick two

Denys Shabalin and Lukas Kellenberger

Scala Native

- Announced a year ago with a first prototype at ScalaDays '16 in New York.
- An ahead-of-time compiler for Scala build on top of the LLVM compiler infrastructure.
- Developed by EPFL and Scala Center.

Scala Native

- As of today:
 - 55 contributors
 - 383 pull requests closed
 - 246 issues fixed

Scala Native

Thanks to everyone who contributed!

Guillaume Massé, Martin Duhem, Hugo Kapp, Hiroyoshi Takahashi, Jonas Fonseca, Lukas Kellenberger, Francois Bertrand, AndreaTP, Eric K Richardson, Marius B. Kotsbak, Kota Mizushima, Łukasz Indykiewicz, Timothy Klim, Paweł Batko, Shunsuke Otani, Nick Pavlov, Cedric Viaccoz, Andrzej Sołtysik, Ankit Soni, Hanns Holger Rutz, Kamil Tomala, Philipp Dörfler, Simon Ochsenreither, Zack Powers, Musabilal, Hubert Plociniczak, Mike Samsonov, Greg Dorrell, Pablo Guerrero, Florian Duraffourg, Alex Dupre, Ragavendar Ramamurthi, Richard Whaling, Roman Zoller, Ruben Berenguel Montoro, Saleem Ansari, Sam Halliday, Felix Mulder, Ragnr, Stefan Ollinger, The Gitter Badger, Tim Nieradzik, Brad Rathke, Viacheslav Blinov, Vincent Munier, Remi, Alexey Kutepov, Adam Voss, Gregor-i, Gute-ist-tot, Kenji Yoshida, Joseph Price, Jentsch, Ignat Loskutov, Martin Mauch

Road towards 0.1

(March 14, 2017)

Goals for 0.1

- All Scala language features are supported
- Sbt integration is sufficient to build and publish existing cross-platform projects
- Enough core libraries to cover for basic standard library usage

Improving the standard library story in 0.2

(April 26, 2017)

Goals for 0.2

- Support for file i/o from java.io.*
- Support for regex from java.util.regex.*
- Event-loop-based Futures

Laying down the foundation for *better* garbage collection in 0.3

(June 6, 2017)

Goal for 0.3

Better GC #128



① Open ebruchez opened this issue on May 23, 2016 · 21 comments



ebruchez commented on May 23, 2016





Adding this as a backlog idea.

sgen is Mono's newish garbage collector, introduced to replace the old Boehm. It is a generational gc, and since it works for Mono, I would think it could fit the bill for Scala Native as well.

Here is the source code. It appears to under the MIT license.



nativeGC := "boehm"

Boehm GC

- Conservative garbage collector
- Originally designed for C/C++ environment
- Good starting point for a new language implementation due to it simple GC interface

Conservative GC

Conservative roots:

GC doesn't *precisely* know which values on the stack are heap references, but object layout is known.

Fully conservative:

GC doesn't *precisely* know which values on the stack or heap are references.

Boehm GC

- How fast/slow are we exactly?
- github.com/smarr/are-we-fast-yet


Boehm GC

5

3.75

2.5

1.25



nativeGC := "none"

Running without GC

- The simplest form of garbage collection: allocate and never free allocated memory
- Practical for short-lived command-line tools
- Sometimes used in applications with insane requirements for application predictability

From: k...@rational.com (Kent Mitchell)

Subject: Re: Does memory leak?

Date: 1995/03/31

newsgroups: comp.lang.ada

This sparked and interesting memory for me. I was once working with a customer who was producing on-board software for a missile. In my analysis of the code, I pointed out that they had a number of problems with storage leaks. Imagine my surprise when the customers chief software engineer said "Of course it leaks". He went on to point out that they had calculated the amount of memory the application would leak in the total possible flight time for the missile and then doubled that number. They added this much additional memory to the hardware to "support" the leaks. Since the missile will explode when it hits it's target or at the end of it's flight, the ultimate in garbage collection is performed without programmer intervention.

Kent Mitchell
Technical Consultant
Rational Software Corporation
| One possible reason that things aren't
| going according to plan is
| that there never *was* a plan!

https://groups.google.com/forum/message/raw?msg=comp.lang.ada/E9bNCvDQ12k/1tezW24ZxdAJ

Running without GC

OpenJDK

OpenJDK FAQ Installing Contributing Sponsoring Developers' Guide

Mailing lists IRC · Wiki

Bylaws · Census Legal

JEP Process

search

Source code

Mercurial Bundles (6)

Groups

(overview)
2D Graphics
Adoption
AWT
Build
Compiler
Conformance
Core Libraries
Governing Board
HotSpot


JEP draft: Epsilon GC: The Arbitrarily Low Overhead Garbage (Non-)Collector

Owner Aleksey Shipilev
Created 2017/02/14 08:23
Updated 2017/04/01 16:29
Type Feature
Status Draft
Component hotspot/gc
Scope Implementation
Effort S
Duration S
Priority 4
Issue 8174901

Summary


Develop a GC that only handles memory allocation, but does not implement any actual memory reclamation mechanism. Once available Java heap is exhausted, perform the orderly JVM shutdown.

Evaluating cost of GC



nativeGC := "?"

GCs in the wild



Always Moving GCs

Non Moving

Mostly Moving

Always Moving Standard choice in most JIT-ed VMs:

- GC is free to compact the memory optimizing it for best locality
- Bump allocation is as fast as it gets in terms of allocation performance.

Semi Space (SS)


Mark Compact (MC)

SS + MS/MC

Fully Precise Conservative Roots

Fully Conservative

Always Moving GCs



Non-Moving GCs



Reference Counting (RC)

Mark And Sweep (MS)

Mostly Moving

Standard pick for AOT compilers:

GC never moves objects in memory

- Compiler may or may not know about GC
- Good interoperability with unmanaged code that can not easily handle a moving GC


Always Moving

> Fully Precise

Conservative Roots

Fully Conservative

Reference Counting



Reference Counting

Non Moving

Reference Counting (RC)

Mark And Sweep (MS)

Mostly Moving

Always Moving


But:

- Naive version can't handle cycles, needs a cycle collector and to make it practical for Scala
- Prone to high constant overhead that's necessary to maintain refcounts

Fully Precise Conservative Roots

Fully Conservative

Reference Counting



Non Moving GCs

Non Moving

Reference Counting (RC)

Mark And Sweep (MS)

Mostly Moving

Always Moving


Both suffer from:

- Fragmentation and memory locality issues due to non-moving nature of the collectors
- Typically backed by free list-based allocator which is not competitive in terms of allocation performance


Fully Precise Conservative Roots

Fully Conservative


Status quo revisited




Status quo revisited





Initial experiments




Stack








Modules



Modules

Stack Marking Phase




Modules

Stack Marking Phase

Modules

Stack Marking Phase


Stack Marking Phase




Stack Marking Phase

Stack Marking Phase


Stack Marking Phase




Stack Marking Phase




Stack Marking Phase






Stack Marking Phase




Stack Marking Phase


Stack Marking Phase




Stack Marking Phase

Stack







Sweeping Phase




Stack







Sweeping Phase




Stack







Sweeping Phase




Modules

Stack







Sweeping Phase




Modules

Stack







Sweeping Phase




Stack







Sweeping Phase




Stack







Sweeping Phase




Stack







Sweeping Phase




Stack







Sweeping Phase




Stack







Sweeping Phase




Stack







Sweeping Phase




Stack







Sweeping Phase




Stack







Sweeping Phase




Stack







Sweeping Phase



MS Performance




Initial experiments




Fully Precise Conservative Roots

Fully Conservative


Initial experiments



Mostly-Moving Sweet Spot



Bartlett



Non Moving

Mark-region garbage collector with opportunistic one-pass defragmentation.

Mostly Moving


Immix


Always Moving "Immix: a mark-region garbage collector with space efficiency, fast collection, and mutator performance" Stephen M. Blackburn, Kathryn S. McKinley


Fully Precise


Conservative Roots


Fully Conservative






































Stack


Marking Phase






Stack


Marking Phase






Stack


Marking Phase






Stack


Marking Phase






Stack


Marking Phase






Stack


Marking Phase








Stack


Marking Phase




















Modules















Modules












Modules

Stack













Sweeping Phase


















Modules















Modules











Modules













Sweeping Phase




Modules










Modules

Immix Performance

Immix Performance



- First prototype is coming in Scala Native 0.3
- Opt-in via nativeGC := "immix"
- We're going to support Boehm until the immix implementation matures and becomes the default

Bonus features in 0.3

- Sbt testing framework integration
- Initial support for file i/o from java.nio.*
- Initial support for zip/jar from java.util.*
- Smaller binaries

Questions?