

Explaining the Relative Nature of General and Special Relativity

Thomas DeGerlia^a

Originally published: June 16, 2026 C.E.

Revision 2.0 June 16, 2026 C.E.

ABSTRACT: In this paper, we reveal that the time dilation between two systems is equal to the ratio of their respective DeGerlia inertial density D , defined as mass over mean radius. Fundamental to this exploration is the recognition that relativity is always relativistic, meaning there is no single privileged frame of observation: no measurement, whether of time or anything else, has any meaning without a comparator. We reveal this by taking our relative compactness equation, plugging in a system compared to that same system at its Schwarzschild radius, and demonstrating that we obtain the same exact result as the gravitational time dilation equation. In order to present this equivalence and demonstrate the relativistic principle, we utilize a framework developed by the author called the DeGerlia Time Dilation framework, a simple, mathematically equivalent time dilation framework that is directly derived from general relativity.

Keywords: time dilation, general relativity, special relativity, gravitational time dilation, Lorentz time dilation, DeGerlia inertial density, inertial density, moment of inertia, Schwarzschild radius

1 Introduction

General relativity is a model for observing our universe that is fundamentally comparative: no quantity has physical meaning without a comparator. The pace of time is no exception: the time dilation between two systems is a product of the systems respective geometric mass distribution. Directly from the gravitational time dilation formula one can derive the underlying two-system logic and ultimately GTD is simply a comparison between a system a systems pace of time relative to the pace of time of an arbitrarily selected benchmark system, which in this case is the same system at its Schwarzschild radius. The formula allows you the freedom to only insert one mass and one radius, and the second is derived directly from the first. This has the effect of hiding the true nature of relativity and that is that it is, above all, comparative. But sends a signal that one need not compare two systems to understand time, and that is flawed thinking; it introduces the mathematical fallacy of an arbitrarily selected comparator, when there is, in fact, no privilege perspective from which to understand time. In this paper we evaluate the physical property responsible for relativistic time dilation and derive the underlying formulation that quantifies the relative time dilation between two systems.

The relative flow of time between two systems is dictated by their relative compactness. The standard formula for compactness, described under general relativity, expresses this as a di-

mensionless parameter. However, in this paper we utilize a principle developed by the author, DeGerlia inertial density, which is an abstracted compactness measure explained herein, that retains the proper unit of this property and that is mass over radius. Thus DeGerlia inertial density is defined as a system's mass over mean radius $D = M/\bar{R}^1$. We do a comparative analysis and tabulate relative time dilation across a variety of systems from classical to relativistic regimes, and show that the same compactness ratio $k = D_1/D_2 = M_1\bar{R}_2/(M_2\bar{R}_1)$ returns the Schwarzschild time-dilation ratio exactly across every tested constraint class, including the fully general case. This establishes that the relative rate of time between systems is not an ad hoc relativistic output requiring separate formulas, but a direct consequence of comparative mass-radius geometry. The result makes explicit a simple relation already contained in general relativity: given two systems' masses and mean radii, their relative time dilation is determined by their respective geometric distribution of mass alone.

We use the DeGerlia framework to calculate gravitational time dilation based on relative inertial density properties. This demonstrates that because we're able to take my 2-system equation and run it with one system being the Schwarzschild radius and the radius of the first system. This validates both the comparative nature of relativity and the applicability of the DeGerlia framework.

Several distinct, common forms of time dilation utilize the same formula. Utilize a common formula, and that is that the time dilation is equal to $\sqrt{1-k}$, the square root of one minus the scale factor. In general relativity, the scale factor is calculated by

^a DeGerlia Expert Consulting, 3000 Lawrence Street, Denver, CO, United States of America. E-mail: tom.degerlia@tomdegerlia.com

$r_s/\bar{R}$. In special relativity, it's calculated as v^2/c^2 , and in general relativity, you can also substitute that: $r_s/\bar{R}$ could be replaced with D/D_{crit} . Those are all equivalent.

Both General and Special Relativity follow a very similar form, and their distinction mirrors the distinction between linear and rotational inertia. This alludes to a very rational and logical unification of relativity.

2 Experimental Model

The experimental model utilized for this study relies on a number of key components: * The hypothetical framework is derived directly from general relativity, and thus is mechanically, mathematically equivalent to well-established general relativity calculations. The framework does not rely upon or attempt to introduce new principles not already established under the theories of general and special relativity. This is simply a re-framing of the existing theory of general relativity for explorative purposes. * We will start by introducing the DeGerlia Framework and then show the complete mathematical equivalence with general relativity. * We then work through a series of examples, each one demonstrating a different comparative case ** The first is the most familiar, and that is the case where both systems have the same mass. Gravitational time dilation is such a case, because to calculate gravitational time dilation one must compare a system with an identical system that's at its Schwarzschild radius. With this example we will demonstrate the two-system nature of all relativistic calculations, comparing two systems of equal mass. Relativity is fundamentally about how things appear relative to other things. Gravitational Time dilation reflects the comparison of systems of equal mass, where the compared radius is the collapse condition radius r_s . We validate this by calculating gravitational time dilation using the traditional formula and comparing the two. Simultaneously reinforcing the validity of the framework. ** We work through a second equal mass calculation where we are comparing a system that's arbitrarily large to a system of equal mass at four-thirds Schwarzschild radius, or $d\tau/dt = 0.5$. ** We work through two systems of equal radius, which represents the Lorentz factor in special relativity. ** We perform calculations for systems of equal density or equal moment of inertia, in addition to the classical case where we compare near-scale objects, and finally a general case where there's no constraint, where you could identify the relative pace of time between any two systems with no similarity between them, and we validate the calculations against what general gravitational time dilation calculations do.

3 Definitions used within this paper

Symbol	Definition / value
GTD	$\sqrt{1-k} = d\tau/dt$
DTD	$\sqrt{k}$ (DeGerlia time dilation)
k	$v^2/c^2 = r_s/\bar{R} = D/D_{\text{crit}}$
D	$M/\bar{R}_{\text{axis}}$ (DeGerlia inertial density)
D_{crit}	$c^2/2G = 6.73295 \times 10^{26} \text{ kg/m}$
r_s	$2GM/c^2$ (Schwarzschild radius)
P	I/V (inertial density) $= D \cdot 3/10\pi$
θ	$\arcsin \sqrt{k}$; GTD $= \cos \theta$, DTD $= \sin \theta$
c	299,792,458 m/s (exact)
G	$6.67430 \times 10^{-11} \text{ m}^3\text{kg}^{-1}\text{s}^{-2}$

4 General Relativity

4.1 Compactness

Compactness is the dimensionless ratio of a system's mass to its radius, scaled by G/c^2 . The most common forms are $C = GM/(Rc^2)$ and $r_s/\bar{R} = 2GM/(Rc^2) = 2C$, where $r_s = 2GM/c^2$ is the Schwarzschild radius. Both measure how close a system sits to its Schwarzschild threshold: $r_s/\bar{R} = 1$ marks the gravitational-collapse condition.

4.2 Compactness

Compactness is a unitless normalized factor utilized in general relativity. However, because it is normalized, it honors a preferred scale near our own, and thus begins to offer a more and more skewed view the further one moves from our own scale.

$$C = \frac{GM}{Rc^2} \quad (1)$$

where this is the standard general-relativistic compactness, $\mathcal{C} \equiv GM/(Rc^2)^2$.

4.3 Time Dilation

4.4 Structure of the GTD Equation as a Two-System Comparison

5 The DeGerlia Time Dilation Framework

An analogous framework that is directly derived from general relativity and has a direct relationship to gravitational time dilation.

5.1 System

Under the DeGerlia Time Dilation Framework a "system" is defined as "any discrete collection of particles and the space between them", or alternatively, "any unit of space and the particles contained within." Because this framework sees the universe not as a clean separation of discrete material systems separated by the vacuum of space, but as a gradient of material density pervasive everywhere throughout the universe. The most extreme densities reside not within near-scale systems but rather, within the cores of highly dense gravitational objects far from our physical scale, such as black holes or sub-atomic particles, and forms a gradient all the way to the near-scale "vacuum of space" where another

gravitational source begins to exert more influence. It does not concern itself with notions of uniformity or even symmetry at all. Sphericalness relies on none of those. It doesn't rely on a clean edge separating matter from vacuum, or anything along those lines. It doesn't rely on static density nor any particular density gradient.

It only requires a mass and a mean radius about the axis of observation relative to an observing mass and radius about that same axis of observation; if you're not getting sufficient granularity within the radius you selected, pick a smaller radius and from that you can derive more information about the interior of that object. One can simply say my system consists of the earth to a radius of x where that radius might encompass just the mean radius of the planet. But if you were talking about Jupiter without a clear periphery separating the surface from the atmosphere, one might characterize the system as out to a radius of x or out to a density of y . If analyzing a large system, it would not be uncommon to take a spherical sample from within that system in order to characterize the behavior of certain regions.

5.2 The Scale Factor k

The following identity relates the time-dilation ratio of two uniform spherical systems to their mass and radius.*

$$k = \frac{D_1}{D_2} = \frac{M_1 \bar{R}_2}{M_2 \bar{R}_1} \quad (2)$$

where I_1, I_2 are the moments of inertia, $\bar{R}_1, \bar{R}_2$ are the radii, M_1, M_2 are the masses, and $D_i = M_i/\bar{R}_i$ is the DeGerlia inertial density of system i . The three forms in Equation 2 are algebraically identical; $(I_1/I_2)(\bar{R}_2/\bar{R}_1)^3$ exposes the inertia-radius structure, D_1/D_2 exposes the compactness-ratio structure, and $M_1 \bar{R}_2/(M_2 \bar{R}_1)$ is the fully expanded form.

A system's pace of time has meaning only relative to another pace of time. The scale factor k governs the relative time-dilation between two uniform spherical systems. The standard gravitational time-dilation calculation takes the Schwarzschild form $\sqrt{1-k}$, where $k = D/D_{\text{crit}} = r_s/\bar{R}$. The compactness ratio $k = D_1/D_2$ and the Schwarzschild form give the same value.

Via the Schwarzschild radius, the same scale factor is:

$$k = \frac{D}{D_{\text{crit}}} = \frac{r_s}{\bar{R}} \quad (3)$$

where $D = M/\bar{R}$ is the system's DeGerlia inertial density and $r_s = 2GM/c^2$ is its Schwarzschild radius. This is the k that appears in the standard $\sqrt{1-k}$ for GTD.

Time dilation is always:

$$\frac{d\tau}{dt} = \sqrt{1-k} \quad (4)$$

where $d\tau/dt$ is the time-dilation factor between the two systems and k is the DeGerlia inertial density ratio for the case being computed. The specific forms are:

- $k = D_1/D_2$ (Equation 2) — via inertial density ratio

- $k = D/D_{\text{crit}} = r_s/\bar{R}$ (Equation 3) — via Schwarzschild radius

Same k symbol across forms: a given numerical k produces the same time-scale-factor result regardless of which form it appears in.

5.3 DeGerlia inertial density D

Inertial density P^1 is the moment of inertia of a system divided by its volume:

$$P = I/V \quad (5)$$

Inertia, in a linear context, is simply mass. Inertial density, in this context, reduces directly to mass density $\rho = M/V$. From this perspective, inertial density is simply the rotational analog to mass density, not unlike the relationship between f equals m and torque equals angular acceleration times m . More succinctly stated: mass density is simply the linear interpretation of inertial density.

Substituting $I = \frac{2}{5}M\bar{R}^2$ and $V = \frac{4}{3}\pi\bar{R}^3$, with R the radius, this reduces to:

$$P = \frac{M}{R} \times \frac{3}{10\pi} \quad (6)$$

Just as ordinary density ($\rho = M/V$) is mass distributed over volume, inertial density is rotational inertia distributed over volume. As stated in the prior work: *mass and density are to linear motion as moment of inertia and inertial density are to rotational motion.*

$D = M/\bar{R}$ is a simplified analog to inertial density, related to P by the geometric factor $3/10\pi$, and represents the mass over radius ratio for a system. Given that this quantity is almost always used in a ratio that would cancel out all geometric vectors and constants, for ease of use, this metric D for inertial density is typically used over the geometrically accurate inertial density, P .

5.4 DeGerlia Threshold D_{crit}

The Schwarzschild condition can be expressed as a static universal constant threshold of DeGerlia inertial density D . There are several advantages to this approach, not the least of which is that you don't have to calculate the threshold for every mass. And, it's much easier to calculate D than P . Inertial density is an intuitive metric that's easier to work with.

Setting $R = r_s$ (the Schwarzschild condition)⁴ and solving yields the **DeGerlia Threshold**: the universal constant of DeGerlia inertial density at which the escape velocity equals the speed of light:

$$D_{\text{crit}} = \frac{c^2}{2G} = (6.73295 \pm 0.00015) \times 10^{26} \text{ kg/m} \quad (7)$$

Note this value is exact; its precision is limited by $G = (6.67430 \pm 0.00015) \times 10^{-11} \text{ m}^3 \text{ kg}^{-1} \text{ s}^{-25}$.

5.5 DeGerlia Time Dilation

DeGerlia Time Dilation is the geometric complement of gravitational time dilation:

$$\text{DTD} = \sqrt{k} \quad (8)$$

* This identity has been previously referred to as the "space-time equivalence"³.

where k is the scale factor of Equation 2. Where $\text{GTD} = \sqrt{1-k}$ is the surviving proper-time rate $d\tau/dt$, $\text{DTD} = \sqrt{k}$ is its complement.

5.6 Converting Between GTD and DTD

GTD and DTD are bound by the Pythagorean identity:

$$\text{GTD}^2 + \text{DTD}^2 = (1-k) + k = 1. \quad (9)$$

5.7 Properties of DTD

6 Relative Time Dilation Examples

Tables 1 and 2 present the complete system properties and derived ratios for eight system pairs spanning the constraint cases that follow: static mass ($M = M$), static radius ($R = R$), constant density ($\rho = \rho$), constant inertia ($I = I$), an unconstrained general case, and a classical case. Across every case, the three algebraic forms of the scale factor k (Equation 2) produce identical values, and the time-dilation ratio computed via the DeGerlia route agrees with the gravitational time-dilation ratio computed independently from the standard Schwarzschild form — to the precision afforded by G . No case requires a separate formula. The worked examples in the subsections that follow show, case by case, exactly how each column of these tables is obtained.

6.1 Case 1: ($M_1 = M_2$, $\bar{R}_1 = \frac{4}{3}r_s$)

The two identical masses cancel, reducing the DeGerlia inertial density ratio down to a ratio of radii.

$$k_d = \frac{M_1 \bar{R}_2}{M_2 \bar{R}_1 D_{\text{crit}}} = \frac{\bar{R}_2}{\bar{R}_1 D_{\text{crit}}}$$

Note, This reflects the k calculation for gravitational time dilation. However, in this case, instead of comparing with r_s , we are comparing with $\frac{4}{3}r_s$, which equates to a gravitational time dilation of $\text{GTD} = 5.00000\text{e}-1$.

System properties:

	System 1 (S_1)	System 2 (S_2)
M (kg)	1.00000e30	1.00000e30
$\bar{R}$ (m)	1.98031e3	1.00000e8

Calculate DTD for each System:

$$\begin{aligned} \text{DTD} &= \sqrt{k} \quad \text{where} \quad k = M/(\bar{R}D_{\text{crit}}) \\ k_1 &= \frac{1.00000\text{e}30\text{kg}}{(1.98031\text{e}3\text{m})(6.73295\text{e}26\text{kg/m})} = 7.50001\text{e}-1 \\ \text{DTD}_1 &= \sqrt{7.50001\text{e}-1} = 8.66026\text{e}-1 \\ k_2 &= \frac{1.00000\text{e}30\text{kg}}{(1.00000\text{e}8\text{m})(6.73295\text{e}26\text{kg/m})} = 1.48523\text{e}-5 \\ \text{DTD}_2 &= \sqrt{1.48523\text{e}-5} = 3.85387\text{e}-3 \\ \frac{\text{DTD}_1}{\text{DTD}_2} &= \frac{8.66026\text{e}-1}{3.85387\text{e}-3} = 2.24716\text{e}2 \end{aligned}$$

Calculate GTD ratio from DTD:

$$\begin{aligned} \frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} &= \frac{\sqrt{1 - \text{DTD}_1^2}}{\sqrt{1 - \text{DTD}_2^2}} = \frac{\sqrt{1 - (8.66026\text{e}-1)^2}}{\sqrt{1 - (3.85387\text{e}-3)^2}} \\ &= \frac{\sqrt{1 - 7.50001\text{e}-1}}{\sqrt{1 - 1.48523\text{e}-5}} \\ &= \frac{\sqrt{2.49999\text{e}-1}}{\sqrt{9.999851477\text{e}-1}} \\ &= \frac{4.99999\text{e}-1}{9.9999257381\text{e}-1} = 5.00003\text{e}-1 \\ &= 1 - 4.99997\text{e}-1 \end{aligned}$$

Verify by Calculating GTD from Schwarzschild Radius Ratio: Schwarzschild radii:

$$\begin{aligned} r_{s1} = r_{s2} &= \frac{2GM}{c^2} = \frac{2(6.67430\text{e}-11\text{m}^3\text{kg}^{-1}\text{s}^{-2})(1.00000\text{e}30\text{kg})}{(2.99792\text{e}8\text{m s}^{-1})^2} \\ &= 1.48523\text{e}3\text{m} \end{aligned}$$

Calculate k values from the r_s/R ratio:

$$\begin{aligned} k_1 &= \frac{r_{s1}}{\bar{R}_1} = \frac{1.48523\text{e}3\text{m}}{1.98031\text{e}3\text{m}} = 7.50000\text{e}-1 \\ k_2 &= \frac{r_{s2}}{\bar{R}_2} = \frac{1.48523\text{e}3\text{m}}{1.00000\text{e}8\text{m}} = 1.48523\text{e}-5 \end{aligned}$$

Calculate GTD via Schwarzschild radius ratio:

$$\begin{aligned} \text{GTD}_{s1} &= \sqrt{1 - k_1} = \sqrt{2.50000\text{e}-1} = 5.00000\text{e}-1 = 1 - 5.00000\text{e}-1 \\ \text{GTD}_{s2} &= \sqrt{1 - k_2} = \sqrt{9.999851477\text{e}-1} = 9.9999257381\text{e}-1 \\ &= 1 - 7.42619\text{e}-6 \\ \frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} &= \frac{5.00000\text{e}-1}{9.9999257381\text{e}-1} = 5.00004\text{e}-1 \\ &= 1 - 4.99996\text{e}-1 \end{aligned}$$

Time-dilation ratio between System 1 and System 2, computed two ways:

$$\begin{aligned} \frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} &= 1 - 4.99996\text{e}-1 \quad (\text{via } r_s) \\ \frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} &= 1 - 4.99997\text{e}-1 \quad (\text{via } D_{\text{crit}}) \end{aligned}$$

Table 1 System properties for each pair comparison case.

	Case 1 $M=M, \sim \frac{4}{3}r_s$	Case 2 $M=M, \sim r_s$	Case 3 $M=M$	Case 4 $R=R$	Case 5 $\rho=\rho$	Case 6 $I=I$	Case 7 General	Case 8 Classical
M_1 (kg)	1.00000e+30	2.00000e+30	2.00000e+30	1.00000e+30	1.00000e+30	1.00000e+32	1.00000e+20	8.00000e+0
M_2 (kg)	1.00000e+30	2.00000e+30	2.00000e+30	1.00000e+24	1.00000e+27	1.00000e+30	1.00000e+30	1.00000e+0
$\bar{R}_1$ (m)	1.98031e+3	2.97049e+3	3.00000e+3	1.00000e+8	1.00000e+8	1.00000e+7	2.00000e-7	2.00000e+0
$\bar{R}_2$ (m)	1.00000e+8	7.00000e+8	7.00000e+8	1.00000e+8	1.00000e+7	1.00000e+8	1.00000e+7	1.00000e+0
ρ_1 (kg/m ³)	3.07406e+19	1.82161e+19	1.76839e+19	2.38732e+5	2.38732e+5	2.38732e+10	2.98416e+39	2.38732e-1
ρ_2 (kg/m ³)	2.38732e+5	1.39203e+3	1.39203e+3	2.38732e-1	2.38732e+5	2.38732e+5	2.38732e+8	2.38732e-1
I_1 (kg·m ²)	1.56865e+36	7.05907e+36	7.20000e+36	4.00000e+45	4.00000e+45	4.00000e+45	1.60000e+6	1.28000e+1
I_2 (kg·m ²)	4.00000e+45	3.92000e+47	3.92000e+47	4.00000e+39	4.00000e+40	4.00000e+45	4.00000e+43	4.00000e-1
D_1 (kg/m)	5.04972e+26	6.73289e+26	6.66667e+26	1.00000e+22	1.00000e+22	1.00000e+25	5.00000e+26	4.00000e+0
D_2 (kg/m)	1.00000e+22	2.85714e+21	2.85714e+21	1.00000e+16	1.00000e+20	1.00000e+22	1.00000e+23	1.00000e+0
r_{s1} (m)	1.48523e+3	2.97046e+3	2.97046e+3	1.48523e+3	1.48523e+3	1.48523e+5	1.48523e-7	1.18819e-26
r_{s2} (m)	1.48523e+3	2.97046e+3	2.97046e+3	1.48523e-3	1.48523e+0	1.48523e+3	1.48523e+3	1.48523e-27
$D_{\text{norm},1}$	7.50001e-1	9.99991e-1	9.90155e-1	1.48523e-5	1.48523e-5	1.48523e-2	7.42617e-1	5.94093e-27
$D_{\text{norm},2}$	1.48523e-5	4.24352e-6	4.24352e-6	1.48523e-11	1.48523e-7	1.48523e-5	1.48523e-4	1.48523e-27
k_s	7.50000e-1	9.99990e-1	9.90155e-1	1.48523e-5	1.48523e-5	1.48523e-2	7.42616e-1	5.94093e-27
k_d	7.50001e-1	9.99991e-1	9.90155e-1	1.48523e-5	1.48523e-5	1.48523e-2	7.42617e-1	5.94093e-27
GTD _{s1}	1-5.00000e-1	1-9.96838e-1	1-9.00777e-1	1-7.42619e-6	1-7.42619e-6	1-7.45394e-3	1-4.92670e-1	1-2.97046e-27
GTD _{s2}	1-7.42619e-6	1-2.12176e-6	1-2.12176e-6	1-7.42616e-12	1-7.42616e-8	1-7.42619e-6	1-7.42644e-5	1-7.42616e-28
GTD _{d1}	1-5.00001e-1	1-9.96948e-1	1-9.00780e-1	1-7.42619e-6	1-7.42619e-6	1-7.45395e-3	1-4.92670e-1	1-2.97047e-27
GTD _{d2}	1-7.42619e-6	1-2.12176e-6	1-2.12176e-6	1-7.42617e-12	1-7.42617e-8	1-7.42619e-6	1-7.42644e-5	1-7.42617e-28

Table 2 Derived ratios across constraint cases.

	Case 1 $M=M, \sim \frac{4}{3}r_s$	Case 2 $M=M, \sim r_s$	Case 3 $M=M$	Case 4 $R=R$	Case 5 $\rho=\rho$	Case 6 $I=I$	Case 7 General	Case 8 Classical
$\sqrt{D_1/D_2}$	2.24716e+2	4.85439e+2	4.83046e+2	1.00000e+3	1.00000e+1	3.16228e+1	7.07107e+1	2.00000e+0
$\sqrt{(M_1\bar{R}_2)/(M_2\bar{R}_1)}$	2.24716e+2	4.85439e+2	4.83046e+2	1.00000e+3	1.00000e+1	3.16228e+1	7.07107e+1	2.00000e+0
$\sqrt{(I_1/I_2)(\bar{R}_2/\bar{R}_1)^3}$	2.24716e+2	4.85439e+2	4.83046e+2	1.00000e+3	1.00000e+1	3.16228e+1	7.07107e+1	2.00000e+0
$(I_1/I_2)^{1/5}(\rho_1/\rho_2)^{3/10}$	2.24716e+2	4.85439e+2	4.83046e+2	1.00000e+3	1.00000e+1	3.16228e+1	7.07107e+1	2.00000e+0
$(M_1\bar{R}_2)/(M_2\bar{R}_1)$	5.04972e+4	2.35651e+5	2.33333e+5	1.00000e+6	1.00000e+2	1.00000e+3	5.00000e+3	4.00000e+0
D_1/D_2	5.04972e+4	2.35651e+5	2.33333e+5	1.00000e+6	1.00000e+2	1.00000e+3	5.00000e+3	4.00000e+0
$(I_1/I_2)(\bar{R}_2/\bar{R}_1)^3$	5.04972e+4	2.35651e+5	2.33333e+5	1.00000e+6	1.00000e+2	1.00000e+3	5.00000e+3	4.00000e+0
GTD _{s1} /GTD _{s2}	1-4.99996e-1	1-9.96838e-1	1-9.00776e-1	1-7.42618e-6	1-7.35193e-6	1-7.44657e-3	1-4.92632e-1	1-2.22785e-27
GTD _{d1} /GTD _{d2}	1-4.99997e-1	1-9.96948e-1	1-9.00780e-1	1-7.42619e-6	1-7.35193e-6	1-7.44658e-3	1-4.92633e-1	1-2.22785e-27
$\sqrt{1-\text{DTD}_1^2}/\sqrt{1-\text{DTD}_2^2}$	1-4.99997e-1	1-9.96948e-1	1-9.00780e-1	1-7.42619e-6	1-7.35193e-6	1-7.44658e-3	1-4.92633e-1	1-2.22785e-27
I_1/I_2	3.92163e-10	1.80078e-11	1.83673e-11	1.00000e+6	1.00000e+5	1.00000e+0	4.00000e-38	3.20000e+1
$(I_1/I_2)^{1/2}$	1.98031e-5	4.24356e-6	4.28571e-6	1.00000e+3	3.16228e+2	1.00000e+0	2.00000e-19	5.65685e+0
$(\rho_1/\rho_2)^{1/5}(\bar{R}_1/\bar{R}_2)$	1.31430e-2	7.09728e-3	7.12540e-3	1.58489e+1	1.00000e+1	1.00000e+0	3.31445e-8	2.00000e+0
$(I_1/I_2)^{1/5}$	1.31430e-2	7.09728e-3	7.12540e-3	1.58489e+1	1.00000e+1	1.00000e+0	3.31445e-8	2.00000e+0
M_1/M_2	1.00000e+0	1.00000e+0	1.00000e+0	1.00000e+6	1.00000e+3	1.00000e+2	1.00000e-10	8.00000e+0
$\sqrt{M_1/M_2}$	1.00000e+0	1.00000e+0	1.00000e+0	1.00000e+3	3.16228e+1	1.00000e+1	1.00000e-5	2.82843e+0
$\bar{R}_1/\bar{R}_2$	1.98031e-5	4.24356e-6	4.28571e-6	1.00000e+0	1.00000e+1	1.00000e-1	2.00000e-14	2.00000e+0
$\sqrt{\bar{R}_1/\bar{R}_2}$	4.45007e-3	2.05999e-3	2.07020e-3	1.00000e+0	3.16228e+0	3.16228e-1	1.41421e-7	1.41421e+0

6.2 Case 2: ($M_1 = M_2$, $\bar{R}_1 \approx r_s$)

The two identical masses cancel, reducing the DeGerlia inertial density ratio down to a ratio of radii.

$$k_d = \frac{M_1 \bar{R}_2}{M_2 \bar{R}_1 D_{\text{crit}}} = \frac{\bar{R}_2}{\bar{R}_1 D_{\text{crit}}}$$

Note, this reflects the k calculation for gravitational time dilation, where we are comparing with r_s . Because GTD = 0 exactly at r_s , we set the comparison radius to $1.00001 r_s$, an "arbitrarily" small amount above r_s .

System properties:

	System 1 (S_1)	System 2 (S_2)
M (kg)	2.00000e30	2.00000e30
$\bar{R}$ (m)	2.97049e3	7.00000e8

Calculate DTD for each System:

$$\begin{aligned} \text{DTD} &= \sqrt{k} \quad \text{where} \quad k = M/(\bar{R} D_{\text{crit}}) \\ k_1 &= \frac{2.00000e30 \text{ kg}}{(2.97049e3 \text{ m})(6.73295e26 \text{ kg/m})} = 9.9999068441e-1 \\ \text{DTD}_1 &= \sqrt{9.9999068441e-1} = 9.9999534220e-1 \\ k_2 &= \frac{2.00000e30 \text{ kg}}{(7.00000e8 \text{ m})(6.73295e26 \text{ kg/m})} = 4.24352e-6 \\ \text{DTD}_2 &= \sqrt{4.24352e-6} = 2.05998e-3 \\ \text{DTD}_1 &= \frac{9.9999534220e-1}{2.05998e-3} = 4.85439e2 \\ \text{DTD}_2 &= \frac{2.05998e-3}{2.05998e-3} = 1 \end{aligned}$$

Calculate GTD ratio from DTD:

$$\begin{aligned} \frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} &= \frac{\sqrt{1 - \text{DTD}_1^2}}{\sqrt{1 - \text{DTD}_2^2}} = \frac{\sqrt{1 - (9.9999534220e-1)^2}}{\sqrt{1 - (2.05998e-3)^2}} \\ &= \frac{\sqrt{1 - 9.9999068441e-1}}{\sqrt{1 - 4.24352e-6}} \\ &= \frac{\sqrt{9.31559e-6}}{\sqrt{9.9999575648e-1}} \\ &= \frac{3.05214e-3}{9.9999787824e-1} = 3.05215e-3 \\ &= 1 - 9.9694785e-1 \end{aligned}$$

Verify by Calculating GTD from Schwarzschild Radius Ratio:
Schwarzschild radii:

$$\begin{aligned} r_{s1} = r_{s2} &= \frac{2GM}{c^2} = \frac{2(6.67430e-11 \text{ m}^3 \text{ kg}^{-1} \text{ s}^{-2})(2.00000e30 \text{ kg})}{(2.99792e8 \text{ m s}^{-1})^2} \\ &= 2.97046e3 \text{ m} \end{aligned}$$

Calculate k values from the r_s/R ratio:

$$\begin{aligned} k_1 &= \frac{r_{s1}}{\bar{R}_1} = \frac{2.97046e3 \text{ m}}{2.97049e3 \text{ m}} = 9.9999000010e-1 \\ k_2 &= \frac{r_{s2}}{\bar{R}_2} = \frac{2.97046e3 \text{ m}}{7.00000e8 \text{ m}} = 4.24352e-6 \end{aligned}$$

Calculate GTD via Schwarzschild radius ratio:

$$\begin{aligned} \text{GTD}_{s1} &= \sqrt{1 - k_1} = \sqrt{9.99990e-6} = 3.16226e-3 = 1 - 9.9683774e-1 \\ \text{GTD}_{s2} &= \sqrt{1 - k_2} = \sqrt{9.9999575648e-1} = 9.9999787824e-1 \\ &= 1 - 2.12176e-6 \\ \frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} &= \frac{3.16226e-3}{9.9999787824e-1} = 3.16227e-3 \\ &= 1 - 9.9683773e-1 \end{aligned}$$

Time-dilation ratio between System 1 and System 2, computed two ways:

$$\begin{aligned} \frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} &= 1 - 9.9683773e-1 \quad (\text{via } r_s) \\ \frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} &= 1 - 9.9694785e-1 \quad (\text{via } D_{\text{crit}}) \end{aligned}$$

6.3 Case 3: ($M_1 = M_2$)

The two identical masses cancel, reducing the DeGerlia inertial density ratio down to a ratio of radii.

$$k_d = \frac{M_1 \bar{R}_2}{M_2 \bar{R}_1 D_{\text{crit}}} = \frac{\bar{R}_2}{\bar{R}_1 D_{\text{crit}}}$$

Note, this is the gravitational time dilation formula. However, in this case, instead of comparing with r_s , we are comparing with $\frac{4}{3}r_s$, which equates to a gravitational time dilation of GTD = $5.00000e-1$.

System properties:

	System 1 (S_1)	System 2 (S_2)
M (kg)	2.00000e30	2.00000e30
$\bar{R}$ (m)	3.00000e3	7.00000e8

Calculate DTD for each System:

$$\begin{aligned} \text{DTD} &= \sqrt{k} \quad \text{where} \quad k = M/(\bar{R} D_{\text{crit}}) \\ k_1 &= \frac{2.00000e30 \text{ kg}}{(3.00000e3 \text{ m})(6.73295e26 \text{ kg/m})} = 9.9015538e-1 \\ \text{DTD}_1 &= \sqrt{9.9015538e-1} = 9.9506552e-1 \\ k_2 &= \frac{2.00000e30 \text{ kg}}{(7.00000e8 \text{ m})(6.73295e26 \text{ kg/m})} = 4.24352e-6 \\ \text{DTD}_2 &= \sqrt{4.24352e-6} = 2.05998e-3 \\ \text{DTD}_1 &= \frac{9.9506552e-1}{2.05998e-3} = 4.83046e2 \\ \text{DTD}_2 &= \frac{2.05998e-3}{2.05998e-3} = 1 \end{aligned}$$

Calculate GTD ratio from DTD:

$$\begin{aligned} \frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} &= \frac{\sqrt{1 - \text{DTD}_1^2}}{\sqrt{1 - \text{DTD}_2^2}} = \frac{\sqrt{1 - (9.9506552e-1)^2}}{\sqrt{1 - (2.05998e-3)^2}} \\ &= \frac{\sqrt{1 - 9.9015538e-1}}{\sqrt{1 - 4.24352e-6}} \\ &= \frac{\sqrt{9.84462e-3}}{\sqrt{9.9999575648e-1}} \\ &= \frac{9.92201e-2}{9.9999787824e-1} = 9.92203e-2 \\ &= 1 - 9.007797e-1 \end{aligned}$$

Verify by Calculating GTD from Schwarzschild Radius Ratio:
Schwarzschild radii:

$$\begin{aligned} r_{s1} = r_{s2} &= \frac{2GM}{c^2} = \frac{2(6.67430e-11 \text{ m}^3 \text{ kg}^{-1} \text{ s}^{-2})(2.00000e30 \text{ kg})}{(2.99792e8 \text{ m s}^{-1})^2} \\ &= 2.97046e3 \text{ m} \end{aligned}$$

Calculate k values from the r_s/R ratio:

$$\begin{aligned} k_1 &= \frac{r_{s1}}{\bar{R}_1} = \frac{2.97046e3 \text{ m}}{3.00000e3 \text{ m}} = 9.9015470e-1 \\ k_2 &= \frac{r_{s2}}{\bar{R}_2} = \frac{2.97046e3 \text{ m}}{7.00000e8 \text{ m}} = 4.24352e-6 \end{aligned}$$

Calculate GTD via Schwarzschild radius ratio:

$$\begin{aligned} \text{GTD}_{s1} &= \sqrt{1 - k_1} = \sqrt{9.84530e-3} = 9.92235e-2 = 1 - 9.007765e-1 \\ \text{GTD}_{s2} &= \sqrt{1 - k_2} = \sqrt{9.9999575648e-1} = 9.9999787824e-1 \\ &= 1 - 2.12176e-6 \\ \frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} &= \frac{9.92235e-2}{9.9999787824e-1} = 9.92237e-2 \\ &= 1 - 9.007763e-1 \end{aligned}$$

Time-dilation ratio between System 1 and System 2, computed two ways:

$$\begin{aligned} \frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} &= 1 - 9.007763e-1 \quad (\text{via } r_s) \\ \frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} &= 1 - 9.007797e-1 \quad (\text{via } D_{\text{crit}}) \end{aligned}$$

6.4 Case 4: ($R_1 = R_2$)

When the two systems share the same radius, the radius terms cancel in k_d :

$$k_d = \frac{M_1 \bar{R}_2}{M_2 \bar{R}_1 D_{\text{crit}}} = \frac{M_1}{M_2 D_{\text{crit}}}$$

The DeGerlia inertial density ratio reduces to a ratio of masses. The Lorentz factor has the same form as Equation 4, with $k = v^2/c^2$. Since velocity is distance per unit time, v^2/c^2 is the square of a ratio of two lengths, with the shared time unit cancelling. Gravitational time dilation confirms this directly: $v^2/c^2 = r_s/\bar{R}$ via the escape velocity identity, so the velocity-based k of special relativity and the radius-based k of general relativity are the same length ratio.

$$= 9.9999257382e-1 = 1 - 7.42618e-6$$

Time-dilation ratio between System 1 and System 2, computed two ways:

$$\begin{aligned} \frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} &= 1 - 7.42618e-6 \quad (\text{via } r_s) \\ \frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} &= 1 - 7.42619e-6 \quad (\text{via } D_{\text{crit}}) \end{aligned}$$

System properties:

	System 1 (S_1)	System 2 (S_2)
M (kg)	1.00000e30	1.00000e24
$\bar{R}$ (m)	1.00000e8	1.00000e8

Calculate DTD for each System:

$$\text{DTD} = \sqrt{k} \quad \text{where} \quad k = M/(\bar{R}D_{\text{crit}})$$

$$k_1 = \frac{1.00000e30 \text{ kg}}{(1.00000e8 \text{ m})(6.73295e26 \text{ kg/m})} = 1.48523e-5$$

$$\text{DTD}_1 = \sqrt{1.48523e-5} = 3.85387e-3$$

$$k_2 = \frac{1.00000e24 \text{ kg}}{(1.00000e8 \text{ m})(6.73295e26 \text{ kg/m})} = 1.48523e-11$$

$$\text{DTD}_2 = \sqrt{1.48523e-11} = 3.85387e-6$$

$$\frac{\text{DTD}_1}{\text{DTD}_2} = \frac{3.85387e-3}{3.85387e-6} = 1.00000e3$$

Calculate GTD ratio from DTD:

$$\begin{aligned} \frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} &= \frac{\sqrt{1 - \text{DTD}_1^2}}{\sqrt{1 - \text{DTD}_2^2}} = \frac{\sqrt{1 - (3.85387e-3)^2}}{\sqrt{1 - (3.85387e-6)^2}} \\ &= \frac{\sqrt{1 - 1.48523e-5}}{\sqrt{1 - 1.48523e-11}} \\ &= \frac{\sqrt{9.999851477e-1}}{\sqrt{9.999999999851477e-1}} \\ &= \frac{9.9999257381e-1}{9.999999999257383e-1} = 9.9999257381e-1 \\ &= 1 - 7.42619e-6 \end{aligned}$$

Verify by Calculating GTD from Schwarzschild Radius Ratio: Schwarzschild radii:

$$\begin{aligned} r_{s1} &= \frac{2GM_1}{c^2} = \frac{2(6.67430e-11 \text{ m}^3 \text{ kg}^{-1} \text{ s}^{-2})(1.00000e30 \text{ kg})}{(2.99792e8 \text{ m s}^{-1})^2} \\ &= 1.48523e3 \text{ m} \end{aligned}$$

$$\begin{aligned} r_{s2} &= \frac{2GM_2}{c^2} = \frac{2(6.67430e-11 \text{ m}^3 \text{ kg}^{-1} \text{ s}^{-2})(1.00000e24 \text{ kg})}{(2.99792e8 \text{ m s}^{-1})^2} \\ &= 1.48523e-3 \text{ m} \end{aligned}$$

Calculate k values from the $r_s/\bar{R}$ ratio:

$$\begin{aligned} k_1 &= \frac{r_{s1}}{\bar{R}_1} = \frac{1.48523e3 \text{ m}}{1.00000e8 \text{ m}} = 1.48523e-5 \\ k_2 &= \frac{r_{s2}}{\bar{R}_2} = \frac{1.48523e-3 \text{ m}}{1.00000e8 \text{ m}} = 1.48523e-11 \end{aligned}$$

Calculate GTD via Schwarzschild radius ratio:

$$\begin{aligned} \text{GTD}_{s1} &= \sqrt{1 - k_1} = \sqrt{9.999851477e-1} = 9.9999257381e-1 \\ &= 1 - 7.42619e-6 \end{aligned}$$

$$\begin{aligned} \text{GTD}_{s2} &= \sqrt{1 - k_2} = \sqrt{9.999999999851477e-1} \\ &= 9.999999999257384e-1 = 1 - 7.42616e-12 \end{aligned}$$

$$\frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} = \frac{9.9999257381e-1}{9.999999999257384e-1}$$

6.5 Case 5: ($\rho_1 = \rho_2$)

When the two systems share the same density, $M \propto \bar{R}^3$, so $M_1/M_2 = (\bar{R}_1/\bar{R}_2)^3$. Substituting into k_d :

$$k_d = \frac{M_1 \bar{R}_2}{M_2 \bar{R}_1 D_{\text{crit}}} = \left(\frac{\bar{R}_1}{\bar{R}_2} \right)^3 \cdot \frac{\bar{R}_2}{\bar{R}_1 D_{\text{crit}}} = \frac{1}{D_{\text{crit}}} \left(\frac{\bar{R}_1}{\bar{R}_2} \right)^2$$

The DeGerlia inertial density ratio reduces to the square of the radius ratio; the linear scale factor follows as $\sqrt{k_d} = \bar{R}_1/\bar{R}_2$, recovering the isometric equivalence.

System properties:

	System 1 (S_1)	System 2 (S_2)
M (kg)	1.00000e30	1.00000e27
$\bar{R}$ (m)	1.00000e8	1.00000e7

Calculate DTD for each System:

$$\text{DTD} = \sqrt{k} \quad \text{where} \quad k = M/(\bar{R} D_{\text{crit}})$$

$$k_1 = \frac{1.00000e30 \text{ kg}}{(1.00000e8 \text{ m})(6.73295e26 \text{ kg/m})} = 1.48523e-5$$

$$\text{DTD}_1 = \sqrt{1.48523e-5} = 3.85387e-3$$

$$k_2 = \frac{1.00000e27 \text{ kg}}{(1.00000e7 \text{ m})(6.73295e26 \text{ kg/m})} = 1.48523e-7$$

$$\text{DTD}_2 = \sqrt{1.48523e-7} = 3.85387e-4$$

$$\text{DTD}_1 = \frac{3.85387e-3}{3.85387e-4} = 1.00000e1$$

$$\text{DTD}_2 = 3.85387e-4$$

Calculate GTD ratio from DTD:

$$\begin{aligned} \frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} &= \frac{\sqrt{1 - \text{DTD}_1^2}}{\sqrt{1 - \text{DTD}_2^2}} = \frac{\sqrt{1 - (3.85387e-3)^2}}{\sqrt{1 - (3.85387e-4)^2}} \\ &= \frac{\sqrt{1 - 1.48523e-5}}{\sqrt{1 - 1.48523e-7}} \\ &= \frac{\sqrt{9.999851477e-1}}{\sqrt{9.9999851477e-1}} \\ &= \frac{9.9999257381e-1}{9.99999257383e-1} = 9.9999264807e-1 \\ &= 1 - 7.35193e-6 \end{aligned}$$

Verify by Calculating GTD from Schwarzschild Radius Ratio:

Schwarzschild radii:

$$r_{s1} = \frac{2GM_1}{c^2} = \frac{2(6.67430e-11 \text{ m}^3 \text{ kg}^{-1} \text{ s}^{-2})(1.00000e30 \text{ kg})}{(2.99792e8 \text{ m s}^{-1})^2}$$

$$= 1.48523e3 \text{ m}$$

$$r_{s2} = \frac{2GM_2}{c^2} = \frac{2(6.67430e-11 \text{ m}^3 \text{ kg}^{-1} \text{ s}^{-2})(1.00000e27 \text{ kg})}{(2.99792e8 \text{ m s}^{-1})^2}$$

$$= 1.48523 \text{ m}$$

Calculate k values from the r_s/R ratio:

$$k_1 = \frac{r_{s1}}{\bar{R}_1} = \frac{1.48523e3 \text{ m}}{1.00000e8 \text{ m}} = 1.48523e-5$$

$$k_2 = \frac{r_{s2}}{\bar{R}_2} = \frac{1.48523 \text{ m}}{1.00000e7 \text{ m}} = 1.48523e-7$$

Calculate GTD via Schwarzschild radius ratio:

$$\text{GTD}_{s1} = \sqrt{1 - k_1} = \sqrt{9.999851477e-1} = 9.9999257381e-1$$

$$= 1 - 7.42619e-6$$

$$\text{GTD}_{s2} = \sqrt{1 - k_2} = \sqrt{9.9999851477e-1} = 9.99999257384e-1$$

$$= 1 - 7.42616e-8$$

$$\frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} = \frac{9.9999257381e-1}{9.99999257384e-1}$$

$$= 9.9999264807e-1 = 1 - 7.35193e-6$$

Time-dilation ratio between System 1 and System 2, computed two ways:

$$\frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} = 1 - 7.35193e-6 \quad (\text{via } r_s)$$

$$\frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} = 1 - 7.35193e-6 \quad (\text{via } D_{\text{crit}})$$

$$\frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} = 1 - 7.35193e-6 \quad (\text{via } D_{\text{crit}})$$

6.6 Case 6: ($I_1 = I_2$)

When the two systems share the same moment of inertia, $M_1 \bar{R}_1^2 = M_2 \bar{R}_2^2$, so $M_1/M_2 = (\bar{R}_2/\bar{R}_1)^2$. Substituting into k_d :

$$k_d = \frac{M_1 \bar{R}_2}{M_2 \bar{R}_1 D_{\text{crit}}} = \left(\frac{\bar{R}_2}{\bar{R}_1} \right)^2 \cdot \frac{\bar{R}_2}{\bar{R}_1 D_{\text{crit}}} = \frac{1}{D_{\text{crit}}} \left(\frac{\bar{R}_2}{\bar{R}_1} \right)^3$$

The DeGerlia inertial density ratio reduces to the cube of the radius ratio.

System properties:

	System 1 (S_1)	System 2 (S_2)
M (kg)	1.00000e32	1.00000e30
$\bar{R}$ (m)	1.00000e7	1.00000e8

Calculate DTD for each System:

$$\text{DTD} = \sqrt{k} \quad \text{where} \quad k = M/(\bar{R} D_{\text{crit}})$$

$$k_1 = \frac{1.00000e32 \text{ kg}}{(1.00000e7 \text{ m})(6.73295e26 \text{ kg/m})} = 1.48523e-2$$

$$\text{DTD}_1 = \sqrt{1.48523e-2} = 1.21870e-1$$

$$k_2 = \frac{1.00000e30 \text{ kg}}{(1.00000e8 \text{ m})(6.73295e26 \text{ kg/m})} = 1.48523e-5$$

$$\text{DTD}_2 = \sqrt{1.48523e-5} = 3.85387e-3$$

$$\frac{\text{DTD}_1}{\text{DTD}_2} = \frac{1.21870e-1}{3.85387e-3} = 3.16228e1$$

$$\text{DTD}_2 = 3.85387e-3$$

Calculate GTD ratio from DTD:

$$\begin{aligned} \frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} &= \frac{\sqrt{1 - \text{DTD}_1^2}}{\sqrt{1 - \text{DTD}_2^2}} = \frac{\sqrt{1 - (1.21870e-1)^2}}{\sqrt{1 - (3.85387e-3)^2}} \\ &= \frac{\sqrt{1 - 1.48523e-2}}{\sqrt{1 - 1.48523e-5}} \\ &= \frac{\sqrt{9.851477e-1}}{\sqrt{9.999851477e-1}} \\ &= \frac{9.9254605e-1}{9.9999257381e-1} = 9.9255342e-1 \\ &= 1 - 7.44658e-3 \end{aligned}$$

Verify by Calculating GTD from Schwarzschild Radius Ratio:

Schwarzschild radii:

$$r_{s1} = \frac{2GM_1}{c^2} = \frac{2(6.67430e-11 \text{ m}^3 \text{ kg}^{-1} \text{ s}^{-2})(1.00000e32 \text{ kg})}{(2.99792e8 \text{ m s}^{-1})^2}$$

$$= 1.48523e5 \text{ m}$$

$$r_{s2} = \frac{2GM_2}{c^2} = \frac{2(6.67430e-11 \text{ m}^3 \text{ kg}^{-1} \text{ s}^{-2})(1.00000e30 \text{ kg})}{(2.99792e8 \text{ m s}^{-1})^2}$$

$$= 1.48523e3 \text{ m}$$

Calculate k values from the r_s/R ratio:

$$k_1 = \frac{r_{s1}}{\bar{R}_1} = \frac{1.48523e5 \text{ m}}{1.00000e7 \text{ m}} = 1.48523e-2$$

$$k_2 = \frac{r_{s2}}{\bar{R}_2} = \frac{1.48523e3 \text{ m}}{1.00000e8 \text{ m}} = 1.48523e-5$$

Calculate GTD via Schwarzschild radius ratio:

$$\text{GTD}_{s1} = \sqrt{1 - k_1} = \sqrt{9.851477e-1} = 9.9254606e-1 = 1 - 7.45394e-3$$

$$\text{GTD}_{s2} = \sqrt{1 - k_2} = \sqrt{9.999851477e-1} = 9.9999257381e-1$$

$$= 1 - 7.42619e-6$$

$$\frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} = \frac{9.9254606e-1}{9.9999257381e-1} = 9.9255343e-1$$

$$= 1 - 7.44657e-3$$

Time-dilation ratio between System 1 and System 2, computed two ways:

$$\frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} = 1 - 7.44657e-3 \quad (\text{via } r_s)$$

$$\frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} = 1 - 7.44658e-3 \quad (\text{via } D_{\text{crit}})$$

$$\frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} = 1 - 7.44658e-3 \quad (\text{via } D_{\text{crit}})$$

6.7 Case 7: (General, unconstrained)

When no constraint is applied between the systems, k_d stays in its full form:

$$k_d = \frac{M_1 \bar{R}_2}{M_2 \bar{R}_1 D_{\text{crit}}}$$

Both mass and radius must be specified independently for each system.

System properties:		
	System 1 (S_1)	System 2 (S_2)
M (kg)	1.00000e20	1.00000e30
$\bar{R}$ (m)	2.00000e−7	1.00000e7

Calculate DTD for each System:

$$\text{DTD} = \sqrt{k} \quad \text{where} \quad k = M/(\bar{R}D_{\text{crit}})$$

$$k_1 = \frac{1.00000\text{e}20\text{ kg}}{(2.00000\text{e}-7\text{ m})(6.73295\text{e}26\text{ kg/m})} = 7.42617\text{e}-1$$

$$\text{DTD}_1 = \sqrt{7.42617\text{e}-1} = 8.61752\text{e}-1$$

$$k_2 = \frac{1.00000\text{e}30\text{kg}}{(1.00000\text{e}7\text{m})(6.73295\text{e}26\text{kg/m})} = 1.48523\text{e}-4$$

$$\text{DTD}_2 = \sqrt{1.48523\text{e-}4} = 1.21870\text{e-}2$$

$$\underline{\underline{\text{DTD}_1 = 8.61752\text{e}-1}}}$$

$$\overline{\text{DTD}_2} = \overline{1.21870\text{e}-2} = 7.07107\text{e1}$$

Calculate GTD ratio from DTD:

$$\begin{aligned} \frac{GTD_{d1}}{GTD_{d2}} &= \frac{\sqrt{1-DTD_1^2}}{\sqrt{1-DTD_2^2}} = \frac{\sqrt{1-(8.61752e-1)^2}}{\sqrt{1-(1.21870e-2)^2}} \\ &= \frac{\sqrt{1-7.42617e-1}}{\sqrt{1-1.48523e-4}} \\ &= \frac{\sqrt{2.57383e-1}}{\sqrt{9.99851477e-1}} \\ &= \frac{5.07330e-1}{9.999257356e-1} = 5.07367e-1 \\ &= 1 - 4.92633e-1 \end{aligned}$$

Verify by Calculating GTD from Schwarzschild Radius Ratio:
Schwarzschild radii:

$$\begin{aligned} r_{s1} &= \frac{2GM_1}{c^2} = \frac{2(6.67430\text{e}-11\text{ m}^3\text{ kg}^{-1}\text{ s}^{-2})(1.00000\text{e}20\text{ kg})}{(2.99792\text{e}8\text{ m s}^{-1})^2} \\ &= 1.48523\text{e}-7\text{ m} \\ r_{s2} &= \frac{2GM_2}{c^2} = \frac{2(6.67430\text{e}-11\text{ m}^3\text{ kg}^{-1}\text{ s}^{-2})(1.00000\text{e}30\text{ kg})}{(2.99792\text{e}8\text{ m s}^{-1})^2} \\ &= 1.48523\text{e}3\text{ m} \end{aligned}$$

Calculate k values from the r_s/R ratio:

$$\begin{aligned} k_1 &= \frac{r_{s1}}{\bar{R}_1} = \frac{1.48523\text{e-}7\text{m}}{2.00000\text{e-}7\text{m}} = 7.42616\text{e-}1 \\ k_2 &= \frac{r_{s2}}{\bar{R}_2} = \frac{1.48523\text{e}3\text{m}}{1.00000\text{e}7\text{m}} = 1.48523\text{e-}4 \end{aligned}$$

Calculate GTD via Schwarzschild radius ratio:

$$\begin{aligned} \text{GTD}_{s1} &= \sqrt{1 - k_1} = \sqrt{2.57384\text{e-}1} = 5.07330\text{e-}1 = 1 - 4.92670\text{e-}1 \\ \text{GTD}_{s2} &= \sqrt{1 - k_2} = \sqrt{9.99851477\text{e-}1} = 9.999257356\text{e-}1 \\ &= 1 - 7.42644\text{e-}5 \\ \frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} &= \frac{5.07330\text{e-}1}{9.999257356\text{e-}1} = 5.07368\text{e-}1 \\ &= 1 - 4.92632\text{e-}1 \end{aligned}$$

Time-dilation ratio between System 1 and System 2, computed two ways:

$$\frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} = 1 - 4.92632\text{e-1} \quad (\text{via } r_s)$$

$$\frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} = 1 - 4.92633\text{e-1} \quad (\text{via } D_{\text{crit}})$$

6.8 Case 8: (Classical)

System properties:		
	System 1 (S_1)	System 2 (S_2)
M (kg)	8.00000	1.00000
$\bar{R}$ (m)	2.00000	1.00000

Calculate DTD for each System:

$$\text{DTD} = \sqrt{k} \quad \text{where} \quad k = M/(\bar{R}D_{\text{crit}})$$

$$k_1 = \frac{8.00000\text{kg}}{(2.00000\text{m})(6.73295\text{e}26\text{kg/m})} = 5.94093\text{e-}27$$

$$\text{DTD}_1 = \sqrt{5.94093\text{e}-27} = 7.70774\text{e}-14$$

$$k_2 = \frac{1.00000\text{kg}}{(1.00000\text{m})(6.73295\text{e}26\text{kg/m})} = 1.48523\text{e-}27$$

$$\text{DTD}_2 = \sqrt{1.48523\text{e}-27} = 3.85387\text{e}-14$$

$$\frac{\text{DTD}_1}{\text{}} = \frac{7.70774\text{e-}14}{\text{}} = 2.00000$$

$$\overline{\text{DTD}_2} = 3.85387\text{e-}14 = 2.00000$$

Calculate GTD ratio from DTD:

[illegible]

Verify by Calculating GTD from Schwarzschild Radius Ratio:
Schwarzschild radii:

$$\begin{aligned} r_{s1} &= \frac{2GM_1}{c^2} = \frac{2(6.67430\text{e-}11\text{ m}^3\text{ kg}^{-1}\text{ s}^{-2})(8.00000\text{ kg})}{(2.99792\text{e}8\text{ m s}^{-1})^2} \\ &= 1.18819\text{e-}26\text{ m} \\ r_{s2} &= \frac{2GM_2}{c^2} = \frac{2(6.67430\text{e-}11\text{ m}^3\text{ kg}^{-1}\text{ s}^{-2})(1.00000\text{ kg})}{(2.99792\text{e}8\text{ m s}^{-1})^2} \\ &= 1.48523\text{e-}27\text{ m} \end{aligned}$$

Calculate k values from the r_s/R ratio:

$$\begin{aligned} k_1 &= \frac{r_{s1}}{\bar{R}_1} = \frac{1.18819\text{e-}26\text{ m}}{2.00000\text{ m}} = 5.94093\text{e-}27 \\ k_2 &= \frac{r_{s2}}{\bar{R}_2} = \frac{1.48523\text{e-}27\text{ m}}{1.00000\text{ m}} = 1.48523\text{e-}27 \end{aligned}$$

Calculate GTD via Schwarzschild radius ratio:

[illegible]

Time-dilation ratio between System 1 and System 2, computed two ways:

$$\frac{\text{GTD}_{s1}}{\text{GTD}_{s2}} = 1 - 2.22785\text{e-}27 \quad (\text{via } r_s)$$

$$\frac{\text{GTD}_{d1}}{\text{GTD}_{d2}} = 1 - 2.22785\text{e-}27 \quad (\text{via } D_{\text{crit}})$$

7 Analysis

The reformulation is meant to carry three points, and nothing more ambitious. First, it is a pace-of-time framework that is sim-

ply easier to work with: expressed in DTD and compactness, comparing two systems is a direct ratio of geometries, with no benchmark, no subtraction-from-one, and — because D_{crit} cancels — no dependence on G . One returns to GTD, the $\sqrt{1-k}$ form, only at the final step, to convert relative pace into relative clock time. Second, general relativity is always two-system; we merely masquerade it as one. Conventional gravitational time dilation looks like a single-system calculation only because it silently fixes the second system — the same mass at its Schwarzschild radius, where $\text{DTD} = 1$. Make that benchmark explicit and the two-system structure, present all along, is plain. Third, treating it as one system is a disservice to the broader mathematics: the collapse to a single system rests on presuming that some property of the hidden second system is a fixed, universal given, a presumption that obscures the real structure and perpetuates a misconception that dilutes the core principle. The honest formulation keeps both systems in view and recognizes the single-system shortcut as a convenience, not as the underlying physics.

8 Conclusions

9 Hypotheses of Explanation

10 Further Exploration

Acknowledgments

This work was conducted independently and received no external funding.

Conflicts of Interest

The author declares no competing interests.

Data Availability

The complete source materials for this paper, including all $\text{\LaTeX}$ source files, derivation documents, and revision history, are publicly available at: https://github.com/denverdata/academic_InertialRelativity_STE_cases.

References

- [1] T. D. DeGerlia, *Introducing Inertial Density and Characterizing the Schwarzschild Condition as a Constant Threshold of Mass over Radius (m/r)*, DEC, 2025, DOI: 10.55277/researchhub.0e0cgoor.
- [2] A. Alho, J. Natário, P. Pani and G. Raposo, *Physical Review D*, 2022, **106**, L041502.
- [3] T. D. DeGerlia, *The Universe of Light - Exploring our Universe through the Lens of the Law of Space-Time Equivalence*, DEC, 2025, DOI: 10.55277/ResearchHub.pi9yjshm.
- [4] K. Schwarzschild, *Sitzungsberichte der Königlich Preussischen Akademie der Wissenschaften (Berlin)*, 1916, 189–196.
- [5] E. Tiesinga, P. J. Mohr, D. B. Newell and B. N. Taylor, *Reviews of Modern Physics*, 2021, **93**, 025010.
- [6] A. Einstein, *Annalen der Physik*, 1905, **17**, 891–921.
- [7] A. Einstein, *Sitzungsberichte der Königlich Preussischen Akademie der Wissenschaften (Berlin)*, 1915, 844–847.
- [8] R. P. Kerr, *Physical Review Letters*, 1963, **11**, 237–238.
- [9] H. Goldstein, C. Poole and J. Safko, *Classical Mechanics*, Addison-Wesley, 3rd edn, 2002, pp. 70–71.