

# WPI

# Human Context Recognition: A Controllable GAN Approach

Joshua DeOliveira, Worcester Polytechnic Institute

Harrison Kim, Northeastern University

MaryClare Martin, College of the Holy Cross

Faculty Advisor: Prof. Elke Rundensteiner

Ph.D. Mentor: Walter Gerych

*Funded by NSF Grant #1852498*

# Progress Summary

---


1. Cleaned our existing codebase by making our programs more modular.
2. Began implementing a Controllable GAN by building user and activity classifiers (explained later).
3. Established a third metric for evaluating the performance of our GAN architectures.
4. Continued exploring our novel methodology for training simple GANs by tuning hyperparameters.
5. Gathered preliminary results demonstrating the benefits of our training methodology over existing practices.

# Modularization of Vanilla GAN

---

- Broke GAN up into functions
- Added comments to specify parameters and return values
- GAN runs in 3 lines with easy specification of parameters

# Controllable GAN



# Controllable GAN Activity Classifier

## Standard Classifier


	precision	recall	f1-score	support
0	0.916	0.960	0.938	682
1	0.948	0.906	0.926	319
2	0.723	0.515	0.602	66
accuracy			0.917	1067
macro avg	0.862	0.794	0.822	1067
weighted avg	0.914	0.917	0.914	1067

## SMOTE-Augmented Classifier

	precision	recall	f1-score	support
0	0.929	0.853	0.889	659
1	0.939	0.955	0.947	627
2	0.897	0.961	0.928	595
accuracy			0.921	1881
macro avg	0.921	0.923	0.921	1881
weighted avg	0.922	0.921	0.921	1881

# Evaluating Our GAN Architectures


Real & Fake Data




Train




Logistic Regression




Only Real Data



Train




Compare Performance  
on Real Test Data



# Conventional GAN Training Methodology

**5/2 Training Ratio**



[1] Lim et al. "Geometric GAN"

[2] Lin, Muyang et. al "GAN Compression: Efficient Architectures for Interactive Conditional GANs"

[3] Lei, Kai et. al "GCN-GAN: A Non-linear Temporal Link Prediction Model for Weighted Dynamic Networks"

[4] Lee, Hyeungill et. al "Generative Adversarial Trainer: Defense to Adversarial Perturbations with GAN"

[5] Mescheder, Lars et. al "Which Training Methods for GANs do actually Converge?"

[6] Gao, Lianli et. al "Lightweight dynamic conditional GAN with pyramid attention for text-to-image synthesis"

[7] Mirza Mehdi, "Conditional Generative Adversarial Nets"

[8] Lee, Minhyeok et. al, "Controllable Generative Adversarial Network"

[9] Goodfellow et. al, "Generative Adversarial Nets"

[10] Shoshan et. al, "GAN-Control: Explicitly Controllable GANs"

# Conventional GAN Training Methodology

---

## Original Motivation

- Stable training is an open problem
- Alternates training
- Simple to implement
- Involves only 2 hyper-parameters
- Ensures **D** is always better than **G**


## Flaws

- **D** can be overtrained
- Leads to inefficient computation
- Minority of epochs spent training **G**
- Doesn't maintain a sense of fair competition between machines




# Proposed Methodology: Dynamic Training


**Phase 1:** Conventional training for first  $T$  epochs



**Phase 2:** Train  $D$  until model yields minimum recall  $R$



**Phase 3:** Switch which machine to train based on fpR



# How Does Dynamic Training Add Value?

---

## Assumptions:

1. Similar runtime for training each machine for an epoch
2. Limited time and/or resources


## Improvements on Conventional Training:

1. Improves training stability
2. Reduces frequency of redundant/inefficient epochs
3. Leads to equal to or quicker convergence
4. Maximizes training of **G**
5. Negligibly additional computation


# Preliminary Results: Median Wasserstein

---

Conventional Training




Dynamic Training




# Preliminary Results: Mean Wasserstein

---



Conventional Training



Dynamic Training



# Preliminary Results: Wasserstein Difference




# Next Steps

---

1. Integrate user and activity classifiers into the main Controllable GAN architecture.
2. Train a Controllable GAN to generate 3 different types of activities undertaken by 3 users.
3. Expand the GAN to generate  $n$  different types of activities undertaken by  $m$  users.
4. Begin updating the GAN for time-series data generation.

# Controllable GAN



Pretrained  
User Classifier

Pretrained  
Label Classifier

Real time series data

