

# Index

## Symbols

---

.trm files, [7-8](#)

## A

---

abort response, [34-12](#)

two-phase commit, [34-12](#)

accounts

creating for materialized views, [38-5](#)

DBA operating system account, [1-21](#)

adaptive query optimization

adaptive plans, [7-42](#)

adaptive query plans, [7-42](#)

ADD LOGFILE clause

ALTER DATABASE statement, [9-13](#)

ADD LOGFILE MEMBER clause

ALTER DATABASE statement, [9-13](#)

adding

columns, [19-62](#)

columns in compressed tables, [19-62](#)

ADMIN\_TABLES procedure

DBMS\_REPAIR package, [24-2](#)

example, [24-9](#)

ADMINISTER\_RESOURCE\_MANAGER system  
privilege, [26-31](#)

administering

the Scheduler, [29-1](#)

administration

distributed databases, [32-1](#)

administrative user accounts, [1-22](#)

SYS, [1-21](#)

SYSBACKUP, [1-21](#)

SYSDG, [1-21](#)

SYSKM, [1-21](#)

administrator passwords, synchronizing password  
file and data dictionary, [1-45](#)

ADR

See automatic diagnostic repository

ADR base, [7-11](#)

ADR home, [7-11](#)

ADRCI utility, [7-11](#)

advanced index compression, [20-20](#)

advanced row compression, [19-8](#)

Advisor

Data Repair, [7-3](#)

Advisor (*continued*)

Undo, [14-8](#)

AFTER SUSPEND trigger

example of registering, [18-15](#)

agent

Heterogeneous Services, definition of, [31-5](#)

aggregate functions

statement transparency in distributed  
databases, [32-29](#)

alert log, [7-7](#)

about, [6-2](#)

size of, [6-3](#)

using, [6-2](#)

viewing, [7-40](#)

when written, [6-5](#)

alert thresholds

setting for locally managed tablespaces, [18-3](#)

alerts

server-generated, [6-6](#)

tablespace space usage, [18-3](#)

threshold-based, [6-6](#)

viewing, [18-5](#)

ALL\_DB\_LINKS view, [32-19](#)

allocation

extents, [19-61](#)

ALTER CLUSTER statement

ALLOCATE EXTENT clause, [21-7](#)

using for hash clusters, [22-11](#)

using for index clusters, [21-7](#)

ALTER DATABASE statement

ADD LOGFILE clause, [9-13](#)

ADD LOGFILE MEMBER clause, [9-13](#)

ARCHIVELOG clause, [10-5](#)

CLEAR LOGFILE clause, [9-18](#)

DATAFILE...OFFLINE DROP clause, [12-9](#)

DROP LOGFILE clause, [9-16](#)

DROP LOGFILE MEMBER clause, [9-16](#)

NOARCHIVELOG clause, [10-5](#)

RENAME FILE clause, [12-16](#)

UNRECOVERABLE DATAFILE clause, [9-18](#)

ALTER INDEX statement

COALESCE clause, [20-10](#)

ALTER SEQUENCE statement, [23-17](#)

ALTER SESSION statement

ADVISE clause, [35-8](#)

CLOSE DATABASE LINK clause, [33-2](#)

- ALTER SESSION statement (*continued*)
  - Enabling resumable space allocation, [18-11](#)
- ALTER SYSTEM FLUSH FLASH\_CACHE, [4-31](#)
- ALTER SYSTEM statement
  - ARCHIVE LOG ALL clause, [10-6](#)
  - DISABLE DISTRIBUTED RECOVERY
    - clause, [35-22](#)
  - ENABLE DISTRIBUTED RECOVERY clause, [35-22](#)
  - enabling Database Resource Manager, [26-39](#)
  - SET RESOURCE\_MANAGER\_PLAN, [26-39](#)
  - SET SHARED\_SERVERS initialization
    - parameter, [3-12](#)
  - SWITCH LOGFILE clause, [9-17](#)
- ALTER TABLE statement
  - ALLOCATE EXTENT clause, [19-61](#)
  - DEALLOCATE UNUSED clause, [19-61](#)
  - DISABLE ALL TRIGGERS clause, [17-12](#)
  - DISABLE integrity constraint clause, [17-18](#)
  - DROP COLUMN clause, [19-64](#)
  - DROP integrity constraint clause, [17-19](#)
  - DROP UNUSED COLUMNS clause, [19-65](#)
  - ENABLE ALL TRIGGERS clause, [17-12](#)
  - ENABLE integrity constraint clause, [17-18](#)
  - external tables, [19-146](#)
  - modifying index-organized table attributes, [19-134](#)
  - MOVE clause, [19-58–19-60](#), [19-134](#)
  - reasons for use, [19-57](#)
  - SET UNUSED clause, [19-65](#)
- ALTER TABLESPACE statement
  - adding an Oracle managed data file, example, [15-18](#)
  - adding an Oracle managed temp file,
    - example, [15-19](#)
  - ONLINE clause, example, [11-24](#)
  - READ ONLY clause, [11-25](#)
  - RENAME DATAFILE clause, [12-14](#)
- ALTER TRIGGER statement
  - DISABLE clause, [17-12](#)
  - ENABLE clause, [17-12](#)
- altering
  - (Scheduler) windows, [28-76](#)
  - event schedule, [28-41](#)
  - event-based job, [28-40](#)
  - indexes, [20-24](#)
  - job classes, [28-72](#)
  - jobs, [28-19](#)
  - programs, [28-28](#)
  - schedules, [28-31](#)
- ANALYZE statement
  - CASCADE clause, [17-5](#)
  - CASCADE clause, FAST option, [17-5](#)
  - corruption reporting, [24-5](#)
  - listing chained rows, [17-6](#)
  - remote tables, [33-6](#)
- ANALYZE statement (*continued*)
  - validating structure, [17-5](#), [24-4](#)
- analyzing schema objects, [17-4](#)
- analyzing tables
  - distributed processing, [33-6](#)
- AND condition
  - for simple subquery materialized views, [36-19](#)
- APPEND hint, [19-11](#)
- application development
  - distributed databases, [31-41](#), [33-1](#), [33-10](#)
- application development for distributed
  - databases, [33-1](#)
  - analyzing execution plan, [33-8](#)
  - database links, controlling connections, [33-2](#)
  - handling errors, [33-2](#), [33-10](#)
  - handling remote procedure errors, [33-10](#)
  - managing distribution of data, [33-1](#)
  - managing referential integrity constraints, [33-2](#)
  - terminating remote connections, [33-2](#)
  - tuning distributed queries, [33-3](#)
  - tuning using collocated inline views, [33-4](#)
  - using cost-based optimization, [33-5](#)
  - using hints to tune queries, [33-7](#)
- archived redo log files
  - alternate destinations, [10-14](#)
  - archiving modes, [10-5](#)
  - data dictionary views, [10-20](#)
  - destination availability state, controlling, [10-14](#)
  - destination status, [10-13](#)
  - destinations, groups, [10-11](#)
  - destinations, specifying, [10-7](#)
  - failed destinations and, [10-15](#)
  - mandatory destinations, [10-16](#)
  - multiplexing, [10-7](#)
  - normal transmission of, [10-14](#)
  - re-archiving to failed destination, [10-18](#)
  - sample destination scenarios, [10-17](#)
  - standby transmission of, [10-14](#)
  - status information, [10-20](#)
  - transmitting, [10-14](#)
- ARCHIVELOG mode, [10-3](#)
  - advantages, [10-3](#)
  - archiving, [10-2](#)
  - automatic archiving in, [10-3](#)
  - definition of, [10-3](#)
  - distributed databases, [10-3](#)
  - enabling, [10-5](#)
  - manual archiving in, [10-3](#)
  - running in, [10-3](#)
  - switching to, [10-5](#)
  - taking data files offline and online in, [12-9](#)
- archiver process (ARCn), [3-29](#)
  - trace output (controlling), [10-19](#)
- archiving
  - alternate destinations, [10-14](#)

archiving (*continued*)

- changing archiving mode, [10-5](#)
- controlling number of processes, [10-7](#)
- destination availability state, controlling, [10-14](#)
- destination failure, [10-15](#)
- destination status, [10-13](#)
- manual, [10-6](#)
- NOARCHIVELOG vs. ARCHIVELOG mode, [10-2](#)
- setting initial mode, [10-5](#)
- to failed destinations, [10-18](#)
- trace output, controlling, [10-19](#)
- viewing information on, [10-20](#)

attribute-clustered tables, [19-23](#)

auditing

- database links, [31-29](#)

authentication

- database administrators, [1-29](#)
- database links, [31-23](#)
- operating system, [1-33](#)
- password files, [1-34](#)
- selecting a method, [1-29](#)
- using password file, [1-34](#)

auto indexes, [20-32](#)

AUTO\_TASK\_CONSUMER\_GROUP

- of Resource Manager, [25-7](#)

AUTOEXTEND clause, [12-6](#)

automatic big table cache, [4-4](#)

automatic diagnostic repository, [7-2](#), [7-6](#)

- in Oracle Client, [7-11](#)
- in Oracle Clusterware, [7-11](#)
- in Oracle Real Application Clusters, [7-11](#)
- structure, contents and location of, [7-11](#)

automatic error mitigation, [7-66](#)

automatic file extension, [12-6](#)

automatic indexes, [20-31](#)

- views, [20-40](#)

automatic indexing

- about, [20-32](#)
- configuring, [20-34](#)
- generating reports, [20-38](#)
- how automatic indexing works, [20-33](#)

automatic maintenance tasks, [25-1](#)

- assigning to maintenance windows, [25-5](#)
- definition, [25-2](#)
- enabling and disabling, [25-4](#)
- predefined, [25-2](#)
- resource allocation, [25-8](#)
- Scheduler job names, [25-3](#)

automatic segment space management, [11-7](#)

automatic undo management, [14-2](#)

- migrating to, [14-15](#)

## B

---

background processes, [3-29](#)

- FMON, [12-24](#)

BACKGROUND\_DUMP\_DEST initialization

- parameter, [7-6](#)

backups

- effects of archiving on, [10-3](#)

big table cache, [4-4](#)

bigfile tablespaces

- altering, [11-37](#)
- creating, [11-9](#)
- creating temporary, [11-18](#)
- description, [11-8](#)

BLOB data type, [19-34](#)

block size, redo log files, [9-9](#)

blockchain tables

- about, [19-168](#)
- adding user columns, [19-179](#)
- altering, [19-181](#)
- benefits, [19-168](#)
- countersigning rows, [19-186](#)
- creating, [19-177](#)
- creating certificates, [19-181](#)
- creating row versions, [19-179](#)
- creating user chains, [19-180](#)
- data dictionary views, [19-197](#)
- delegate signing rows, [19-185](#)
- deleting rows, [19-191](#)
- dropping, [19-192](#)
- dropping user columns, [19-179](#)
- getting byte values, [19-195](#)
- getting bytes for hash, [19-193](#)
- getting bytes for signature, [19-195](#)
- hidden columns, [19-171](#)
- restrictions, [19-176](#)
- retention period, [19-174](#)
- retention period for rows, [19-175](#)
- signing rows, [19-183](#)
- using for log history, [19-197](#)
- validating data, [19-187](#)

BLOCKSIZE clause

- of CREATE TABLESPACE, [11-21](#)

## C

---

caches

- sequence numbers, [23-21](#)

calendaring expressions, [28-32](#)

calls

- remote procedure, [31-43](#)

cancelling SQL statements, [3-40](#)

capacity planning

- space management
- capacity planning, [18-38](#)

- CASCADE clause
  - when dropping unique or primary keys, [17-18](#)
- CATBLOCK.SQL script, [6-10](#)
- CDB resource plans, [26-21](#)
  - PDB performance profiles, [26-60](#), [26-69](#)
- CDBs
  - CDB resource plans
    - viewing information about, [26-77](#)
  - Database Resource Manager, [26-56](#)
  - resource management, [26-3](#)
- centralized user management
  - distributed systems, [31-25](#)
- certificates
  - creating, [19-181](#)
- chain condition syntax, [28-55](#)
- chain rules, [28-55](#)
- chain steps
  - defining, [28-53](#)
- chained rows
  - eliminating from table, procedure, [17-7](#)
- chains
  - creating, [28-53](#)
  - creating and managing job, [28-50](#)
  - creating jobs for, [28-59](#)
  - disabling, [28-61](#)
  - dropping, [28-60](#)
  - dropping rules from, [28-61](#)
  - enabling, [28-58](#)
  - handling stalled, [28-65](#)
  - monitoring running, [28-64](#)
  - overview, [27-11](#)
  - pausing, [28-62](#)
  - running, [28-60](#)
  - setting privileges, [29-2](#)
  - steps
    - pausing, [28-62](#)
    - skipping, [28-63](#)
  - stopping, [28-62](#)
  - stopping individual steps, [28-62](#)
- change vectors, [9-2](#)
- CHAR data type
  - increasing column length, [19-61](#)
- CHECK\_OBJECT procedure
  - DBMS\_REPAIR package, [24-2](#)
  - example, [24-10](#)
  - finding extent of corruption, [24-6](#)
- checkpoint process (CKPT), [3-29](#)
- checksums
  - for data blocks, [12-18](#)
  - redo log blocks, [9-17](#)
- CLEAR LOGFILE clause
  - ALTER DATABASE statement, [9-18](#)
- clearing redo log files, [9-18](#)
- client/server architectures
  - distributed databases, [31-6](#)
  - globalization support, [31-45](#)
- cloning
  - a database, [1-9](#)
  - an Oracle home, [1-9](#)
- CLOSE DATABASE LINK clause
  - ALTER SESSION statement, [33-2](#)
- closing database links, [32-17](#)
- closing windows, [28-77](#)
- clusters, [21-5](#)
  - about, [21-1](#)
  - allocating extents, [21-7](#)
  - altering, [21-7](#)
  - analyzing, [17-4](#)
  - cluster indexes, [21-9](#)
  - cluster keys, [21-1](#), [21-4](#)
  - clustered tables, [21-1](#), [21-3](#), [21-6](#), [21-8](#), [21-10](#)
  - columns for cluster key, [21-4](#)
  - creating, [21-5](#)
  - data dictionary views reference, [21-11](#)
  - deallocating extents, [21-7](#)
  - dropping, [21-9](#)
  - estimating space, [21-4](#), [21-5](#)
  - guidelines for managing, [21-3](#)
  - location, [21-4](#)
  - privileges, [21-5](#), [21-7](#), [21-10](#)
  - selecting tables, [21-3](#)
  - single-table hash clusters, [22-7](#)
  - truncating, [17-8](#)
  - validating structure, [17-5](#)
- coalescing indexes
  - costs, [20-10](#)
- cold backup
  - performing with a detached Oracle Scheduler job, [28-15](#)
- collections
  - materialized views, [36-26](#)
  - restrictions, [36-28](#)
  - replication, [36-26](#)
- collocated inline views
  - tuning distributed queries, [33-4](#)
- column objects
  - materialized views
    - column subsetting, [36-24](#)
  - replication, [36-22](#)
- column subsetting
  - materialized views
    - column objects, [36-24](#)
- columns
  - adding, [19-62](#)
  - adding to compressed table, [19-62](#)
  - displaying information about, [19-200](#)
  - dropping, [19-63](#), [19-65](#)
  - dropping in compressed tables, [19-66](#)
  - encrypted, [19-28](#)
  - increasing length, [19-61](#)
  - invisible, [19-25](#)
  - modifying definition, [19-61](#)

- columns (*continued*)
  - renaming, [19-63](#)
  - virtual, [19-2](#)
  - virtual, indexing, [20-5](#)
- commands
  - submitting, [1-10](#)
- COMMENT statement, [19-198](#)
- comments
  - adding to problem activity log, [7-21](#)
- commit phase, [34-10](#), [34-21](#)
  - in two-phase commit, [34-12](#), [34-13](#)
- commit point site, [34-6](#)
  - commit point strength, [34-7](#), [35-2](#)
  - determining, [34-7](#)
  - distributed transactions, [34-6](#), [34-7](#)
  - how the database determines, [34-7](#)
- commit point strength
  - definition, [34-7](#)
  - specifying, [35-2](#)
- COMMIT statement
  - FORCE clause, [35-9](#), [35-10](#)
  - forcing, [35-7](#)
  - two-phase commit and, [31-34](#)
- COMMIT\_POINT\_STRENGTH initialization
  - parameter, [34-7](#)
- committing transactions
  - commit point site for distributed transactions, [34-6](#)
- complete refresh, [36-21](#), [37-8](#)
- complex materialized views, [36-6](#), [36-8](#)
  - value for PCTUSED, [37-8](#)
- components
  - srvctl component names and abbreviations, [2-34](#)
- compression, [38-3](#)
  - indexes, [20-18](#)
    - advanced compression, [20-20](#)
    - prefix compression, [20-19](#)
  - levels, [19-8](#)
  - tables, [19-8](#)
    - adding a column, [19-62](#)
    - dropping columns in, [19-66](#)
  - tablespaces, [11-10](#)
- configuring
  - Oracle Scheduler, [29-2](#)
- CONNECT command, SQL\*Plus, [1-13](#), [1-15](#)
- connected user database links, [32-10](#)
  - advantages and disadvantages, [31-15](#)
  - definition, [31-14](#)
  - REMOTE\_OS\_AUTHENT initialization parameter, [31-15](#)
- connecting
  - with SQL\*Plus, [1-12](#)
- connection qualifiers
  - database links and, [32-11](#)
  - diagnosing problems with, [40-1](#)
- connections
  - terminating remote, [33-2](#)
- constraints, [17-13](#)
  - deferrable, [37-11](#)
  - disabling at table creation, [17-17](#)
  - distributed system application development issues, [33-2](#)
  - dropping integrity constraints, [17-19](#)
  - enable novalidate state, [17-15](#)
  - enabling example, [17-17](#)
  - enabling when violations exist, [17-15](#)
  - exceptions, [17-15](#), [17-20](#)
  - exceptions to integrity constraints, [17-20](#)
  - integrity constraint states, [17-14](#)
  - keeping index when disabling, [17-18](#)
  - keeping index when dropping, [17-18](#)
  - ORA-02055 constraint violation, [33-2](#)
  - renaming, [17-19](#)
  - setting at table creation, [17-16](#)
  - when to disable, [17-14](#)
    - See also integrity constraints
- control files
  - adding, [8-5](#)
  - changing size, [8-4](#)
  - conflicts with data dictionary, [8-8](#)
  - creating, [8-1](#), [8-4](#), [8-6](#)
  - creating as Oracle Managed Files, [15-20](#)
  - data dictionary views reference, [8-11](#)
  - default name, [8-4](#)
  - dropping, [8-10](#)
  - errors during creation, [8-9](#)
  - importance of multiplexed, [8-3](#)
  - initial creation, [8-4](#)
  - location of, [8-3](#)
  - log sequence numbers, [9-4](#)
  - mirroring, [8-3](#)
  - moving, [8-5](#)
  - multiplexed, [8-3](#)
  - names, [8-2](#)
  - number of, [8-3](#)
  - relocating, [8-5](#)
  - renaming, [8-5](#)
  - requirement of one, [8-1](#)
  - size of, [8-3](#)
  - troubleshooting, [8-8](#)
- CONTROL\_FILES initialization parameter
  - specifying file names, [8-2](#)
  - when creating a database, [8-4](#)
- copying jobs, [28-25](#)
- core files, [7-8](#)
- corruption
  - repairing data block, [24-1](#)
- cost-based optimization, [33-5](#)
  - distributed databases, [31-44](#)
  - hints, [33-7](#)
  - using for distributed queries, [33-5](#)

- cpu resource management
  - CPU scope, [26-131](#)
- CPU\_COUNT initialization parameter, [26-33](#)
- CREATE BIGFILE TABLESPACE statement, [11-9](#)
- CREATE BIGFILE TEMPORARY TABLESPACE statement, [11-18](#)
- CREATE CLUSTER statement
  - creating clusters, [21-5](#)
  - example, [21-5](#)
  - for hash clusters, [22-4](#)
  - HASH IS clause, [22-4](#), [22-8](#)
  - HASHKEYS clause, [22-4](#), [22-9](#)
- CREATE CONTROLFILE statement
  - about, [8-6](#)
  - checking for inconsistencies, [8-8](#)
  - NORESETLOGS clause, [8-7](#)
  - Oracle Managed Files, using, [15-20](#)
  - RESETLOGS clause, [8-7](#)
- CREATE DATABASE LINK statement, [32-8](#)
- CREATE DATABASE statement
  - CONTROLFILE REUSE clause, [8-4](#)
  - MAXLOGFILES parameter, [9-10](#)
  - MAXLOGMEMBERS parameter, [9-10](#)
  - used to create an undo tablespace, [14-11](#)
  - using Oracle Managed Files, [15-9](#)
  - using Oracle Managed Files, examples, [15-25](#), [15-29](#)
- CREATE INDEX statement
  - NOLOGGING, [20-7](#)
  - ON CLUSTER clause, [21-7](#)
  - with a constraint, [20-15](#)
- CREATE SCHEMA statement
  - multiple tables and views, [17-2](#)
- CREATE SEQUENCE statement, [23-17](#)
  - CACHE option, [23-22](#)
- CREATE SYNONYM statement, [23-26](#)
- CREATE TABLE statement
  - CLUSTER clause, [21-6](#)
  - creating a private temporary table, [19-38](#)
  - creating global temporary table, [19-36](#)
  - example of, [19-34](#)
  - INCLUDING clause, [19-131](#)
  - MONITORING clause, [19-55](#)
  - NOLOGGING clause, [19-7](#)
  - ORGANIZATION EXTERNAL clause, [19-142](#)
  - PCTTHRESHOLD clause, [19-131](#)
- CREATE TABLESPACE statement
  - BLOCKSIZE CLAUSE, using, [11-21](#)
  - FORCE LOGGING clause, using, [11-21](#)
  - LOST WRITE PROTECTION clause, [11-47](#)
  - using Oracle Managed Files, [15-15](#)
  - using Oracle Managed Files, examples, [15-16](#)
- CREATE TEMPORARY TABLESPACE statement, [11-17](#)
  - using Oracle Managed Files, [15-18](#)
  - using Oracle managed files, example, [15-19](#)
- CREATE UNDO TABLESPACE statement
  - using Oracle Managed Files, [15-15](#)
  - using Oracle Managed Files, example, [15-17](#)
  - using to create an undo tablespace, [14-12](#)
- CREATE VIEW statement
  - about, [23-3](#)
  - OR REPLACE clause, [23-5](#)
  - WITH CHECK OPTION, [23-3](#), [23-6](#)
- CREATE\_CREDENTIAL procedure, [3-36](#), [28-9](#)
- CREATE\_SIMPLE\_PLAN procedure
  - Database Resource Manager, [26-79](#), [26-82](#)
- creating
  - chains, [28-53](#)
  - control files, [8-4](#)
  - event schedule, [28-40](#)
  - event-based job, [28-39](#)
  - indexes, [20-12](#)
    - after inserting table data, [20-3](#)
    - associated with integrity constraints, [20-15](#)
    - NOLOGGING, [20-7](#)
    - online, [20-17](#)
    - prerequisites, [20-13](#)
    - USING INDEX clause, [20-15](#)
  - job classes, [28-72](#)
  - jobs, [28-4](#)
  - programs, [28-26](#)
  - Scheduler windows, [28-75](#)
  - schedules, [28-30](#)
  - sequences, [23-22](#)
  - window groups, [28-80](#)
- creating data files, [12-5](#)
- creating database links, [32-6](#)
  - connected user, [32-11](#)
  - connected user scenarios, [32-32](#)
  - current user, [32-11](#)
  - current user scenario, [32-33](#)
  - examples, [31-17](#)
  - fixed user, [32-10](#)
  - fixed user scenario, [32-31](#)
  - obtaining necessary privileges, [32-7](#)
  - private, [32-8](#)
  - public, [32-8](#)
  - service names within link names, [32-11](#)
  - shared, [32-12](#)
  - shared connected user scenario, [32-32](#)
  - specifying types, [32-7](#)
- creating databases
  - using Oracle Managed Files, [15-9](#)
- creating sequences, [23-17](#)
- creating synonyms, [23-26](#)
- creating views, [23-3](#)
- credentials, Oracle Scheduler
  - about, [27-10](#)
  - granting privileges on, [27-10](#)



- critical errors
  - diagnosing, [7-2](#)
- CRSCTL utility
  - Oracle Restart, [2-4](#)
- current user database links
  - advantages and disadvantages, [31-16](#)
  - cannot access in shared schema, [31-26](#)
  - definition, [31-14](#)
  - shared schema, [31-26](#)
- CURRVAL pseudo-column, [23-19](#)
  - restrictions, [23-20](#)
- cursors
  - and closing database links, [33-2](#)
- customize package page, accessing, [7-60](#)
- customizing an incident package, [7-59](#), [7-60](#)

## D

- data
  - loading using external tables, [19-142](#)
- data block corruption
  - repairing, [24-1](#)
- data blocks
  - shadow lost write protection, [11-44](#)
  - shared in clusters, [21-1](#)
  - verifying, [12-18](#)
- data dictionary
  - conflicts with control files, [8-8](#)
  - purging pending rows from, [35-11](#), [35-12](#)
- data encryption
  - distributed systems, [31-28](#)
- data file headers
  - when renaming tablespaces, [11-42](#)
- data files
  - adding to a tablespace, [12-5](#)
  - bringing online and offline, [12-8](#)
  - checking associated tablespaces, [11-60](#)
  - copying using database, [12-19](#)
  - creating, [12-5](#)
  - creating Oracle Managed Files, [15-7](#), [15-23](#)
  - data dictionary views reference, [12-33](#)
  - database administrators access, [1-21](#)
  - default directory, [12-5](#)
  - definition, [12-2](#)
  - deleting, [11-43](#)
  - dropping, [12-9](#), [12-17](#)
  - dropping Oracle managed, [15-24](#)
  - file numbers, [12-2](#)
  - fully specifying file names, [12-5](#)
  - guidelines for managing, [12-2](#)
  - headers when renaming tablespaces, [11-42](#)
  - identifying OS file names, [12-15](#)
  - location, [12-5](#)
  - mapping files to physical devices, [12-22](#)
  - minimum number of, [12-3](#)
  - MISSING, [8-8](#)

- data files (*continued*)
  - offline
    - relocating, [12-13](#)
    - renaming, [12-13](#)
  - online, [12-9](#)
    - relocating, [12-11](#)
    - renaming, [12-11](#)
  - relocating, [12-10](#)
  - renaming, [12-10](#)
  - reusing, [12-5](#)
  - shadow lost write protection, [11-44](#)
  - size of, [12-5](#)
  - statements to create, [12-5](#)
  - storing separately from redo log files, [12-5](#)
  - verifying data blocks, [12-18](#)
- data manipulation language, [31-1](#)
  - statements allowed in distributed transactions, [31-32](#)
- Data Recovery Advisor, repairing data corruptions
  - with, [7-77](#)
- Data Repair Advisor, [7-3](#)
- database
  - cloning, [1-9](#)
- database administrators, [1-3](#)
  - authentication, [1-29](#)
  - DBA role, [1-24](#)
  - operating system account, [1-21](#)
  - password files for, [1-30](#)
  - responsibilities of, [1-3](#)
  - security and privileges of, [1-21](#)
  - security officer versus, [5-1](#)
  - task definitions, [1-5](#)
  - utilities for, [1-49](#)
- Database Configuration Assistant
  - shared server configuration, [3-14](#)
- database destinations, Oracle Scheduler
  - about, [27-8](#)
  - creating, [28-10](#)
- Database In-Memory
  - See Oracle Database In-Memory
- database jobs, Oracle Scheduler, [27-21](#)
- database links, [32-6](#)
  - advantages, [31-10](#)
  - auditing, [31-29](#)
  - authentication, [31-23](#)
  - authentication without passwords, [31-24](#)
  - closing, [32-17](#), [33-2](#)
  - connected user, [31-14](#), [31-15](#), [32-10](#), [32-32](#)
  - connections, determining open, [32-20](#)
  - controlling connections, [33-2](#)
  - creating, [32-6](#), [32-31–32-33](#)
  - creating shared, [32-14](#)
  - creating, examples, [31-17](#)
  - creating, scenarios, [32-31](#)
  - current user, [31-14](#), [31-16](#), [32-10](#)
  - data dictionary USER views, [32-19](#)

database links (*continued*)

- definition, [31-8](#)
- diagnosing problems with, [40-1](#)
- distributed queries, [31-32](#)
- distributed transactions, [31-33](#)
- dropping, [32-17](#)
- enforcing global naming, [32-2](#)
- enterprise users and, [31-26](#)
- fixed user, [31-14](#), [31-16](#), [32-31](#)
- global, [31-13](#)
- global names, [31-10](#)
  - loopback, [31-12](#)
- global object names, [31-35](#)
- handling errors, [33-2](#)
- host name, [32-21](#)
- incoming database links, [32-22](#)
- limiting number of connections, [32-18](#)
- listing, [32-19](#), [35-3](#), [35-5](#)
- loopback, [31-12](#)
- managing, [32-16](#)
- materialized view sites, [38-5](#)
- minimizing network connections, [32-12](#)
- name resolution, [31-35](#)
- names for, [31-12](#)
- private, [31-13](#)
- public, [31-13](#)
- referential integrity in, [33-2](#)
- remote transactions, [31-32](#), [31-33](#)
- resolution, [31-35](#)
- restrictions, [31-20](#)
- roles on remote database, [31-20](#)
- schema objects and, [31-18](#)
- SCN activity, [32-23](#)
- service names used within link names, [32-11](#)
- shared, [31-9](#), [32-13](#)–[32-15](#)
- shared SQL, [31-33](#)
- synonyms for schema objects, [31-19](#)
- tuning distributed queries, [33-3](#)
- tuning queries with hints, [33-7](#)
- tuning using collocated inline views, [33-4](#)
- types of links, [31-13](#)
- types of users, [31-14](#)
- users, specifying, [32-9](#)
- using cost-based optimization, [33-5](#)
- viewing, [32-19](#)

## database objects

- obtaining growth trends for, [18-40](#)

database program unit, definition, [27-1](#)database resident connection pooling, [3-5](#)

- advantages, [3-5](#)
- configuration parameters, [3-24](#)
- configuring the connection pool, [3-23](#)
- data dictionary views reference, [3-27](#)
- determining the state of, [3-28](#)
- disabling, [3-22](#)
- enabling, [3-22](#)

database resident connection pooling (*continued*)

- multi-pool, using, [3-26](#)
- triggers, [3-5](#)

## Database Resource Manager

- active session pool with queuing, [26-19](#)
- administering system privilege, [26-31](#)
- and operating system control, [26-126](#)
- automatic consumer group switching, [26-18](#)
- CDB resource plans, [26-21](#)
- CDBs, [26-3](#), [26-56](#)
- CREATE\_SIMPLE\_PLAN procedure, [26-79](#), [26-82](#)
- data dictionary views reference, [26-130](#)
- description, [26-2](#)
- enabling, [26-39](#)
- execution time limit, [26-19](#)
- monitoring PDBs, [26-121](#)
- PDB resource plans, [26-26](#)
- PDBs, [26-56](#)
- resource allocation methods, [26-88](#)
- resource consumer groups, [26-7](#), [26-42](#), [26-86](#)
- resource plan directives, [26-7](#), [26-89](#), [26-94](#)
- resource plans, [26-7](#), [26-11](#), [26-30](#), [26-39](#), [26-82](#), [26-96](#), [26-107](#)
- STATISTICS\_LEVEL parameter, [26-4](#)
- undo pool, [26-19](#)
- validating plan schema changes, [26-94](#)

Database Smart Flash Cache, [4-30](#)

- flushing, [4-31](#)
- tuning, [4-31](#)

## database writer process

- calculating checksums for data blocks, [12-18](#)

database writer process (DBWn), [3-29](#)

## databases

- administering, [1-1](#)
- administration of distributed, [32-1](#)
- planning, [1-7](#)
- renaming, [8-6](#), [8-7](#)

date expressions, [37-9](#)DB\_BLOCK\_CHECKING initialization parameter, [24-4](#), [24-5](#)DB\_BLOCK\_CHECKSUM initialization parameter, [12-18](#)

- enabling redo block checking with, [9-17](#)

DB\_BLOCK\_SIZE initialization parameter and nonstandard block sizes, [11-21](#)DB\_CACHE\_SIZE initialization parameter specifying multiple block sizes, [11-21](#)DB\_CACHE\_SIZE parameter, [26-34](#)DB\_CREATE\_FILE\_DEST initialization parameter setting, [15-6](#)DB\_CREATE\_ONLINE\_LOG\_DEST\_n initialization parameter setting, [15-6](#)



- DB\_FILES initialization parameter
  - determining value for, [12-4](#)
- DB\_nK\_CACHE\_SIZE initialization parameter
  - specifying multiple block sizes, [11-21](#)
- DB\_PERFORMANCE\_PROFILE parameter, [26-61](#)
- DB\_RECOVERY\_FILE\_DEST initialization parameter
  - setting, [15-6](#)
- DB\_UNRECOVERABLE\_SCN\_TRACKING initialization parameter, [19-47](#)
- DBA
  - See database administrators
- DBA role, [1-24](#)
- DBA\_2PC\_NEIGHBORS view, [35-5](#)
  - using to trace session tree, [35-5](#)
- DBA\_2PC\_PENDING view, [35-3](#), [35-11](#), [35-20](#)
  - using to list in-doubt transactions, [35-3](#)
- DBA\_DB\_LINK view, [32-23](#)
- DBA\_DB\_LINK\_SOURCES view, [32-22](#), [32-23](#)
- DBA\_DB\_LINKS view, [32-19](#)
- DBA\_EXTERNAL\_SCN\_ACTIVITY view, [32-23](#)
- DBA\_REGISTERED\_MVIEWS view, [36-31](#)
- DBA\_TYPE\_VERSIONS
  - replication, [36-23](#)
- DBMS\_CREDENTIAL package, [3-36](#)
- DBMS\_FILE\_TRANSFER package
  - copying data files, [12-18](#)
- DBMS\_JOB
  - about, [A-1](#)
  - moving jobs to Oracle Scheduler, [A-2](#)
- DBMS\_METADATA package
  - GET\_DDL function, [17-33](#)
  - using for object definition, [17-33](#)
- DBMS\_MVIEW package, [36-31](#)
  - EXPLAIN\_MVIEW procedure, [39-5](#)
  - REFRESH procedure, [39-4](#)
  - REGISTER\_MVIEW procedure, [36-31](#)
- DBMS\_PROCESS package, [3-31](#)
- DBMS\_REDEFINITION package
  - performing online redefinition with, [19-74](#)
- DBMS\_REFRESH package
  - MAKE procedure, [39-3](#)
  - REFRESH procedure, [39-4](#)
- DBMS\_REPAIR
  - logical corruptions, [24-6](#)
- DBMS\_REPAIR package
  - examples, [24-8](#)
  - procedures, [24-2](#)
  - using, [24-3](#), [24-12](#)
- DBMS\_RESOURCE\_MANAGER package, [26-7](#), [26-31](#), [26-48](#)
  - procedures (table of), [26-31](#)
- DBMS\_RESOURCE\_MANAGER\_PRIVS package, [26-31](#)
  - procedures (table of), [26-31](#)
- DBMS\_RESUMABLE package, [18-14](#)
- DBMS\_SCHEDULER
  - in-memory trace, [29-18](#)
- DBMS\_SCHEDULER.GET\_FILE, retrieving
  - external job stdout with, [28-17](#)
- DBMS\_SERVER\_ALERT package
  - setting alert thresholds, [18-2](#)
- DBMS\_SPACE package, [18-33](#)
  - example for unused space, [18-35](#)
  - FREE\_BLOCK procedure, [18-35](#)
  - SPACE\_USAGE procedure, [18-35](#)
  - UNUSED\_SPACE procedure, [18-35](#)
- DBMS\_SPACE\_ADMIN
  - DROP\_EMPTY\_SEGMENTS procedure, [18-34](#)
  - MATERIALIZED\_DEFERRED\_SEGMENTS procedure, [19-32](#)
- DBMS\_SQLDIAG package, [7-47](#)
- DBMS\_TNS package, [32-21](#)
- DBMS\_TRANSACTION package
  - PURGE\_LOST\_DB\_ENTRY procedure, [35-12](#)
- DBVERIFY utility, [24-4](#)
- DDL log, [7-9](#)
- DEALLOCATE UNUSED clause, [18-33](#)
- deallocating unused space, [18-16](#)
  - DBMS\_SPACE package, [18-33](#)
  - DEALLOCATE UNUSED clause, [18-33](#)
- debug log, [7-10](#)
- declarative referential integrity constraints, [33-2](#)
- dedicated server processes, [3-2](#)
  - trace files for, [6-2](#)
- default temporary tablespace
  - renaming, [11-42](#)
- DEFAULT\_CONSUMER\_GROUP for Database Resource Manager, [26-54](#), [26-110](#)
- deferred segment creation
  - in tables, [19-29](#)
  - indexes, [20-6](#)
- deferred segments
  - materializing, [19-32](#)
- defining
  - chain steps, [28-53](#)
- deleting
  - certificates, [19-183](#)
- dependencies
  - between schema objects, [17-23](#)
  - displaying, [17-35](#)
- destinations, Oracle Scheduler
  - about, [27-8](#)
  - creating, [28-10](#)
- detached jobs, [27-26](#)
  - creating, [28-15](#)
- DIAGNOSTIC\_DEST initialization parameter, [6-2](#), [7-6](#), [7-11](#)

- dictionary-managed tablespaces
  - migrating SYSTEM to locally managed, [11-58](#)
- Digital POLYCENTER Manager on NetView, [31-30](#)
- direct path load
  - fast refresh, [37-8](#)
- direct-path INSERT
  - benefits, [19-43](#)
  - how it works, [19-44](#)
  - index maintenance, [19-48](#)
  - locking considerations, [19-49](#)
  - logging mode, [19-46](#)
  - parallel INSERT, [19-45](#)
  - parallel load compared with parallel INSERT, [19-43](#)
  - space considerations, [19-48](#)
- directory objects
  - external procedures, [3-36](#)
- disabling
  - chains, [28-61](#)
  - jobs, [28-23](#)
  - programs, [28-28](#)
  - window groups, [28-82](#)
  - windows, [28-78](#)
- disabling recoverer process, [35-22](#)
- dispatcher process (Dnnn), [3-29](#)
- dispatcher processes, [3-16](#), [3-19](#)
- DISPATCHERS initialization parameter
  - setting initially, [3-16](#)
- distributed applications
  - distributing data, [33-1](#)
- distributed databases
  - administration overview, [31-21](#)
  - application development, [31-41](#), [33-1](#), [33-10](#)
  - client/server architectures, [31-6](#)
  - commit point strength, [34-7](#)
  - cost-based optimization, [31-44](#)
  - direct and indirect connections, [31-6](#)
  - distributed processing, [31-3](#)
  - distributed queries, [31-32](#)
  - distributed updates, [31-32](#)
  - enhancing security, [35-23](#)
  - exclusively mapped global users, [31-26](#)
  - forming global database names, [32-2](#)
  - global object names, [31-20](#), [32-1](#)
  - globalization support, [31-45](#)
  - location transparency, [31-42](#), [32-24](#)
  - management tools, [31-30](#)
  - managing read consistency, [35-23](#)
  - nodes of, [31-6](#)
  - overview, [31-2](#)
  - remote object security, [32-25](#)
  - remote queries and updates, [31-32](#)
  - replicated databases and, [31-4](#)
  - resumable space allocation, [18-9](#)
  - running in ARCHIVELOG mode, [10-3](#)
- distributed databases (*continued*)
  - running in NOARCHIVELOG mode, [10-3](#)
  - scenarios, [32-31](#)
  - schema object name resolution, [31-37](#)
  - security, [31-22](#)
  - shared schema users, [31-26](#)
  - site autonomy of, [31-22](#)
  - SQL transparency, [31-43](#)
  - transaction processing, [31-31](#)
  - transparency, [31-42](#)
- distributed processing
  - distributed databases, [31-3](#)
- distributed queries, [31-32](#)
  - analyzing tables, [33-6](#)
  - application development issues, [33-3](#)
  - cost-based optimization, [33-5](#)
  - optimizing, [31-44](#)
- distributed systems
  - data encryption, [31-28](#)
- distributed transactions, [31-33](#)
  - case study, [34-18](#)
  - commit point site, [34-6](#)
  - commit point strength, [34-7](#), [35-2](#)
  - committing, [34-7](#)
  - database server role, [34-5](#)
  - defined, [34-1](#)
  - DML and DDL, [34-2](#)
  - enhancing security, [35-23](#)
  - failure during, [35-20](#)
  - global coordinator, [34-5](#)
  - lock timeout interval, [35-20](#)
  - locked resources, [35-20](#)
  - locks for in-doubt, [35-21](#)
  - manually overriding in-doubt, [35-7](#)
  - naming, [35-2](#), [35-8](#)
  - session trees, [34-3](#), [34-5](#), [34-6](#), [35-5](#)
  - setting advice, [35-8](#)
  - transaction control statements, [34-3](#)
  - transaction timeouts, [35-20](#)
  - two-phase commit, [34-18](#), [35-6](#)
  - viewing database links, [35-3](#)
- distributed updates, [31-32](#)
- DML
  - See data manipulation language
- DML error logging, inserting data with, [19-50](#)
- DRCP
  - initialization parameters, [3-21](#)
- DRIVING\_SITE hint, [33-8](#)
- DROP ALL STORAGE clause, [17-9](#)
- DROP CLUSTER statement
  - CASCADE CONSTRAINTS clause, [21-9](#)
  - dropping cluster, [21-9](#)
  - dropping cluster index, [21-9](#)
  - dropping hash cluster, [22-11](#)
  - INCLUDING TABLES clause, [21-9](#)

DROP LOGFILE clause  
     ALTER DATABASE statement, [9-16](#)  
 DROP LOGFILE MEMBER clause  
     ALTER DATABASE statement, [9-16](#)  
 DROP SYNONYM statement, [23-27](#)  
 DROP TABLE statement  
     about, [19-120](#)  
     CASCADE CONSTRAINTS clause, [19-120](#)  
     for clustered tables, [21-10](#)  
 DROP TABLESPACE statement, [11-43](#)  
 dropping  
     chain steps, [28-61](#)  
     chains, [28-60](#)  
     columns  
         marking unused, [19-65](#)  
         remove unused columns, [19-65](#)  
     columns in compressed tables, [19-66](#)  
     data files, [12-17](#)  
     data files, Oracle managed, [15-24](#)  
     database links, [32-17](#)  
     job classes, [28-72](#)  
     jobs, [28-22](#)  
     programs, [28-28](#)  
     rules from chains, [28-61](#)  
     schedules, [28-31](#)  
     tables  
         consequences of, [19-120](#)  
     temp files, [12-17](#)  
         Oracle managed, [15-24](#)  
     window groups, [28-81](#)  
     windows, [28-78](#)  
 dropping multiple jobs, [28-22](#)  
 DUMP\_ORPHAN\_KEYS procedure  
     DBMS\_REPAIR package, [24-2](#)  
     example, [24-11](#)  
     recovering data, [24-7](#)  
 dumps, [7-8](#)  
 dynamic statistics, [7-42](#)

## E

e-mail notifications, Scheduler, [28-91](#)  
 ECID, [7-5](#)  
 editions  
     in CONNECT command, [1-13](#)  
     managing, [17-28](#)  
 EMPHASIS resource allocation method, [26-88](#)  
 empty tables  
     dropping segments, [18-34](#)  
 enabling  
     chains, [28-58](#)  
     jobs, [28-24](#)  
     programs, [28-29](#)  
     window groups, [28-82](#)  
     windows, [28-79](#)

enabling recoverer process  
     distributed transactions, [35-22](#)  
 encryption  
     column, [19-28](#)  
     tablespace, [11-11](#)  
 enterprise users  
     definition, [31-26](#)  
 error logging, DML  
     inserting data with, [19-50](#)  
 errors  
     alert log and, [6-2](#)  
     assigning names with  
         PRAGMA\_EXCEPTION\_INIT, [33-10](#)  
     critical, [7-2](#)  
     exception handler, [33-10](#)  
     integrity constrain violation, [33-2](#)  
     ORA-00028, [3-38](#)  
     ORA-01173, [8-9](#)  
     ORA-01176, [8-9](#)  
     ORA-01177, [8-9](#)  
     ORA-01215, [8-9](#)  
     ORA-01216, [8-9](#)  
     ORA-01591, [35-21](#)  
     ORA-02049, [35-20](#)  
     ORA-02050, [35-6](#)  
     ORA-02051, [35-6](#)  
     ORA-02054, [35-6](#)  
     RAISE\_APPLICATION\_ERROR() procedure,  
         [33-10](#)  
     remote procedure, [33-10](#)  
     rollback required, [33-2](#)  
     trace files and, [6-2](#)  
     when creating control file, [8-9](#)  
 event message  
     passing to event-based job, [28-41](#)  
 event schedule  
     altering, [28-41](#)  
     creating, [28-40](#)  
 event-based job  
     altering, [28-40](#)  
     creating, [28-39](#)  
     passing event messages to, [28-41](#)  
 events  
     using to start Scheduler jobs, [28-36](#)  
 events (Scheduler)  
     overview, [28-37](#)  
 example  
     setting maximum utilization limit for plans and  
         subplans, [26-102](#)  
 examples  
     managing parallel statement execution using  
         Resource Manager, [26-104](#)  
 exception handler, [33-10](#)  
 exceptions  
     assigning names with  
         PRAGMA\_EXCEPTION\_INIT, [33-10](#)

- exceptions (*continued*)
  - integrity constraints, [17-20](#)
  - user-defined, [33-10](#)
- executing
  - remote external jobs, [29-5](#)
- execution context identifier, [7-5](#)
- execution plans
  - analyzing for distributed queries, [33-8](#)
- EXISTS condition
  - materialized views with subqueries, [36-19](#)
- EXPLAIN\_MVIEW procedure, [39-5](#)
- expressions, calendaring, [28-32](#)
- extents
  - allocating cluster extents, [21-7](#)
  - allocating for tables, [19-61](#)
  - data dictionary views for, [18-36](#)
  - deallocating cluster extents, [21-7](#)
  - displaying free extents, [18-38](#)
- external destinations, Oracle Scheduler
  - about, [27-8](#)
  - creating, [28-10](#)
- external jobs
  - retrieving stdout and stderr, [27-23](#), [27-24](#), [28-17](#)
- external jobs, Oracle Scheduler, [27-22](#)
- external procedures
  - credentials, [3-36](#)
  - directory objects, [3-36](#)
  - managing processes for, [3-35](#)
- external tables
  - altering, [19-146](#)
  - creating, [19-142](#)
  - defined, [19-140](#)
  - dropping, [19-157](#)
  - Hadoop, [19-140](#)
  - inline, [19-140](#), [19-149](#)
  - partition values in file paths, [19-158](#)
  - partitioned, [19-150](#)
    - altering, [19-157](#)
    - creating, [19-153](#)
    - restrictions, [19-152](#)
  - privileges required, [19-157](#)
  - querying, [19-149](#)
  - uploading data example, [19-142](#)

## F

- fast recovery area
  - as archive log destination, [10-8](#)
  - with Oracle managed files, [15-5](#)
- fast refresh, [36-5](#), [36-21](#), [37-8](#)
  - avoiding problems, [39-6](#)
  - determining possibility of, [39-5](#)
  - direct path load, [37-8](#)
- fault diagnosability infrastructure, [7-2](#), [7-5](#)

- file mapping
  - examples, [12-31](#)
  - how it works, [12-23](#)
  - how to use, [12-27](#)
  - overview, [12-23](#)
  - structures, [12-25](#)
  - views, [12-29](#)
- file names
  - Oracle Managed Files, [15-8](#)
- file system
  - used for Oracle managed files, [15-3](#)
- file watchers
  - about, [28-43](#)
  - changing detection interval, [28-48](#)
  - creating, [28-44](#)
  - managing, [28-48](#)
- files
  - creating Oracle Managed Files, [15-7](#), [15-23](#)
- filter columns, [37-4](#)
- finalizing
  - an incident package, definition, [7-53](#)
- FINISH\_REDEF\_TABLE procedure
  - dml\_lock\_timeout parameter, [19-76](#)
- FIX\_CORRUPT\_BLOCKS procedure
  - DBMS\_REPAIR, [24-2](#)
  - example, [24-11](#)
  - marking blocks corrupt, [24-7](#)
- fixed user database links
  - advantages and disadvantages, [31-16](#)
  - creating, [32-10](#)
  - definition, [31-14](#)
- flashback data archive, [38-3](#)
- Flashback Drop
  - about, [19-121](#)
  - purging recycle bin, [19-124](#)
  - querying recycle bin, [19-124](#)
  - recycle bin, [19-122](#)
  - restoring objects, [19-125](#)
- Flashback Table
  - overview, [19-119](#)
- flood-controlled incidents
  - defined, [7-4](#)
  - viewing, [7-23](#)
- FMON background process, [12-24](#)
- FORCE clause
  - COMMIT statement, [35-9](#)
  - ROLLBACK statement, [35-9](#)
- force full database caching mode, [4-27](#)
  - disabling, [4-30](#)
  - enabling, [4-29](#)
  - prerequisites, [4-29](#)
- FORCE LOGGING
  - precedence of settings, [9-19](#)
- FORCE LOGGING clause
  - CREATE TABLESPACE, [11-21](#)
- force refresh, [36-21](#), [37-9](#)

- forcing
  - COMMIT or ROLLBACK, [35-3](#), [35-7](#)
- forcing a log switch, [9-17](#)
  - using ARCHIVE\_LAG\_TARGET, [9-11](#)
  - with the ALTER SYSTEM statement, [9-17](#)
- foreign keys
  - replicated tables, [38-1](#)
- forget phase
  - in two-phase commit, [34-14](#)
- free space
  - listing free extents, [18-38](#)
  - tablespaces and, [11-61](#)
- full transportable export/import, [13-13](#)
- function-based indexes, [20-17](#)

## G

---

- generic connectivity
  - definition, [31-6](#)
- global coordinators, [34-5](#)
  - distributed transactions, [34-5](#)
- global database consistency
  - distributed databases and, [34-13](#)
- global database links, [31-13](#)
  - creating, [32-9](#)
- global database names
  - changing the domain, [32-3](#)
  - database links, [31-10](#)
    - loopback, [31-12](#)
  - enforcing for database links, [31-12](#)
  - enforcing global naming, [32-2](#)
  - forming distributed database names, [32-2](#)
  - impact of changing, [31-40](#)
  - querying, [32-3](#)
- global object names
  - database links, [31-35](#)
  - distributed databases, [32-1](#)
- global temporary tables
  - assigning to a tablespace, [19-38](#)
  - creating, [19-36](#)
- global users, [32-33](#)
  - exclusively mapped in distributed systems, [31-26](#)
  - shared schema in distributed systems, [31-26](#)
- GLOBAL\_NAME view
  - using to determine global database name, [32-3](#)
- GLOBAL\_NAMES initialization parameter
  - database links, [31-12](#)
- globalization support
  - client/server architectures, [31-45](#)
  - distributed databases, [31-45](#)
- GRANT statement
  - SYSOPER/SYSDBA privileges, [1-47](#)
- granting privileges and roles
  - SYSOPER/SYSDBA privileges, [1-47](#)

- groups, Oracle Scheduler, [27-18](#)
- growth trends
  - of database objects, [18-40](#)
- GV\$DBLINK view, [32-20](#)

## H

---

- Hadoop
  - external tables, [19-140](#)
- hash clusters
  - advantages and disadvantages, [22-1](#)
  - altering, [22-11](#)
  - choosing key, [22-8](#)
  - contrasted with index clusters, [22-1](#)
  - controlling space use of, [22-7](#)
  - creating, [22-4](#)
  - data dictionary views reference, [22-11](#)
  - dropping, [22-11](#)
  - estimating storage, [22-10](#)
  - examples, [22-9](#)
  - hash function, [22-1](#), [22-3](#), [22-4](#), [22-8](#)
  - HASH IS clause, [22-4](#), [22-8](#)
  - HASHKEYS clause, [22-4](#), [22-9](#)
  - single-table, [22-7](#)
  - sorted, [22-4](#)
- hash functions
  - for hash cluster, [22-1](#)
- health checks, [7-2](#)
- Health Monitor, [7-31](#)
  - checks, [7-32](#)
    - generating reports, [7-35](#)
    - viewing reports, [7-35](#)
    - viewing reports using ADRCI, [7-37](#)
- heterogeneous distributed systems
  - definition, [31-5](#)
- Heterogeneous Services
  - overview, [31-5](#)
- hints, [33-7](#)
  - DRIVING\_SITE, [33-8](#)
  - NO\_MERGE, [33-8](#)
  - using to tune distributed queries, [33-7](#)
- horizontal partitioning
  - See row subsetting
- HP OpenView, [31-30](#)
- Hybrid Columnar Compression, [19-8](#)

## I

---

- IBM NetView/6000, [31-30](#)
- IM column store
  - See In-Memory Column Store
- immutable table
  - retention period, [19-160](#)
- immutable tables
  - about, [19-159](#)
  - adding user columns, [19-163](#)

- immutable tables (*continued*)
  - altering, [19-163](#)
  - creating, [19-162](#)
  - creating row versions, [19-164](#)
  - deleting rows, [19-164](#)
  - dropping, [19-165](#)
  - dropping user columns, [19-163](#)
  - restrictions, [19-161](#)
  - row retention period, [19-161](#)
- Import
  - materialized view logs, [37-5](#)
- import operations
  - PDBs, [13-15](#), [13-26](#)
- in-doubt transactions, [34-14](#)
  - after a system failure, [35-6](#)
  - automatic resolution, [34-15](#)
  - deciding how to handle, [35-6](#)
  - deciding whether to perform manual override, [35-7](#)
  - defined, [34-12](#)
  - manual resolution, [34-17](#)
  - manually committing, [35-9](#)
  - manually committing, example, [35-13](#)
  - manually overriding, [35-7](#), [35-9](#)
  - manually overriding, scenario, [35-13](#)
  - manually rolling back, [35-10](#)
  - overview, [34-14](#)
  - pending transactions table, [35-20](#)
  - purging rows from data dictionary, [35-11](#), [35-12](#)
  - recoverer process and, [35-22](#)
  - rolling back, [35-9](#), [35-10](#)
  - SCNs and, [34-17](#)
  - simulating, [35-21](#)
  - tracing session tree, [35-5](#)
  - viewing database links, [35-3](#)
- In-Memory Column Store, [4-37](#)
- in-memory full jobs
  - example of creating, [28-7](#)
- in-memory jobs, [27-28](#)
- in-memory runtime, jobs
  - example of creating, [28-7](#)
- Incident Manager, accessing, [7-46](#)
- incident package
  - correlated, [7-55](#)
  - correlated, creating, editing, and uploading, [7-63](#)
  - correlated, deleting, [7-64](#)
  - customizing, [7-59](#), [7-60](#)
  - defined, [7-2](#)
  - viewing, [7-60](#)
- incident packages, [7-52](#)
- incident packaging service, [7-2](#)
- incidents
  - about, [7-3](#)
- incidents (*continued*)
  - flood-controlled, [7-4](#)
  - viewing, [7-23](#)
- incidents, SQL, [7-42](#)
- incompatibilities
  - adding job or program, [28-66](#)
  - dropping, [28-67](#)
  - job or program, [28-66](#)
  - removing job or program, [28-67](#)
  - using, [28-65](#)
- index clusters
  - See clusters
- index-organized tables, [19-126](#)
  - analyzing, [19-137](#)
  - AS subquery, [19-132](#)
  - converting to heap, [19-139](#)
  - creating, [19-128](#)
  - described, [19-127](#)
  - INCLUDING clause, [19-131](#)
  - maintaining, [19-134](#)
  - ORDER BY clause, using, [19-138](#)
  - parallel creation, [19-132](#)
  - prefix compression, [19-133](#)
  - rebuilding with MOVE clause, [19-134](#)
  - storing nested tables, [19-130](#)
  - storing object types, [19-130](#)
  - threshold value, [19-131](#)
- indexes
  - advanced index compression, [20-20](#)
  - altering, [20-24](#)
  - analyzing, [17-4](#)
  - automatic indexes, [20-31](#)
  - choosing columns to index, [20-4](#)
  - cluster indexes, [21-7–21-9](#)
  - coalescing, [20-10](#), [20-26](#)
  - column order for performance, [20-5](#)
  - creating, [20-12](#)
    - prerequisites, [20-13](#)
  - data dictionary views reference, [20-41](#)
  - deferred segment creation, [20-6](#)
  - determining unusable status of, [20-26](#), [20-27](#)
  - disabling and dropping constraints cost, [20-11](#)
  - dropping, [20-5](#), [20-31](#)
  - estimating size, [20-6](#)
  - estimating space use, [18-40](#)
  - function-based, [20-17](#)
  - guidelines for managing, [20-1](#)
  - invisible, [20-8](#), [20-9](#), [20-22](#), [20-28](#)
  - keeping when disabling constraint, [17-18](#)
  - keeping when dropping constraint, [17-18](#)
  - limiting for a table, [20-5](#)
  - materialized view sites, [37-6](#)
  - monitoring space use of, [20-30](#)
  - monitoring usage, [20-29](#)
  - multiple on a set of columns, [20-9](#)
  - on foreign keys, [38-1](#)



indexes (*continued*)

- parallelizing index creation, [20-7](#)
- rebuilding, [20-10](#), [20-26](#)
- rebuilt after direct-path INSERT, [19-48](#)
- renaming, [20-29](#)
- setting storage parameters for, [20-6](#)
- shrinking, [18-31](#)
- space used by, [20-30](#)
- tablespace for, [20-7](#)
- temporary segments and, [20-3](#)
- unusable, [20-8](#), [20-21](#), [20-26](#)
- validating structure, [17-5](#)
- when to create, [20-4](#)

## INITIAL parameter

- cannot alter, [19-58](#)

## initialization parameters

- COMMIT\_POINT\_STRENGTH, [34-7](#)
- CONTROL\_FILES, [8-2](#), [8-4](#)
- DB\_BLOCK\_CHECKING, [24-5](#)
- DB\_BLOCK\_CHECKSUM, [9-17](#), [12-18](#)
- DB\_BLOCK\_SIZE, [11-21](#)
- DB\_CACHE\_SIZE, [11-21](#)
- DB\_FILES, [12-4](#)
- DB\_nK\_CACHE\_SIZE, [11-21](#)
- DISPATCHERS, [3-16](#)
- editing, [38-7](#)
- GLOBAL\_NAMES, [31-12](#)
- LOG\_ARCHIVE\_DEST, [10-7](#)
- LOG\_ARCHIVE\_DEST\_n, [10-7](#), [10-18](#)
- LOG\_ARCHIVE\_DEST\_STATE\_n, [10-14](#)
- LOG\_ARCHIVE\_MAX\_PROCESSES, [10-7](#)
- LOG\_ARCHIVE\_MIN\_SUCCEED\_DEST, [10-16](#)
- LOG\_ARCHIVE\_TRACE, [10-19](#)
- OPEN\_LINKS, [32-18](#)
- REMOTE\_LOGIN\_PASSWORDFILE, [1-45](#)
- REMOTE\_OS\_AUTHENT, [31-15](#)
- RESOURCE\_MANAGER\_PLAN, [26-39](#)
- shared server and, [3-10](#)
- SHARED\_SERVERS, [3-12](#)
- SORT\_AREA\_SIZE, [20-3](#)
- SQL\_TRACE, [6-2](#)

## INITTRANS parameter

- altering, [19-58](#)

inline external tables, [19-140](#), [19-149](#)

## INSERT statement

- with DML error logging, [19-50](#)

## installing

- Release Update Revisions (Revisions), [1-9](#)
- Release Updates (Updates), [1-9](#)

instance caging, [26-108](#)

- with maximum utilization limit, [26-109](#)

## instances

- managing CPU for multiple, [26-108](#)

integrity constraints, [17-13](#)

- cost of disabling, [20-11](#)

integrity constraints (*continued*)

- cost of dropping, [20-11](#)
- creating indexes associated with, [20-15](#)
- dropping tablespaces and, [11-43](#)
- ORA-02055 constraint violation, [33-2](#)
- See also constraints

invisible columns, [19-25](#)invisible indexes, [20-8](#), [20-9](#), [20-28](#)

- creating, [20-22](#)

## IOT

- See index-organized tables

IPS, [7-2](#)

## J

## job child processes

- replication, [38-7](#)

## job classes

- altering, [28-72](#)
- creating, [28-72](#)
- dropping, [28-72](#)
- managing Scheduler job attributes, resources, and priorities with, [28-71](#)
- overview, [27-12](#)
- viewing, [27-12](#)

job coordinator, [27-32](#)job credentials, [28-9](#)job destination ID, defined, [28-20](#), [28-88](#)

## job log, Scheduler

- viewing, [28-85](#)

job recovery (Scheduler), [29-23](#)

## job resources

- managing, [28-68](#)

## job scheduling

- dependency, [27-1](#)
- event-based, [27-1](#)
- time-based, [27-1](#)

## JOB\_QUEUE\_PROCESSES initialization

- parameter, [27-33](#), [38-7](#), [A-2](#)

jobs, [28-7](#)

- adding to an incompatibility, [28-66](#)
- altering, [28-19](#)
- copying, [28-25](#)
- creating, [28-4](#)
- creating and managing Scheduler, [28-2](#)
- creating for chains, [28-59](#)
- credentials, [27-10](#)
- database, [27-21](#)
- detached, [27-26](#)
- disabling, [28-23](#)
- dropping, [28-22](#)
- dropping an incompatibility, [28-67](#)
- e-mail notifications, [28-91](#)
- enabling, [28-24](#)
- event-based, [28-39](#)
- external, [27-22](#)

jobs (*continued*)

- in-memory, [27-28](#)
- in-memory full, example of creating, [28-7](#)
- in-memory runtime, example of creating, [28-7](#)
- incompatibilities, [28-66](#)
- lightweight, [27-27](#)
- lightweight, example of creating, [28-7](#)
- monitoring, [28-84](#)
- monitoring with events raised by the Scheduler, [28-88](#)
- multiple-destination, [27-29](#)
  - status of child jobs, [29-14](#)
- overview, [27-6](#)
- priorities, [28-73](#)
- remote database, [27-21](#)
- remote external
  - about, [27-24](#)
- removing from an incompatibility, [28-67](#)
- resources, [28-68](#), [28-69](#)
- running, [28-20](#)
- script jobs, [27-28](#)
- starting when a file arrives on a system, [28-42](#)
- starting with events raised by your application, [28-38](#)
- status, [28-84](#), [29-32](#)
- stopping, [28-20](#)
- trace messages, [29-18](#)
- troubleshooting remote, [29-22](#)
- viewing information on running, [29-13](#)

## join views

- definition, [23-4](#)
- DELETE statements, [23-11](#)
- key-preserved tables in, [23-9](#)
- modifying, [23-7](#)
- rules for modifying, [23-10](#)
- updating, [23-7](#)

## joins

- statement transparency in distributed databases, [32-29](#)

## K

## key-preserved tables

- in join views, [23-9](#)
- in outer joins, [23-13](#)

## keys

- cluster, [21-1](#)

keystore, [11-11](#), [19-28](#)

## L

large objects, [19-34](#)lightweight jobs, [27-27](#)

- example of creating, [28-7](#)

## links

- See database links

## LIST CHAINED ROWS clause

- of ANALYZE statement, [17-7](#)

## listeners

- removing with srvctl, [2-68](#)

listing database links, [32-19](#), [35-3](#), [35-5](#)

## loading data

- using external tables, [19-142](#)

LOBs, [19-34](#)

## local coordinators

- distributed transactions, [34-5](#)

local temporary tablespaces, [11-15](#)locally managed tablespaces, [11-5](#)

- automatic segment space management in, [11-7](#)

DBMS\_SPACE\_ADMIN package, [11-55](#)detecting and repairing defects, [11-55](#)

- migrating SYSTEM from dictionary-managed, [11-58](#)

shrinking, temporary, [11-42](#)temp files, [11-17](#)temporary, creating, [11-17](#)

## location transparency in distributed databases

- creating using synonyms, [32-25](#)

creating using views, [32-24](#)restrictions, [32-29](#)

- using procedures, [32-29](#)

## lock timeout interval

- distributed transactions, [35-20](#)

## locks

- in-doubt distributed transactions, [35-20](#), [35-21](#)
- monitoring, [6-10](#)

## log

- window (Scheduler), [28-74](#)

log archive destination groups, [10-11](#)

## log sequence number

- control files, [9-4](#)

## log switches

- description, [9-4](#)
- forcing, [9-17](#)
- log sequence numbers, [9-4](#)
- multiplexed redo log files and, [9-7](#)
- privileges, [9-17](#)
- using ARCHIVE\_LAG\_TARGET, [9-11](#)
- waiting for archiving to complete, [9-7](#)

log writer process (LGWR), [3-29](#)

- multiplexed redo log files and, [9-7](#)
- online redo logs available for use, [9-3](#)
- trace files and, [9-7](#)
- writing to online redo log files, [9-3](#)

LOG\_ARCHIVE\_DEST initialization parameter specifying destinations using, [10-7](#)LOG\_ARCHIVE\_DEST\_n initialization parameter, [10-7](#)GROUP attribute, [10-11](#), [10-12](#)PRIORITY attribute, [10-11](#), [10-12](#)REOPEN attribute, [10-18](#)

- LOG\_ARCHIVE\_DEST\_STATE\_n initialization parameter, [10-14](#)
- LOG\_ARCHIVE\_DUPLEX\_DEST initialization parameter
  - specifying destinations using, [10-7](#)
- LOG\_ARCHIVE\_MAX\_PROCESSES initialization parameter, [10-7](#)
- LOG\_ARCHIVE\_MIN\_SUCCEED\_DEST initialization parameter, [10-16](#)
- LOG\_ARCHIVE\_TRACE initialization parameter, [10-19](#)
- LOGGING clause
  - CREATE TABLESPACE, [11-21](#)
- logging mode
  - direct-path INSERT, [19-46](#)
  - NOARCHIVELOG mode and, [19-47](#)
- logical corruptions from DBMS\_REPAIR, [24-6](#)
- logical standby, [27-37](#)
- logical volume managers
  - mapping files to physical devices, [12-22](#), [12-32](#)
  - used for Oracle Managed Files, [15-3](#)
- LOGON trigger
  - setting resumable mode, [18-12](#)
- logs
  - job, [29-15](#)
  - window (Scheduler), [28-74](#), [29-15](#)
- LONG columns, [32-29](#)
- LONG RAW columns, [32-29](#)
- lost write protection
  - shadow lost write protection, [11-44](#)
- LOST WRITE PROTECTION clause, [11-47](#)

## M

- maintenance tasks, automatic
  - See automatic maintenance tasks
- maintenance window
  - creating, [25-6](#)
  - definition, [25-2](#)
  - MAINTENANCE\_WINDOW\_GROUP, [25-3](#)
  - modifying, [25-5](#)
  - predefined, [25-9](#)
  - removing, [25-7](#)
  - Scheduler, [25-3](#)
- MAKE procedure, [39-3](#)
- managing
  - indexes automatically, [20-31](#)
  - sequences, [23-16](#)
  - space threshold alerts for the undo tablespace, [14-14](#)
  - synonyms, [23-26](#)
  - tables, [19-1](#)
  - transactions, [30-1](#)
  - views, [23-1](#)

- manual archiving
  - in ARCHIVELOG mode, [10-6](#)
- manual overrides
  - in-doubt transactions, [35-9](#)
- many to many subqueries
  - materialized views, [36-15](#)
- many to one subqueries
  - materialized views, [36-13](#)
- master materialized view sites, [37-1](#)
- master materialized views, [37-2](#)
  - materialized view logs, [37-3](#)
- master sites, [36-1](#)
  - advantages of, [38-4](#)
  - compared with materialized view sites, [38-3](#)
  - internal triggers, [37-2](#)
  - materialized view registration, [36-30](#)
  - materialized views, [37-1](#)
- master tables
  - materialized view logs, [37-3](#)
  - materialized views, [37-2](#)
  - redefining online, [37-3](#)
  - reorganizing, [37-3](#)
- materialized view logs, [36-21](#), [37-3](#)
  - column logging, [36-19](#)
    - many to many subqueries, [36-19](#)
    - many to one subqueries, [36-19](#)
    - ON PREBUILT TABLE clause, [36-19](#)
    - one to many subqueries, [36-19](#)
  - combination, [37-3](#)
  - creating, [38-8](#)
  - filter columns, [37-4](#)
  - Import, [37-5](#)
  - join columns, [37-4](#)
  - logging columns, [37-4](#)
  - object ID, [37-3](#)
  - object tables, [38-8](#)
  - primary key, [37-3](#)
  - privileges required to create, [38-8](#)
  - REFs, [36-30](#)
  - ROWID, [37-3](#)
  - trigger, [37-2](#)
  - troubleshooting, [40-4](#)
  - underlying table for, [37-3](#)
- materialized view sites, [36-2](#)
  - adding
    - avoiding problems, [39-6](#)
  - advantages of, [38-4](#)
  - compared with master sites, [38-3](#)
  - database links, [38-5](#)
- materialized views
  - BUILD DEFERRED
    - troubleshooting, [40-4](#)
  - capabilities, [39-5](#)
  - collection columns
    - restrictions, [36-28](#)

materialized views (*continued*)

- column objects
  - column subsetting, [36-24](#)
- column subsetting
  - column objects, [36-24](#)
- complex, [36-6](#), [36-8](#)
  - value for PCTUSED, [37-8](#)
- constraints
  - deferrable, [37-11](#)
- creating schemas for, [38-5](#)
- creator, [36-10](#)
- data subsetting, [36-3](#), [36-12](#)
- disconnected computing, [36-3](#)
- index, [37-6](#)
- Logical Partition Change Tracking (LPCT), [37-8](#)
- master materialized view sites, [37-1](#)
- master materialized views, [37-2](#)
- master sites, [37-1](#)
- master tables, [37-2](#)
- materialized view logs, [36-21](#), [37-3](#)
- monitoring, [39-9](#)
- nested tables
  - restrictions, [36-28](#)
- network loads, [36-3](#)
- object materialized views, [39-1](#)
  - OID preservation, [36-26](#)
- object tables, [36-25](#)
- owner, [36-10](#)
- Partition Change Tracking (PCT), [37-8](#)
- preparing for, [38-4](#)
- primary key, [36-4](#)
- privileges, [36-10](#), [38-7](#)
- read-only, [1](#), [36-2](#)
  - registration, [36-31](#)
  - unregistering, [36-31](#)
- refresh groups, [36-21](#), [37-6](#)
  - size, [37-6](#)
- refresher, [36-10](#)
- refreshing, [36-21](#), [37-7](#)
  - complete, [37-8](#)
  - failures, [40-3](#)
  - fast, [36-5](#), [37-8](#), [39-5](#)
  - force, [37-9](#)
  - initiating, [37-9](#)
  - interval, [37-9](#)
  - on-demand, [37-10](#)
  - retries, [40-3](#)
  - troubleshooting, [40-2](#), [40-4](#)
- REFs, [36-28](#)
  - logging, [36-30](#)
  - scoped, [36-29](#)
  - unscoped, [36-30](#)
  - WITH ROWID clause, [36-30](#)
- registration, [36-30](#)
- reorganizing, [37-3](#)

materialized views (*continued*)

- row subsetting, [36-12](#)
- rowid, [36-6](#)
- simple, [36-8](#)
- simple subquery
  - AND condition, [36-19](#)
- subqueries, [36-13](#)
  - column logging, [36-19](#)
  - EXISTS condition, [36-19](#)
  - joins, [36-19](#)
  - many to many, [36-15](#)
  - many to one, [36-13](#)
  - one to many, [36-14](#)
  - OR condition, [36-19](#)
  - restrictions, [36-19](#)
- trace file, [40-3](#)
- types of, [36-4](#)
- unions with subqueries, [36-16](#)
  - restrictions, [36-20](#)
- user-define, [36-22](#)
- user-defined data types
  - ON COMMIT REFRESH clause, [36-22](#)
- uses for, [36-3](#)
- varrays
  - r, [36-28](#)
- materializing deferred segments, [19-32](#)
- MAX\_DUMP\_FILE\_SIZE initialization parameter, [6-4](#), [7-6](#)
- MAX\_IOPS parameter, [26-38](#)
- MAX\_MBPS parameter, [26-38](#)
- MAXDATAFILES parameter
  - changing, [8-6](#)
- MAXINSTANCES, [8-6](#)
- MAXLOGFILES parameter
  - changing, [8-6](#)
  - CREATE DATABASE statement, [9-10](#)
- MAXLOGHISTORY parameter
  - changing, [8-6](#)
- MAXLOGMEMBERS parameter
  - changing, [8-6](#)
  - CREATE DATABASE statement, [9-10](#)
- MAXTRANS parameter
  - altering, [19-58](#)
- media recovery
  - effects of archiving on, [10-3](#)
- MEMOPTIMIZE\_POOL\_SIZE initialization parameter, [4-38](#)
- Memoptimized Rowstore
  - about, [4-38](#)
  - fast ingest, [4-38](#)
  - fast lookup, [4-38](#)
  - MEMOPTIMIZE\_POOL\_SIZE initialization parameter, [4-38](#)
- memory
  - automatic memory management, [4-5](#)
  - automatic shared memory management, [4-11](#)

memory (*continued*)  
 Database Smart Flash Cache, [4-30](#)  
 managing, [4-2](#)  
 manual memory management, [4-10](#)  
 manual shared memory management, [4-19](#)  
 unified memory management, [4-5](#)

migrated rows  
 eliminating from table, procedure, [17-7](#)

MINEXTENTS parameter  
 cannot alter, [19-58](#)

mirrored files  
 control files, [8-3](#)  
 online redo log, [9-7](#)  
 online redo log location, [9-8](#)  
 online redo log size, [9-9](#)

MISSING data files, [8-8](#)

monitoring  
 performance, [6-10](#)  
 running chains, [28-64](#)

MONITORING clause  
 CREATE TABLE, [19-55](#)

MONITORING USAGE clause  
 of ALTER INDEX statement, [20-29](#)

Monthly Recommended Patches (MRP), [1-18](#)

moving control files, [8-5](#)

multiple instances, managing CPU for, [26-108](#)

multiple jobs  
 dropping, [28-22](#)

multiple temporary tablespaces, [11-18](#), [11-20](#)

multiple-destination jobs, Oracle Scheduler, [27-29](#)  
 status of child jobs, [29-14](#)

multiplexed control files  
 importance of, [8-3](#)

multiplexing  
 archived redo log files, [10-7](#)  
 control files, [8-3](#)  
 redo log file groups, [9-6](#)  
 redo log files, [9-6](#)

## N

name resolution in distributed databases  
 database links, [31-35](#)  
 impact of global name changes, [31-40](#)  
 procedures, [31-39](#)  
 schema objects, [31-20](#), [31-37](#)  
 synonyms, [31-39](#)  
 views, [31-39](#)  
 when global database name is complete,  
[31-35](#)  
 when global database name is partial, [31-35](#)  
 when no global database name is specified,  
[31-36](#)

nested tables  
 materialized views, [36-26](#)  
 restrictions, [36-28](#)

nested tables (*continued*)  
 replication, [36-26](#)

networks  
 connections, minimizing, [32-12](#)  
 distributed databases use of, [31-2](#)

NEXTVAL pseudo-column, [23-19](#)  
 restrictions, [23-20](#)

NO\_DATA\_FOUND keyword, [33-10](#)

NO\_MERGE hint, [33-8](#)

NOARCHIVELOG mode  
 archiving, [10-2](#)  
 definition, [10-3](#)  
 dropping data files, [12-9](#)  
 LOGGING mode and, [19-47](#)  
 media failure, [10-3](#)  
 no hot backups, [10-3](#)  
 running in, [10-3](#)  
 switching to, [10-5](#)  
 taking data files offline in, [12-9](#)

NOLOGGING clause  
 CREATE TABLESPACE, [11-21](#)

NOLOGGING mode  
 direct-path INSERT, [19-46](#)

normal transmission mode  
 definition, [10-15](#)

Novell NetWare Management System, [31-30](#)

## O

object identifiers  
 agreement for replication, [36-23](#)

object materialized views, [39-1](#)  
 OID preservation, [36-26](#)

object privileges  
 for external tables, [19-157](#)

object quarantine, [6-12](#)

object tables  
 materialized view logs, [38-8](#)  
 materialized views, [36-25](#)

object-relational model  
 replication, [36-22](#)

objects  
 See schema objects

OF object\_type clause  
 object materialized views, [39-1](#)

offline tablespaces  
 priorities, [11-22](#)  
 taking offline, [11-22](#)

ON COMMIT REFRESH clause  
 of CREATE MATERIALIZED VIEW, [36-22](#)

ON PREBUILT TABLE clause, [36-19](#)

one to many subqueries  
 materialized views, [36-14](#)

online redefinition of tables, [19-68](#), [37-3](#)  
 examples, [19-98](#)  
 features of, [19-69](#)

- online redefinition of tables (*continued*)
  - intermediate synchronization, [19-81](#)
  - monitoring, [19-85](#)
  - redefining a single partition
    - rules for, [19-97](#)
  - redefining partitions, [19-96](#)
  - refreshing dependent materialized views, [19-81](#)
  - restarting after failure, [19-88](#)
  - restrictions, [19-71](#)
  - rolling back, [19-92](#)
  - terminate and cleanup, [19-95](#)
  - Virtual Private Database policies, [19-78](#)
  - with DBMS\_REDEFINITION, [19-74](#)
- online redo log files
  - See online redo logs
- online redo logs, [9-1](#), [9-2](#)
  - creating groups, [9-12](#)
  - creating members, [9-13](#)
  - data dictionary views reference, [9-20](#)
  - dropping groups, [9-15](#)
  - dropping members, [9-15](#)
  - forcing a log switch, [9-17](#)
  - guidelines for configuring, [9-5](#)
  - INVALID members, [9-16](#)
  - location of, [9-8](#)
  - managing, [9-1](#)
  - moving files, [9-14](#)
  - number of files in the, [9-10](#)
  - optimum configuration for the, [9-10](#)
  - renaming files, [9-14](#)
  - renaming members, [9-14](#)
  - specifying ARCHIVE\_LAG\_TARGET, [9-11](#)
  - STALE members, [9-16](#)
    - See also redo log files]
- online segment shrink, [18-31](#)
- OPEN\_LINKS initialization parameter, [32-18](#)
- opening windows, [28-76](#)
- operating system authentication, [1-31](#), [1-33](#)
- operating systems
  - database administrators requirements for, [1-21](#)
  - renaming and relocating files, [12-13](#)
- optimizer statistics
  - dynamic, [7-42](#)
- OR condition
  - materialized views with subqueries, [36-19](#)
- ORA-02055 error
  - integrity constraint violation, [33-2](#)
- ORA-02067 error
  - rollback required, [33-2](#)
- ORA-12838 error, direct path insert, [19-45](#)
- Oracle Call Interface
  - See OCI
- Oracle Data Guard
  - support by the Scheduler, [27-37](#), [29-29](#)
- Oracle Database In-Memory, [4-37](#)
- Oracle Database users
  - types of, [1-3](#)
- Oracle home
  - cloning, [1-9](#)
- Oracle managed files, [15-1](#)
  - naming, [15-8](#)
  - scenarios for using, [15-25](#)
- Oracle Managed Files
  - adding to an existing database, [15-30](#)
  - behavior, [15-23](#)
  - benefits, [15-3](#)
  - CREATE DATABASE statement, [15-9](#)
  - creating, [15-7](#)
  - creating control files, [15-20](#)
  - creating data files, [15-15](#)
  - creating online redo log files, [15-22](#)
  - creating temp files, [15-18](#)
  - described, [15-2](#)
  - dropping data file, [15-24](#)
  - dropping online redo log files, [15-24](#)
  - dropping temp file, [15-24](#)
  - initialization parameters, [15-5](#)
  - renaming, [15-24](#)
- Oracle Managed Files feature
  - See Oracle managed files
- Oracle release numbers, [1-18](#)
- Oracle Restart
  - about, [2-2](#)
  - configuration
    - adding components to, [2-15](#)
    - modifying, [2-19](#)
    - removing components from, [2-16](#)
    - viewing for a component, [2-18](#)
  - configuring, [2-11](#)
  - CRSCTL utility, [2-4](#)
  - disabling and enabling management for a component, [2-17](#)
  - environment variables in, [2-20](#)
  - patches
    - installing, [2-29](#)
  - registering a component with, [2-15](#)
  - starting, [2-4](#)
  - starting and stopping components managed by, [2-29](#)
    - Oracle home, [2-29](#)
  - status of components, [2-18](#)
  - stopping, [2-4](#)
- Oracle Scheduler
  - creating credentials, [28-9](#)
- Oracle Scheduler agent
  - on Windows, [29-11](#)
  - OracleSchedulerExecutionAgent, [29-11](#)
  - tasks, [29-10](#)
  - Windows Service, [29-11](#)
- Oracle Scheduler Agent, [29-5](#)



Oracle Scheduler agents  
     registering with databases, [29-12](#)  
 OracleSchedulerExecutionAgent, [29-11](#)  
 ORAPWD utility, [1-43](#)  
 ORGANIZATION EXTERNAL clause  
     of CREATE TABLE, [19-142](#)  
 orphan key table  
     example of building, [24-9](#)  
 OSBACKUPDBA group, [1-31](#)  
 OSDBA group, [1-31](#)  
 OSDGDBA group, [1-31](#)  
 OSKMDBA group, [1-31](#)  
 OSOPER group, [1-31](#)  
 OTHER\_GROUPS  
     for Database Resource Manager, [26-8](#)  
 OTHER\_GROUPS for Database Resource  
     Manager, [26-89](#), [26-94](#), [26-107](#)  
 outer joins, [23-13](#)  
     key-preserved tables in, [23-13](#)  
 overlapping windows, [27-15](#)

## P

---

packages  
     DBMS\_FILE\_TRANSFER, [12-18](#)  
     DBMS\_METADATA, [17-33](#)  
     DBMS\_REPAIR, [24-2](#)  
     DBMS\_RESOURCE\_MANAGER, [26-7](#),  
         [26-31](#), [26-48](#)  
     DBMS\_RESOURCE\_MANAGER\_PRIVS,  
         [26-31](#)  
     DBMS\_RESUMABLE, [18-14](#)  
     DBMS\_SPACE, [18-33](#), [18-35](#)  
     DBMS\_STORAGE\_MAP, [12-29](#)  
 packaging and uploading problems, [7-55](#)  
 parallel execution  
     managing, [3-32](#)  
     parallel hints, [3-33](#)  
     parallelizing index creation, [20-7](#)  
     resumable space allocation, [18-9](#)  
 parallel hints, [3-33](#)  
 parallel statement execution  
     directive attributes for managing, [26-104](#)  
     managing using Resource Manager, [26-16](#)  
 parallelizing table creation, [19-6](#), [19-40](#)  
 partitioned tables  
     moving a partition online, [19-60](#)  
     redefining partitions online, [19-96](#)  
     rules for, [19-97](#)  
 password file  
     adding users, [1-47](#)  
     creating, [1-43](#)  
     ORAPWD utility, [1-43](#)  
     removing, [1-49](#)  
     setting REMOTE\_LOGIN\_PASSWORD, [1-45](#)

password file (*continued*)  
     synchronizing administrator passwords with  
         the data dictionary, [1-45](#)  
     viewing members, [1-48](#)  
 password file authentication, [1-34](#)  
 passwords  
     case sensitivity of, [1-29](#), [1-35](#), [1-36](#)  
     password file, [1-47](#)  
     setting REMOTE\_LOGIN\_PASSWORD  
         parameter, [1-45](#)  
 patch sets, [1-18](#)  
 patches  
     installing  
         Oracle Restart, [2-29](#)  
 pausing chains and chain steps, [28-62](#)  
 PCTINCREASE parameter, [19-58](#)  
 PCTUSED parameter  
     value for complex materialized views, [37-8](#)  
 PDB performance profiles, [26-60](#)  
     managing, [26-69](#)  
 PDB resource plans, [26-26](#)  
 PDBs  
     buffer pool size, [26-34](#)  
     CDB resource plans, [26-21](#)  
         creating, [26-57](#), [26-60](#)  
         directives, [26-24](#)  
         disabling, [26-76](#)  
         enabling, [26-64](#)  
         managing, [26-64](#)  
         shares, [26-21](#)  
         utilization limits, [26-22](#)  
         viewing information about, [26-77](#)  
     CPU limits, [26-33](#)  
     Database Resource Manager, [26-56](#)  
     I/O limits, [26-38](#)  
     import operations, [13-15](#), [13-26](#)  
     PDB resource plans, [26-26](#)  
         creating, [26-79](#)  
         disabling, [26-82](#)  
         enabling, [26-80](#)  
         modifying, [26-81](#)  
     PGA size, [26-34](#)  
     resource management, [26-3](#)  
     SGA size, [26-34](#)  
     shared pool size, [26-34](#)  
 pending area for Database Resource Manager  
     plans, [26-96](#)  
     validating plan schema changes, [26-94](#)  
 pending transaction tables, [35-20](#)  
 performance  
     index column order, [20-5](#)  
     location of data files and, [12-5](#)  
     monitoring, [6-10](#)  
 PGA\_AGGREGATE\_LIMIT parameter, [26-34](#)  
 PGA\_AGGREGATE\_TARGET parameter, [26-34](#)

## PL/SQL

- replaced views and program units, [23-5](#)

- plan schemas for Database Resource Manager,

- [26-11](#), [26-39](#), [26-111](#)

- validating plan changes, [26-94](#)

- plans for Database Resource Manager

- examples, [26-96](#)

- PRAGMA\_EXCEPTION\_INIT procedure

- assigning exception names, [33-10](#)

- prefix compression, [19-133](#), [20-19](#)

- prepare phase

- abort response, [34-12](#)

- in two-phase commit, [34-10](#)

- prepared response, [34-11](#)

- read-only response, [34-11](#)

- recognizing read-only nodes, [34-11](#)

- steps, [34-12](#)

- prepare/commit phases

- effects of failure, [35-20](#)

- failures during, [35-6](#)

- locked resources, [35-20](#)

- pending transaction table, [35-20](#)

- prepared response

- two-phase commit, [34-11](#)

- prespawned processes, [3-30](#)

- PRIMARY KEY constraints

- associated indexes, [20-15](#)

- dropping associated indexes, [20-31](#)

- enabling on creation, [20-15](#)

- foreign key references when dropped, [17-18](#)

- indexes associated with, [20-15](#)

- materialized views, [36-4](#)

- replicated tables, [38-1](#)

- priorities

- job, [28-73](#)

- priority transactions

- acknowledging rollback, [30-4](#)

- behavior, [30-7](#), [30-8](#)

- determining system-level wait targets, [30-5](#)

- distributed transaction behavior, [30-7](#)

- monitoring, [30-6](#)

- restrictions, [30-8](#)

- setting mode, [30-4](#)

- setting system-level wait targets, [30-3](#)

- setting transaction priority, [30-2](#)

- statistics incremented in ROLLBACK mode,

- [30-6](#)

- statistics incremented in TRACK mode, [30-7](#)

- using, [30-2](#)

- private database links, [31-13](#)

- private synonyms, [23-26](#)

- private temporary tables

- creating, [19-38](#)

- privileges

- adding redo log groups, [9-12](#)

- altering index, [20-24](#)

- privileges (*continued*)

- altering tables, [19-56](#)

- closing a database link, [33-2](#)

- creating database links, [32-7](#)

- creating tables, [19-33](#)

- creating tablespaces, [11-4](#)

- database administrator, [1-21](#)

- drop table, [19-120](#)

- dropping indexes, [20-31](#)

- dropping online redo log members, [9-16](#)

- dropping redo log groups, [9-16](#)

- enabling and disabling triggers, [17-11](#)

- for external tables, [19-157](#)

- forcing a log switch, [9-17](#)

- managing with procedures, [32-29](#)

- managing with synonyms, [32-27](#)

- managing with views, [32-25](#)

- manually archiving, [10-6](#)

- materialized views, [36-10](#), [38-7](#)

- renaming objects, [17-22](#)

- renaming redo log members, [9-14](#)

- Scheduler, [29-30](#)

- sequences, [23-17](#), [23-25](#)

- setting chain (Scheduler), [29-2](#)

- synonyms, [23-26](#), [23-27](#)

- taking tablespaces offline, [11-22](#)

- truncating, [17-9](#)

- using a view, [23-6](#)

- using sequences, [23-18](#)

- views, [23-3](#), [23-5](#), [23-15](#)

- problem activity log

- adding comments to, [7-21](#)

- problems

- about, [7-3](#)

- adding comments to activity log, [7-21](#)

- problems (critical errors)

- packaging and uploading, [7-55](#)

- procedures

- external, [3-35](#)

- location transparency in distributed

- databases, [32-27](#)

- name resolution in distributed databases,

- [31-39](#)

- remote calls, [31-43](#)

- process manager (PMAN), [3-29](#)

- process monitor (PMON), [3-29](#)

- processes, [3-2](#)

- prespawned, [3-30](#)

- See also server processes

- PRODUCT\_COMPONENT\_VERSION view, [1-20](#)

- programs

- altering, [28-28](#)

- creating, [28-26](#)

- creating and managing, to define Scheduler

- jobs, [28-25](#)

- disabling, [28-28](#)

programs (*continued*)  
 dropping, [28-28](#)  
 enabling, [28-29](#)  
 overview, [27-4](#)  
 proxy resident connection pooling, [3-8](#)  
 per-PDB, [3-8](#)  
 per-service, [3-8](#)  
 public database links, [31-13](#)  
 connected user, [32-32](#)  
 fixed user, [32-31](#)  
 public fixed user database links, [32-31](#)  
 public synonyms, [23-26](#)  
 PURGE\_LOST\_DB\_ENTRY procedure  
 DBMS\_TRANSACTION package, [35-12](#)

## Q

quarantine  
 objects, [6-12](#)  
 SQL statements, [7-78](#)  
 queries  
 distributed, [31-32](#)  
 distributed application development issues,  
[33-3](#)  
 location transparency and, [31-43](#)  
 remote, [31-32](#)  
 quotas  
 tablespace, [11-3](#)

## R

RAISE\_APPLICATION\_ERROR() procedure,  
[33-10](#)  
 read consistency  
 managing in distributed databases, [35-23](#)  
 read-o, [36-31](#)  
 read-only materialized views, [1](#), [36-2](#)  
 registration  
 manual, [36-31](#)  
 read-only response  
 two-phase commit, [34-11](#)  
 read-only tables, [19-66](#)  
 read-only tablespaces  
 data file headers when rename, [11-42](#)  
 delaying opening of data files, [11-28](#)  
 enabling database for object storage, [11-29](#)  
 making read-only, [11-25](#)  
 making writable, [11-27](#)  
 on object storage  
 accessing, [11-32](#)  
 creating default credential, [11-33](#)  
 deleting, [11-35](#)  
 moving, [11-33](#)  
 querying, [11-35](#)  
 setting ACE, [11-30](#)  
 setting HTTP proxy, [11-29](#)

read-only tablespaces (*continued*)  
 on object storage (*continued*)  
 using, [11-29](#)  
 WORM devices, [11-28](#)  
 Real Application Clusters  
 allocating extents for cluster, [21-7](#)  
 sequence numbers and, [23-17](#)  
 threads of online redo log, [9-2](#)  
 rebuilding indexes, [20-26](#)  
 costs, [20-10](#)  
 online, [20-26](#)  
 reclaiming unused space, [18-16](#)  
 recoverer process, [3-29](#)  
 disabling, [35-22](#)  
 distributed transaction recovery, [35-22](#)  
 enabling, [35-22](#)  
 pending transaction table, [35-22](#)  
 recovering  
 Scheduler jobs, [29-23](#)  
 recovery  
 creating new control files, [8-6](#)  
 recycle bin  
 about, [19-122](#)  
 purging, [19-124](#)  
 renamed objects, [19-122](#)  
 restoring objects from, [19-125](#)  
 viewing, [19-124](#)  
 REDEF\_TABLE procedure, [19-73](#)  
 example, [19-98](#)  
 redefining tables  
 online  
 replication, [37-3](#)  
 redefining tables online  
 See online redefinition of tables, [19-68](#)  
 redo log files, [9-1](#), [9-2](#)  
 active (current), [9-4](#)  
 archiving, [10-2](#)  
 available for use, [9-3](#)  
 block size, setting, [9-9](#)  
 circular use of, [9-3](#)  
 clearing, [9-18](#)  
 contents of, [9-2](#)  
 creating as Oracle Managed Files, [15-22](#)  
 creating as Oracle Managed Files, example,  
[15-25](#)  
 creating groups, [9-12](#)  
 creating members, [9-12](#), [9-13](#)  
 distributed transaction information in, [9-3](#)  
 dropping groups, [9-15](#)  
 dropping members, [9-15](#)  
 group members, [9-6](#)  
 groups, defined, [9-6](#)  
 how many in redo log, [9-10](#)  
 inactive, [9-4](#)  
 instance recovery use of, [9-2](#)  
 LGWR and the, [9-3](#)

- redo log files (*continued*)
  - log switches, [9-4](#)
  - maximum number of members, [9-10](#)
  - members, [9-6](#)
  - mirrored, log switches and, [9-7](#)
  - multiplexed, [9-6](#), [9-7](#)
  - online, defined, [9-2](#)
  - planning the, [9-5](#)
  - redo entries, [9-2](#)
  - requirements, [9-8](#)
  - specifying at database creation, [15-11](#)
  - storing separately from data files, [12-5](#)
  - threads, [9-2](#)
  - valid and invalid configurations, [9-8](#)
  - verifying blocks, [9-17](#)
    - See also online redo logs
- redo logs
  - See online redo log
- redo records, [9-2](#)
  - LOGGING and NOLOGGING, [11-21](#)
- referential integrity
  - distributed database application development, [33-2](#)
- refresh
  - automatic, [37-9](#)
  - complete, [37-8](#)
  - failures, [40-3](#)
  - fast, [37-8](#)
    - determining possibility of, [39-5](#)
  - force, [37-9](#)
  - group, [37-9](#)
  - initiating, [37-9](#)
  - interval, [37-9](#)
  - manual, [37-10](#)
  - materialized views, [36-21](#), [37-7](#)
  - monitoring, [39-12](#)
  - on-demand, [37-10](#)
  - retries, [40-3](#)
  - rollback segments
    - troubleshooting, [40-4](#)
  - scheduling, [37-9](#)
    - troubleshooting, [40-4](#)
  - troubleshooting
    - ORA-12004 error, [40-4](#)
    - ORA-942 error, [40-4](#)
  - truncating materialized views
    - troubleshooting, [40-4](#)
- refresh groups, [36-2](#), [36-21](#), [37-6](#)
  - monitoring, [39-11](#)
  - size considerations, [37-6](#)
  - troubleshooting, [40-2](#)
- REFRESH procedure, [37-10](#), [39-4](#)
- REFRESH\_ALL\_MVIEWS procedure, [37-10](#), [39-4](#)
- REFRESH\_DEPENDENT procedure, [37-10](#), [39-4](#)
- REFs
  - materialized views, [36-28](#)
- REFs (*continued*)
  - replication, [36-28](#)
- REGISTER\_MVIEW procedure, [36-31](#)
- release numbers, [1-18](#)
- release update (Update, RU), [1-18](#)
- Release Update Revisions (Revisions)
  - installing, [1-9](#)
- Release Updates (Updates)
  - installing, [1-9](#)
- releases, [1-18](#)
  - checking the Oracle Database release number, [1-20](#)
  - definition, [1-18](#)
- relocating control files, [8-5](#)
- remote data
  - querying, [32-29](#)
  - updating, [32-29](#)
- remote database jobs, [27-21](#)
  - Scheduler agent setup, [29-9](#)
- remote external jobs
  - about, [27-24](#)
  - executing, [29-5](#)
  - Scheduler agent setup, [29-9](#)
- remote procedure calls, [31-43](#)
  - distributed databases and, [31-43](#)
- remote queries
  - distributed databases and, [31-32](#)
- remote transactions, [31-33](#)
  - defined, [31-33](#)
- REMOTE\_LOGIN\_PASSWORDFILE initialization parameter, [1-45](#)
- REMOTE\_OS\_AUTHENT initialization parameter
  - connected user database links, [31-15](#)
- RENAME statement, [17-22](#)
- renaming control files, [8-5](#)
- renaming files
  - Oracle Managed Files, [15-24](#)
- renaming indexes, [20-29](#)
- REOPEN attribute
  - LOG\_ARCHIVE\_DEST\_n initialization parameter, [10-18](#)
- repair table
  - example of building, [24-9](#)
- repairing data block corruption
  - DBMS\_REPAIR, [24-1](#)
- repeat interval, schedule, [28-32](#)
- replication
  - filter columns, [37-4](#)
  - job child processes, [38-7](#)
  - master sites
    - advantages, [38-4](#)
  - materialized view logs, [36-21](#)
  - materialized view sites
    - advantages, [38-4](#)
  - monitoring
    - materialized view environments, [39-9](#)

- replication (*continued*)
  - read-only materialized views, [36-2](#)
  - refresh, [36-21](#)
  - refresh groups, [36-2](#), [36-21](#)
  - sites, [36-1](#)
    - choosing, [38-3](#)
  - tables, [38-1](#)
  - unsupported data types
    - BFILE, [38-1](#)
    - LONG, [38-1](#)
  - unsupported table types, [38-3](#)
  - user-defined data types, [36-22](#)
  - virtual private database (VPD), [38-6](#)
- replication catalog
  - DBA\_REGISTERED\_MVIEWS, [36-31](#)
  - USER\_REFRESH, [40-3](#)
  - USER\_REFRESH\_CHILDREN, [40-3](#)
- replication objects
  - at materialized view sites
    - problems creating, [40-2](#)
  - indexes
    - on foreign keys, [38-1](#)
  - tables, [38-1](#)
    - foreign keys, [38-1](#)
    - primary keys, [38-1](#)
- reporting problems to Oracle Support, [7-51](#)
- RESOLVE\_TNSNAME function, [32-21](#)
- resource allocation methods
  - active session pool, [26-88](#)
  - ACTIVE\_SESS\_POOL\_MTH, [26-88](#)
  - CPU, [26-10](#)
  - CPU resource, [26-88](#)
  - EMPHASIS, [26-88](#)
  - limit on degree of parallelism, [26-88](#)
  - MAX\_UTILIZATION\_METHOD, [26-12](#)
  - PARALLEL\_DEGREE\_LIMIT\_MTH, [26-88](#)
  - PARALLEL\_DEGREE\_LIMIT\_P1, [26-13](#)
  - PARALLEL\_QUEUE\_TIMEOUT, [26-16](#)
  - PARALLEL\_STMT\_CRITICAL, [26-14](#)
  - PGA, [26-17](#)
  - QUEUEING\_MTH, [26-88](#)
  - queuing resource allocation method, [26-88](#)
- resource consumer groups, [26-7](#)
  - changing, [26-48](#)
  - creating, [26-86](#)
  - DEFAULT\_CONSUMER\_GROUP, [26-54](#), [26-110](#)
  - deleting, [26-110](#)
  - granting the switch privilege, [26-54](#)
  - managing, [26-42](#), [26-49](#)
  - OTHER\_GROUPS, [26-8](#), [26-89](#), [26-94](#), [26-107](#)
  - parameters, [26-86](#)
  - revoking the switch privilege, [26-55](#)
  - setting initial, [26-43](#)
  - switching a session, [26-48](#)
- resource consumer groups (*continued*)
  - switching sessions for a user, [26-49](#)
  - SYS\_GROUP, [26-107](#)
  - updating, [26-110](#)
- Resource Manager
  - AUTO\_TASK\_CONSUMER\_GROUP
    - consumer group, [25-7](#)
  - canceling long-running SQL statements, [26-18](#)
  - managing parallel statement execution, [26-16](#)
  - quarantine SQL statements, [26-18](#)
- resource plan directives, [26-7](#), [26-94](#)
  - deleting, [26-113](#)
  - for managing parallel statement execution, [26-104](#)
  - specifying, [26-89](#)
  - updating, [26-112](#)
- resource plans, [26-7](#), [26-30](#)
  - CDB, [26-21](#)
  - creating, [26-82](#)
  - DEFAULT\_MAINTENANCE\_PLAN, [25-8](#)
  - DELETE\_PLAN\_CASCADE, [26-111](#)
  - deleting, [26-111](#)
  - examples, [26-96](#)
  - parameters, [26-88](#)
  - PDB, [26-26](#)
  - plan schemas, [26-11](#), [26-39](#), [26-111](#)
  - SYSTEM\_PLAN, [26-107](#)
  - top plan, [26-39](#), [26-94](#)
  - updating, [26-111](#)
  - validating, [26-94](#)
- RESOURCE\_MANAGER\_CPU\_SCOPE
  - initialization parameter, [26-131](#)
- RESOURCE\_MANAGER\_PLAN initialization
  - parameter, [26-39](#)
- resources (job)
  - altering, [28-69](#)
  - creating, [28-68](#)
  - managing, [28-68](#)
  - specifying for jobs, [28-69](#)
- result sets, SQL, [19-35](#)
- resumable space allocation
  - correctable errors, [18-8](#)
  - detecting suspended statements, [18-12](#)
  - disabling, [18-10](#)
  - distributed databases, [18-9](#)
  - enabling, [18-10](#)
  - example, [18-15](#)
  - how resumable statements work, [18-7](#)
  - naming statements, [18-12](#)
  - parallel execution and, [18-9](#)
  - resumable operations, [18-8](#)
  - setting as default for session, [18-12](#)
  - timeout interval, [18-11](#), [18-13](#)
- RESUMABLE\_TIMEOUT initialization parameter
  - setting, [18-10](#)

- retention guarantee (for undo), [14-6](#)
- reversing table changes, [19-119](#)
- roles
  - DBA role, [1-24](#)
  - obtained through database links, [31-20](#)
- ROLLBACK statement
  - FORCE clause, [35-9](#), [35-10](#)
  - forcing, [35-7](#)
- rollbacks
  - ORA-02, [33-2](#)
- rolling upgrade, [27-37](#)
- row subsetting, [36-12](#)
  - materialized views, [36-12](#)
- rowids
  - rowid materialized views, [36-6](#)
- rows
  - listing chained or migrated, [17-6](#)
- rsmgr:io rate limit, [26-38](#)
- rules
  - adding to a chain, [28-55](#)
  - dropping from chains, [28-61](#)
- running
  - chains, [28-60](#)
  - jobs, [28-20](#)

## S

- savepoints
  - in-doubt transactions, [35-9](#), [35-10](#)
- scalable sequences, [23-23](#)
- schagent utility, [29-11](#)
- Scheduler
  - administering, [29-1](#)
  - architecture, [27-32](#)
  - closing a PDB, [27-37](#)
  - configuring, [29-2](#)
  - credentials for jobs, [27-10](#)
  - data dictionary views reference, [29-32](#)
  - e-mail notifications, [28-91](#)
  - examples of using, [29-24](#)
  - import and export, [29-20](#)
  - maintenance window, [25-3](#)
  - monitoring and managing, [29-13](#)
  - monitoring jobs, [28-84](#)
  - objects, [27-3](#)
  - overview, [27-1](#)
  - security, [29-20](#)
  - support for Oracle Data Guard, [27-37](#), [29-29](#)
  - troubleshooting, [29-21](#)
    - job does not run, [29-21](#)
  - using in RAC, [27-35](#)
- Scheduler agent, [29-5](#)
  - configuration, [29-9](#)
  - installation, [29-9](#)
  - setup, [29-9](#)
- Scheduler chain condition syntax, [28-55](#)
- Scheduler job credentials
  - specifying, [28-9](#)
- Scheduler objects, naming, [28-2](#)
- Scheduler privileges reference, [29-30](#)
- SCHEDULER\_BATCH\_ERRORS view, [28-22](#)
- schedules
  - altering, [28-31](#)
  - creating, [28-30](#)
  - creating and managing, to define Scheduler jobs, [28-29](#)
  - dropping, [28-31](#)
  - overview, [27-5](#)
- schema objects, [17-26](#)
  - analyzing, [17-4](#)
  - creating multiple objects, [17-2](#)
  - data dictionary views reference, [17-34](#)
  - defining using DBMS\_METADATA package, [17-33](#)
  - dependencies between, [17-23](#)
  - distributed database naming conventions for, [31-20](#)
  - global names, [31-20](#)
  - listing by type, [17-34](#)
  - name resolution in distributed databases, [31-20](#), [31-37](#)
  - name resolution in SQL statements, [17-26](#)
  - privileges to rename, [17-22](#)
  - referencing with synonyms, [32-26](#)
  - renaming, [17-22](#)
  - validating structure, [17-5](#)
  - viewing information, [17-33](#), [18-35](#)
- schema objects space usage
  - data dictionary views reference, [18-36](#)
- schemas
  - creating for materialized views, [38-5](#)
- SCN
  - See system change number
- script jobs, [27-28](#)
- security
  - accessing a database, [5-1](#)
  - administrator of, [5-1](#)
  - centralized user management in distributed databases, [31-25](#)
  - database security, [5-1](#)
  - distributed databases, [31-22](#)
  - establishing policies, [5-1](#)
  - privileges, [5-1](#)
  - remote objects, [32-25](#)
  - Scheduler, [29-20](#)
  - using synonyms, [32-27](#)
- Segment Advisor, [18-18](#)
  - configuring Scheduler job, [18-29](#)
  - invoking with Oracle Enterprise Manager Cloud Control, [18-20](#)
  - invoking with PL/SQL, [18-21](#)
  - running manually, [18-19](#)



- Segment Advisor (*continued*)
  - using, [18-18](#)
  - viewing results, [18-24](#)
  - views, [18-30](#)
- SEGMENT\_FIX\_STATUS procedure
  - DBMS\_REPAIR, [24-2](#)
- segments
  - available space, [18-35](#)
  - data dictionary views for, [18-36](#)
  - deallocating unused space, [18-16](#)
  - displaying information on, [18-37](#)
  - dropping for empty tables, [18-34](#)
  - shrinking, [18-31](#)
- SELECT statement
  - FOR UPDATE clause and location
    - transparency, [32-29](#)
- SEQUENCE\_CACHE\_ENTRIES parameter, [23-22](#)
- sequences
  - accessing, [23-18](#)
  - altering, [23-17](#)
  - caching sequence numbers, [23-21](#)
  - creating, [23-17](#), [23-22](#)
  - CURRVAL, [23-20](#)
  - data dictionary views reference, [23-28](#)
  - dropping, [23-25](#)
  - managing, [23-16](#)
  - NEXTVAL, [23-19](#)
  - Oracle Real Applications Clusters and, [23-17](#)
  - scalable, [23-23](#)
- SERVER parameter
  - net service name, [32-14](#)
- server processes, [3-2](#)
  - archiver (ARCn), [3-29](#)
  - background, [3-29](#)
  - checkpoint (CKPT), [3-29](#)
  - database writer (DBWn), [3-29](#)
  - dedicated, [3-2](#)
  - dispatcher (Dnnn), [3-29](#)
  - dispatchers, [3-16](#)
  - log writer (LGWR), [3-29](#)
  - monitoring locks, [6-10](#)
  - process monitor (PMON), [3-29](#)
  - recoverer (RECO), [3-29](#)
  - shared server, [3-3](#)
  - system monitor (SMON), [3-29](#)
  - trace files for, [6-2](#)
- server-generated alerts, [6-6](#)
- servers
  - role in two-phase commit, [34-5](#)
- service names
  - database links and, [32-11](#)
- services
  - creating with SRVCTL and Oracle Restart, [2-22](#)
- session trees for distributed transactions
  - clients, [34-4](#)
  - commit point site, [34-6](#), [34-7](#)
  - database servers, [34-5](#)
  - definition, [34-3](#)
  - global coordinators, [34-5](#)
  - local coordinators, [34-5](#)
  - tracing transactions, [35-5](#)
- sessions
  - acknowledge priority transactions rollback, [30-4](#)
  - active, [3-38](#)
  - inactive, [3-39](#)
  - priority transactions, [30-1](#)
  - setting advice for transactions, [35-8](#)
  - setting priority transaction mode, [30-4](#)
  - setting system-level wait targets, [30-3](#)
  - setting transaction priority, [30-2](#)
  - terminating, [3-37](#)
- SGA
  - See system global area
- SGA\_MIN\_SIZE parameter, [26-34](#)
- SGA\_TARGET parameter, [26-34](#)
- shadow lost write protection, [11-44](#)
  - creating tablespaces for, [11-47](#)
  - disabling, [11-50](#)
  - dropping a shadow tablespace, [11-52](#)
  - enabling for a data file, [11-49](#)
  - enabling for a database, [11-47](#)
  - enabling for a PDB, [11-47](#)
  - enabling for a tablespace, [11-49](#)
  - removing, [11-51](#)
  - suspending, [11-51](#)
- shared database links
  - configuring, [32-14](#)
  - creating, [32-14](#)
  - dedicated servers, creating links to, [32-14](#)
  - determining whether to use, [32-13](#)
  - example, [31-18](#)
  - shared servers, creating links to, [32-15](#)
- shared server, [3-3](#)
  - configuring dispatchers, [3-14](#)
  - data dictionary views reference, [3-19](#)
  - disabling, [3-12](#), [3-19](#)
  - initialization parameters, [3-10](#)
  - interpreting trace output, [6-6](#)
  - setting minimum number of servers, [3-12](#)
  - trace files for processes, [6-2](#)
- shared SQL
  - for remote and distributed statements, [31-33](#)
- shared temporary tablespaces, [11-15](#)
- SHARED\_POOL\_SIZE parameter, [26-34](#)
- shrinking segments online, [18-31](#)
- simple materialized views, [36-8](#)

- Simple Network Management Protocol (SNMP)
  - support
    - database management, [31-30](#)
- single-file tablespaces
  - description, [11-8](#)
- single-table hash clusters, [22-7](#)
- site autonomy
  - distributed databases, [31-22](#)
- SKIP\_CORRUPT\_BLOCKS procedure, [24-7](#)
  - DBMS\_REPAIR, [24-2](#)
  - example, [24-12](#)
- skipping chain steps, [28-63](#)
- SORT\_AREA\_SIZE initialization parameter
  - index creation and, [20-3](#)
- space
  - deallocating unused, [18-33](#)
  - reclaiming unused, [18-16](#)
- space allocation
  - resumable, [18-6](#)
- space management
  - data types, space requirements, [18-35](#)
  - deallocating unused space, [18-16](#)
  - Segment Advisor, [18-16](#)
  - shrink segment, [18-16](#)
- space usage alerts for tablespaces, [18-3](#)
- SQL
  - result sets, [19-35](#)
  - submitting, [1-10](#)
  - test cases, [7-41](#)
- SQL failure
  - repairing with SQL Repair Advisor, [7-70](#)
- SQL incidents, [7-42](#)
- SQL patch
  - disabling using Cloud Control, [7-74](#)
  - disabling using DBMS\_SQLDIAG package
    - subprogram, [7-75](#)
  - removing using Cloud Control, [7-74](#)
  - removing using DBMS\_SQLDIAG package
    - subprogram, [7-75](#)
  - viewing using Cloud Control, [7-74](#)
- SQL Repair Advisor
  - about, [7-71](#)
  - exporting and importing a patch using the
    - DBMS\_SQLDIAG package
    - subprograms, [7-76](#)
  - repairing SQL failure with, [7-70](#)
  - running using Cloud Control, [7-71](#)
  - running using the DBMS\_SQLDIAG package
    - subprograms, [7-72](#)
- SQL statements
  - about quarantine, [7-79](#)
  - cancelling, [3-40](#)
  - distributed databases and, [31-32](#)
  - quarantine, [7-78](#)
- SQL test case builder, [7-3](#)
- SQL Test Case Builder, [7-42](#)
  - accessing the Incident Manager, [7-46](#)
  - accessing the Support Workbench, [7-47](#)
  - command-line interface, [7-47](#)
  - gathering diagnostic data, [7-41](#)
  - graphical interface, [7-46](#)
  - key concepts, [7-42](#)
  - output, [7-44](#)
  - running, [7-48](#)
  - SQL incidents, [7-42](#)
  - user interfaces, [7-46](#)
  - what it captures, [7-42](#)
- SQL\_TRACE initialization parameter
  - trace files and, [6-2](#)
- SQL\*Loader
  - about, [1-49](#), [19-41](#)
- SQL\*Plus, [1-10](#)
  - about, [1-11](#)
  - connecting with, [1-12](#)
- SRVCTL
  - add asm command, [2-36](#)
  - add command, usage description, [2-35](#)
  - add database command, [2-38](#)
  - add listener command, [2-40](#)
  - add ons command, [2-40](#)
  - adding a disk group with, [2-36](#)
  - case sensitivity, [2-33](#), [2-92](#)
  - case sensitivity of commands, [2-34](#), [2-92](#)
  - command reference, [2-33](#)
  - commands
    - downgrade database, [2-52](#)
    - upgrade database, [2-91](#)
  - commands, case sensitivity, [2-33](#), [2-92](#)
  - component names, [2-34](#)
  - config asm command, [2-45](#)
  - config command, usage description, [2-45](#)
  - config database command, [2-46](#)
  - config listener command, [2-47](#)
  - config ons command, [2-47](#)
  - config service command, [2-48](#)
  - creating and deleting databases services with, [2-22](#)
  - disable asm command, [2-49](#)
  - disable command, usage description, [2-48](#)
  - disable database command, [2-49](#)
  - disable diskgroup command, [2-50](#)
  - disable listener command, [2-50](#)
  - disable ons command, [2-51](#)
  - disable service command, [2-51](#)
  - enable asm command, [2-54](#)
  - enable command, usage description, [2-53](#)
  - enable database command, [2-54](#)
  - enable diskgroup command, [2-54](#)
  - enable listener command, [2-55](#)
  - enable ons command, [2-55](#)
  - enable service command, [2-56](#)

**SRVCTL** (*continued*)

- getenv asm command, [2-57](#)
- getenv command, usage description, [2-56](#)
- getenv database command, [2-57](#)
- getenv listener command, [2-58](#)
- help for, [2-14](#)
- modify asm command, [2-59](#)
- modify command, usage description, [2-58](#)
- modify database command, [2-60](#)
- modify listener command, [2-61](#)
- modify ons command, [2-61](#)
- modify service command, [2-62](#)
- preparing to run, [2-13](#)
- reference, [2-33](#)
- remove asm command, [2-66](#)
- remove command, usage description, [2-66](#)
- remove database command, [2-67](#)
- remove diskgroup command, [2-68](#)
- remove listener command, [2-68](#)
- remove ons command, [2-69](#)
- remove service command, [2-69](#)
- setenv asm command, [2-71](#)
- setenv command, usage description, [2-70](#)
- setenv database command, [2-72](#)
- setenv listener command, [2-73](#)
- start asm command, [2-73](#)
- start command, usage description, [2-73](#)
- start database command, [2-74](#)
- start diskgroup command, [2-75](#)
- start home command, [2-75](#)
- start listener command, [2-76](#)
- start ons command, [2-76](#)
- start service command, [2-77](#)
- status asm command, [2-78](#)
- status command, usage description, [2-78](#)
- status database command, [2-79](#)
- status diskgroup command, [2-79](#)
- status home command, [2-80](#)
- status listener command, [2-80](#)
- status ons command, [2-81](#)
- status service command, [2-81](#)
- stop asm command, [2-83](#)
- stop command, usage description, [2-82](#)
- stop database command, [2-84](#)
- stop diskgroup command, [2-84](#)
- stop home command, [2-85](#)
- stop listener command, [2-86](#)
- stop ons command, [2-86](#)
- stop service command, [2-87](#)
- unsetenv asm command, [2-89](#)
- unsetenv command, usage description, [2-88](#)
- unsetenv database command, [2-90](#)
- unsetenv listener command, [2-90](#)

**STALE** status

- of redo log members, [9-16](#)

stalled chain (Scheduler), [28-65](#)

standby transmission mode

- definition of, [10-15](#)

statement transparency in distributed database

- managing, [32-29](#)

statistics

- automatically collecting for tables, [19-55](#)

STATISTICS\_LEVEL initialization parameter

- Database Resource Manager, [26-4](#)

statistics, optimizer

- dynamic, [7-42](#)

stderr

- for local external jobs, [27-23](#), [27-24](#)
- retrieving, [27-23](#), [27-24](#)

stdout

- for local external jobs, [27-23](#), [27-24](#)
- retrieving, [27-23](#), [27-24](#), [28-17](#)

steps, chain

- dropping, [28-61](#)

stopping

- chain steps, [28-62](#)
- chains, [28-62](#)
- jobs, [28-20](#)

storage parameters

- INITIAL, [19-58](#)
- INITTRANS, altering, [19-58](#)
- MAXTRANS, altering, [19-58](#)
- MINEXTENTS, [19-58](#)
- PCTINCREASE, [19-58](#)

storage subsystems

- mapping files to physical devices, [12-22](#), [12-32](#)

stored procedures

- managing privileges, [32-29](#)
- remote object security, [32-29](#)

submitting SQL and commands to the database, [1-10](#)

subqueries

- in remote updates, [31-32](#)
- in unions
- materialized views, [36-16](#)
- materialized views, [36-13](#), [36-19](#)
- AND condition, [36-19](#)
- column logging, [36-19](#)
- EXISTS condition, [36-19](#)
- joins, [36-19](#)
- many to many, [36-15](#)
- many to one, [36-13](#)
- one to many, [36-14](#)
- restrictions, [36-19](#)
- statement transparency in distributed databases, [32-29](#)

subsetting

- materialized views, [36-12](#)
- column objects, [36-24](#)

SunSoft SunNet Manager, [31-30](#)

Support Workbench, [7-10](#)  
     for Oracle ASM instance, [7-24](#)  
     viewing problems with, [7-23](#)  
 Support Workbench, accessing, [7-47](#)  
 SWITCH LOGFILE clause  
     ALTER SYSTEM statement, [9-17](#)  
 synonyms  
     creating, [23-26](#), [32-26](#)  
     data dictionary views reference, [23-28](#)  
     definition and creation, [32-26](#)  
     displaying dependencies of, [17-35](#)  
     dropping, [23-27](#)  
     examples, [32-26](#)  
     location transparency in distributed  
         databases, [32-25](#)  
     managing, [23-26](#), [23-27](#)  
     managing privileges in remote database,  
         [32-27](#)  
     name resolution in distributed databases,  
         [31-39](#)  
     private, [23-26](#)  
     public, [23-26](#)  
     remote object security, [32-27](#)  
 SYS account, [1-21](#)  
     objects owned, [1-23](#)  
 SYS\_GROUP for Database Resource Manager,  
     [26-107](#)  
 SYSAUX tablespace, [11-4](#)  
     cannot rename, [11-42](#)  
     monitoring occupants, [11-53](#)  
     moving occupants, [11-53](#)  
 SYSBACKUP account, [1-21](#), [1-23](#)  
     connecting as, [1-25](#)  
 SYSDBA account  
     connecting as, [1-25](#)  
 SYSDBA administrative privilege  
     adding users to the password file, [1-47](#)  
     determining who has privileges, [1-48](#)  
     granting and revoking, [1-47](#)  
 SYSDG account, [1-21](#), [1-23](#)  
     connecting as, [1-25](#)  
 SYSKM account, [1-21](#), [1-23](#)  
     connecting as, [1-25](#)  
 SYSOPER account  
     connecting as, [1-25](#)  
 SYSOPER administrative privilege  
     adding users to the password file, [1-47](#)  
     determining who has privileges, [1-48](#)  
     granting and revoking, [1-47](#)  
 SYSRAC account, [1-23](#)  
     connecting as, [1-25](#)  
 SYSTEM account, [1-21](#)  
     objects owned, [1-23](#)  
 system change numbers  
     coordination in a distributed database system,  
         [34-13](#)

system change numbers (*continued*)  
     in-doubt transactions, [35-10](#)  
     using V\$DATAFILE to view information about,  
         [12-34](#)  
     when assigned, [9-2](#)  
 system global area, [23-21](#)  
     holds sequence number cache, [23-21](#)  
 system monitor process (SMON), [3-29](#)  
 system privileges  
     ADMINISTER\_RESOURCE\_MANAGER,  
         [26-31](#)  
     for external tables, [19-157](#)  
 SYSTEM tablespace  
     cannot rename, [11-42](#)  
     restrictions on taking offline, [12-8](#)  
     when created, [11-4](#)  
 SYSTEM\_PLAN for Database Resource  
     Manager, [26-107](#)

## T

table compression, [38-3](#)  
 table size  
     estimating, [18-39](#)  
 tables  
     about, [19-2](#)  
     adding columns, [19-62](#)  
     allocating extents, [19-61](#)  
     altering, [19-57](#)  
     altering physical attributes, [19-58](#)  
     analyzing, [17-4](#)  
     attribute-clustered, [19-23](#)  
     bulk updates, [19-54](#)  
     compressed, [19-8](#)  
     creating, [19-33](#)  
     data dictionary views reference, [19-198](#)  
     deferred segment creation, [19-29](#)  
     designing before creating, [19-5](#)  
     dropping, [19-120](#)  
     dropping columns, [19-63](#)  
     estimating size, [19-32](#)  
     estimating space use, [18-39](#)  
     external, [19-139](#)  
     Flashback Drop, [19-121](#)  
     Flashback Table, [19-119](#)  
     global temporary, [19-36](#)  
     guidelines for managing, [19-3](#)  
     hash clustered  
         See hash clusters, [22-4](#)  
     hybrid partitioned, [19-158](#)  
     increasing column length, [19-61](#)  
     index-organized, [19-126](#)  
     invisible columns, [19-25](#)  
     key-preserved, [23-9](#)  
     limiting indexes on, [20-5](#)  
     managing, [19-1](#)

tables (*continued*)

- modifying column definition, [19-61](#)
- moving, [19-58](#)
- parallelizing creation, [19-6](#), [19-40](#)
- partitioned, [19-139](#)
- partitions
  - moving online, [19-60](#)
- private temporary, [19-38](#)
- read-only, [19-66](#)
- redefining online, [19-68](#)
  - replication, [37-3](#)
- renaming columns, [19-63](#)
- replicating, [38-1](#)
- researching and reversing erroneous changes
  - to, [19-119](#)
- restrictions when creating, [19-32](#)
- setting storage parameters, [19-32](#)
- shrinking, [18-31](#)
- specifying location, [19-6](#)
- statistics collection, automatic, [19-55](#)
- temporary, [19-35](#)
- truncating, [17-8](#)
- types, [19-5](#)
- unrecoverable (NOLOGGING), [19-7](#)
- validating structure, [17-5](#)
- zone maps, [19-24](#)

tablespace set, [13-30](#)

## tablespaces

- adding data files, [12-5](#)
- assigning user quotas, [11-3](#)
- autoextending, [11-36](#)
- automatic segment space management, [11-7](#)
- bigfile, [11-8](#)
- checking default storage parameters, [11-60](#)
- compressed, [11-10](#)
- containing XMLTypes, [13-10](#)
- data dictionary views reference, [11-59](#)
- DBMS\_SPACE\_ADMIN package, [11-55](#)
- detecting and repairing defects, [11-55](#)
- diagnosing and repairing problems in locally
  - managed, [11-55](#)
- dictionary managed, [11-10](#)
- dropping, [11-43](#)
- encrypted, [11-11](#)
  - creating, [11-13](#)
- guidelines for managing, [11-2](#)
- increasing size, [11-36](#)
- listing files of, [11-60](#)
- listing free space in, [11-61](#)
- locally managed, [11-5](#)
- locally managed temporary, [11-17](#)
- location, [12-5](#)
- migrating SYSTEM to locally managed, [11-58](#)
- on a WORM device, [11-28](#)
- Oracle Managed Files, managing, [15-25](#), [15-29](#)

tablespaces (*continued*)

- quotas, assigning, [11-3](#)
- read-only, [11-25](#)
  - mounting, [13-7](#)
- renaming, [11-35](#), [11-42](#)
- shrinking, [11-37](#)
- single-file, [11-8](#), [11-37](#)
- space usage alerts, [18-3](#)
- specifying nonstandard block sizes, [11-21](#)
- SYSAUX, [11-4](#), [11-42](#)
- SYSAUX, managing, [11-52](#)
- SYSTEM, [11-4](#), [11-5](#)
- taking offline normal, [11-22](#)
- taking offline temporarily, [11-22](#)
- temp files in locally managed, [11-17](#)
- temporary, [11-15](#), [11-20](#)
- temporary bigfile, [11-18](#)
- temporary for creating large indexes, [20-16](#)
- undo, [14-2](#)
- using multiple, [11-2](#)
- using Oracle Managed Files, [15-15](#)

temp files, [11-17](#)

- creating as Oracle managed, [15-18](#)
- dropping, [12-17](#)
- dropping Oracle managed, [15-24](#)

TEMP\_UNDO\_ENABLED parameter, [14-15](#)

temporary segments

- index creation and, [20-3](#)

temporary tables, [38-3](#)

- global, [19-35](#)
- private, [19-35](#)

temporary tablespace, default

- specifying at database creation, [15-13](#)

temporary tablespaces

- altering, [11-41](#)
- bigfile, [11-18](#)
- creating, [11-17](#)
- groups, [11-18](#)
- renaming default, [11-42](#)
- shrinking, locally managed, [11-42](#)

temporary undo, [14-15](#)

terminating user sessions

- active sessions, [3-38](#)
- identifying sessions, [3-38](#)
- inactive session, example, [3-39](#)
- inactive sessions, [3-39](#)

test case

- builder, SQL, [7-3](#)

threads

- online redo log, [9-2](#)

threshold based alerts

- managing with Oracle Enterprise Manager
  - Cloud Control, [6-7](#)

threshold-based alerts

- server-generated, [6-6](#)

- thresholds
  - setting alert, [18-3](#)
- trace file segmentation, [6-4](#)
- trace files, [7-8](#)
  - location of, [6-2](#)
  - log writer process and, [9-7](#)
  - materialized views, [40-3](#)
  - using, [6-2](#)
  - when written, [6-5](#)
- trace files, finding, [7-40](#)
- traces, [7-8](#)
- tracing
  - archivelog process, [10-19](#)
- transaction control statements
  - distributed transactions and, [34-3](#)
- transaction failures
  - simulating, [35-21](#)
- transaction management
  - overview, [34-9](#)
- transaction processing
  - distributed systems, [31-31](#)
- transactions
  - closing database links, [33-2](#)
  - distributed and two-phase commit, [31-34](#)
  - in-doubt, [34-12](#), [34-14](#), [34-17](#), [35-6](#)
  - managing, [30-1](#)
  - naming distributed, [35-2](#), [35-8](#)
  - remote, [31-33](#)
- transmitting archived redo log files, [10-14](#)
- Transparent Data Encryption
  - columns, [19-28](#)
  - keystore, [11-11](#), [19-28](#)
  - tablespaces, [11-11](#)
- transporting data
  - across platforms, [13-8](#)
  - character sets, [13-10](#)
  - compatibility considerations, [13-12](#)
  - full transportable export/import, [13-13](#)
    - limitations, [13-14](#)
    - when to use, [13-2](#)
  - limitations, [13-10](#)
  - national character sets, [13-10](#)
  - PDBs, [13-15](#), [13-26](#)
  - transferring data files, [13-53](#)
  - transportable tables, [13-36](#)
    - limitations, [13-37](#)
  - transportable tablespaces, [13-26](#)
    - from backup, [13-13](#), [13-27](#)
    - limitations, [13-27](#)
    - tablespace set, [13-30](#)
    - transportable set, [13-28](#)
    - when to use, [13-2](#)
    - wizard in Oracle Enterprise Manager Cloud Control, [13-27](#)
  - XMLTypes in, [13-10](#)

- triggers
  - disabling, [17-12](#)
  - enabling, [17-12](#)
  - for materialized view log, [37-2](#)
- True Cache
  - configuring and using, [4-40](#)
- TRUNCATE statement
  - DROP ALL STORAGE, [17-9](#)
  - DROP STORAGE, [17-9](#)
  - DROP STORAGE clause, [17-9](#)
  - REUSE STORAGE, [17-9](#)
  - REUSE STORAGE clause, [17-9](#)
- tuning
  - analyzing tables, [33-6](#)
  - cost-based optimization, [33-5](#)
- two-phase commit
  - case study, [34-18](#)
  - commit phase, [34-12](#), [34-21](#)
  - described, [31-34](#)
  - discovering problems with, [35-6](#)
  - distributed transactions, [34-9](#)
  - example, [34-18](#)
  - forget phase, [34-14](#)
  - in-doubt transactions, [34-14](#), [34-17](#)
  - phases, [34-9](#)
  - prepare phase, [34-10](#), [34-12](#)
  - recognizing read-only nodes, [34-11](#)
  - specifying commit point strength, [35-2](#)
  - steps in commit phase, [34-13](#)
  - tracing session tree in distributed transactions, [35-5](#)
  - viewing database links, [35-3](#)

## U

- Undo Advisor, [14-8](#)
- undo management
  - automatic, [14-2](#)
  - described, [14-2](#)
  - initialization parameters for, [14-3](#)
  - temporary undo, [14-15](#)
- undo retention
  - automatic tuning of, [14-5](#)
  - explained, [14-4](#)
  - guaranteeing, [14-6](#)
  - setting, [14-8](#)
- undo segments
  - in-doubt distributed transactions, [35-7](#)
- undo space
  - data dictionary views reference, [14-17](#)
- undo space management
  - automatic undo management mode, [14-2](#)
- Undo tablespace
  - specifying at database creation, [15-12](#)
- undo tablespaces
  - altering, [14-12](#)



undo tablespaces (*continued*)

- creating, [14-11](#)
- data dictionary views reference, [14-17](#)
- dropping, [14-13](#)
- managing, [14-10](#)
- managing space threshold alerts, [14-14](#)
- monitoring, [14-17](#)
- PENDING OFFLINE status, [14-14](#)
- renaming, [11-42](#)
- sizing a fixed-size, [14-8](#)
- switching, [14-13](#)
- user quotas, [14-14](#)

unions

- with subqueries
  - materialized views, [36-16](#)
  - restrictions for materialized views, [36-20](#)

UNIQUE key constraints

- associated indexes, [20-15](#)
- dropping associated indexes, [20-31](#)
- enabling on creation, [20-15](#)
- foreign key references when dropped, [17-18](#)
- indexes associated with, [20-15](#)

UNRECOVERABLE DATAFILE clause

- ALTER DATABASE statement, [9-18](#)

UNREGISTER\_MVIEW procedure, [36-31](#)

unusable indexes, [20-8](#)

updates

- bulk, [19-54](#)
- location transparency and, [31-43](#)

us, [36-24](#)

user accounts

- predefined, [5-3](#)

USER\_DB\_LINKS view, [32-19](#)

USER\_DUMP\_DEST initialization parameter, [7-6](#)

USER\_REFRESH view, [40-3](#)

USER\_REFRESH\_CHILDREN view, [40-3](#)

user-defined data types

- materialized views, [36-22](#)
  - collections, [36-26](#)
  - object tables, [36-25](#)
  - ON COMMIT REFRESH clause, [36-22](#)
  - REFs, [36-28](#)
  - type agreement, [36-23](#)
- replication, [36-22](#)
  - collections, [36-26](#)
  - column objects, [36-22](#)
  - REFs, [36-28](#)
  - type agreement, [36-23](#)

users

- assigning tablespace quotas, [11-3](#)
- session, terminating, [3-39](#)
- SYS, [1-21](#)
- SYSBACKUP, [1-21](#)
- SYSDG, [1-21](#)
- SYSKM, [1-21](#)
- SYSTEM, [1-21](#)

utilities

- for the database administrator, [1-49](#)
  - SQL\*Loader, [1-49](#), [19-41](#)

utilization limits for PDBs, [26-22](#)

UTLCHAIN.SQL script

- listing chained rows, [17-7](#)

UTLCHN1.SQL script

- listing chained rows, [17-7](#)

UTLLOCKT.SQL script, [6-10](#)

## V

V\$ARCHIVE view, [10-19](#)

V\$DATABASE view, [10-20](#)

V\$DBLINK view, [32-20](#)

V\$DIAG\_CRITICAL\_ERROR view, [7-14](#)

V\$DIAG\_INFO view, [7-14](#)

V\$DISPATCHER view

- monitoring shared server dispatchers, [3-17](#)

V\$DISPATCHER\_RATE view

- monitoring shared server dispatchers, [3-17](#)

V\$ENCRYPTED\_TABLESPACES view, [11-14](#), [11-59](#)

V\$LOG view, [9-20](#), [10-19](#)

- displaying archiving status, [10-19](#)

V\$LOG\_HISTORY view, [9-20](#)

V\$LOGFILE view, [9-20](#)

- log file status, [9-16](#)

V\$PWFIL\_USERS view, [1-48](#)

V\$QUARANTINE view, [6-13](#)

V\$QUEUE view

- monitoring shared server dispatchers, [3-17](#)

V\$RSRCPDBMETRIC view, [26-121](#)

- CPU usage, [26-123](#)
- I/O generated, [26-125](#)
- memory usage, [26-126](#)
- parallel execution, [26-124](#)

V\$RSRCPDBMETRIC\_HISTORY view, [26-121](#)

V\$SESSION view, [3-39](#)

V\$THREAD view, [9-20](#)

V\$VERSION view, [1-20](#)

VALIDATE STRUCTURE clause

- of ANALYZE statement, [17-5](#)

VALIDATE STRUCTURE ONLINE clause

- of ANALYZE statement, [17-5](#)

varrays

- materialized, [36-26](#)
- materialized views
  - restrictions, [36-28](#)
- replication, [36-26](#)

verifying blocks

- redo log files, [9-17](#)

viewing

- alerts, [18-5](#)
- incident package details, [7-60](#)

## views

- creating, [23-3](#)
- creating with errors, [23-5](#)
- data dictionary
  - for archived redo log files, [10-20](#)
  - for clusters, [21-11](#)
  - for control files, [8-11](#)
  - for data files, [12-33](#)
  - for database resident connection pooling, [3-27](#)
  - for Database Resource Manager, [26-130](#)
  - for hash clusters, [22-11](#)
  - for indexes, [20-41](#)
  - for Oracle Scheduler, [29-32](#)
  - for redo log, [9-20](#)
  - for schema objects, [17-34](#)
  - for sequences, [23-28](#)
  - for shared server, [3-19](#)
  - for space usage in schema objects, [18-36](#)
  - for synonyms, [23-28](#)
  - for tables, [19-198](#)
  - for tablespaces, [11-59](#)
  - for undo space, [14-17](#)
  - for views, [23-28](#)
- data dictionary views for, [23-28](#)
- DBA\_2PC\_NEIGHBORS, [35-5](#)
- DBA\_2PC\_PENDING, [35-3](#)
- DBA\_DB\_LINKS, [32-19](#)
- displaying dependencies of, [17-35](#)
- dropping, [23-15](#)
- file mapping views, [12-29](#)
- FOR UPDATE clause and, [23-3](#)
- invalid, [23-6](#)
- join
  - See join views, [23-4](#)
- location transparency in distributed databases, [32-24](#)
- managing, [23-1](#), [23-5](#)
- managing privileges with, [32-25](#)
- name resolution in distributed databases, [31-39](#)
- ORDER BY clause and, [23-3](#)
- remote object security, [32-25](#)
- restrictions, [23-6](#)
- using, [23-6](#)
- V\$ARCHIVE, [10-19](#)
- V\$DATABASE, [10-20](#)
- V\$LOG, [10-19](#)
- V\$LOGFILE, [9-16](#)

views (*continued*)

- wildcards in, [23-4](#)
- WITH CHECK OPTION, [23-3](#)
- virtual columns, [19-2](#), [38-3](#)
  - indexing, [20-5](#)
- Virtual Private Database
  - redefining tables online, [19-78](#)
- virtual private database (VPD), [38-6](#)

---

W

- wildcards
  - in views, [23-4](#)
- window groups
  - creating, [28-80](#)
  - disabling, [28-82](#)
  - dropping, [28-81](#)
  - dropping a member from, [28-81](#)
  - enabling, [28-82](#)
  - managing job scheduling and job priorities with, [28-79](#)
  - overview, [27-18](#)
- window logs, [28-74](#)
- windows (Scheduler)
  - altering, [28-76](#)
  - closing, [28-77](#)
  - creating, [28-75](#)
  - disabling, [28-78](#)
  - dropping, [28-78](#)
  - enabling, [28-79](#)
  - opening, [28-76](#)
  - overlapping, [27-15](#)
  - overview, [27-14](#)
- windows, managing job scheduling and resource allocation with, [28-74](#)
- WITH ROWID clause
  - REFs, [36-30](#)
- WORM devices
  - and read-only tablespaces, [11-28](#)
- WRH\$\_UNDOSTAT view, [14-17](#)

---

X

- XMLTypes
  - transporting data, [13-10](#)

---

Z

- zone maps, [19-24](#)