

UTL_IDENT

The `UTL_IDENT` package specifies which Database or client PL/SQL is running.

This chapter contains the following topics:

- [Overview](#)
- [Security Model](#)
- [Constants](#)

UTL_IDENT Overview

The `UTL_IDENT` package is intended for use for conditional compilation of PL/SQL packages that are supported by Oracle, TimesTen Database, and clients such as Oracle Forms.

UTL_IDENT Security Model

The `UTL_IDENT` package runs as the package owner `SYS`. The public synonym `UTL_IDENT`, and `EXECUTE` permission on this package is granted to `PUBLIC`.

UTL_IDENT Constants

The `UTL_IDENT` package defines several constants to use when specifying parameter values.

These constants are shown in the following table.

Table 292-1 UTL_IDENT Constants

Constant	Type	Value	Description
<code>IS_ORACLE_SERVER</code>	BOOLEAN	TRUE/FALSE	Stipulates if Oracle Server or not
<code>IS_ORACLE_CLIENT</code>	BOOLEAN	TRUE/FALSE	Stipulates if Oracle Client or not
<code>IS_TIMESTEN</code>	BOOLEAN	TRUE/FALSE	Stipulates if TimesTen or not
<code>IS_ORACLE_FORMS</code>	BOOLEAN	TRUE/FALSE	Stipulates if Oracle Forms or not