


OWA_CUSTOM

The `OWA_CUSTOM` package provides a Global PLSQL Agent Authorization callback function. It is used when PLSQL Agent's authorization scheme is set to `GLOBAL` or `CUSTOM` when there is no overriding `OWA_CUSTOM` package.

 **See Also:**

For more information about implementation of this package:

- *Oracle Fusion Middleware Administrator's Guide for Oracle HTTP Server*
- *Oracle Fusion Middleware User's Guide for mod_plsql*

- The chapter contains the following topics:
- [Constants](#)
 - [Summary of OWA_CUSTOM Subprograms](#)

OWA_CUSTOM Constants

- `OWA_CUSTOM` defines several constants to use when specifying parameter values.
- `dbms_server_timezone` `CONSTANT VARCHAR2(3) := 'PST';`
 - `dbms_server_gmtdiff` `CONSTANT NUMBER := NULL;`

Summary of OWA_CUSTOM Subprograms

The `AUTHORIZE` function is the only subprogram in the `OWA_CUSTOM` package.

Table 250-1 *OWA_CUSTOM Package Subprograms*

Subprogram	Description
AUTHORIZE Function	Provides a Global PLSQL Agent Authorization callback function

AUTHORIZE Function

This function is used when PLSQL Agent's authorization scheme is set to `GLOBAL` or `CUSTOM` when there is no overriding `OWA_CUSTOM` package.

Syntax

```
OWA_CUSTOM.AUTHORIZE
RETURN BOOLEAN;
```