

Oracle® Database Utilities



23ai
F46696-26
April 2025

ORACLE®

Oracle Database Utilities, 23ai

F46696-26

Copyright © 2002, 2025, Oracle and/or its affiliates.

Primary Author: Douglas Williams

Contributors: Francisco Alavez, Hermann Baer, William Beauregard, Thirupathi Bhukya, Chi Ching Chui, Michael Cusson, Alexey Filanovskiy, Yuhong Gu, Martin Gubar, Dana Joly, Rich Phillips, Madhu Ravishankar, Mike Sakayeda, Roy Swonger, Bill Wright, Qin Yu

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

Audience	xlii
Documentation Accessibility	xlii
Diversity and Inclusion	xliii
Related Documentation	xliii
Syntax Diagrams	xliii
Conventions	xliii

Part I Oracle Data Pump

1 Overview of Oracle Data Pump

1.1	Oracle Data Pump Components	1-2
1.2	How Does Oracle Data Pump Move Data?	1-4
1.2.1	Using Data File Copying to Move Data	1-4
1.2.2	Using Direct Path to Move Data	1-5
1.2.3	Using External Tables to Move Data	1-7
1.2.4	Using Conventional Path to Move Data	1-7
1.2.5	Using Network Link Import to Move Data	1-8
1.2.6	Using a Parameter File (Parfile) with Oracle Data Pump	1-9
1.3	Using Oracle Data Pump With CDBs	1-9
1.3.1	About Using Oracle Data Pump in a Multitenant Environment	1-10
1.3.2	Using Oracle Data Pump to Move Data Into a CDB	1-10
1.3.3	Using Oracle Data Pump to Move PDBs Within or Between CDBs	1-13
1.4	Cloud Premigration Advisor Tool	1-13
1.4.1	What is the Cloud Premigration Advisor Tool (CPAT)	1-13
1.5	Required Roles for Oracle Data Pump Export and Import Operations	1-14
1.6	What Happens During the Processing of an Oracle Data Pump Job?	1-15
1.6.1	Coordination of an Oracle Data Pump Job	1-16
1.6.2	Tracking Progress Within an Oracle Data Pump Job	1-16
1.6.3	Filtering Data and Metadata During an Oracle Data Pump Job	1-17
1.6.4	Transforming Metadata During an Oracle Data Pump Job	1-17
1.6.5	Maximizing Job Performance of Oracle Data Pump	1-17

1.6.6	Loading and Unloading Data with Oracle Data Pump	1-18
1.7	How to Monitor Status of Oracle Data Pump Jobs	1-19
1.8	How to Monitor the Progress of Running Jobs with V\$SESSION_LONGOPS	1-19
1.9	File Allocation with Oracle Data Pump	1-20
1.9.1	Understanding File Allocation in Oracle Data Pump	1-20
1.9.2	Specifying Files and Adding Additional Dump Files	1-20
1.9.3	Default Locations for Dump, Log, and SQL Files	1-21
1.9.3.1	Understanding Dump, Log, and SQL File Default Locations	1-21
1.9.3.2	Understanding How to Use Oracle Data Pump with Oracle RAC	1-23
1.9.3.3	Using Directory Objects When Oracle Automatic Storage Management Is Enabled	1-24
1.9.3.4	The DATA_PUMP_DIR Directory Object and Pluggable Databases	1-24
1.9.4	Using Substitution Variables with Oracle Data Pump Exports	1-25
1.10	Exporting and Importing Between Different Oracle Database Releases	1-25
1.11	Exporting and Importing Blockchain Tables with Oracle Data Pump	1-27
1.12	Unload and Load Vectors Using Oracle Data Pump	1-28
1.13	Managing SecureFiles Large Object Exports with Oracle Data Pump	1-29
1.14	Oracle Data Pump Process Exit Codes	1-30
1.15	How Oracle Data Pump Manages Dump File Blocks	1-30
1.15.1	Dump Files for Exports	1-31
1.15.2	Trailer Block File Layout in Dump Files	1-31
1.15.3	Header Block File Layout in Dump Files	1-33
1.15.4	Types of Dump File Trailer Blocks	1-33
1.16	How to Monitor Oracle Data Pump Jobs with Unified Auditing	1-34
1.17	Encrypted Data Security Warnings for Oracle Data Pump Operations	1-35
1.18	How Does Oracle Data Pump Handle Timestamp Data?	1-35
1.18.1	TIMESTAMP WITH TIMEZONE Restrictions	1-35
1.18.1.1	Understanding TIMESTAMP WITH TIME ZONE Restrictions	1-36
1.18.1.2	Oracle Data Pump Support for TIMESTAMP WITH TIME ZONE Data	1-36
1.18.1.3	Time Zone File Versions on the Source and Target	1-37
1.18.2	TIMESTAMP WITH LOCAL TIME ZONE Restrictions	1-38
1.19	Character Set and Globalization Support Considerations	1-38
1.19.1	Data Definition Language (DDL)	1-38
1.19.2	Single-Byte Character Sets and Export and Import	1-38
1.19.3	Multibyte Character Sets and Export and Import	1-38
1.20	Oracle Data Pump Behavior with Data-Bound Collation	1-39

2 Oracle Data Pump Export

2.1	What Is Oracle Data Pump Export?	2-1
2.2	Starting Oracle Data Pump Export	2-2
2.2.1	Oracle Data Pump Export Interfaces	2-2

2.2.2	Oracle Data Pump Export Modes	2-3
2.2.2.1	Full Export Mode	2-3
2.2.2.2	Schema Mode	2-5
2.2.2.3	Table Mode	2-5
2.2.2.4	Tablespace Mode	2-6
2.2.2.5	Transportable Tablespace Mode	2-6
2.2.3	Network Considerations for Oracle Data Pump Export	2-7
2.3	Filtering During Export Operations	2-8
2.3.1	Oracle Data Pump Export Data Filters	2-8
2.3.2	Oracle Data Pump Metadata Filters	2-9
2.4	Parameters Available in Data Pump Export Command-Line Mode	2-10
2.4.1	About Oracle Data Pump Export Parameters	2-14
2.4.2	ABORT_STEP	2-16
2.4.3	ACCESS_METHOD	2-16
2.4.4	ATTACH	2-17
2.4.5	CHECKSUM	2-18
2.4.6	CHECKSUM_ALGORITHM	2-19
2.4.7	CLUSTER	2-20
2.4.8	COMPRESSION	2-21
2.4.9	COMPRESSION_ALGORITHM	2-22
2.4.10	CONTENT	2-23
2.4.11	CREDENTIAL	2-24
2.4.12	DATA_OPTIONS	2-25
2.4.13	DIRECTORY	2-26
2.4.14	DUMPFIL	2-27
2.4.15	ENABLE_SECURE_ROLES	2-30
2.4.16	ENCRYPTION	2-30
2.4.17	ENCRYPTION_ALGORITHM	2-32
2.4.18	ENCRYPTION_MODE	2-33
2.4.19	ENCRYPTION_PASSWORD	2-34
2.4.20	ENCRYPTION_PWD_PROMPT	2-36
2.4.21	ESTIMATE	2-37
2.4.22	ESTIMATE_ONLY	2-38
2.4.23	EXCLUDE	2-38
2.4.24	FILESIZE	2-40
2.4.25	FLASHBACK_SCN	2-41
2.4.26	FLASHBACK_TIME	2-42
2.4.27	FULL	2-44
2.4.28	HELP	2-45
2.4.29	INCLUDE	2-45
2.4.30	JOB_NAME	2-48
2.4.31	KEEP_MASTER	2-48

2.4.32	LOGFILE	2-49
2.4.33	LOGTIME	2-50
2.4.34	METRICS	2-52
2.4.35	NETWORK_LINK	2-53
2.4.36	NOLOGFILE	2-54
2.4.37	PARALLEL	2-55
2.4.38	PARALLEL_THRESHOLD	2-56
2.4.39	PARFILE	2-58
2.4.40	QUERY	2-59
2.4.41	REMAP_DATA	2-61
2.4.42	REUSE_DUMPFILES	2-62
2.4.43	SAMPLE	2-63
2.4.44	SCHEMAS	2-64
2.4.45	SERVICE_NAME	2-64
2.4.46	SOURCE_EDITION	2-66
2.4.47	STATUS	2-66
2.4.48	TABLES	2-67
2.4.49	TABLESPACES	2-70
2.4.50	TRANSPORT_DATAFILES_LOG	2-70
2.4.51	TRANSPORT_FULL_CHECK	2-72
2.4.52	TRANSPORT_TABLESPACES	2-73
2.4.53	TRANSPORTABLE	2-74
2.4.54	TTS_CLOSURE_CHECK	2-76
2.4.55	VERSION	2-77
2.4.56	VIEWS_AS_TABLES	2-78
2.5	Commands Available in Data Pump Export Interactive-Command Mode	2-80
2.5.1	About Oracle Data Pump Export Interactive Command Mode	2-81
2.5.2	ADD_FILE	2-82
2.5.3	CONTINUE_CLIENT	2-83
2.5.4	EXIT_CLIENT	2-83
2.5.5	FILESIZE	2-83
2.5.6	HELP	2-84
2.5.7	KILL_JOB	2-84
2.5.8	PARALLEL	2-85
2.5.9	START_JOB	2-86
2.5.10	STATUS	2-86
2.5.11	STOP_JOB	2-87
2.6	Examples of Using Oracle Data Pump Export	2-87
2.6.1	Performing a Table-Mode Export	2-88
2.6.2	Data-Only Unload of Selected Tables and Rows	2-88
2.6.3	Estimating Disk Space Needed in a Table-Mode Export	2-88
2.6.4	Performing a Schema-Mode Export	2-89

2.6.5	Performing a Parallel Full Database Export	2-89
2.6.6	Using Interactive Mode to Stop and Reattach to a Job	2-89
2.6.7	Continuing Table Loads when LOB Data Type Corruptions are Found	2-90
2.7	Syntax Diagrams for Oracle Data Pump Export	2-92

3 Oracle Data Pump Import

3.1	What Is Oracle Data Pump Import?	3-1
3.2	Starting Oracle Data Pump Import	3-1
3.2.1	Oracle Data Pump Import Interfaces	3-2
3.2.2	Oracle Data Pump Import Modes	3-3
3.2.2.1	About Oracle Data Pump Import Modes	3-3
3.2.2.2	Full Import Mode	3-3
3.2.2.3	Schema Mode	3-5
3.2.2.4	Table Mode	3-5
3.2.2.5	Tablespace Mode	3-5
3.2.2.6	Transportable Tablespace Mode	3-6
3.2.3	Network Considerations for Oracle Data Pump Import	3-6
3.3	Filtering During Import Operations	3-7
3.3.1	Oracle Data Pump Import Data Filters	3-7
3.3.2	Oracle Data Pump Import Metadata Filters	3-8
3.4	Parameters Available in Oracle Data Pump Import Command-Line Mode	3-8
3.4.1	About Import Command-Line Mode	3-13
3.4.2	ABORT_STEP	3-15
3.4.3	ACCESS_METHOD	3-15
3.4.4	ATTACH	3-17
3.4.5	CLUSTER	3-18
3.4.6	CONTENT	3-19
3.4.7	CREDENTIAL	3-20
3.4.8	DATA_OPTIONS	3-22
3.4.9	DIRECTORY	3-24
3.4.10	DUMPFIL	3-25
3.4.11	ENABLE_SECURE_ROLES	3-28
3.4.12	ENCRYPTION_PASSWORD	3-28
3.4.13	ENCRYPTION_PWD_PROMPT	3-29
3.4.14	ESTIMATE	3-31
3.4.15	EXCLUDE	3-32
3.4.16	FLASHBACK_SCN	3-34
3.4.17	FLASHBACK_TIME	3-35
3.4.18	FULL	3-36
3.4.19	HELP	3-38
3.4.20	INCLUDE	3-38

3.4.21	INDEX_THRESHOLD	3-40
3.4.22	JOB_NAME	3-41
3.4.23	KEEP_MASTER	3-42
3.4.24	LOGFILE	3-43
3.4.25	LOGTIME	3-44
3.4.26	MASTER_ONLY	3-45
3.4.27	METRICS	3-45
3.4.28	NETWORK_LINK	3-46
3.4.29	NOLOGFILE	3-48
3.4.30	ONESTEP_INDEX	3-48
3.4.31	PARALLEL	3-49
3.4.32	PARALLEL_THRESHOLD	3-52
3.4.33	PARFILE	3-53
3.4.34	PARTITION_OPTIONS	3-54
3.4.35	QUERY	3-56
3.4.36	REMAP_DATA	3-58
3.4.37	REMAP_DATAFILE	3-59
3.4.38	REMAP_DIRECTORY	3-60
3.4.39	REMAP_SCHEMA	3-61
3.4.40	REMAP_TABLE	3-63
3.4.41	REMAP_TABLESPACE	3-64
3.4.42	SCHEMAS	3-65
3.4.43	SERVICE_NAME	3-66
3.4.44	SKIP_UNUSABLE_INDEXES	3-67
3.4.45	SOURCE_EDITION	3-68
3.4.46	SQLFILE	3-69
3.4.47	STATUS	3-71
3.4.48	STREAMS_CONFIGURATION	3-71
3.4.49	TABLE_EXISTS_ACTION	3-72
3.4.50	REUSE_DATAFILES	3-74
3.4.51	TABLES	3-74
3.4.52	TABLESPACES	3-77
3.4.53	TARGET_EDITION	3-78
3.4.54	TRANSFORM	3-79
3.4.55	TRANSPORT_DATAFILES	3-87
3.4.56	TRANSPORT_FULL_CHECK	3-89
3.4.57	TRANSPORT_TABLESPACES	3-90
3.4.58	TRANSPORTABLE	3-92
3.4.59	VERIFY_CHECKSUM	3-94
3.4.60	VERIFY_ONLY	3-95
3.4.61	VERSION	3-96
3.4.62	VIEWS_AS_TABLES (Network Import)	3-97

3.5	Commands Available in Data Pump Export Interactive-Command Mode	3-99
3.5.1	Commands Available in Oracle Data Pump Import Interactive-Command Mode	3-106
3.5.2	CONTINUE_CLIENT	3-108
3.5.3	EXIT_CLIENT	3-108
3.5.4	HELP	3-109
3.5.5	KILL_JOB	3-109
3.5.6	PARALLEL	3-110
3.5.7	START_JOB	3-110
3.5.8	STATUS	3-111
3.5.9	STOP_JOB	3-112
3.6	Examples of Using Oracle Data Pump Import	3-112
3.6.1	Performing a Data-Only Table-Mode Import	3-113
3.6.2	Performing a Schema-Mode Import	3-113
3.6.3	Performing a Network-Mode Import	3-113
3.6.4	Using Wildcards in URL-Based Dumpfile Names	3-114
3.7	Syntax Diagrams for Oracle Data Pump Import	3-114

4 Oracle Data Pump Legacy Mode

4.1	Oracle Data Pump Legacy Mode Use Cases	4-1
4.2	Parameter Mappings	4-1
4.2.1	Using Original Export Parameters with Oracle Data Pump	4-2
4.2.2	Using Original Import Parameters with Oracle Data Pump	4-5
4.3	Management of File Locations in Oracle Data Pump Legacy Mode	4-9
4.4	Adjusting Existing Scripts for Oracle Data Pump Log Files and Errors	4-11
4.4.1	Log Files	4-12
4.4.2	Error Cases	4-12
4.4.3	Exit Status	4-12

5 Oracle Data Pump Performance

5.1	Data Performance Improvements for Oracle Data Pump Export and Import	5-1
5.2	Tuning Performance	5-2
5.2.1	How To Manage Oracle Data Pump Resource Consumption	5-2
5.2.2	Effect of Compression and Encryption on Performance	5-3
5.2.3	Memory Considerations When Exporting and Importing Statistics	5-3
5.3	Initialization Parameters That Affect Oracle Data Pump Performance	5-3
5.3.1	Performance Guidelines for Oracle Data Pump Parameters	5-4
5.3.2	Setting the Size Of the Buffer Cache In a GoldenGate Replication Environment	5-4
5.3.3	Managing Resource Usage for Multiple User Oracle Data Pump Jobs	5-4

6 Using the Oracle Data Pump API

6.1	How Does the Oracle Data Pump Client Interface API Work?	6-1
6.2	DBMS_DATAPUMP Job States	6-1
6.3	What Are the Basic Steps in Using the Oracle Data Pump API?	6-4
6.4	Examples of Using the Oracle Data Pump API	6-4
6.4.1	Using the Oracle Data Pump API Examples with Your Database	6-5
6.4.2	Performing a Simple Schema Export with Oracle Data Pump	6-5
6.4.3	Performing a Table Mode Export to Object Store with Oracle Data Pump	6-7
6.4.4	Importing a Dump File and Remapping All Schema Objects	6-11
6.4.5	Importing a Table from an Object Store Using Oracle Data Pump	6-13
6.4.6	Using Exception Handling During a Simple Schema Export	6-16
6.4.7	Displaying Dump File Information for Oracle Data Pump Jobs	6-19
6.4.8	Network Mode and Schema Mode Import Over a Network Link	6-22

Part II SQL*Loader

7 Understanding How to Use SQL*Loader

7.1	SQL*Loader Features	7-1
7.2	SQL*Loader Parameters	7-3
7.3	SQL*Loader Control File	7-4
7.4	Input Data and Data Fields in SQL*Loader	7-4
7.4.1	How SQL*Loader Reads Input Data and Data Files	7-5
7.4.2	Fixed Record Format	7-5
7.4.3	Variable Record Format and SQL*Loader	7-6
7.4.4	Stream Record Format and SQL*Loader	7-7
7.4.5	Logical Records and SQL*Loader	7-8
7.4.6	Data Field Setting and SQL*Loader	7-9
7.5	LOBFILES and Secondary Data Files (SDFs)	7-9
7.6	Data Conversion and Data Type Specification	7-10
7.7	SQL*Loader Discarded and Rejected Records	7-11
7.7.1	The SQL*Loader Bad File	7-11
7.7.1.1	Records Rejected by SQL*Loader	7-11
7.7.1.2	Records Rejected by Oracle Database During a SQL*Loader Operation	7-11
7.7.2	The SQL*Loader Discard File	7-11
7.8	Log File and Logging Information	7-12
7.9	Conventional Path Loads, Direct Path Loads, and External Table Loads	7-12
7.9.1	Conventional Path Loads	7-12
7.9.2	Direct Path Loads	7-13
7.9.3	Parallel Direct Path	7-13
7.9.4	External Table Loads	7-13

7.9.5	Choosing External Tables Versus SQL*Loader	7-14
7.9.6	Behavior Differences Between SQL*Loader and External Tables	7-15
7.9.6.1	Multiple Primary Input Data Files	7-15
7.9.6.2	Syntax and Data Types	7-15
7.9.6.3	Byte-Order Marks	7-16
7.9.6.4	Default Character Sets, Date Masks, and Decimal Separator	7-16
7.9.6.5	Use of the Backslash Escape Character	7-16
7.9.7	Loading Tables Using Data Stored into Object Storage	7-16
7.10	Loading Objects, Collections, and LOBs with SQL*Loader	7-18
7.10.1	Supported Object Types	7-18
7.10.1.1	column objects	7-19
7.10.1.2	row objects	7-19
7.10.2	Supported Collection Types	7-19
7.10.2.1	Nested Tables	7-19
7.10.2.2	VARRAYs	7-20
7.10.3	SODA Collections and SQL*Loader	7-20
7.10.4	Supported LOB Data Types	7-21
7.11	Partitioned Object Support in SQL*Loader	7-21
7.12	Application Development: Direct Path Load API	7-21
7.13	SQL*Loader Case Studies	7-22
7.13.1	How to Access and Use the Oracle SQL*Loader Case Studies	7-22
7.13.2	Case Study Files	7-23
7.13.3	Running the Case Studies	7-24
7.13.4	Case Study Log Files	7-24
7.13.5	Checking the Results of a Case Study	7-24

8 SQL*Loader Command-Line Reference

8.1	Starting SQL*Loader	8-1
8.1.1	Specifying Parameters on the Command Line	8-1
8.1.2	Alternative Ways to Specify SQL*Loader Parameters	8-2
8.1.3	Using SQL*Loader to Load Data Across a Network	8-3
8.2	Command-Line Parameters for SQL*Loader	8-3
8.2.1	BAD	8-7
8.2.2	BINDSIZE	8-8
8.2.3	COLUMNARRAYROWS	8-9
8.2.4	COMPRESS_STREAM	8-9
8.2.5	CONTROL	8-10
8.2.6	CREDENTIAL	8-11
8.2.7	DATA	8-13
8.2.8	DATE_CACHE	8-14
8.2.9	DEFAULTS	8-15

8.2.10	DEGREE_OF_PARALLELISM	8-17
8.2.11	DIRECT	8-18
8.2.12	DIRECT_PATH_LOCK_WAIT	8-18
8.2.13	DISCARD	8-19
8.2.14	DISCARDMAX	8-20
8.2.15	DNFS_ENABLE	8-21
8.2.16	DNFS_READBUFFERS	8-22
8.2.17	EMPTY_LOBS_ARE_NULL	8-22
8.2.18	ERRORS	8-23
8.2.19	EXTERNAL_TABLE	8-24
8.2.20	FILE	8-26
8.2.21	GRANULE_SIZE	8-27
8.2.22	GSM_HOST	8-27
8.2.23	GSM_NAME	8-28
8.2.24	GSM_PORT	8-29
8.2.25	HELP	8-29
8.2.26	LOAD	8-30
8.2.27	LOAD_SHARDS	8-30
8.2.28	LOG	8-31
8.2.29	MULTITHREADING	8-32
8.2.30	NO_INDEX_ERRORS	8-33
8.2.31	OPTIMIZE PARALLEL	8-33
8.2.32	PARALLEL	8-34
8.2.33	PARFILE	8-35
8.2.34	PARTITION_MEMORY	8-35
8.2.35	READER_COUNT	8-36
8.2.36	READSIZE	8-37
8.2.37	RESUMABLE	8-38
8.2.38	RESUMABLE_NAME	8-38
8.2.39	RESUMABLE_TIMEOUT	8-39
8.2.40	ROWS	8-40
8.2.41	SDF_PREFIX	8-41
8.2.42	SILENT	8-42
8.2.43	SKIP	8-43
8.2.44	SKIP_INDEX_MAINTENANCE	8-43
8.2.45	SKIP_UNUSABLE_INDEXES	8-44
8.2.46	STREAMSIZE	8-45
8.2.47	TRIM	8-46
8.2.48	USERID	8-47
8.3	Exit Codes for Inspection and Display	8-48

9 SQL*Loader Control File Reference

9.1	Control File Contents	9-2
9.2	Comments in the Control File	9-4
9.3	Specifying Command-Line Parameters in the Control File	9-4
9.3.1	OPTIONS Clause for Schema Data	9-5
9.3.2	OPTIONS Clause for SODA Collections	9-6
9.3.3	Specifying the Number of Default Expressions to Be Evaluated At One Time	9-7
9.4	Specifying File Names and Object Names	9-7
9.4.1	File Names That Conflict with SQL and SQL*Loader Reserved Words	9-7
9.4.2	Specifying SQL Strings in the SQL*Loader Control File	9-7
9.4.3	Operating Systems and SQL Loader Control File Characters	9-8
9.4.3.1	Specifying a Complete Path	9-8
9.4.3.2	Backslash Escape Character	9-8
9.4.3.3	Nonportable Strings	9-9
9.4.3.4	Using the Backslash as an Escape Character	9-9
9.4.3.5	Escape Character Is Sometimes Disallowed	9-9
9.5	Identifying XMLType Tables	9-9
9.6	Specifying Field Order	9-12
9.7	Specifying Data Files	9-12
9.7.1	Understanding How to Specify Data Files	9-13
9.7.2	Examples of INFILE Syntax	9-14
9.7.3	Specifying Multiple Data Files	9-15
9.8	Specifying CSV Format Files	9-15
9.9	Loading VECTOR Columns from Character Data and fvec Format Files	9-16
9.10	Identifying Data in the Control File with BEGINDATA	9-18
9.11	Specifying Data File Format and Buffering	9-18
9.12	Specifying the Bad File	9-19
9.12.1	Understanding and Specifying the Bad File	9-19
9.12.2	Examples of Specifying a Bad File Name	9-20
9.12.3	How Bad Files Are Handled with LOBFILES and SDFs	9-20
9.12.4	Criteria for Rejected Records	9-21
9.13	Specifying the Discard File	9-21
9.13.1	Understanding and Specifying the Discard File	9-22
9.13.2	Specifying the Discard File in the Control File	9-23
9.13.3	Limiting the Number of Discard Records	9-23
9.13.4	Examples of Specifying a Discard File Name	9-23
9.13.5	Criteria for Discarded Records	9-24
9.13.6	How Discard Files Are Handled with LOBFILES and SDFs	9-24
9.13.7	Specifying the Discard File from the Command Line	9-24
9.14	Specifying a NULLIF Clause At the Table Level	9-24
9.15	Specifying Datetime Formats At the Table Level	9-25

9.16	Handling Different Character Encoding Schemes	9-26
9.16.1	Multibyte (Asian) Character Sets	9-26
9.16.2	Unicode Character Sets	9-26
9.16.3	Database Character Sets	9-27
9.16.4	Data File Character Sets	9-28
9.16.5	Input Character Conversion with SQL*Loader	9-28
9.16.5.1	Options for Converting Character Sets Using SQL*Loader	9-28
9.16.5.2	Considerations When Loading Data into VARRAYs or Primary-Key-Based REFs	9-29
9.16.5.3	CHARACTERSET Parameter	9-30
9.16.5.4	Control File Character Set	9-31
9.16.5.5	Character-Length Semantics	9-31
9.16.6	Shift-sensitive Character Data	9-33
9.17	Interrupted SQL*Loader Loads	9-33
9.17.1	Understanding Causes of Interrupted SQL*Loader Loads	9-33
9.17.2	Discontinued Conventional Path Loads	9-34
9.17.3	Discontinued Direct Path Loads	9-34
9.17.3.1	Load Discontinued Because of Space Errors	9-34
9.17.3.2	Load Discontinued Because Maximum Number of Errors Exceeded	9-35
9.17.3.3	Load Discontinued Because of Irrecoverable Errors	9-35
9.17.3.4	Load Discontinued Because a Ctrl+C Was Issued	9-35
9.17.4	Status of Tables and Indexes After an Interrupted Load	9-35
9.17.5	Using the Log File to Determine Load Status	9-36
9.17.6	Continuing Single-Table Loads	9-36
9.18	Assembling Logical Records from Physical Records	9-36
9.18.1	Using CONCATENATE to Assemble Logical Records	9-37
9.18.2	Using CONTINUEIF to Assemble Logical Records	9-37
9.19	Loading Logical Records into Tables	9-40
9.19.1	Specifying Table Names	9-41
9.19.2	INTO TABLE Clause	9-41
9.19.3	Table-Specific Loading Method	9-42
9.19.4	Loading Data into Empty Tables with INSERT	9-42
9.19.5	Loading Data into Nonempty Tables	9-43
9.19.5.1	Options for Loading Data Into Nonempty Tables	9-43
9.19.5.2	APPEND	9-44
9.19.5.3	APPEND_PARALLEL	9-44
9.19.5.4	REPLACE	9-44
9.19.5.5	Updating Existing Rows with REPLACE	9-45
9.19.5.6	TRUNCATE	9-45
9.19.6	Table-Specific OPTIONS Parameter	9-45
9.19.7	Loading Records Based on a Condition	9-45
9.19.8	Using the WHEN Clause with LOBFILES and SDFs	9-46

9.19.9	Specifying Default Data Delimiters	9-46
9.19.9.1	fields_spec	9-47
9.19.9.2	termination_spec	9-47
9.19.9.3	enclosure_spec	9-47
9.19.10	Handling Records with Missing Specified Fields	9-48
9.19.10.1	SQL*Loader Management of Short Records with Missing Data	9-48
9.19.10.2	TRAILING NULLCOLS Clause	9-49
9.20	Index Options with SQL*Loader	9-49
9.20.1	Understanding the SORTED INDEXES Parameter	9-49
9.20.2	Understanding the SINGLEROW Parameter	9-50
9.21	Benefits of Using Multiple INTO TABLE Clauses	9-50
9.21.1	Understanding the SQL*Loader INTO TABLE Clause	9-51
9.21.2	Distinguishing Different Input Record Formats	9-51
9.21.3	Relative Positioning Based on the POSITION Parameter	9-52
9.21.4	Distinguishing Different Input Row Object Subtypes	9-52
9.21.5	Loading Data into Multiple Tables	9-54
9.21.6	Summary of Using Multiple INTO TABLE Clauses	9-54
9.21.7	Extracting Multiple Logical Records	9-54
9.21.7.1	Example of Extracting Multiple Logical Records From a Physical Record	9-55
9.21.7.2	Example of Relative Positioning Based on Delimiters	9-55
9.22	Bind Arrays and Conventional Path Loads	9-56
9.22.1	Differences Between Bind Arrays and Conventional Path Loads	9-56
9.22.2	Size Requirements for Bind Arrays	9-56
9.22.3	Performance Implications of Bind Arrays	9-57
9.22.4	Specifying Number of Rows Versus Size of Bind Array	9-57
9.22.5	Setting Up SQL*Loader Bind Arrays	9-58
9.22.5.1	Calculations to Determine Bind Array Size	9-58
9.22.5.2	Determining the Size of the Length Indicator	9-59
9.22.5.3	Calculating the Size of Field Buffers	9-60
9.22.6	Minimizing Memory Requirements for Bind Arrays	9-62
9.22.7	Calculating Bind Array Size for Multiple INTO TABLE Clauses	9-62

10 SQL*Loader Field List Reference

10.1	Field List Contents	10-2
10.2	Specifying the Position of a Data Field.	10-3
10.2.1	POSITION	10-3
10.2.2	Using POSITION with Data Containing Tabs	10-4
10.2.3	Using POSITION with Multiple Table Loads	10-4
10.2.4	Examples of Using POSITION in SQL*Loader Specifications	10-5
10.3	Specifying Columns and Fields	10-5
10.3.1	Options for Column and Field Specification	10-5

10.3.2	Specifying Filler Fields	10-6
10.3.3	Specifying the Data Type of a Data Field	10-7
10.4	SQL*Loader Data Types	10-8
10.4.1	Portable and Nonportable Data Type Differences	10-8
10.4.2	Nonportable Data Types	10-9
10.4.2.1	Categories of Nonportable Data Types	10-10
10.4.2.2	BINARY_DOUBLE	10-11
10.4.2.3	BINARY_FLOAT	10-11
10.4.2.4	BYTEINT	10-12
10.4.2.5	DECIMAL	10-12
10.4.2.6	DOUBLE	10-13
10.4.2.7	FLOAT	10-13
10.4.2.8	INTEGER(n)	10-14
10.4.2.9	LONG VARRAW	10-14
10.4.2.10	SMALLINT	10-15
10.4.2.11	VARGRAPHIC	10-16
10.4.2.12	VARCHAR	10-17
10.4.2.13	VARRAW	10-18
10.4.2.14	ZONED	10-18
10.4.3	Portable Data Types	10-19
10.4.3.1	Categories of Portable Data Types	10-20
10.4.3.2	CHAR	10-21
10.4.3.3	Datetime and Interval	10-21
10.4.3.4	GRAPHIC	10-26
10.4.3.5	GRAPHIC EXTERNAL	10-27
10.4.3.6	Numeric EXTERNAL	10-27
10.4.3.7	RAW	10-28
10.4.3.8	VARCHARC	10-29
10.4.3.9	VARRAWC	10-30
10.4.3.10	Conflicting Native Data Type Field Lengths	10-31
10.4.3.11	Field Lengths for Length-Value Data Types	10-31
10.4.4	SODA Collection Data Types	10-31
10.4.4.1	RAW(*)	10-32
10.4.4.2	CONTENTFILE(soda_filename)	10-34
10.4.5	Data Type Conversions	10-36
10.4.6	Data Type Conversions for Datetime and Interval Data Types	10-37
10.4.7	Specifying Delimiters	10-38
10.4.7.1	Syntax for Termination and Enclosure Specification	10-39
10.4.7.2	Delimiter Marks in the Data	10-40
10.4.7.3	Maximum Length of Delimited Data	10-41
10.4.7.4	Loading Trailing Blanks with Delimiters	10-41
10.4.8	How Delimited Data Is Processed	10-41

10.4.8.1	Fields Using Only TERMINATED BY	10-42
10.4.8.2	Fields Using ENCLOSED BY Without TERMINATED BY	10-42
10.4.8.3	Fields Using ENCLOSED BY With TERMINATED BY	10-42
10.4.8.4	Fields Using OPTIONALLY ENCLOSED BY With TERMINATED BY	10-43
10.4.9	Conflicting Field Lengths for Character Data Types	10-44
10.4.9.1	Predetermined Size Fields	10-44
10.4.9.2	Delimited Fields	10-45
10.4.9.3	Date Field Masks	10-45
10.5	Specifying Field Conditions	10-46
10.5.1	Comparing Fields to BLANKS	10-46
10.5.2	Comparing Fields to Literals	10-46
10.6	Using the WHEN, NULLIF, and DEFAULTIF Clauses	10-46
10.7	Examples of Using the WHEN, NULLIF, and DEFAULTIF Clauses	10-48
10.8	Loading Data Across Different Platforms	10-50
10.9	Understanding how SQL*Loader Manages Byte Ordering	10-51
10.9.1	Byte Order Syntax	10-52
10.9.2	Using Byte Order Marks (BOMs)	10-53
10.9.2.1	Suppressing Checks for BOMs	10-54
10.10	Loading All-Blank Fields	10-55
10.11	Trimming Whitespace	10-55
10.11.1	Data Types for Which Whitespace Can Be Trimmed	10-57
10.11.2	Specifying Field Length for Data Types for Which Whitespace Can Be Trimmed	10-58
10.11.2.1	Predetermined Size Fields	10-58
10.11.2.2	Delimited Fields	10-58
10.11.3	Relative Positioning of Fields	10-59
10.11.3.1	No Start Position Specified for a Field	10-59
10.11.3.2	Previous Field Terminated by a Delimiter	10-59
10.11.3.3	Previous Field Has Both Enclosure and Termination Delimiters	10-59
10.11.4	Leading Whitespace	10-60
10.11.4.1	Previous Field Terminated by Whitespace	10-60
10.11.4.2	Optional Enclosure Delimiters	10-61
10.11.5	Trimming Trailing Whitespace	10-61
10.11.6	Trimming Enclosed Fields	10-61
10.12	How the PRESERVE BLANKS Option Affects Whitespace Trimming	10-61
10.13	How [NO] PRESERVE BLANKS Works with Delimiter Clauses	10-62
10.14	Applying SQL Operators to Fields	10-63
10.14.1	Referencing Fields	10-65
10.14.2	Common Uses of SQL Operators in Field Specifications	10-66
10.14.3	Combinations of SQL Operators	10-66
10.14.4	Using SQL Strings with a Date Mask	10-67
10.14.5	Interpreting Formatted Fields	10-67

10.14.6	Using SQL Strings to Load the ANYDATA Database Type	10-67
10.15	Using SQL*Loader to Generate Data for Input	10-68
10.15.1	Loading Data Without Files	10-69
10.15.2	CONSTANT Parameter	10-69
10.15.3	EXPRESSION Parameter	10-70
10.15.4	RECNUM Parameter	10-70
10.15.5	SYSDATE Parameter	10-71
10.15.6	SEQUENCE Parameter	10-72
10.15.7	Generating Sequence Numbers for Multiple Tables	10-73

11 Loading Objects, LOBs, and Collections with SQL*Loader

11.1	Loading Column Objects	11-1
11.1.1	Understanding Column Object Attributes	11-2
11.1.2	Loading Column Objects in Stream Record Format	11-2
11.1.3	Loading Column Objects in Variable Record Format	11-3
11.1.4	Loading Nested Column Objects	11-4
11.1.5	Loading Column Objects with a Derived Subtype	11-5
11.1.6	Specifying Null Values for Objects	11-6
11.1.6.1	Specifying Attribute Nulls	11-6
11.1.6.2	Specifying Atomic Nulls	11-6
11.1.7	Loading Column Objects with User-Defined Constructors	11-7
11.2	Loading Object Tables with SQL*Loader	11-10
11.2.1	Examples of Loading Object Tables with SQL*Loader	11-11
11.2.2	Loading Object Tables with Subtypes	11-12
11.3	Loading REF Columns with SQL*Loader	11-13
11.3.1	Specifying Table Names in a REF Clause	11-14
11.3.2	System-Generated OID REF Columns	11-15
11.3.3	Primary Key REF Columns	11-16
11.3.4	Unscoped REF Columns That Allow Primary Keys	11-16
11.4	Loading LOBs with SQL*Loader	11-18
11.4.1	Overview of Loading LOBs with SQL*Loader	11-18
11.4.2	Options for Using SQL*Loader to Load LOBs	11-19
11.4.3	Loading LOB Data from a Primary Data File	11-20
11.4.3.1	LOB Data in Predetermined Size Fields	11-21
11.4.3.2	LOB Data in Delimited Fields	11-22
11.4.3.3	LOB Data in Length-Value Pair Fields	11-23
11.4.4	Loading LOB Data from LOBFILES	11-24
11.4.4.1	Overview of Loading LOB Data from LOBFILES	11-24
11.4.4.2	Dynamic Versus Static LOBFILE Specifications	11-25
11.4.4.3	Examples of Loading LOB Data from LOBFILES	11-25
11.4.4.4	Considerations When Loading LOBs from LOBFILES	11-30

11.4.5	Loading Data Files that Contain LLS Fields	11-31
11.5	Loading BFILE Columns with SQL*Loader	11-32
11.6	Loading Collections (Nested Tables and VARRAYs)	11-33
11.6.1	Overview of Loading Collections (Nested Tables and VARRAYs)	11-33
11.6.2	Restrictions in Nested Tables and VARRAYs	11-34
11.6.3	Secondary Data Files (SDFs)	11-36
11.7	Choosing Dynamic or Static SDF Specifications	11-37
11.8	Loading a Parent Table Separately from Its Child Table	11-37
11.8.1	Memory Issues When Loading VARRAY Columns	11-38
11.9	Loading Modes and Options for SODA Collections	11-39
11.9.1	SQL*Loader and SODA_COLLECTION	11-39
11.9.2	Loading Empty SODA Collections Using INSERT	11-41
11.9.3	Loading Empty SODA Collections Using APPEND	11-41
11.9.4	Loading Empty SODA Collections Using REPLACE and TRUNCATE	11-41
11.9.5	Permitted SQL*Loader Command-Line Parameters for SODA Collections	11-41
11.9.6	Examples of Loading SODA Collections	11-42
11.9.6.1	Creating and Loading a Small SODA Collection	11-42
11.10	Load Character Vector Data Using SQL*Loader Example	11-44
11.11	Load Binary Vector Data Using SQL*Loader Example	11-48

12 Conventional and Direct Path Loads

12.1	Data Loading Methods	12-2
12.2	Loading ROWID Columns	12-2
12.3	Conventional Path Loads	12-2
12.3.1	Conventional Path Load	12-3
12.3.2	When to Use a Conventional Path Load	12-3
12.3.3	Conventional Path Load of a Single Partition	12-4
12.4	Direct Path Loads	12-4
12.4.1	About SQL*Loader Direct Path Load	12-5
12.4.2	Loading into Synonyms	12-5
12.4.3	Field Defaults on the Direct Path	12-5
12.4.4	Integrity Constraints	12-5
12.4.5	When to Use a Direct Path Load	12-6
12.4.6	Restrictions on a Direct Path Load of a Single Partition	12-6
12.4.7	Restrictions on Using Direct Path Loads	12-6
12.4.8	Advantages of a Direct Path Load	12-7
12.4.9	Direct Path Load of a Single Partition or Subpartition	12-8
12.4.10	Direct Path Load of a Partitioned or Subpartitioned Table	12-8
12.4.11	Data Conversion During Direct Path Loads	12-9
12.5	Automatic Parallel Load of Table Data with SQL*Loader	12-10
12.6	Loading Modes and Options for Automatic Parallel Loads	12-11

12.6.1	Loading Modes for Automatic Parallel Loads	12-12
12.6.2	Non-Sharded Automatic Parallel Loading Modes for SQL*Loader	12-12
12.6.3	Sharded Automatic Parallel Loading Modes for SQL*Loader	12-15
12.7	Using Direct Path Load	12-20
12.7.1	Setting Up for Direct Path Loads	12-21
12.7.2	Specifying a Direct Path Load	12-21
12.7.3	Building Indexes	12-21
12.7.3.1	Improving Performance	12-22
12.7.3.2	Calculating Temporary Segment Storage Requirements	12-22
12.7.4	Indexes Left in an Unusable State	12-23
12.7.5	Preventing Data Loss with Data Saves	12-23
12.7.5.1	Using Data Saves to Protect Against Data Loss	12-24
12.7.5.2	Using the ROWS Parameter	12-24
12.7.5.3	Data Save Versus Commit	12-24
12.7.6	Data Recovery During Direct Path Loads	12-25
12.7.6.1	Media Recovery and Direct Path Loads	12-25
12.7.6.2	Instance Recovery and Direct Path Loads	12-25
12.7.7	Loading Long Data Fields	12-26
12.7.8	Loading Data As PIECED	12-26
12.7.9	Auditing SQL*Loader Operations That Use Direct Path Mode	12-27
12.8	Optimizing Performance of Manual Direct Path Loads	12-27
12.8.1	Minimizing Time and Space Required for Direct Path Loads	12-27
12.8.2	Preallocating Storage for Faster Loading	12-28
12.8.3	Presorting Data for Faster Indexing	12-28
12.8.3.1	Advantages of Presorting Data	12-28
12.8.3.2	SORTED INDEXES Clause	12-29
12.8.3.3	Unsorted Data	12-29
12.8.3.4	Multiple-Column Indexes	12-29
12.8.3.5	Choosing the Best Sort Order	12-30
12.8.4	Infrequent Data Saves	12-30
12.8.5	Minimizing Use of the Redo Log	12-30
12.8.5.1	Disabling Archiving	12-31
12.8.5.2	Specifying the SQL*Loader UNRECOVERABLE Clause	12-31
12.8.5.3	Setting the SQL NOLOGGING Parameter	12-31
12.8.6	Specifying the Number of Column Array Rows and Size of Stream Buffers	12-32
12.8.7	Specifying a Value for DATE_CACHE	12-32
12.9	Optimizing Direct Path Loads on Multiple-CPU Systems	12-33
12.10	Avoiding Index Maintenance	12-34
12.11	Direct Path Loads, Integrity Constraints, and Triggers	12-35
12.11.1	Integrity Constraints	12-35
12.11.1.1	Enabled Constraints	12-35
12.11.1.2	Disabled Constraints	12-36

12.11.1.3	Reenable Constraints	12-36
12.11.2	Database Insert Triggers	12-37
12.11.2.1	Replacing Insert Triggers with Integrity Constraints	12-38
12.11.2.2	When Automatic Constraints Cannot Be Used	12-38
12.11.2.3	Preparation of Database Triggers	12-38
12.11.2.4	Using an Update Trigger	12-39
12.11.2.5	Duplicating the Effects of Exception Conditions	12-39
12.11.2.6	Using a Stored Procedure	12-39
12.11.3	Permanently Disabled Triggers and Constraints	12-40
12.11.4	Increasing Performance with Concurrent Conventional Path Loads	12-40
12.12	Optimizing Performance of Direct Path Loads	12-40
12.12.1	Restrictions on Automatic and Manual Parallel Direct Path Loads	12-41
12.12.2	About SQL*Loader Parallel Data Loading Models	12-42
12.12.3	Concurrent Conventional Path Loads	12-42
12.12.4	Intersegment Concurrency with Direct Path	12-42
12.12.5	Intrasegment Concurrency with Direct Path	12-43
12.12.6	Restrictions on Manual Parallel Direct Path Loads	12-43
12.12.7	Initiating Multiple SQL*Loader Sessions Manually	12-43
12.12.8	Parameters for Manual Parallel Direct Path Loads	12-44
12.12.8.1	Using the FILE Parameter to Specify Temporary Segments	12-45
12.12.9	Enabling Constraints After a Parallel Direct Path Load	12-46
12.12.10	PRIMARY KEY and UNIQUE KEY Constraints	12-46
12.13	General Performance Improvement Hints	12-46

13 SQL*Loader Express

13.1	What is SQL*Loader Express Mode?	13-1
13.2	Using SQL*Loader Express Mode	13-1
13.2.1	Starting SQL*Loader in Express Mode	13-2
13.2.2	Default Values Used by SQL*Loader Express Mode	13-2
13.2.3	How SQL*Loader Express Mode Handles Byte Order	13-3
13.3	SQL*Loader Express Mode Parameter Reference	13-4
13.3.1	BAD	13-6
13.3.2	CHARACTERSET	13-7
13.3.3	CSV	13-8
13.3.4	DATA	13-9
13.3.5	DATE_FORMAT	13-10
13.3.6	DEGREE_OF_PARALLELISM	13-11
13.3.7	DIRECT	13-12
13.3.8	DNFS_ENABLE	13-13
13.3.9	DNFS_READBUFFERS	13-14
13.3.10	ENCLOSED_BY	13-14

13.3.11	EXTERNAL_TABLE	13-15
13.3.12	FIELD_NAMES	13-16
13.3.13	LOAD	13-17
13.3.14	NULLIF	13-18
13.3.15	OPTIONALLY_ENCLOSED_BY	13-18
13.3.16	PARFILE	13-19
13.3.17	SILENT	13-20
13.3.18	TABLE	13-21
13.3.19	TERMINATED_BY	13-21
13.3.20	TIMESTAMP_FORMAT	13-22
13.3.21	TRIM	13-22
13.3.22	USERID	13-23
13.4	SQL*Loader Express Mode Command-Line Parameters for SODA Collections	13-24
13.5	SQL*Loader Express Mode Syntax Diagrams	13-25

Part III External Tables

14 External Tables Concepts

14.1	How Are External Tables Created?	14-1
14.2	CREATE_EXTERNAL_PART_TABLE Procedure	14-4
14.3	CREATE_EXTERNAL_TABLE Procedure	14-11
14.4	Location of Data Files and Output Files	14-13
14.5	Access Parameters for External Tables	14-14
14.6	Data Type Conversion During External Table Use	14-14
14.7	Vectors in External Tables	14-17

15 The ORACLE_LOADER Access Driver

15.1	About the ORACLE_LOADER Access Driver	15-1
15.2	access_parameters Clause	15-2
15.3	record_format_info Clause	15-4
15.3.1	Overview of record_format_info Clause	15-6
15.3.2	FIXED Length	15-8
15.3.3	VARIABLE size	15-9
15.3.4	DELIMITED BY	15-9
15.3.5	XMLTAG	15-11
15.3.6	CHARACTERSET	15-13
15.3.7	PREPROCESSOR	15-13
15.3.8	PREPROCESSOR_TIMEOUT	15-18
15.3.9	EXTERNAL VARIABLE DATA	15-20
15.3.10	LANGUAGE	15-22

15.3.11	TERRITORY	15-22
15.3.12	DATA IS...ENDIAN	15-22
15.3.13	BYTEORDERMARK [CHECK NOCHECK]	15-23
15.3.14	STRING SIZES ARE IN	15-24
15.3.15	LOAD WHEN	15-24
15.3.16	BADFILE NOBADFILE	15-25
15.3.17	DISCARDFILE NODISCARDFILE	15-26
15.3.18	LOGFILE NOLOGFILE	15-26
15.3.19	SKIP	15-27
15.3.20	FIELD NAMES	15-27
15.3.21	READSIZE	15-30
15.3.22	DATE_CACHE	15-30
15.3.23	string	15-30
15.3.24	condition_spec	15-31
15.3.25	[directory object name:] [filename]	15-32
15.3.26	condition	15-33
15.3.26.1	range start : range end	15-33
15.3.27	IO_OPTIONS clause	15-34
15.3.28	DNFS_DISABLE DNFS_ENABLE	15-35
15.3.29	DNFS_READBUFFERS	15-35
15.4	field_definitions Clause	15-36
15.4.1	Overview of field_definitions Clause	15-36
15.4.2	delim_spec	15-41
15.4.2.1	Example: External Table with Terminating Delimiters	15-42
15.4.2.2	Example: External Table with Enclosure and Terminator Delimiters	15-43
15.4.2.3	Example: External Table with Optional Enclosure Delimiters	15-43
15.4.3	trim_spec	15-43
15.4.4	MISSING FIELD VALUES ARE NULL	15-45
15.4.5	field_list	15-45
15.4.6	pos_spec Clause	15-46
15.4.6.1	pos_spec Clause Syntax	15-47
15.4.6.2	start	15-47
15.4.6.3	*	15-47
15.4.6.4	increment	15-47
15.4.6.5	end	15-48
15.4.6.6	length	15-48
15.4.7	datatype_spec Clause	15-49
15.4.7.1	datatype_spec Clause Syntax	15-50
15.4.7.2	[UNSIGNED] INTEGER [EXTERNAL] [(len)]	15-51
15.4.7.3	DECIMAL [EXTERNAL] and ZONED [EXTERNAL]	15-51
15.4.7.4	ORACLE_DATE	15-51
15.4.7.5	ORACLE_NUMBER	15-52

15.4.7.6	Floating-Point Numbers	15-52
15.4.7.7	DOUBLE	15-52
15.4.7.8	FLOAT [EXTERNAL]	15-52
15.4.7.9	BINARY_DOUBLE	15-53
15.4.7.10	BINARY_FLOAT	15-53
15.4.7.11	RAW	15-53
15.4.7.12	CHAR	15-53
15.4.7.13	date_format_spec	15-54
15.4.7.14	VARCHAR and VARRAW	15-56
15.4.7.15	VARCHARC and VARRAWC	15-58
15.4.8	init_spec Clause	15-58
15.4.9	LLS Clause	15-59
15.5	column_transforms Clause	15-60
15.5.1	transform	15-60
15.5.1.1	column_name FROM	15-61
15.5.1.2	NULL	15-62
15.5.1.3	CONSTANT	15-62
15.5.1.4	CONCAT	15-62
15.5.1.5	LOBFILE	15-62
15.5.1.6	lobfile_attr_list	15-62
15.5.1.7	STARTOF source_field (length)	15-63
15.6	Parallel Loading Considerations for the ORACLE_LOADER Access Driver	15-64
15.7	Performance Hints When Using the ORACLE_LOADER Access Driver	15-64
15.8	Restrictions When Using the ORACLE_LOADER Access Driver	15-65
15.9	Reserved Words for the ORACLE_LOADER Access Driver	15-66

16 The ORACLE_DATAPUMP Access Driver

16.1	Using the ORACLE_DATAPUMP Access Driver	16-1
16.2	access_parameters Clause	16-2
16.2.1	Comments	16-4
16.2.2	ENCRYPTION	16-4
16.2.3	LOGFILE NOLOGFILE	16-5
16.2.3.1	Log File Naming in Parallel Loads	16-5
16.2.4	COMPRESSION	16-6
16.2.5	VERSION Clause	16-7
16.2.6	HADOOP_TRAILERS Clause	16-8
16.2.7	Effects of Using the SQL ENCRYPT Clause	16-8
16.3	Unloading and Loading Data with the ORACLE_DATAPUMP Access Driver	16-9
16.3.1	Parallel Loading and Unloading	16-12
16.3.2	Combining Dump Files	16-13
16.4	Supported Data Types	16-14

16.5	Unsupported Data Types	16-15
16.5.1	Unloading and Loading BFILE Data Types	16-16
16.5.2	Unloading LONG and LONG RAW Data Types	16-18
16.5.3	Unloading and Loading Columns Containing Final Object Types	16-19
16.5.4	Tables of Final Object Types	16-20
16.6	Performance Hints When Using the ORACLE_DATAPUMP Access Driver	16-21
16.7	Restrictions When Using the ORACLE_DATAPUMP Access Driver	16-21
16.8	Reserved Words for the ORACLE_DATAPUMP Access Driver	16-22

17 ORACLE_BIGDATA Access Driver

17.1	Accessing External Data Using the ORACLE_BIGDATA Driver	17-1
17.2	Enabling and Configuring your Database for Object Storage Access	17-2
17.3	Setting Up Credentials and Location Parameters for Object Stores	17-2
17.3.1	How to Create a Credential for Object Stores	17-2
17.3.1.1	Creating the Credential Object with DBMS_CREDENTIAL.CREATE_CREDENTIAL	17-3
17.3.2	How to Define the Location Clause for Object Storage	17-4
17.4	ORACLE_BIGDATA Accessing Files	17-4
17.4.1	Syntax Rules for Specifying Properties	17-5
17.4.2	ORACLE_BIGDATA Common Access Parameters	17-6
17.4.3	ORACLE_BIGDATA Specific Access Parameters	17-8
17.4.3.1	Avro-Specific Access Parameters	17-8
17.4.3.2	Examples of Creating External Tables with Avro Files	17-9
17.4.3.3	Parquet-Specific Access Parameters	17-10
17.4.3.4	Examples of Creating External Tables with Avro Files	17-10
17.4.3.5	Textfile and CSV-Specific Access Parameters	17-12
17.4.3.6	Examples of Creating External Tables	17-17
17.5	ORACLE_BIGDATA Accessing Apache Iceberg	17-18
17.5.1	Apache Iceberg Tables Overview	17-19
17.5.2	Supported Configurations for Apache Iceberg	17-19
17.5.3	Iceberg-Specific Access Parameters	17-19
17.5.4	Examples of Table Creation and Inline External Table SQL for Iceberg Tables	17-20
17.5.4.1	Creating a Table Pointing to the Manifest File	17-20
17.5.4.2	Inline External Table Query (Manifest File Reference)	17-21
17.5.4.3	Creating a Table Using DBMS_CLOUD	17-21
17.5.4.4	Creating a Table Using AWS Glue as a Catalog	17-22
17.5.4.5	Inline External Table Query Using AWS Glue Catalog	17-22
17.5.4.6	Creating an External Table Using DBMS_CLOUD with AWS Glue Catalog	17-23
17.6	ORACLE_BIGDATA Accessing Delta Sharing	17-23
17.6.1	Delta Sharing Protocol Overview	17-24
17.6.2	Supported Configurations for Delta Sharing Protocol	17-24

17.6.3	Creating Credentials for Delta Sharing	17-24
17.6.4	Listing and Describing Delta Share Metadata	17-25
17.6.5	Delta Sharing Access Parameters	17-27
17.6.6	Examples of Creating External Tables for Delta Sharing	17-27
17.7	ORACLE_BIGDATA Accessing JSON Documents File Type	17-29
17.7.1	Overview of JSON Document Support	17-29
17.7.2	Access Parameters for JSON Document	17-29
17.7.3	Examples of JSONDOC Usage	17-30
17.7.3.1	Querying Line-Delimited JSON Documents	17-30
17.7.3.2	Querying JSON Arrays	17-31
17.7.3.3	Object wrapped JSON Arrays	17-32
17.7.3.4	Extended JSON (EJSON) Support	17-33
17.7.3.5	Single-JSON Document with Multiline Files	17-33

18 External Tables Examples for Oracle Database

18.1	Using the ORACLE_LOADER Access Driver to Create Partitioned External Tables	18-1
18.2	Using the ORACLE_LOADER Access Driver to Create Partitioned Hybrid Tables	18-4
18.3	Using the ORACLE_DATAPUMP Access Driver to Create Partitioned External Tables	18-5
18.4	Using the ORACLE_BIGDATA Access Driver to Create Partitioned External Tables	18-8
18.5	Using the ORA_PARTITION_VALIDATION Function to Validate Partitioned External Tables	18-10
18.6	Using SQL*Loader for External Tables with Partition Values in File Paths	18-11
18.7	Loading LOBs with External Tables	18-11
18.7.1	Overview of LOBs and External Tables	18-11
18.7.2	Loading LOBs From External Tables with ORACLE_LOADER Access Driver	18-13
18.7.2.1	Loading LOBs from Primary Data Files	18-13
18.7.2.2	Loading LOBs from LOBFILE Files	18-14
18.7.2.3	Loading LOBs from LOB Location Specifiers	18-17
18.7.3	Loading LOBs with ORACLE_DATAPUMP Access Driver	18-18
18.8	Loading CSV Files From External Tables	18-20
18.9	Using Vector Data Types in External Tables	18-27
18.9.1	Understanding Vector Data Types in External Tables	18-27
18.9.2	Creating External Tables Using Oracle Loader Driver	18-28
18.9.3	Creating External Tables Using ORACLE_DATAPUMP Driver	18-28
18.9.4	Querying an Inline External Table	18-29
18.9.5	Performing a Semantic Similarity Search Using External Table	18-30

Part IV Other Utilities

19 Cloud Premigration Advisor Tool

19.1	What is the Cloud Premigration Advisor Tool	19-2
19.2	Prerequisites for Using the Cloud Premigration Advisor Tool	19-3
19.3	Downloading and Configuring Cloud Premigration Advisor Tool	19-4
19.4	Getting Started with the Cloud Premigration Advisor Tool (CPAT)	19-5
19.5	Connection Strings for Cloud Premigration Advisor Tool	19-6
19.6	Required Command-Line Strings for Cloud Premigration Advisor Tool	19-8
19.7	FULL Mode and SCHEMA Mode	19-9
19.8	Interpreting Cloud Premigration Advisor Tool (CPAT) Report Data	19-9
19.9	Command-Line Syntax and Properties	19-11
19.9.1	Premigration Advisor Tool Command-Line Syntax	19-11
19.9.2	Premigration Advisor Tool Command-Line Properties	19-12
19.9.2.1	analysisprops	19-13
19.9.2.2	connectstring	19-14
19.9.2.3	excludeschemas	19-15
19.9.2.4	full	19-16
19.9.2.5	gettargetprops	19-16
19.9.2.6	help	19-17
19.9.2.7	logginglevel	19-17
19.9.2.8	maxrelevantobjects	19-18
19.9.2.9	maxtextdatarows	19-19
19.9.2.10	migrationmethod	19-19
19.9.2.11	outdir	19-20
19.9.2.12	outfileprefix	19-20
19.9.2.13	pdbname	19-21
19.9.2.14	reportformat	19-22
19.9.2.15	schemas	19-23
19.9.2.16	sqltext	19-24
19.9.2.17	sysdba	19-24
19.9.2.18	targetcloud	19-25
19.9.2.19	username	19-26
19.9.2.20	version	19-26
19.9.2.21	updatecheck	19-27
19.10	List of Checks Performed By the Premigration Advisor Tool	19-28
19.10.1	dp_has_low_streams_pool_size	19-34
19.10.2	gg_enabled_replication	19-35
19.10.3	gg_force_logging	19-36
19.10.4	gg_has_low_streams_pool_size	19-37
19.10.5	gg_not_unique	19-38
19.10.6	gg_not_unique_bad_col_no	19-39
19.10.7	gg_not_unique_bad_col_yes	19-40

19.10.8	gg_objects_not_supported	19-41
19.10.9	gg_supplemental_log_data_min	19-41
19.10.10	gg_tables_not_supported	19-42
19.10.11	gg_tables_not_supported	19-43
19.10.12	gg_user_objects_in_ggadmin_schemas	19-44
19.10.13	has_absent_default_tablespace	19-44
19.10.14	has_absent_temp_tablespace	19-45
19.10.15	has_active_data_guard_dedicated	19-46
19.10.16	has_active_data_guard_serverless	19-47
19.10.17	has_basic_file_lobs	19-48
19.10.18	has_clustered_tables	19-48
19.10.19	has_columns_of_rowid_type	19-49
19.10.20	has_columns_with_local_timezone	19-50
19.10.21	has_columns_with_media_data_types_adb	19-51
19.10.22	has_columns_with_media_data_types_default	19-52
19.10.23	has_columns_with_spatial_data_types	19-53
19.10.24	has_common_objects	19-54
19.10.25	has_compression_disabled_for_objects	19-54
19.10.26	has_csmig_schema	19-55
19.10.27	has_data_in_other_tablespaces_dedicated	19-56
19.10.28	has_data_in_other_tablespaces_serverless	19-57
19.10.29	has_db_link_synonyms	19-58
19.10.30	has_db_links	19-59
19.10.31	has_dbms_credentials	19-59
19.10.32	has_dbms_credentials	19-60
19.10.33	has_directories	19-61
19.10.34	has_enabled_scheduler_jobs	19-62
19.10.35	has_external_tables_dedicated	19-63
19.10.36	has_external_tables_default	19-63
19.10.37	has_external_tables_serverless	19-64
19.10.38	has_fmw_registry_in_system	19-65
19.10.39	has_illegal_characters_in_comments	19-65
19.10.40	has_ilm_ado_policies	19-66
19.10.41	has_incompatible_jobs	19-67
19.10.42	has_index_organized_tables	19-68
19.10.43	has_java_objects	19-68
19.10.44	has_java_source	19-69
19.10.45	has_libraries	19-70
19.10.46	has_logging_off_for_partitions	19-70
19.10.47	has_logging_off_for_subpartitions	19-71
19.10.48	has_logging_off_for_tables	19-72
19.10.49	has_low_streams_pool_size	19-72

19.10.50	has_noexport_object_grants	19-73
19.10.51	has_oracle_streams	19-74
19.10.52	has_parallel_indexes_enabled	19-75
19.10.53	has_profile_not_default	19-76
19.10.54	has_public_synonyms	19-76
19.10.55	has_refs_to_restricted_packages_dedicated	19-77
19.10.56	has_refs_to_restricted_packages_serverless	19-78
19.10.57	has_refs_to_user_objects_in_sys	19-78
19.10.58	has_role_privileges	19-79
19.10.59	has_sqlt_objects_adb	19-80
19.10.60	has_sqlt_objects_default	19-81
19.10.61	has_sys_privileges	19-82
19.10.62	has_tables_that_fail_with_dblink	19-82
19.10.63	has_tables_with_long_raw_datatype	19-83
19.10.64	has_tables_with_xmltype_column	19-84
19.10.65	has_trusted_server_entries	19-85
19.10.66	has_unstructured_xml_indexes Check	19-86
19.10.67	has_user_defined_objects_in_sys	19-86
19.10.68	has_user_defined_objects_in_system	19-87
19.10.69	has_user_defined_objects_no_quota	19-88
19.10.70	has_user_defined_pvfs	19-89
19.10.71	has_users_with_10g_password_version	19-89
19.10.72	has_xmlschema_objects	19-90
19.10.73	has_xmltype_tables	19-91
19.10.74	modified_db_parameters_dedicated	19-92
19.10.75	modified_db_parameters_serverless	19-92
19.10.76	nls_character_set_conversion	19-93
19.10.77	nls_national_character_set	19-94
19.10.78	nls_nchar_ora_910	19-95
19.10.79	options_in_use_not_available_dedicated	19-96
19.10.80	options_in_use_not_available_serverless	19-97
19.10.81	standard_traditional_audit_adb	19-97
19.10.82	standard_traditional_audit_default	19-98
19.10.83	timezone_table_compatibility_higher_dedicated	19-99
19.10.84	timezone_table_compatibility_higher_default	19-100
19.10.85	timezone_table_compatibility_higher_serverless	19-100
19.10.86	unified_and_standard_traditional_audit_adb	19-101
19.10.87	unified_and_standard_traditional_audit_default	19-102
19.10.88	xdb_resource_view_has_entries Check	19-103
19.11	Best Practices for Using the Premigration Advisor Tool	19-103
19.11.1	Generate Properties File on the Target Database Instance	19-104
19.11.2	Focus the CPAT Analysis	19-104

19.11.3	Reduce the Amount of Data in Reports	19-105
19.11.4	Generate the JSON Report and Save Logs	19-105
19.11.5	Use Output Prefixes to Record Different Migration Scenarios	19-106

20 DBMS_CLOUD Family of Packages

20.1	Using the DBMS_CLOUD Family of Packages	20-1
20.2	Installing DBMS_CLOUD	20-2
20.3	Create SSL Wallet with Certificates	20-4
20.4	Configure Your Environment to Use the New SSL Wallet	20-5
20.5	Configure the Database with ACES for DBMS_CLOUD	20-5
20.6	Verify Configuration of DBMS_CLOUD	20-9
20.7	Configuring Users or Roles to use DBMS_CLOUD	20-10
20.7.1	Grant Minimal Privileges to a User or Role for DBMS_CLOUD	20-11
20.7.2	Configure ACES for a User or Role to Use DBMS_CLOUD	20-12
20.7.3	Verify Setup of Users and Roles to Use DBMS_CLOUD	20-15

21 Migrating From JSON To Duality

21.1	JSON Columns in Duality Views	21-2
21.2	About Migrations From JSON To Duality	21-3
21.3	JSON To Duality Migrator Components: Converter and Importer	21-5
21.4	JSON Configuration Fields Specifying Migrator Parameters	21-8
21.5	School Administration Example, Migrator Input Documents	21-13
21.6	Before Using the Converter (1): Create Database Document Sets	21-18
21.7	Before Using the Converter (2): Optionally Create Data-Guide JSON Schemas	21-22
21.8	JSON-To-Duality Converter: What It Does	21-36
21.9	Migrating To Duality, Simplified Recipe	21-37
21.10	Using the Converter, Default Behavior	21-62
21.11	Import After Default Conversion	21-77
21.12	Using the Converter with useFlexFields=false	21-109
21.13	Import After Conversion with useFlexFields=false	21-114
21.14	Errors That Migrator Configuration Alone Can't Fix	21-133

22 Oracle SQL Access to Kafka

22.1	About Oracle SQL Access to Kafka Version 2	22-2
22.2	Global Tables and Views for Oracle SQL Access to Kafka	22-4
22.3	Understanding how Oracle SQL Access to Kafka Queries are Performed	22-4
22.4	Streaming Kafka Data Into Oracle Database	22-5
22.5	Querying Kafka Data Records by Timestamp	22-6
22.6	About the Kafka Database Administrator Role	22-7

22.7	Enable Kafka Database Access to Users	22-7
22.8	Data Formats Supported with Oracle SQL Access to Kafka	22-8
22.8.1	JSON Format and Oracle SQL Access to Kafka	22-9
22.8.2	Delimited Text Format and Oracle SQL Access to Kafka	22-9
22.8.3	Avro Formats and Oracle SQL Access to Kafka	22-11
22.8.3.1	About Using Avro Format with Oracle SQL Access to Kafka	22-12
22.8.3.2	Primitive Avro Types Supported with Oracle SQL Access to Kafka	22-12
22.8.3.3	Complex Avro Types Supported with Oracle SQL Access to Kafka	22-13
22.8.3.4	Avro Logical Types Supported with Oracle SQL Access to Kafka	22-15
22.9	Configuring Access to a Kafka Cluster	22-18
22.9.1	Create a Cluster Access Directory	22-18
22.9.2	The Kafka Configuration File (osakafka.properties)	22-19
22.9.2.1	About the Kafka Configuration File	22-19
22.9.2.2	Oracle SQL Access for Kafka Configuration File Properties	22-20
22.9.2.3	Creating the Kafka Access Directory	22-23
22.9.3	Kafka Configuration File Properties	22-23
22.9.4	Security Configuration Files Required for the Cluster Access Directory	22-25
22.9.4.1	SASL_SSL/GSSAPI	22-26
22.9.4.2	SASL_PLAINTEXT/GSSAPI	22-27
22.9.4.3	SASL_PLAINTEXT/SCRAM-SHA-256	22-27
22.9.4.4	SASL_SSL/PLAIN	22-28
22.9.4.5	SSL with Client Authentication	22-28
22.9.4.6	SSL without Client Authentication	22-29
22.10	Creating Oracle SQL Access to Kafka Applications	22-29
22.11	Security for Kafka Cluster Connections	22-31
22.12	Configuring Access to Unsecured Kafka Clusters	22-32
22.13	Configuring Access to Secure Kafka Clusters	22-33
22.14	Administering Oracle SQL Access to Kafka Clusters	22-35
22.14.1	Updating Access to Kafka Clusters	22-35
22.14.2	Disabling or Deleting Access to Kafka Clusters	22-35
22.15	Guidelines for Using Kafka Data with Oracle SQL Access to Kafka	22-36
22.15.1	Kafka Temporary Tables and Applications	22-36
22.15.2	Sharing Kafka Data with Multiple Applications Using Streaming	22-37
22.15.3	Dropping and Recreating Kafka Tables	22-37
22.16	Choosing a Kafka Cluster Access Mode for Applications	22-38
22.16.1	Configuring Incremental Loads of Kafka Records Into an Oracle Database Table	22-38
22.16.2	Streaming Access to Kafka Records in Oracle SQL Queries	22-39
22.16.3	Seekable access to Kafka Records in Oracle SQL queries	22-40
22.17	Creating Oracle SQL Access to Kafka Applications	22-40
22.17.1	Creating Load Applications with Oracle SQL Access to Kafka	22-41
22.17.2	Creating Streaming Applications with Oracle SQL Access to Kafka	22-42

22.17.3	Creating Seekable Applications with Oracle SQL Access to Kafka	22-44
22.18	Using Kafka Cluster Access for Applications	22-46
22.18.1	How to Diagnose Oracle SQL Access to Kafka Issues	22-46
22.18.2	Identifying and Resolving Oracle SQL Access to Kafka Issues	22-48

23 ADRCI: ADR Command Interpreter

23.1	About the ADR Command Interpreter (ADRCI) Utility	23-2
23.2	Definitions for Oracle Database ADRC	23-2
23.3	Starting ADRCI and Getting Help	23-5
23.3.1	Using ADRCI in Interactive Mode	23-5
23.3.2	Getting Help	23-5
23.3.3	Using ADRCI in Batch Mode	23-6
23.4	Setting the ADRCI Homepath Before Using ADRCI Commands	23-7
23.5	Viewing the Alert Log	23-9
23.6	Finding Trace Files	23-10
23.7	Viewing Incidents	23-11
23.8	Packaging Incidents	23-12
23.8.1	About Packaging Incidents	23-12
23.8.2	Creating Incident Packages	23-13
23.8.2.1	Creating a Logical Incident Package	23-13
23.8.2.2	Adding Diagnostic Information to a Logical Incident Package	23-15
23.8.2.3	Generating a Physical Incident Package	23-16
23.9	ADRCI Command Reference	23-17
23.9.1	CREATE REPORT	23-19
23.9.2	ECHO	23-20
23.9.3	EXIT	23-20
23.9.4	HOST	23-20
23.9.5	IPS	23-21
23.9.5.1	Using the <ADR_HOME> and <ADR_BASE> Variables in IPS Commands	23-23
23.9.5.2	IPS ADD	23-23
23.9.5.3	IPS ADD FILE	23-25
23.9.5.4	IPS ADD NEW INCIDENTS	23-25
23.9.5.5	IPS COPY IN FILE	23-26
23.9.5.6	IPS COPY OUT FILE	23-26
23.9.5.7	IPS CREATE PACKAGE	23-27
23.9.5.8	IPS DELETE PACKAGE	23-29
23.9.5.9	IPS FINALIZE	23-30
23.9.5.10	IPS GENERATE PACKAGE	23-30
23.9.5.11	IPS GET MANIFEST	23-31
23.9.5.12	IPS GET METADATA	23-31

23.9.5.13	IPS PACK	23-32
23.9.5.14	IPS REMOVE	23-34
23.9.5.15	IPS REMOVE FILE	23-35
23.9.5.16	IPS SET CONFIGURATION	23-36
23.9.5.17	IPS SHOW CONFIGURATION	23-36
23.9.5.18	IPS SHOW FILES	23-39
23.9.5.19	IPS SHOW INCIDENTS	23-40
23.9.5.20	IPS SHOW PACKAGE	23-41
23.9.5.21	IPS UNPACK FILE	23-41
23.9.6	PURGE	23-42
23.9.7	QUIT	23-43
23.9.8	RUN	23-44
23.9.9	SELECT	23-44
23.9.9.1	AVG	23-47
23.9.9.2	CONCAT	23-48
23.9.9.3	COUNT	23-48
23.9.9.4	DECODE	23-49
23.9.9.5	LENGTH	23-49
23.9.9.6	MAX	23-50
23.9.9.7	MIN	23-50
23.9.9.8	NVL	23-51
23.9.9.9	REGEXP_LIKE	23-51
23.9.9.10	SUBSTR	23-52
23.9.9.11	SUM	23-52
23.9.9.12	TIMESTAMP_TO_CHAR	23-53
23.9.9.13	TOLOWER	23-53
23.9.9.14	TOUPPER	23-54
23.9.10	SET BASE	23-54
23.9.11	SET BROWSER	23-55
23.9.12	SET CONTROL	23-55
23.9.13	SET ECHO	23-57
23.9.14	SET EDITOR	23-57
23.9.15	SET HOMEPATH	23-58
23.9.16	SET TERMOUT	23-58
23.9.17	SHOW ALERT	23-59
23.9.18	SHOW BASE	23-61
23.9.19	SHOW CONTROL	23-61
23.9.20	SHOW HM_RUN	23-64
23.9.21	SHOW HOMEPATH	23-65
23.9.22	SHOW HOMES	23-65
23.9.23	SHOW INCDIR	23-65
23.9.24	SHOW INCIDENT	23-67

23.9.25	SHOW LOG	23-70
23.9.26	SHOW PROBLEM	23-71
23.9.27	SHOW REPORT	23-73
23.9.28	SHOW TRACEFILE	23-73
23.9.29	SPOOL	23-74
23.10	Troubleshooting ADRCI	23-75

24 DBVERIFY: Offline Database Verification Utility

24.1	Using DBVERIFY to Validate Disk Blocks of a Single Data File	24-1
24.1.1	DBVERIFY Syntax When Validating Blocks of a Single File	24-2
24.1.2	DBVERIFY Parameters When Validating Blocks of a Single File	24-2
24.1.3	Example DBVERIFY Output For a Single Data File	24-3
24.2	Using DBVERIFY to Validate a Segment	24-4
24.2.1	DBVERIFY Syntax When Validating a Segment	24-5
24.2.2	DBVERIFY Parameters When Validating a Single Segment	24-5
24.2.3	Example DBVERIFY Output For a Validated Segment	24-6

25 DBNEWID Utility

25.1	What Is the DBNEWID Utility?	25-1
25.2	Ramifications of Changing the DBID and DBNAME	25-1
25.3	Considerations for Global Database Names	25-2
25.4	Changing Both CDB and PDB DBIDs Using DBNEWID	25-3
25.5	Changing the DBID and DBNAME of a Database	25-3
25.5.1	Changing the DBID and Database Name	25-4
25.5.2	Changing Only the Database ID	25-6
25.5.3	Changing Only the Database Name	25-7
25.5.4	Troubleshooting DBNEWID	25-8
25.6	DBNEWID Syntax	25-10
25.6.1	DBNEWID Parameters	25-10
25.6.2	Restrictions and Usage Notes	25-11
25.6.3	Additional Restrictions for Releases Earlier Than Oracle Database 10g	25-12

26 Using LogMiner to Analyze Redo Log Files

26.1	LogMiner Benefits	26-2
26.2	Introduction to LogMiner	26-3
26.2.1	LogMiner Configuration	26-3
26.2.1.1	Objects in LogMiner Configuration Files	26-3
26.2.1.2	LogMiner Configuration Example	26-4
26.2.1.3	LogMiner Requirements	26-4

26.2.2	Directing LogMiner Operations and Retrieving Data of Interest	26-7
26.3	Using LogMiner in a CDB	26-7
26.3.1	LogMiner V\$ Views and DBA Views in a CDB	26-8
26.3.2	The V\$LOGMNR_CONTENTS View in a CDB	26-9
26.3.3	Enabling Supplemental Logging in a CDB	26-10
26.4	How to Configure Supplemental Logging for Oracle GoldenGate	26-11
26.4.1	Oracle GoldenGate Integration with Oracle Database for Fine-Grained Supplemental Logging	26-11
26.4.2	Logical Replication of Tables with LogMiner and Oracle GoldenGate	26-12
26.4.3	Views that Show Tables Enabled for Oracle GoldenGate Automatic Capture	26-13
26.5	LogMiner Dictionary Files and Redo Log Files	26-14
26.5.1	LogMiner Dictionary Options	26-14
26.5.1.1	Using the Online Catalog	26-15
26.5.1.2	Extracting a LogMiner Dictionary to the Redo Log Files	26-16
26.5.1.3	Extracting the LogMiner Dictionary to a Flat File	26-17
26.5.2	Specifying Redo Log Files for Data Mining	26-18
26.6	Starting LogMiner	26-19
26.7	Querying V\$LOGMNR_CONTENTS for Redo Data of Interest	26-19
26.7.1	How to Use V\$LOGMNR_CONTENTS to Find Redo Data	26-20
26.7.2	How the V\$LOGMNR_CONTENTS View Is Populated	26-22
26.7.3	Querying V\$LOGMNR_CONTENTS Based on Column Values	26-23
26.7.3.1	Example of Querying V\$LOGMNR_CONTENTS Column Values	26-23
26.7.3.2	The Meaning of NULL Values Returned by the MINE_VALUE Function	26-24
26.7.3.3	Usage Rules for the MINE_VALUE and COLUMN_PRESENT Functions	26-24
26.7.3.4	Restrictions When Using the MINE_VALUE Function To Get an NCHAR Value	26-24
26.7.4	Querying V\$LOGMNR_CONTENTS Based on XMLType Columns and Tables	26-24
26.7.4.1	How V\$LOGMNR_CONTENTS Based on XMLType Columns and Tables are Queried	26-25
26.7.4.2	Restrictions When Using LogMiner With XMLType Data	26-27
26.7.4.3	Example of a PL/SQL Procedure for Assembling XMLType Data	26-27
26.8	Filtering and Formatting Data Returned to V\$LOGMNR_CONTENTS	26-29
26.8.1	Showing Only Committed Transactions	26-30
26.8.2	Skipping Redo Corruptions	26-32
26.8.3	Filtering Data by Time	26-33
26.8.4	Filtering Data by SCN	26-34
26.8.5	Formatting Reconstructed SQL Statements for Reprocessing	26-34
26.8.6	Formatting the Appearance of Returned Data for Readability	26-35
26.9	Reapplying DDL Statements Returned to V\$LOGMNR_CONTENTS	26-36
26.10	Calling DBMS_LOGMNR.START_LOGMNR Multiple Times	26-36
26.11	LogMiner and Supplemental Logging	26-37
26.11.1	Understanding Supplemental Logging and LogMiner	26-38
26.11.2	Database-Level Supplemental Logging	26-39

26.11.2.1	Minimal Supplemental Logging	26-39
26.11.2.2	Database-Level Identification Key Logging	26-39
26.11.2.3	Procedural Supplemental Logging	26-41
26.11.3	Disabling Database-Level Supplemental Logging	26-41
26.11.4	Table-Level Supplemental Logging	26-42
26.11.4.1	Table-Level Identification Key Logging	26-42
26.11.4.2	Table-Level User-Defined Supplemental Log Groups	26-43
26.11.4.3	Usage Notes for User-Defined Supplemental Log Groups	26-44
26.11.5	Tracking DDL Statements in the LogMiner Dictionary	26-44
26.11.6	DDL_DICT_TRACKING and Supplemental Logging Settings	26-45
26.11.7	DDL_DICT_TRACKING and Specified Time or SCN Ranges	26-46
26.12	Accessing LogMiner Operational Information in Views	26-47
26.12.1	Options for Viewing LogMiner Operational Information	26-47
26.12.2	Querying V\$LOGMNR_LOGS	26-48
26.12.3	Querying Views for Supplemental Logging Settings	26-49
26.12.4	Querying Individual PDBs Using LogMiner	26-50
26.13	Steps in a Typical LogMiner Session	26-52
26.13.1	Understanding How to Run LogMiner Sessions	26-52
26.13.2	Typical LogMiner Session Task 1: Enable Supplemental Logging	26-54
26.13.3	Typical LogMiner Session Task 2: Extract a LogMiner Dictionary	26-54
26.13.4	Typical LogMiner Session Task 3: Specify Redo Log Files for Analysis	26-55
26.13.5	Start LogMiner	26-56
26.13.6	Query V\$LOGMNR_CONTENTS	26-57
26.13.7	Typical LogMiner Session Task 6: End the LogMiner Session	26-58
26.14	Examples Using LogMiner	26-58
26.14.1	Examples of Mining by Explicitly Specifying the Redo Log Files of Interest	26-59
26.14.1.1	Example 1: Finding All Modifications in the Last Archived Redo Log File	26-60
26.14.1.2	Example 2: Grouping DML Statements into Committed Transactions	26-62
26.14.1.3	Example 3: Formatting the Reconstructed SQL	26-64
26.14.1.4	Example 4: Using the LogMiner Dictionary in the Redo Log Files	26-67
26.14.1.5	Example 5: Tracking DDL Statements in the Internal Dictionary	26-75
26.14.1.6	Example 6: Filtering Output by Time Range	26-78
26.14.2	LogMiner Use Case Scenarios	26-80
26.14.2.1	Using LogMiner to Track Changes Made by a Specific User	26-80
26.14.2.2	Using LogMiner to Calculate Table Access Statistics	26-82
26.15	Supported Data Types, Storage Attributes, and Database and Redo Log File Versions	26-83
26.15.1	Supported Data Types and Table Storage Attributes	26-84
26.15.2	Database Compatibility Requirements for LogMiner	26-85
26.15.3	Unsupported Data Types and Table Storage Attributes	26-86
26.15.4	Supported Databases and Redo Log File Versions	26-86

27 Using the Metadata APIs

27.1	Why Use the DBMS_METADATA API?	27-2
27.2	Overview of the DBMS_METADATA API	27-2
27.3	Using the DBMS_METADATA API to Retrieve an Object's Metadata	27-4
27.3.1	How to Use the DBMS_METADATA API to Retrieve Object Metadata	27-5
27.3.2	Typical Steps Used for Basic Metadata Retrieval	27-5
27.3.3	Retrieving Multiple Objects	27-7
27.3.4	Placing Conditions on Transforms	27-8
27.3.5	Accessing Specific Metadata Attributes	27-11
27.4	Using the DBMS_METADATA API to Recreate a Retrieved Object	27-13
27.5	Using the DBMS_METADATA API to Retrieve Collections of Different Object Types	27-16
27.6	Filtering the Return of Heterogeneous Object Types	27-17
27.7	Using the DBMS_METADATA_DIFF API to Compare Object Metadata	27-19
27.8	Performance Tips for the Programmatic Interface of the DBMS_METADATA API	27-27
27.9	Example Usage of the DBMS_METADATA API	27-27
27.9.1	What Does the DBMS_METADATA Example Do?	27-28
27.9.2	Output Generated from the GET_PAYROLL_TABLES Procedure	27-30
27.10	Summary of DBMS_METADATA Procedures	27-32
27.11	Summary of DBMS_METADATA_DIFF Procedures	27-33

28 Original Import

28.1	What Is the Import Utility?	28-2
28.2	Table Objects: Order of Import	28-3
28.3	Before Using Import	28-3
28.3.1	Overview of Import Preparation	28-4
28.3.2	Running catexp.sql or catalog.sql	28-4
28.3.3	Verifying Access Privileges for Import Operations	28-4
28.3.3.1	Importing Objects Into Your Own Schema	28-5
28.3.3.2	Importing Grants	28-5
28.3.3.3	Importing Objects Into Other Schemas	28-6
28.3.3.4	Importing System Objects	28-6
28.3.4	Processing Restrictions	28-7
28.4	Importing into Existing Tables	28-7
28.4.1	Manually Creating Tables Before Importing Data	28-7
28.4.2	Disabling Referential Constraints	28-7
28.4.3	Manually Ordering the Import	28-8
28.5	Effect of Schema and Database Triggers on Import Operations	28-8
28.6	Invoking Import	28-9

28.6.1	Command-Line Entries	28-9
28.6.2	Parameter Files	28-10
28.6.3	Interactive Mode	28-11
28.6.4	Invoking Import As SYSDBA	28-11
28.6.5	Getting Online Help	28-11
28.7	Import Modes	28-11
28.8	Import Parameters	28-14
28.8.1	BUFFER	28-17
28.8.2	COMMIT	28-17
28.8.3	COMPILE	28-18
28.8.4	CONSTRAINTS	28-18
28.8.5	DATA_ONLY	28-19
28.8.6	DATAFILES	28-19
28.8.7	DESTROY	28-19
28.8.8	FEEDBACK	28-20
28.8.9	FILE	28-20
28.8.10	FILESIZE	28-20
28.8.11	FROMUSER	28-21
28.8.12	FULL	28-22
28.8.12.1	Points to Consider for Full Database Exports and Imports	28-22
28.8.13	GRANTS	28-23
28.8.14	HELP	28-23
28.8.15	IGNORE	28-23
28.8.16	INDEXES	28-24
28.8.17	INDEXFILE	28-24
28.8.18	LOG	28-25
28.8.19	PARFILE	28-25
28.8.20	RECORDLENGTH	28-25
28.8.21	RESUMABLE	28-25
28.8.22	RESUMABLE_NAME	28-26
28.8.23	RESUMABLE_TIMEOUT	28-26
28.8.24	ROWS	28-26
28.8.25	SHOW	28-27
28.8.26	SKIP_UNUSABLE_INDEXES	28-27
28.8.27	STATISTICS	28-28
28.8.28	STREAMS_CONFIGURATION	28-28
28.8.29	STREAMS_INSTANTIATION	28-28
28.8.30	TABLES	28-29
28.8.30.1	Table Name Restrictions	28-30
28.8.31	TABLESPACES	28-31
28.8.32	TOID_NOVALIDATE	28-31
28.8.33	TOUSER	28-32

28.8.34	TRANSPORT_TABLESPACE	28-33
28.8.35	TTS_OWNERS	28-33
28.8.36	USERID (username/password)	28-33
28.8.37	VOLSIZE	28-33
28.9	Example Import Sessions	28-34
28.9.1	Example Import of Selected Tables for a Specific User	28-34
28.9.2	Example Import of Tables Exported by Another User	28-34
28.9.3	Example Import of Tables from One User to Another	28-35
28.9.4	Example Import Session Using Partition-Level Import	28-35
28.9.4.1	Example 1: A Partition-Level Import	28-36
28.9.4.2	Example 2: A Partition-Level Import of a Composite Partitioned Table	28-36
28.9.4.3	Example 3: Repartitioning a Table on a Different Column	28-37
28.9.5	Example Import Using Pattern Matching to Import Various Tables	28-39
28.10	Exit Codes for Inspection and Display	28-39
28.11	Error Handling During an Import	28-40
28.11.1	Row Errors	28-40
28.11.1.1	Failed Integrity Constraints	28-40
28.11.1.2	Invalid Data	28-41
28.11.2	Errors Importing Database Objects	28-41
28.11.2.1	Object Already Exists	28-41
28.11.2.2	Sequences	28-42
28.11.2.3	Resource Errors	28-42
28.11.2.4	Domain Index Metadata	28-42
28.12	Table-Level and Partition-Level Import	28-42
28.12.1	Guidelines for Using Table-Level Import	28-43
28.12.2	Guidelines for Using Partition-Level Import	28-43
28.12.3	Migrating Data Across Partitions and Tables	28-44
28.13	Controlling Index Creation and Maintenance	28-44
28.13.1	Delaying Index Creation	28-45
28.13.2	Index Creation and Maintenance Controls	28-45
28.13.2.1	Example of Postponing Index Maintenance	28-45
28.14	Network Considerations for Using Oracle Net with Original Import	28-46
28.15	Character Set and Globalization Support Considerations	28-46
28.15.1	User Data	28-47
28.15.1.1	Effect of Character Set Sorting Order on Conversions	28-47
28.15.2	Data Definition Language (DDL)	28-47
28.15.3	Single-Byte Character Sets	28-48
28.15.4	Multibyte Character Sets	28-48
28.16	Using Instance Affinity	28-48
28.17	Considerations When Importing Database Objects	28-49
28.17.1	Importing Object Identifiers	28-50
28.17.2	Importing Existing Object Tables and Tables That Contain Object Types	28-51

28.17.3	Importing Nested Tables	28-51
28.17.4	Importing REF Data	28-52
28.17.5	Importing BFILE Columns and Directory Aliases	28-52
28.17.6	Importing Foreign Function Libraries	28-53
28.17.7	Importing Stored Procedures, Functions, and Packages	28-53
28.17.8	Importing Java Objects	28-53
28.17.9	Importing External Tables	28-54
28.17.10	Importing Advanced Queue (AQ) Tables	28-54
28.17.11	Importing LONG Columns	28-54
28.17.12	Importing LOB Columns When Triggers Are Present	28-55
28.17.13	Importing Views	28-55
28.17.14	Importing Partitioned Tables	28-56
28.18	Support for Fine-Grained Access Control	28-56
28.19	Snapshots and Snapshot Logs	28-56
28.19.1	Snapshot Log	28-56
28.19.2	Snapshots	28-57
28.19.2.1	Importing a Snapshot	28-57
28.19.2.2	Importing a Snapshot into a Different Schema	28-57
28.20	Transportable Tablespaces	28-58
28.21	Storage Parameters	28-58
28.21.1	The OPTIMAL Parameter	28-59
28.21.2	Storage Parameters for OID Indexes and LOB Columns	28-59
28.21.3	Overriding Storage Parameters	28-59
28.22	Read-Only Tablespaces	28-59
28.23	Dropping a Tablespace	28-60
28.24	Reorganizing Tablespaces	28-60
28.25	Importing Statistics	28-60
28.26	Using Export and Import to Partition a Database Migration	28-61
28.26.1	Advantages of Partitioning a Migration	28-61
28.26.2	Disadvantages of Partitioning a Migration	28-62
28.26.3	How to Use Export and Import to Partition a Database Migration	28-62
28.27	Tuning Considerations for Import Operations	28-62
28.27.1	Changing System-Level Options	28-63
28.27.2	Changing Initialization Parameters	28-63
28.27.3	Changing Import Options	28-64
28.27.4	Dealing with Large Amounts of LOB Data	28-64
28.27.5	Dealing with Large Amounts of LONG Data	28-64
28.28	Using Different Releases of Export and Import	28-65
28.28.1	Restrictions When Using Different Releases of Export and Import	28-65
28.28.2	Examples of Using Different Releases of Export and Import	28-66

A Instant Client for SQL*Loader, Export, and Import

A.1	What is the Tools Instant Client?	A-1
A.2	Choosing Which Instant Client to Install	A-2
A.3	Installing Instant Client Tools by Downloading from OTN	A-3
A.3.1	Installing Instant Client and Instant Client Tools RPM Packages for Linux	A-3
A.3.2	Installing Instant Client and Instant Client Tools from Unix or Windows Zip Files	A-4
A.4	Installing Tools Instant Client from the Client Release Media	A-4
A.5	List of Oracle Instant Client Tools Files	A-5
A.6	Configuring Tools Instant Client Package	A-6
A.7	Connecting to a Database with the Tools Instant Client Package	A-8
A.8	Uninstalling Tools Instant Client Package and Instant Client	A-9

B SQL*Loader Syntax Diagrams

Preface

This document describes how to use Oracle Database utilities for data transfer, data maintenance, and database administration.

- [Audience](#)
- [Documentation Accessibility](#)
- [Diversity and Inclusion](#)
- [Related Documentation](#)
- [Syntax Diagrams](#)
- [Conventions](#)

Audience

The utilities described in this book are intended for database administrators (DBAs), application programmers, security administrators, system operators, and other Oracle Database users who perform the following tasks:

- Archive data, back up Oracle Database, or move data between different Oracle Databases using the Export and Import utilities (both the original versions and the Oracle Data Pump versions)
- Load data into Oracle Database tables from operating system files, using SQL*Loader
- Load data from external sources, using the external tables feature
- Perform a physical data structure integrity check on an offline database, using the `DBVERIFY` utility
- Maintain the internal database identifier (DBID) and the database name (`DBNAME`) for an operational database, using the `DBNEWID` utility
- Extract and manipulate complete representations of the metadata for Oracle Database objects, using the Metadata API
- Query and analyze redo log files (through a SQL interface), using the LogMiner utility
- Use the Automatic Diagnostic Repository Command Interpreter (ADRCI) utility to manage Oracle Database diagnostic data

To use this manual, you need a working knowledge of SQL and of Oracle fundamentals. You can find such information in *Oracle Database Concepts*. In addition, to use SQL*Loader, you must know how to use the file management facilities of your operating system.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Related Documentation

For more information, refer to the Oracle Database documentation set. In particular, check the following documents:

- *Oracle Database Concepts*
- *Oracle Database SQL Language Reference*
- *Oracle Database Administrator's Guide*
- *Oracle Database PL/SQL Packages and Types Reference*

Also refer to My Oracle Support notes that are relevant to Oracle Data Pump tasks, and in particular, refer to recommended proactive patches for your release:

[Data Pump Recommended Proactive Patches For 19.10 and Above \(Doc ID 2819284.1\)](#)

Oracle Data Pump patches are not included in Oracle Database release updates, but instead are provide in bundled patches that contain SQL, PL/SQL packages, and XML stylesheets for Oracle Data Pump. Oracle recommends that you apply the most recent Oracle Data Pump bundle patch for your release. Because these patches do not include Oracle Database binaries, you can apply Oracle Data Pump patches online while the database is running , so long as Oracle Data Pump is not in use at the time.

Some of the examples in this book use the sample schemas of the seed database, which is installed by default when you install Oracle Database. Refer to *Oracle Database Sample Schemas* for information about how these schemas were created, and how you can use them yourself.

Syntax Diagrams

Syntax descriptions are provided in this book for various SQL, PL/SQL, or other command-line constructs in graphic form or Backus Naur Form (BNF). See *Oracle Database SQL Language Reference* for information about how to interpret these descriptions.

Conventions

The following text conventions are used in this document: