

Floor Care SYSTEMS

BRAVO® 1500+

FLOOR STRIPPER

Specially formulated for high and ultra high speed floor care programs.

SAVES YOU TIME & MONEY

- ✓ **Powerful Stripping Action**
Quickly penetrates and emulsifies finish.
- ✓ **Reduces Labor**
Strips the accumulation of finish that normally accompanies high and ultra high speed floor care programs.
- ✓ **Low Foam Formula**
Results in less time emptying pickup tanks.
- ✓ **Mild, Pleasant Fragrance**
Fresh, green apple scent.

STRIPPING

Sealing


Finishing

Cleaning


Maintaining

BRAVO® 1500+


DIRECTIONS FOR USE




1. Mix a 1:4 dilution using hot water. (1 gallon of BRAVO® 1500+ to 4 gallons of water). If stripping an extreme amount of finish build-up, use BRAVO 1500+ at 1:3 or 1:2 for added strength.




3. Let stripper solution soak for 7-10 minutes. Re-wet as necessary, **do not allow solution to dry on floor**. Longer soak times may be necessary in cases of extreme buildup.




5. Pick up all of the solution with a clean mop, wet vac or automatic scrubber. Mop up any "tracks" left by wet vacs or automatic scrubbers before they dry.



7. Let floor dry completely before applying recommended SC JOHNSON PROFESSIONAL brand floor sealer or finish.



2. Apply liberal amounts of solution uniformly to floor with a mop. Start with the edges to give them more soak time. If splashing occurs, wipe off surfaces with a clean rag dampened with water.



4. Hand or machine scrub **thoroughly** using black pads or stripping brush.



6. Thoroughly rinse floor with clear water.

SPECIFICATIONS

Fragrance: green apple

pH: >13.0

Dilution: 1:4 with water (may also be used 1:2 and 1:3)

Shelf Life: 2 years

PRECAUTIONS

- Do not use on wood floors or painted surfaces.
- Test for softening or color bleeding on linoleum, rubber, or asphalt floors.
- Use in well ventilated areas.
- Do not use for selective stripping of finish on TECHNIQUE® sealer.

APPLICATIONS

Bravo 1500+ is a powerful floor finish stripper specifically formulated for use in high and ultra high speed floor programs.

PACKAGING

Pack/Size
4/1 gallon (3.8 L)
1/5 gallon (18.9 L)

Product Code
4639
4641

SAFETY REMINDER

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures.

FAILURE TO FOLLOW THESE PRECAUTIONS COULD LEAD TO PRODUCT FAILURE OR SLIPPERY CONDITIONS.

KEEP FROM FREEZING

KEEP OUT OF REACH OF CHILDREN

©1995 S.C. Johnson & Son, Inc.
SC Johnson Professional is a Division of S.C. Johnson & Son, Inc.
Racine, WI 53403-5011 U.S.A.

All Rights Reserved.

SC JOHNSON PROFESSIONAL®
® Can. Trade Mark Reg'd. to S.C. Johnson & Son, Inc.
Reg'd. User S.C. JOHNSON AND SON, LIMITED
Brantford, Ont., Canada N3T 5R1.

For further information on special applications or other SC Johnson Professional Products, contact your SC Johnson Professional representative, or call us at **1-800-558-2332**

SC JOHNSON PROFESSIONAL FLOOR CARE SYSTEMS