

*Even Better
Than Before!*

Floor Care SYSTEMS

Vectra™

FLOOR FINISH

Diamond-like brilliance, clarity and durability. SC Johnson Professional's best conventional floor finish Just Got Better!

SAVES YOU TIME & MONEY

✓ **Patented Formula**

New technology to the industry designed to make your life easier and your floors look even better.

✓ **Faster Cure Time**

Cures on the floor faster than traditional floor coatings during the critical early minutes after application. As a customer, you benefit from great early durability, reduced scratching and marking, and reduced facility downtime.

✓ **More Dirt Resistant**

Diamond-like clarity and gloss but now resists dirt imbedment, black heel marks, scratching and scuffing even more effectively than before.

✓ **Better Buff Response**

Provides better buff response and repairability than before. Responds well to 175 through 1500 RPM equipment.

✓ **Versatility**

Works well in a wide variety of settings and across a wide spectrum of climate conditions.



Available in a variety of package sizes including a 1 gallon (3.8 L) bottle, a 5 gallon (18.9 L) Envirobox™ and a 55 gallon (209 L) drum.

Stripping

Sealing










FINISHING

Cleaning

Maintaining

SC Johnson®
Professional

DIRECTIONS FOR USE

APPLYING FLOOR FINISH	MAINTENANCE	RECOATING
 <p>1. Strip floor using SC JOHNSON PROFESSIONAL brand stripper according to label directions.</p>	 <p>1. Dust mop or sweep.</p>	 <p>1. Dust mop or sweep.</p>
 <p>2. Apply 2-4 coats using a clean mop. Apply additional coats if a higher gloss is desired.</p>	 <p>2. Clean floor with mop or automatic scrubber using recommended SC JOHNSON PROFESSIONAL brand cleaner according to label directions.</p>	 <p>2. Deep scrub floor using recommended SC JOHNSON PROFESSIONAL brand cleaner according to label directions.</p>
 <p>3. Allow approximately 30 minutes drying time between coats. Temperatures, humidity and ventilation may affect drying time.</p>	 <p>3. If desired, spray buff using recommended SC JOHNSON PROFESSIONAL brand floor maintainer to enhance gloss.</p>	 <p>3. Apply 1 - 3 coats using a clean mop.</p>

SPECIFICATIONS

Non-volatile Solids: 19.0%

Drying Time:

Recoat – Approx. 30 minutes (under normal conditions)

Traffic – Approx. 30 minutes (under normal conditions)

Shelf Life: 2 years

Slip Resistance: 0.5 minimum (ASTM D2047)

This product is not regulated by W.H.M.I.S. For additional product information, please refer to the M.S.D.S. and/or product label.

FOR BEST RESULTS

- Do not dilute.
- Do not use on surfaces colder than 50°F/10°C.
- To avoid contamination, do not return unused finish to original container.

PACKAGING

Pack/Size	Product Code
4-1 Gallon / 3.8 L Containers	4078
1-5 Gallon / 18.9 L ENVIROBOX™	4071
1-55 Gallon / 209 L Drum	4074

SAFETY REMINDER

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS's are available on line at www.scjprofessional.com or by calling 1-800-725-6737.

FOR COMMERCIAL/INDUSTRIAL USE ONLY
KEEP FROM FREEZING
KEEP OUT OF REACH OF CHILDREN

© 1998 S.C. Johnson Commercial Markets, Inc.
 S.C. Johnson Professional is a Division of
 S.C. Johnson Commercial Markets, Inc.,
 8310 16th Street, Sturtevant, WI 53177-0902 U.S.A.
 All Rights Reserved.

For further information on special applications or other SC Johnson Professional Products, contact your SC Johnson Professional representative, or call us at **1-800-558-2332** or visit our web site at: <http://www.scjprofessional.com>