



FANTASTECH ENERGY SOLUTION LLC

# KOOR Active Stack

51.2V Stackable LiFePO4 Battery — Spec Sheet

**51.2V · 314Ah · 16 kWh**

Model: Koor Stackable S314 16kWh



Floor-standing modular stack  
287 lb — 4 sections + control head

**ACTIVE CELL BALANCING****AUTO PRECHARGE****BUILT-IN HEATER PADS****200A CONTINUOUS****4.3" TOUCH SCREEN****STACKS TO 15 UNITS****10-YEAR WARRANTY**

## ELECTRICAL SPECIFICATIONS

|                                 |                                                                      |
|---------------------------------|----------------------------------------------------------------------|
| Nominal Voltage                 | 51.2V                                                                |
| Nominal Capacity                | 314Ah                                                                |
| Nominal Energy                  | 16.08 kWh                                                            |
| Cell Chemistry                  | LiFePO4                                                              |
| Charging Voltage                | 56.0 – 58.4V                                                         |
| Discharge Cutoff Voltage        | 43.2V                                                                |
| Charge Method                   | CC-CV — standard 62.8A (0.2C), cutoff 6.28A (0.02C)                  |
| Max. Charge / Discharge Current | 200A continuous / 200A continuous                                    |
| Parallel Expansion              | Up to 15 units on one comm chain (auto-address, RS485 / CAN cascade) |

## BATTERY MANAGEMENT & PROTECTION

|                   |                                                                                                                                           |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Built-in BMS      | Monitors and protects voltage, current and temperature on every string                                                                    |
| Cell Balancing    | Active balancing — moves charge between cells instead of bleeding it off, so the pack stays in step over its life                         |
| Precharge Circuit | Factory-installed automated precharge with a 5–8 second time-delay relay. Soft-starts the inverter on its own; no manual precharge button |
| Protections       | Over / under-voltage, overcurrent, short circuit, over / under-temperature, cell imbalance                                                |
| Communication     | Dual RS485, CAN, RS232                                                                                                                    |

## THERMAL MANAGEMENT

|                       |                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| Heating               | Internal heater pads wired into the BMS heating circuit — automatic sub-zero charge protection, no external heater needed |
| Charge Temp. Range    | 0°C to 45°C (32°F to 113°F)                                                                                               |
| Discharge Temp. Range | –20°C to 60°C (–4°F to 140°F)                                                                                             |
| Storage Temp. Range   | –20°C to 45°C (–4°F to 113°F)                                                                                             |

## DISPLAY & MONITORING

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| Screen            | 4.3" TFT smart touch screen, built into the front control panel |
| Live Readouts     | Voltage, current, state of charge, temperature                  |
| Status Indicators | RUN / ALM / capacity LEDs                                       |

## MECHANICAL / PHYSICAL

|                   |                                                                |
|-------------------|----------------------------------------------------------------|
| Footprint (W × D) | 720 × 526 mm (28.3 × 20.7 in)                                  |
| Overall Height    | ≈1,176 mm / 46.3 in (base + 4 stacked sections + control head) |
| Weight            | 130 kg ± 5 kg (287 lb ± 11 lb)                                 |
| Enclosure         | Steel, floor-standing modular stack                            |

## CERTIFICATIONS & WARRANTY

|                |                                            |
|----------------|--------------------------------------------|
| Transport      | UN38.3 tested, MSDS on file — per shipment |
| Safety Listing | Not UL listed                              |
| Warranty       | <b>10-Year Manufacturer Warranty</b>       |

## WHAT SETS THE ACTIVE STACK APART

- **Active cell balancing** — moves charge to where it is needed instead of bleeding the high cells down, so the pack stays matched for its whole life.
- **Automated precharge** — the pack soft-starts the inverter itself on power-up. No manual precharge switch to remember.
- **Built-in heater pads** — protects the pack from sub-zero charging without a space heater or heat tape.
- **200A continuous both ways** — charges and discharges at full tilt behind a 12kW inverter.
- **Stacks to 15 units** — one comm chain, auto-addressing, up to 241 kWh on a single bank.
- **10-Year Warranty**, backed by a manufacturing partner with 14 years in LiFePO4 production.

Not UL listed — confirm code and AHJ requirements before specifying on a permitted job. Specifications may change without prior notice. © Fantastech Energy Solution LLC.

Fantastech Energy Solution LLC | 3645 S 1200 W, Goshen, IN 46528 | 574-218-1973 | derek@fantastech.org