FANTASTECH ENERGY SOLUTION LLC

KOOR Active Stack

51.2V Stackable LiFePO4 Battery — Spec Sheet

51.2V · 314Ah · 16 kWh

Model: Koor Stackable S314 16kWh

10-YEAR WARRANTY

Handled right here in Goshen, Indiana — not overseas



Floor-standing modular stack
287 lb — 4 sections + control head

ACTIVE CELL BALANCING | AUTO PRECHARGE | BUILT-IN HEATER PADS | 200A CONTINUOUS | 4.3" TOUCH SCREEN | STACKS TO 15 UNITS | 10-YEAR WARRANTY

ELECTRICAL SPECIFICATIONS

Nominal Voltage	51.2V
Nominal Capacity	314Ah
Nominal Energy	16.08 kWh
Cell Chemistry	LiFePO4
Charging Voltage	56.0 – 58.4V
Discharge Cutoff Voltage	43.2V
Charge Method	CC–CV — standard 62.8A (0.2C), cutoff 6.28A (0.02C)
Max. Charge / Discharge Current	200A continuous / 200A continuous
Parallel Expansion	Up to 15 units on one comm chain (RS485 / CAN cascade). Each pack is addressed by DIP switch: master = address 0 (all switches OFF), next pack address 1, and so on

BATTERY MANAGEMENT & PROTECTION

Built-in BMS	Monitors and protects voltage, current and temperature on every string
Cell Balancing	Active balancing — moves charge between cells instead of bleeding it off, so the pack stays in step over its life
Precharge Circuit	Automated precharge. Soft-starts the inverter on its own; no manual precharge button
Built-in Breaker	DC breaker built into every module
Protections	Over / under-voltage, overcurrent, short circuit, over / under-temperature, cell imbalance
Communication	Dual RS485, CAN, RS232

THERMAL MANAGEMENT

Heating	Internal heater pads wired into the BMS heating circuit — automatic sub-zero charge protection, no external heater needed
Charge Temp. Range	0°C to 45°C (32°F to 113°F)
Discharge Temp. Range	−20°C to 60°C (−4°F to 140°F)
Storage Temp. Range	−20°C to 45°C (−4°F to 113°F)

DISPLAY & MONITORING

Screen	Big, crisp 4.3" TFT touch screen on the front control panel — very user friendly
Live Readouts	Voltage, current, state of charge, temperature
Status Indicators	RUN / ALM / capacity LEDs

MECHANICAL / PHYSICAL

Footprint (W × D)	720 × 526 mm (28.3 × 20.7 in)
Overall Height	≈1,176 mm / 46.3 in (base + 4 stacked sections + control head)
Weight	130 kg ± 5 kg (287 lb ± 11 lb)
Enclosure	Steel, floor-standing modular stack

CERTIFICATIONS & WARRANTY

Transport	UN38.3 tested, MSDS on file — per shipment
Safety Listing	Not UL listed
Warranty	**10-Year Manufacturer Warranty**

WHAT SETS THE ACTIVE STACK APART

- **Active cell balancing** — moves charge to where it is needed instead of bleeding the high cells down, so the pack stays in step for its whole life.
- **Automated precharge** — the pack soft-starts the inverter itself on power-up. No manual precharge switch to remember.
- **Built-in heater pads** — protects the pack from sub-zero charging without a space heater or heat tape.
- **200A continuous both ways** — charges and discharges at full tilt behind a 12kW inverter.
- **Big, crisp display** — very user friendly. Charge level, volts, amps and temperature right on the front.
- **Stacks to 15 units** — one comm chain, each pack set by its own DIP switch (master = address 0), up to 241 kWh on a single bank. Commercial options available.
- **10-Year Warranty**, handled right here in Goshen, Indiana — not overseas.
- **Our own value brand** — dependable power at a value price. We spec it, build it and warranty it.

Not UL listed — confirm code and AHJ requirements before specifying on a permitted job. Specifications may change without prior notice. © Fantastech Energy Solution LLC.

Fantastech Energy Solution LLC | 3645 S 1200 W, Goshen, IN 46528 | 574-218-1973 | derek@fantastech.org