


INSTALL

1 Mount the faucet




Feed the attached tubes and cable through the hole. Lower the faucet, then **push it back** until the black tubes meet the back of the hole.

From below, slide the steel plate **above the retained washer and nut**. Wide slot around the shank; narrow slot around the black tubes and cable. **Hand-tighten the nut.**

2 Add the cold-water tee

1/4 in plastic tube? Use the black tee below. **Braided hose?** See install guide pp. 13-16, then return at **Step 3**.



Close the cold-water shutoff. Run the tap or dispenser on that line until flow stops. Put a cup and towel under the fitting.

Push the collet press against the release ring and hold. With your other hand, **pull the white tube out.**

Push the tee's short tube into that fitting. Reconnect the original tube to the open end. Leave the filtered run attached.

3 Match the rear connections

Pull the CO2 and TAP shipping caps off the soda machine.

Caps fit over the outside of the fittings. Leave the fittings in place.



CO2 Red / cylinder
SODA Blue / faucet
TAP White / filter
FLAVOR Black / either port

Faucet cable


Click into the square jack.

Push every tube fully home (a little over 1/2 in), then tug gently. Either black tube fits either FLAVOR port.

Lay the filter flat. Keep long tubes in easy, coiled curves.

TURN IT ON

4 Prepare the cylinder




Washer in the big nut; start by hand, nip up with the wrench. Tether and pressure come set from the factory.

Leak or hiss? Close water and cylinder. See guide, pp. 31-32.


5 Water, then gas, then power

1 WATER




Open the water shutoff **slowly**. Watch every water joint for a **full minute**.

2 GAS



Open the **cylinder valve**; the regulator is **set at the factory**. The upper needle settles near **75**. Listen at the nut and both red-tube ends **before power**: a hiss is a leak.

3 POWER



Seat the cord in the **top-left rear socket**. Plug into grounded 120 V. **It chimes.**


YOUR FIRST GLASS

6 Fill both flavors

On the machine display, **tap a flavor on the left**, then open **Fill**.

Lift off the **funnel cover**. Invert one whole **14.8 fl oz bottle** into the funnel. Tap **Start filling**.

Wait for Filled, then press the cover back on. Repeat for the other flavor.



7 Chill. Choose. Pour.

FIRST CHILL: ABOUT 1 HOUR

Fill your glass with ice.

Choose: tap the faucet display for a flavor. Tap once to wake a dim screen.

Pour: put it under the faucet. Press the lever; release to stop.

