

Quick start

From the box to your first glass.

HAVE READY


A **1-3/8 in counter hole**, cold water and grounded **120 V**. A filled **5 lb CO2 cylinder** with the supplied regulator and CO2 tether fitted and leak-checked. Two **14.8 fl oz** bottles of SodaStream-compatible concentrate.

Place the appliance: 1-5/8 in clear at each side, 2-3/8 in behind, and room above to invert a bottle into the funnel.

INSTALL

Cylinder closed. Power unplugged.

1 Mount the faucet




Feed the attached tubes and cable through the hole. Lower the faucet, then **push it back** until the black tubes meet the back of the hole.

From below, slide the steel plate **above the retained washer and nut**. Wide slot around the shank; narrow slot around the black tubes. **Hand-tighten the nut**.


2 Add the cold-water tee

1/4 in plastic tube? Use the black tee below.
Braided hose? Follow install guide pp. 9-11, then return at **Step 3**.



Close the cold-water shutoff. Run the cold tap until it stops. Put a cup and towel under the fitting.

Push the collet press against the release ring and hold. With your other hand, **pull the white tube out**.



Reconnect the original tube to the tee's open end. The white filtered run is already attached.

3 Match the rear connections

Pull off the CO2 and TAP shipping caps.

Fittings stay in place. Open ports shown below.



- CO2** Red / cylinder
- SODA** Blue / faucet
- TAP** White / filter
- FLAVOR** Black / either port


Click into the square jack.

Push every tube fully home (a little over 1/2 in), then tug gently. Either black tube fits either FLAVOR port.

Lay the filter flat. Keep long tubes in easy, coiled curves.

TURN IT ON

4 Prepare the cylinder




Have the cylinder shop fit and leak-check the regulator and gray tether connector. Keep the two gray fittings assembled.

Leak or continuing hiss? Close water and cylinder; get help.


5 Water, then gas, then power

1 WATER




Open the water shutoff **slowly**. Watch every water joint for a **full minute**.

2 GAS



Open the **cylinder valve** and **small knob**. Use the **big knob** to set the upper needle in **green**. Check the gray connector and red CO2 port for leaks **before power**.

3 POWER



Seat the cord in the **top-left rear socket**. Plug into grounded 120 V. **It chimes**.


YOUR FIRST GLASS

6 Fill both flavors

On the enclosure display, choose **FILL** and select a flavor.

Invert one whole **14.8 fl oz bottle** into the funnel. Then press **START FILL**.

Wait for Filled. Repeat for the second flavor.



7 Chill. Choose. Pour.

FIRST CHILL: ABOUT 1 HOUR

Choose: tap the faucet display to select a flavor. A dim screen takes one tap to wake.

Pour: place a glass under the faucet and press the lever. Release it to stop.

