Household R-600a / exterior disposal warning

FULL-SIZE FIT PROOF / US LETTER / PRINT AT 100%, ACTUAL SIZE

Exterior / disposal / 190 x 71 mm / 6.5 mm body capitals


CAUTION

RISK OF FIRE OR EXPLOSION. DISPOSE OF PROPERLY IN ACCORDANCE WITH THE APPLICABLE FEDERAL OR LOCAL REGULATIONS. FLAMMABLE REFRIGERANT USED.

Placement: on the outside of the enclosure; a rear or side face can carry this label.
This warning does not need to occupy the brand / serial / QR nameplate.
Wording: UL 60335-2-24 (2017), 7.1DV.4.1(d). Body capitals: at least 6.4 mm.

Separate appliance information: manufacturer / model, voltage, AC frequency, rated current, manufacturing date or date code, R-600a, actual charge in grams, and foam blowing-agent ID.
Use established unit values. The study text 5A / 600W is not a measured appliance rating.

The disposal warning plus the service panel on page 2 cover the four applicable messages.
The enclosed, foam-embedded evaporator has no user-contact defrost-warning location.
No commercial storage paragraph, packaging paragraph, or A3 diamond is specified here.



50 mm at actual size. Do not use Fit or Shrink to page.

Household design specification. Paper is a fit template; use permanent production markings.
EPA Rule 22 / UL 60335-2-24 (April 28, 2017). Sources: hardware/markings/README.md.

Household R-600a / compressor compartment

FULL-SIZE FIT PROOF / US LETTER / PRINT AT 100%, ACTUAL SIZE

Compressor compartment / service and tubing / 190 x 163 mm / 6.5 mm body capitals

DANGER



R-600a

**RISK OF FIRE OR EXPLOSION DUE TO PUNCTURE OF REFRIGERANT TUBING.
FLAMMABLE REFRIGERANT USED.
TO BE REPAIRED ONLY BY TRAINED SERVICE PERSONNEL.
DO NOT PUNCTURE REFRIGERANT TUBING.
CONSULT REPAIR MANUAL/OWNER'S GUIDE BEFORE ATTEMPTING TO SERVICE THIS PRODUCT.
ALL SAFETY PRECAUTIONS MUST BE FOLLOWED.
FOLLOW HANDLING INSTRUCTIONS CAREFULLY.**

Place near the compressor compartment and its exposed tubing, visible on gaining access.
Combined equivalent wording for 7.1DV.4.1(b), (c), (e); all instructions retained.
ISO 7010 W021 triangle: 18 mm high. R-600a identification visible at compressor access.
Service-opening locations: PMS 185 red; process tube red at least 25 mm from compressor.

50 mm at actual size. Do not use Fit or Shrink to page.

Household design specification. Paper is a fit template; use permanent production markings.
EPA Rule 22 / UL 60335-2-24 (April 28, 2017). Sources: hardware/markings/README.md.