

Harness RFQ

Ten low-voltage cable assemblies for a domestic kitchen appliance (a countertop soda dispenser), currently at prototype. Every assembly lands on a controller PCB at one end and on a valve, motor, sensor or display at the other. This document is the complete build package: materials, workmanship, board-side contact order, and a pin-level wire list for each of the ten.

Nothing here is proprietary; ask about anything that is ambiguous rather than assuming.

Scope

In: ten assemblies — J1, J2, J3, J4, J5, J6, J7, J9, J11, J13.

Out: the J10 12 V inlet (2 × 16 AWG, ferrules, on-shelf) and every AC mains run (AC-1...6, 16 AWG + 18 AWG SJOOW), built in place per `wiring.md`.

Everything in this RFQ is 22 AWG or 28 AWG.

The WAGO fan-outs are built in-house

The five branch nodes in the table below are **excluded from the quote**. A vendor supplies each affected assembly as its trunk only — every board-side conductor run to its full length and terminated at the device end — and the lever nut and its branch legs are made off here. A 221 lever nut takes no crimp and no tooling, and on the one assembly priced both ways the fan-out was 45 % of the assembled cost.

So: quote the wire lists below as written, and ignore the `— ... branch` rows.

Build quantity

Quote **25, 50, and 100 sets** (a set = all ten assemblies).

Workmanship standard

IPC/WHMA-A-620, Class 2. Every assembly 100% continuity- and isolation-tested pin-to-pin against its wire list below, including the deliberate non-connection at J2 contact 3.

Materials

Item	Spec	Notes
Signal / actuator wire	22 AWG stranded tinned-copper silicone , 600 V, black	all ten assemblies except J3 — see Open question 1, the gauge is not settled
Ribbon	28 AWG 4-conductor jacketed ribbon, black	J3 only
Board-end housings	JST XH , 2.5 mm pitch, female crimp housing + contacts	XHP- <i>n</i> per assembly; "XH2.54" is the series name, the pitch is 2.50 mm
Device-end tabs	Female Faston disconnects, 6.3 mm and 4.8 mm	at 20–24 AWG these are TE 2178438-1 (250 / 6.3 mm) and 170214-2 (187 / 4.8 mm); per-device size map not yet recorded
Screw landings	Insulated bootlace ferrules, DIN, 22 AWG	J5 relay terminals, J9 display terminals
Fan-out splices	WAGO 221-420 (10-way) and 221-415 (5-way)	supplied loose or made off, see below
Sleeve		both cut ends finished with black heat-shrink

Item	Spec	Notes
	Black PET expandable braided, 1/4" / 1/2" / 3/4" per assembly	
Ties	Black UV-nylon, flush-cut, no proud tail	

Every conductor is black. Identification is **by assembly name at the housing** (heat-shrink marker), not per-conductor. Do not substitute a color code.

The WAGO fan-outs are in-assembly splices

Five assemblies terminate a shared rail in a WAGO 221 lever nut at the **device end**, not at the board: one rail conductor rides the trunk and explodes at the manifold or reservoir. The nut body press-fits into a well printed in the enclosure wall. Do not substitute heat-shrink butt splices.

Assembly	Nut	Ways used	Feed	Branches
J1 MANIFOLD A	221-420	9 of 10	COM	8 valve +
J2 MANIFOLD B	221-415	5 of 5	COM	V-I, V-J, fan, V-K +
J4 SENSORS	221-415	4 of 5	GND	1-wire bus, flow meter, moisture plate
J6 REEDS A	221-415	5 of 5	GND	4 reeds
J7 REEDS B	221-420	7 of 10	GND	6 reeds

Board-end contact order

Read contact order from this table, not from conductor names elsewhere. Two connectors are numbered opposite to how their signals read: J1 runs OUT8 → COM, and J6 runs GND, RA4 ... RA1. Contact 1 is the pin-1 end of the housing.

Conn.	Housing	1	2	3	4	5	6	7	8	9
J1 MANIFOLD A	XHP-9	OUT8	OUT7	OUT6	OUT5	OUT4	OUT3	OUT2	OUT1	COM
J2 MANIFOLD B	XHP-6	COM	FAN	empty	OUT3	OUT2	OUT1			
J3 FAUCET	XHP-4	GND	V5	I035	I033					
J4 SENSORS	XHP-7	3V3	GND	V5	I025	I026	I027	I023		
J5 RELAYS	XHP-4	GND	V5	I02	I019					
J6 REEDS A	XHP-5	GND	RA4	RA3	RA2	RA1				
J7 REEDS B	XHP-7	RB1	RB2	RB3	RB4	CL0	CHI	GND		
J9 DISPLAY	XHP-4	B	A	GND	V12					
J11 GAS	XHP-4	GND	V5	D0UT	A0UT					
J13 PUMPS	XHP-4	AM2	AM1	BM2	BM1					

J2 contact 3 is deliberately empty

J2's wafer is 6-way; only five conductors are populated. OUT4 is a routed spare that drives no valve. **Crimp five contacts into an XHP-6 in their labelled positions and leave contact 3 empty. Do not close the gap.** Contact 3 is mid-housing, not on an end — a loom filling 1–5 consecutively lands every conductor one position off, which puts the shared 12 V rail on a driver output. Verify the empty cavity at final test.

J4 and J7 share a housing

Both are XHP-7. A swap would put J4's 3V3 / V5 onto J7's reed inputs. **Label both at the housing.**

Wire lists

Lengths are conductor cut lengths from the board contact to the device termination, service loop excluded — add your standard allowance. They are design targets from the enclosure layout, not yet measured against a built enclosure.

J1 — MANIFOLD A · XHP-9 · 3/4" sleeve

Contact	Signal	To	Length	Termination
1–8	OUT8 ... OUT1	valves V-H...V-A, one each	~450 mm	female Faston
9	COM	221-420 at the manifold	~300 mm	ferrule
—	8 × COM branch	221-420 → each valve +	~150 mm	ferrule / female Faston

Trunk is 300 mm to the manifold, then a 150 mm fan-out per valve. Low-side switching: COM carries shared 12 V to every valve + ; each valve – returns on its own OUT .

J2 — MANIFOLD B · XHP-6, 5 populated · 1/2" sleeve

Contact	Signal	To	Length	Termination
1	COM	221-415 at the manifold	~300 mm	ferrule
2	FAN	condenser fan –	~400 mm	female Faston
3	—	empty, do not populate	—	—
4	OUT3	valve V-K – at the aft strip	~500 mm	female Faston
5	OUT2	valve V-J –	~450 mm	female Faston
6	OUT1	valve V-I –	~450 mm	female Faston
—	4 × COM branch	221-415 → V-I, V-J, fan, V-K	150 / 150 / 100 / 200 mm	ferrule / female Faston

All four branches leave the 221-415 at the manifold, 300 mm along the trunk.

J3 — FAUCET · XHP-4 · 28 AWG 4-conductor ribbon

Contact	Signal	To	Length	Termination
1	GND	faucet display GND	~1 m	per display, see Open questions
2	V5	faucet display 5 V	~1 m	"
3	I035	display TX	~1 m	"
4	I033	display RX	~1 m	"

Straight-through 4-conductor ribbon up the umbilical, no branch. TTL UART; ESD clamping is on the board, so no cable-end component is required.

J4 — SENSORS · XHP-7 · 1/4" sleeve · three-way branch

Contact	Signal	To	Length	Termination
1	3V3	1-wire temp bus	~600 mm	per device
2	GND	221-415 on the –X wall aft	~600 mm	ferrule

Contact	Signal	To	Length	Termination
3	V5	flow meter	~150 mm	per device
4	I025	flow meter pulse	~150 mm	per device
5	I026	1-wire data	~600 mm	per device
6	I027	moisture sensor DO	~600 mm	per device
7	I023	moisture sensor switched VCC	~600 mm	per device
—	3 × GND branch	221-415 → 1-wire, flow meter, moisture	short pigtails	ferrule

The flow-meter leg (contacts 3, 4) leaves the trunk at ~150 mm; the other two legs run on to ~600 mm.

J5 — RELAYS · XHP-4 · 1/4" sleeve

Contact	Signal	To	Length	Termination
1	GND	relay #1 and #2 GND	~150 mm	ferrule, teed to both
2	V5	relay #1 and #2 VCC	~150 mm	ferrule, teed to both
3	I02	relay #2 IN	~150 mm	ferrule
4	I019	relay #1 IN	~150 mm	ferrule

V5 and GND tee at the relay screw terminals — **no WAGO on this assembly.**

J6 — REEDS A · XHP-5 · 1/4" sleeve

Contact	Signal	To	Length	Termination
1	GND	221-415 at reservoir A	~600 mm	ferrule
2–5	RA4 ... RA1	reservoir A level reeds 4...1	~600 mm	reed leads
—	4 × GND branch	221-415 → each reed	short pigtails	ferrule

Note the reversed order: contact 2 is RA4 , contact 5 is RA1 .

J7 — REEDS B · XHP-7 · 1/4" sleeve

Contact	Signal	To	Length	Termination
1–4	RB1 ... RB4	reservoir B level reeds 1...4	~600 mm	reed leads
5	CL0	carbonator low reed	~600 mm	reed leads
6	CHI	carbonator high reed	~600 mm	reed leads
7	GND	221-420 at the cold-core end	~600 mm	ferrule
—	6 × GND branch	221-420 → each reed	short pigtails	ferrule

Same XHP-7 as J4 — label at the housing.

J9 — DISPLAY · XHP-4 · 1/2" sleeve

Contact	Signal	To	Length	Termination
1	B	display RS485 B	~1 m	ferrule
2	A	display RS485 A	~1 m	ferrule

Contact	Signal	To	Length	Termination
3	GND	display 7–36 V input GND	~1 m	ferrule
4	V12	display 7–36 V input +	~1 m	ferrule

A and **B** twisted pair over the run; V12 / GND ride the same sleeve.

J11 — GAS · XHP-4 · 1/4" sleeve

Contact	Signal	To	Length	Termination
1	GND	MQ-6 GND	~600 mm	per device
2	V5	MQ-6 VCC	~600 mm	per device
3	DOUT	MQ-6 digital trip	~600 mm	per device
4	AOUT	MQ-6 analog	~600 mm	per device

Straight-through, no branch.

J13 — PUMPS · XHP-4 · 1/2" sleeve

Contact	Signal	To	Length	Termination
1	AM2	pump A motor tab 2	~400 mm	female Faston
2	AM1	pump A motor tab 1	~400 mm	female Faston
3	BM2	pump B motor tab 2	~400 mm	female Faston
4	BM1	pump B motor tab 1	~400 mm	female Faston

Two differential H-bridge pairs, no shared rail and no fan-out. The pumps ride a cartridge that withdraws from the enclosure, so these four run **unbroken** from housing to motor tab, and the length must hold with the cartridge drawn fully out — do not shorten.

Open questions for the vendor

- Wire gauge into the XH housings — open, and we want your read.** The schedule says 22 AWG silicone. 22 AWG silicone does not pass crimp-compatibility checks into JST XH: the XH contact's 22–30 AWG rating is a conductor rating, and silicone's insulation OD at 22 AWG is over what the barrel closes on. The same 22 AWG passes into XH in UL 1007, UL 1015, UL 1061 and ThermoThin, and silicone passes into XH from 24 AWG down. **Please quote the option you would actually build**, from: (a) 24 AWG silicone on the XH looms, (b) 22 AWG thin-wall (UL 1061 or similar), (c) 22 AWG silicone with a different board-side connector family. Current draw on these looms is negligible except MANIFOLD A COM, which carries $\leq \sim 1.4$ A over ~ 300 mm.
- Faston sizes.** `cable-assemblies.md` calls for both 6.3 mm and 4.8 mm disconnects; the per-device map is not yet recorded. Quote against a stated assumption and we will confirm before release.
- WAGO nuts — supplied or made off?** Preference is made off as part of the assembly. If your process cannot land a lever nut in-line, quote with the nut supplied loose and the branch conductors ferruled to length.
- Device-end terminations on J3, J4, J11.** Sensor and display leads land per device rather than on a standard terminal. Quote these as flying leads, tinned and ferruled, unless you would rather we specify a mating connector.
- 28 AWG ribbon.** Confirm you can crimp XH contacts onto 28 AWG, or propose the gauge you would rather run in the umbilical.

What we need back

1. **Unit price at 25, 50 and 100 sets**, and any NRE / setup charged per assembly design.
2. **Lead time** for the first article and for a production run.
3. **Your answer to Open question 1** — the wire gauge into the JST XH housings. This is the one open engineering item and we would rather take your recommendation than impose ours.
4. Whether you will build to **IPC/WHMA-A-620 Class 2** and provide continuity + isolation test records per assembly.
5. Anything in the wire lists you would change to make the part cheaper or more manufacturable.

We are quoting several suppliers on the identical package.