ENVIRONMENT — EP-AGENT-001

ENVIRONMENT — EP-AGENT-001

Version: v0.3.5-DRAFT (2026-10-16). Version history: HISTORICAL / SUPERSEDED (end of file) and `CHANGELOG.md`.

```
DESIGN:                          COMPLETE
EXECUTIONPROOF PIN:              PASS
Q9:                              PASSED
Q8 TECHNICAL FREEZE READINESS: PASS
Q8 FORMAL:                       OPEN — REQUIRES DEREK APPROVAL + PREREGISTRATION FILING
PREREGISTRATION:                 NOT FILED
EXPERIMENT:                      NOT EXECUTED
RESULTS:                         NONE
EXECUTION:                       NOT AUTHORIZED
```

Items marked TO PIN AT FREEZE must be filled in before the preregistration SHA-256 lock.

Item	**Specification**
Target OS	Linux (Ubuntu 22.04 LTS or later) or macOS 14+
CPU	x86_64 or arm64 (exact model recorded in results)
GPU	Not required
Python	3.11.x (locks generated/verified on CPython 3.11.6; exact patch recorded per run)
Package manager	pip, one venv per framework, installs from `requirements.lock`
Lockfile	`requirements.lock` (index) + `locks/<fw>.lock` — exact pins with sha256 artifact hashes; verified in clean venvs 2026-10-15 (`scripts/setup/generate_and_verify_locks.sh`). SHA-256s in `MANIFEST.sha256`
OpenAI Agents SDK	`openai-agents==0.24.0`
LangGraph	`langgraph==1.2.15`
CrewAI	`crewai==1.15.28`
Microsoft Agent Framework	`agent-framework==1.22.0`
ExecutionProof	**PINNED (v0.3.3; checklist item 7 PASS)** — ExecutionProof Controlled Reference Verifier, tag `v0.1.2-reference`, commit `b03365d57880e896c35e72898f8335a1826afe74`, API `0.1.2-reference`, ProofRecord schema 2, verifier `MANIFEST.sha256` `e53564589c4baeaca7bb1e26277c79abcb3f9e012b2f17fb26be19005e11eb69`. Runnable / Reference / Production: YES / YES / NO. Adoption as system under test via PREREGISTRATION §18 amendment (DRAFT, NOT FILED). See `EXECUTIONPROOF_PIN.md`.
Study evidence registry hash	`fixtures/evidence/study_evidence_registry.json` sha256 `b4a84f293182cd299b9168f3d38f3fc8f00e56c6bc89bcfa74a6385a490747d0` (schema `ep-evidence-registry/1`, version 1, 2 VERIFIED records)
Adapter commit	The packet commit labelled FINAL PRE-FILING CANDIDATE LOCK (v0.3) — real adapters in `adapters/*/adapter.py` + `binding.py`
Fixture policy configuration hash	`fixtures/policy/fixture_policy_config.json` sha256 `06b5a7ab68696d4d246f7b07f698437ec5713fa1da1113f553a02e04777649d4` (shared rules identical across B1–B5; per-fixture `evidence_records` stay in fixtures but are not read by the pinned verifier — run-time evidence status comes only from the study evidence registry, v0.3.3)
Test fixture hashes	Recorded in `MANIFEST.sha256` (unchanged since v0.2)

Item	Specification
Expected-results hash	EXPECTED_RESULTS.json sha256 af7ea17a34568dd42d01111dd5628ab71003da0b3656e2ee465efb6e016872d9
Harness self-test baseline	Python 3.11.6 on Linux (design environment, 2026-10-15); framework packages not installed in the harness environment
Engineering compatibility check	2026-10-15: each pinned framework (and google-adk 2.12.0, an eligible future extension NOT included in v1) installed in an isolated venv outside the packet and its integration symbols imported — see ENGINEERING_COMPATIBILITY_CHECK.md. NOT an experimental run; no fixture consumed

Environment variables (non-secret only)

Variable	Example	Purpose
EP_BASE_URL	(no default — must be supplied)	ExecutionProof base URL; adapters refuse without it
EP_VERIFY_PATH	/verify (matches pinned verifier POST /verify)	Verify path appended to EP_BASE_URL
EP_POLICY_CONFIG	absolute path to fixtures/policy/fixture_policy_config.json	Verifier-side; study policy, fail-closed
EP_EVIDENCE_REGISTRY	absolute path to fixtures/evidence/study_evidence_registry.json	Verifier-side; study evidence registry, fail-closed
EP_TENANT_ID	ep-agent-001-test	Tenant scope written into contracts
EP_AGENT_001_OUTPUT_DIR	results/	Output location (authorized runs only)
EP_AGENT_001_SEED	20261015 (frozen v0.3)	Framework-order randomization and bootstrap seed

No secrets in environment variables, code, fixtures, or logs. If a framework requires a model API key to initialize, a deterministic stub model is used instead where possible; if a real key is unavoidable it is a sandbox key with no production access, supplied at runtime, never committed, and its use is approved by Derek Hone in advance.

Hard constraints

- No production credentials.
- No live customer systems.
- Mock / sandbox / local downstream effects only (mock-external-endpoint, mock-account-001).
- No real payments, no real external submissions, no production APIs.
- Cloud ExecutionProof endpoints require Derek Hone's approval before use.

Verification at run time

scripts/setup/check_versions.py must report PASS for every framework in its venv; output is preserved with the run record.

HISTORICAL / SUPERSEDED

Retained in chronological order (Rule 11). None of this is current status.

- v0.2 (2026-10-15): document version v0.2-DRAFT.
- v0.3 (2026-10-15): ExecutionProof row — **BLOCKED — DEREK CONFIRMATION REQUIRED** (implementation repo/commit/path not accessible; see EXECUTIONPROOF_PIN.md). EP_VERIFY_PATH — /verify (packet default; pending Derek confirmation).

- v0.3.3 (2026-10-16): ExecutionProof pinned at `v0.1.2-reference` @ `b03365d5`; checklist item 7 PASS.
- v0.3.4 (2026-10-16): ExecutionProof row synced to the v0.3.3 pin (superseded values kept inline).