

lecture_07

February 6, 2017

```
In [25]: %plot --format svg
```

```
In [30]: setdefaults
```

1 Roots: Open methods

1.1 Newton-Raphson

First-order approximation for the location of the root (i.e. assume the slope at the given point is constant, what is the solution when $f(x)=0$)

$$f'(x_i) = \frac{f(x_i)-0}{x_i-x_{i+1}}$$

$$x_{i+1} = x_i - \frac{f(x_i)}{f'(x_i)}$$

Use Newton-Raphson to find solution when $e^x = x$

```
In [1]: f= @(x) exp(-x)-x;
        df= @(x) -exp(-x)-1;
```

```
        x_i= 0;
        c
        error_approx = abs((x_r-x_i)/x_r)
        x_i=x_r;
```

```
error: 'c' undefined near line 1 column 1
error: 'x_r' undefined near line 1 column 21
error: evaluating argument list element number 1
error: 'x_r' undefined near line 1 column 5
```

```
In [2]: x_r = x_i-f(x_i)/df(x_i)
        error_approx = abs((x_r-x_i)/x_r)
        x_i=x_r;
```

```
x_r = 0.50000
error_approx = 1
```

```
In [3]: x_r = x_i-f(x_i)/df(x_i)
        error_approx = abs((x_r-x_i)/x_r)
        x_i=x_r;
```

```
x_r = 0.56631
error_approx = 0.11709
```

```
In [4]: x_r = x_i-f(x_i)/df(x_i)
        error_approx = abs((x_r-x_i)/x_r)
        x_i=x_r;
```

```
x_r = 0.56714
error_approx = 0.0014673
```

In the bungee jumper example, we created a function $f(m)$ that when $f(m)=0$, then the mass had been chosen such that at $t=4$ s, the velocity is 36 m/s.

$$f(m) = \sqrt{\frac{gm}{c_d}} \tanh\left(\sqrt{\frac{gc_d}{m}}t\right) - v(t).$$

to use the Newton-Raphson method, we need the derivative $\frac{df}{dm}$

$$\frac{df}{dm} = \frac{1}{2} \sqrt{\frac{g}{mc_d}} \tanh\left(\sqrt{\frac{gc_d}{m}}t\right) - \frac{g}{2m} \operatorname{sech}^2\left(\sqrt{\frac{gc_d}{m}}t\right)$$

```
In [6]: setdefaults
        g=9.81; % acceleration due to gravity
        m=linspace(50, 200,100); % possible values for mass 50 to 200 kg
        c_d=0.25; % drag coefficient
        t=4; % at time = 4 seconds
        v=36; % speed must be 36 m/s
        f_m = @(m) sqrt(g*m/c_d).*tanh(sqrt(g*c_d./m)*t)-v; % anonymous function f_m
        df_m = @(m) 1/2*sqrt(g./m/c_d).*tanh(sqrt(g*c_d./m)*t)-g/2./m*sech(sqrt(g*c_d./m)*t).^2;
```

```
In [7]: newtraph(f_m,df_m,140,0.00001)
```

```
ans = 142.74
```

1.2 Secant Methods

Not always able to evaluate the derivative. Approximation of derivative:

$$f'(x_i) = \frac{f(x_{i-1})-f(x_i)}{x_{i-1}-x_i}$$

$$x_{i+1} = x_i - \frac{f(x_i)}{f'(x_i)}$$

$$x_{i+1} = x_i - \frac{f(x_i)}{\frac{f(x_{i-1})-f(x_i)}{x_{i-1}-x_i}} = x_i - \frac{f(x_i)(x_{i-1}-x_i)}{f(x_{i-1})-f(x_i)}$$

What values should x_i and x_{i-1} take?

To reduce arbitrary selection of variables, use the

1.3 Modified Secant method

Change the x evaluations to a perturbation δ .

$$x_{i+1} = x_i - \frac{f(x_i)(\delta x_i)}{f(x_i+\delta x_i)-f(x_i)}$$


```
In [8]: mod_secant(f_m,1e-6,50,0.00001)
```

```
ans = 142.74
```

```
In [32]: Amt_numerical=mod_secant(@(A) car_payments(A,30000,0.05,5),1e-6,50,0.001)
        car_payments(Amt,30000,0.05,5)
```

```
Amt_numerical = 563.79
```

```
ans = -160.42
```



```
In [23]: Amt*12*5
```

```
ans = 3.3968e+04
```

Amortization calculation makes the same calculation for the monthly payment amount, A , paying off the principle amount, P , over n pay periods with monthly interest rate, r .

```
In [27]: % Amortization calculation
```

```
A = @(P,r,n) P*(r*(1+r)^n)/((1+r)^n-1);
```

```
Amt=A(30000,0.05/12,5*12)
```

```
Amt = 566.14
```

1.4 Matlab's function

Matlab and Octave combine bracketing and open methods in the `fzero` function.

In [33]: `help fzero`

'fzero' is a function from the file `/usr/share/octave/4.0.0/m/optimization/fzero.m`

```
-- Function File: fzero (FUN, X0)
-- Function File: fzero (FUN, X0, OPTIONS)
-- Function File: [X, FVAL, INFO, OUTPUT] = fzero (...)
    Find a zero of a univariate function.
```

FUN is a function handle, inline function, or string containing the name of the function to evaluate.

X0 should be a two-element vector specifying two points which bracket a zero. In other words, there must be a change in sign of the function between X0(1) and X0(2). More mathematically, the following must hold

$$\text{sign}(\text{FUN}(\text{X0}(1))) * \text{sign}(\text{FUN}(\text{X0}(2))) \leq 0$$

If X0 is a single scalar then several nearby and distant values are probed in an attempt to obtain a valid bracketing. If this is not successful, the function fails.

OPTIONS is a structure specifying additional options. Currently, 'fzero' recognizes these options: "FunValCheck", "OutputFcn", "TolX", "MaxIter", "MaxFunEvals". For a description of these options, see `*note optimset: XREFoptimset`.

On exit, the function returns X, the approximate zero point and FVAL, the function value thereof.

INFO is an exit flag that can have these values:

- * 1 The algorithm converged to a solution.
- * 0 Maximum number of iterations or function evaluations has been reached.
- * -1 The algorithm has been terminated from user output function.
- * -5 The algorithm may have converged to a singular point.

OUTPUT is a structure containing runtime information about the 'fzero' algorithm. Fields in the structure are:

- * iterations Number of iterations through loop.
- * nfev Number of function evaluations.
- * bracketx A two-element vector with the final bracketing of the zero along the x-axis.
- * brackety A two-element vector with the final bracketing of the zero along the y-axis.

See also: `optimset`, `fsolve`.

Additional help for built-in functions and operators is available in the online version of the manual. Use the command `'doc <topic>'` to search the manual index.

Help and information about Octave is also available on the WWW at <http://www.octave.org> and via the help@octave.org mailing list.

```
In [40]: fzero(@(A) car_payments(A,30000,0.05,5,0),500)
```

```
ans = 563.79
```

1.5 Comparison of Solvers


It's helpful to compare to the convergence of different routines to see how quickly you find a solution.

Comparing the freefall example

```
In [84]: N=20;
iterations = linspace(1,400,N);
ea_nr=zeros(1,N); % appr error Newton-Raphson
ea_ms=zeros(1,N); % appr error Modified Secant
ea_fp=zeros(1,N); % appr error false point method
ea_bs=zeros(1,N); % appr error bisect method
for i=1:length(iterations)
    [root_nr,ea_nr(i),iter_nr]=newtraph(f_m,df_m,200,0,iterations(i));
    [root_ms,ea_ms(i),iter_ms]=mod_secant(f_m,1e-6,300,0,iterations(i));
    [root_fp,ea_fp(i),iter_fp]=falsepos(f_m,1,300,0,iterations(i));
    [root_bs,ea_bs(i),iter_bs]=bisect(f_m,1,300,0,iterations(i));
end

semilogy(iterations,abs(ea_nr),iterations,abs(ea_ms),iterations,abs(ea_fp),iterations,abs(ea_bs))
legend('newton-raphson','mod-secant','false point','bisection')
```

```
warning: axis: omitting non-positive data in log plot
warning: called from
  __line__ at line 120 column 16
  line at line 56 column 8
  __plt__>__plt2vv__ at line 500 column 10
  __plt__>__plt2__ at line 246 column 14
  __plt__ at line 133 column 15
  semilogy at line 60 column 10
warning: axis: omitting non-positive data in log plot
warning: axis: omitting non-positive data in log plot
warning: axis: omitting non-positive data in log plot
```



```
In [75]: ea_ms
```

```
ea_ms =
```

```
Columns 1 through 7:
```

```
43.43883    0.00000    0.00000    0.00000    0.00000    0.00000    0.00000
```

Columns 8 through 14:

0.00000 0.00000 0.00000 0.00000 0.00000 0.00000 0.00000


Columns 15 through 20:

0.00000 0.00000 0.00000 0.00000 0.00000 0.00000

```
In [101]: N=20;
          f=@(x) x^10-1;
          df=@(x) 10*x^9;
          iterations = linspace(1,50,N);
          ea_nr=zeros(1,N); % appr error Newton-Raphson
          ea_ms=zeros(1,N); % appr error Modified Secant
          ea_fp=zeros(1,N); % appr error false point method
          ea_bs=zeros(1,N); % appr error bisect method
          for i=1:length(iterations)
              [root_nr,ea_nr(i),iter_nr]=newtraph(f,df,0.5,0,iterations(i));
              [root_ms,ea_ms(i),iter_ms]=mod_secant(f,1e-6,0.5,0,iterations(i));
              [root_fp,ea_fp(i),iter_fp]=falsepos(f,0,5,0,iterations(i));
              [root_bs,ea_bs(i),iter_bs]=bisect(f,0,5,0,iterations(i));
          end

          semilogy(iterations,abs(ea_nr),iterations,abs(ea_ms),iterations,abs(ea_fp),iterations,
          legend('newton-raphson','mod-secant','false point','bisection'))

warning: axis: omitting non-positive data in log plot
warning: called from
    __line__ at line 120 column 16
    line at line 56 column 8
    __plt__>__plt2vv__ at line 500 column 10
    __plt__>__plt2__ at line 246 column 14
    __plt__ at line 133 column 15
    semilogy at line 60 column 10
warning: axis: omitting non-positive data in log plot
warning: axis: omitting non-positive data in log plot
warning: axis: omitting non-positive data in log plot
```



```
In [102]: ea_bs
          newtraph(f,df,0.5,0,12)
```

```
ea_bs =
```

```
Columns 1 through 6:
```

```
9.5357e+03 -4.7554e-01 -2.1114e-01 6.0163e-02 -2.4387e-03 6.1052e-04
```

```
Columns 7 through 12:
```

```
2.2891e-04 -9.5367e-06 2.3842e-06 8.9407e-07 -2.2352e-07 9.3132e-09
```

```
Columns 13 through 18:
```

```
-2.3283e-09 -8.7311e-10 3.6380e-11 -9.0949e-12 -3.4106e-12 8.5265e-13
```

```
Columns 19 and 20:
```

```
-3.5527e-14 8.8818e-15
```



```
ans = 16.208
```

```
In [93]: df(300)
```

```
ans = 1.9683e+23
```

```
In [ ]:
```