

Ant

Build Tool for Java

Overview

- ANT - Another Neat Tool
- A product of the Apache Software Foundation
- <https://ant.apache.org/>
- A Java application that can call the Java compiler
 - Requires JDK, not just JRE

Why not use make?

- Makefiles are based on shell commands
 - Shell commands are mostly platform dependent
- It is easy to introduce hidden errors into a Makefile

```
hello: main.o factorial.o hello.o
$(CC) main.o factorial.o hello.o -o hello
```

- Ex. A space before a tab before a command `$(CC)` invalidates the Makefile

Why Use Ant?

- Platform independence
 - Lots of predefined tasks implemented in Java
 - Hides platform-specific properties, ex path separators
- XML build scripts can be validated
- Ant can be extended (more platform independent tasks)

Preparing for Ant

- Prerequisites
 - JDK installed
 - JAVA_HOME environment variable set to JDK install folder (the folder that contains bin/, include/, lib/)

Downloading Ant

- Download from <https://ant.apache.org/bindownload.cgi>
- Two code bases: 1.9.x and 1.10.x
 - 1.9.x requires JDK 5
 - 1.10.x requires JDK 8

Installing Ant

- Unzip (untar) the downloaded archive to a folder of your choice (/tools in this tutorial).
- Create an environment variable called ANT_HOME
 - `export ANT_HOME=/tools/apache-ant-1.10.1`
- Add ant bin/ folder to your PATH environment variable
 - `export PATH=$PATH:$ANT_HOME/bin`
- Confirm installation:
 - `$ ant -version`

Example

build.xml

```
<?xml version="1.0"?>  
<project name="Hello" default="info">  
  <target name="info">  
    <echo>Hello, World</echo>  
  </target>  
</project>
```

\$ ant

info:

[echo] Hello, World

BUILD SUCCESSFUL

Total time: 0 seconds

\$

Command line options

- Ant looks for build.xml in the current directory
 - \$ ant [-f path to build script] [target]
- Other
 - \$ ant -help ant -h
 - \$ ant -projecthelp ant -p
 - \$ ant -version

build.xml (begin)

```
<?xml version="1.0"?>
<!--
    build.xml
    Ant script for CS364, Program #1

    David Apostol
-->
<project name="Hi-Low Guesser" default="compile" basedir=".">
    <!-- define properties to be used later -->
    <property name="src.dir" location="src" />
    <property name="build.dir" location="build" />
```

build.xml (middle)

```
<!-- delete existing directories (and contents) -->
<target name="clean" description="delete build artifacts">
    <delete dir="${build.dir}" />
</target>

<!-- create output directory -->
<target name="init">
    <mkdir dir="${build.dir}" />
</target>

<target name="compile"
    description="compile project source code"
    depends="clean, init">
    <javac srcdir="${src.dir}" destdir="${build.dir}" />
</target>
```

build.xml (end)

```
<target name="run-server" description="run the server" depends="compile">
  <java
    fork="true"
    failonerror="yes"
    classpath="${build.dir}"
    classname="hw1.GuessServer">
    <arg line="4444 10"/>
  </java>
</target>
```

```
<target name="run-client" description="run the client" depends="compile">
  <java
    fork="true"
    failonerror="yes"
    classpath="${build.dir}"
    classname="hw1.GuessClient">
    <arg line="localhost 4444"/>
  </java>
</target>
</project>
```