

# Documentation for Final Delivery

CSCI 465 – Fall 2020

Derek Trom, Elena Corpus

9 December 2020

# Table of Contents

1. Assumptions for Delivery 2 .....	2
2. Current Status.....	2
3. IO Module.....	2
4. Scanner.....	2
5. Parser.....	2
6. Symbol Table.....	2
7. Intermediate Code Generation/ Code Generator.....	3
8. Syntax.....	3-5

## **1. Assumptions for Delivery 2:**

- a. Compile the variable declarations (integer only, so no type checking)
- b. Handle simplified expressions
- c. Handle Assignment statements
- d. Handle I/O calls (at least for reading and writing numbers).

## **2. Current Status:**

- a. **IO Module:** Currently completed and up too standards in order to feed into scanner.
- b. **Scanner:** Can currently create lexemes for each feature in the requirements.
- c. **Parser:** The parser is recursive in nature with one (1) lookahead value, or LL(1). This means that the semantic analysis will have to be tightly coupled with the parser in the near future to allow for the confirmation of correctness.
- d. **Symbol Table:** Currently has linked-list and support for scopes.

## **3. IO Module:**

- a. Responsible for reading input the pascal file and writing output to the scanner.
- b. The IO Module reads from the file character by character and is able to put the character back into a file stream.
- c. This gets the lexemes from the scanner needed for the lexical analysis and receives errors from the classes for the Lexer.

## **4. Scanner:**

- a. Is responsible for the lexical analysis in the program.
- b. This scans the input from the IO module and translates the input into lexemes to be used by the parser.

## **5. Parser:**

- a. Using Flex and Bison as automated generators for lexical analysis and parsing will be used to verify the scanner and parser.
- b. In addition, the current parser generates an abstract syntax tree.

## **6. Symbol Table:**

- a. This keeps track of all the lexemes and its values.

- b. The parser is now able to add entries into the symbol table, with context, verify that there are no conflicting symbols, and create multiple levels of symbol tables for different blocks within the program, e.g. functions, procedures, etc.
- c. Print statements are shown for each entrance into a function call for proof of concept and its error messages as well.

## 7. Intermediate Code Generation / Code Generator:

- a. Now generates machine-dependent code
- b. Using the abstract syntax tree to generate the MIPS code

## 8. Syntax

start : program

program : PROGRAM ID SEMICOLON block PERIOD

block : constant-definition-part  
       /\*type-definition-part\*/  
       variable-declaration-part  
       procedure-and-function-declaration-part  
       statement-part

constant-definition-part : CONST constant-definition |  $\epsilon$

constant-definition : ID constant-definition-variable EQUALS  
 constant-no-id SEMICOLON constant-definition-recursive

constant-definition-variable : COMMA ID constant-definition-variable  
 |  $\epsilon$

constant-definition-recursive : constant-definition |  $\epsilon$

type-definition-part : TYPE type-definition |  $\epsilon$

type-definition : ID EQUALS type type-definition-recursive

type-definition-recursive : SEMICOLON type-definition |  $\epsilon$

variable-definition-part : VAR variable-declaration |  $\epsilon$

variable-definition : ID variable-definition-variable COLON  
 type SEMICOLON variable-definition-recursive |  $\epsilon$

variable-definition-variable : COMMA ID variable-definition-variable  
|  $\epsilon$

variable-definition-recursive : variable-definition |  $\epsilon$

type : simple-type /\*| array-type\*/

array-type : ARRAY LBRACK index-type RBRACK OF simple-type

index-type : ID | index-range

index-constant : sign INTVAL | CHARVAL | sign constant-name

index-range : index-constant DOTDOT index-constant

simple-type : STRING | INTEGER | REAL | CHAR

constant-name : ID

sign : ADD | MINUS |  $\epsilon$

procedure-and-function-definition-part : procedure-declaration  
SEMICOLON | function-declaration SEMICOLON |  $\epsilon$

procedure-declaration : PROCEDURE ID  
LPAREN formal-parameters RPAREN SEMICOLON  
block  
procedure-and-function-definition-part

formal-parameters : ID formal-parameters-variable COLON type

formal-parameters-variable : COMMA ID formal-parameters-variable |  $\epsilon$

function-declaration : FUNCTION ID  
LPAREN formal-parameters RPAREN  
COLON type SEMICOLON  
block  
procedure-and-function-declaration-part

statement-part : compound-statement

compound-statement : BEGIN statement statement-recursive SEMICOLON  
END

statement : simple-statement | structured-statement

statement-recursive : SEMICOLON statement statement-recursive |  $\epsilon$

simple-statement : assignment-statement | procedure-statement |  
application | read-statement | write-statement

assignment-statement : variable ASSIGN expression

procedure-statement : ID

application : ID LPAREN expression application-recursive  
RPAREN

application-recursive : COMMA expression application-recursive |  $\epsilon$

read-statement : READ read-statement-part | READLN read-  
statement-part

read-statement-part : LPAREN ID read-statement-recursive RPAREN

read-statement-recursive : COMMA ID read-statement-recursive |  $\epsilon$

write-statement : WRITE write-statement-part | WRITELN  
write-statement-part

write-statement-part : LPAREN expression write-statement-  
recursive RPAREN

write-statement-recursive : COMMA expression write-statement-recursive  
|  $\epsilon$

structured-statement : compound-statement | if-statement | while-  
statement | for-statement

if-statement : IF expression THEN statement if-statement-else

if-statement-else : ELSE statement |  $\epsilon$

while-statement : WHILE expression DO statement

for-statement : FOR ID ASSIGN expression for-statement-to  
expression DO statement

for-statement-to : TO | DOWNTWO

expression : simple-expression expression-relational

simple-expression	: sign term expression-add
expression-add	: add-term term expression-add   $\epsilon$
add-term	: ADD   MINUS   OR
term	: factor term-mult
term-mult	: mult-term factor term-mult   $\epsilon$
mult-term	: MULT   IDIV   DIV   AND
factor	: application   variable   constant   NOT factor
expression-relational	: relational-operator simple-expression   $\epsilon$
relational-operator	: EQ   NEQ   LT   LTE   GTE   GT
variable	: ID   ID LBRACK expression RBRACK
parameter-identifier	: ID
constant	: constant-no-id   sign constant-identifier
constant-no-id	: constant-number   sign constant-identifier
CHARVAL   STRINGVAL	
constant-number	: sign INTEGerno   sign REALNO
constant-identifier	: ID