Floating Point

15-213: Introduction to Computer Systems
4th Lecture, Sept. 8, 2016

Today's Instructor:

Randy Bryant

Correction from last time

Unsigned Multiplication in C

Operands: *w* bits

True Product: 2**w* bits

Discard *w* bits: *w* bits



- **Standard Multiplication Function**
  - Ignores high order *w* bits
- **Implements Modular Arithmetic**

  $\mathrm{UMult}_w(u\,,v) = u \cdot v \bmod 2^w$

	1110 1001	E9	223
*	1101 0101	* D5	* 213
	1100 0001 1101 1101	C1DD	47499
	1101 1101	DD	221

Signed Multiplication in C

Operands: *w* bits

True Product: 2**w* bits

Discard *w* bits: *w* bits



- **Standard Multiplication Function**
  - Ignores high order *w* bits
  - *Some of which are different for signed vs. unsigned multiplication*
  - Lower bits are the same

	1111 1111 1110 1001	E9	-23
*	1111 1111 1101 0101	* D5	* -43
	0000 0011 1101 1101	03DD	989
	1101 1101	DD	-35

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Fractional binary numbers

- What is 1011.101_2?

Fractional Binary Numbers



- Representation
  - Bits to right of “binary point” represent fractional powers of 2
  - Represents rational number:

$$\sum_{k=-j}^{i} b_k \times 2^k$$

Fractional Binary Numbers: Examples

- Value / Representation

Value		Representation	
5 3/4	= 23/4	`101.11`$_2$	= 4 + 1 + 1/2 + 1/4
2 7/8	= 23/8	`10.111`$_2$	= 2 + 1/2 + 1/4 + 1/8
1 7/16	= 23/16	`1.0111`$_2$	= 1 + 1/4 + 1/8 + 1/16

- Observations
  - Divide by 2 by shifting right (unsigned)
  - Multiply by 2 by shifting left
  - Numbers of form $0.111111\ldots_2$ are just below 1.0
    - $1/2 + 1/4 + 1/8 + \ldots + 1/2^i + \ldots \rightarrow 1.0$
    - Use notation $1.0 - \varepsilon$

Representable Numbers

- Limitation #1
  - Can only exactly represent numbers of the form $x/2^k$
    - Other rational numbers have repeating bit representations
  - Value Representation
    - 1/3 `0.0101010101[01]`$\ldots_2$
    - 1/5 `0.001100110011[0011]`$\ldots_2$
    - 1/10 `0.0001100110011[0011]`$\ldots_2$
- Limitation #2
  - Just one setting of binary point within the *w* bits
    - Limited range of numbers (very small values? very large?)

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

IEEE Floating Point

- IEEE Standard 754
  - Established in 1985 as uniform standard for floating point arithmetic
    - Before that, many idiosyncratic formats
  - Supported by all major CPUs
  - Some CPUs don't implement IEEE 754 in full
    e.g., early GPUs
- Driven by numerical concerns
  - Nice standards for rounding, overflow, underflow
  - Hard to make fast in hardware
    - Numerical analysts predominated over hardware designers in defining standard

Floating Point Representation

Example:
$15213_{10} = (-1)^0 \times 1.1101101101101_2 \times 2^{13}$

- Numerical Form:

$$(-1)^s\ M\ \ 2^E$$

  - Sign bit s determines whether number is negative or positive
  - Significand M normally a fractional value in range [1.0,2.0).
  - Exponent E weights value by power of two

- Encoding
  - MSB s is sign bit s
  - exp field encodes E (but is not equal to E)
  - frac field encodes M (but is not equal to M)

Precision options

- Single precision: 32 bits
  $\approx$ 7 decimal digits, $10^{\pm 38}$

- Double precision: 64 bits
  $\approx$ 16 decimal digits, $10^{\pm 308}$

- Other formats: half precision, quad precision

"Normalized" Values

$v = (-1)^s M\ 2^E$

- When: exp ≠ 000…0 and exp ≠ 111…1

- Exponent coded as a biased value: $E = Exp - Bias$
  - Exp: unsigned value of exp field
  - Bias = $2^{k-1} - 1$, where k is number of exponent bits
    - Single precision: 127 (Exp: 1…254, E: -126…127)
    - Double precision: 1023 (Exp: 1…2046, E: -1022…1023)

- Significand coded with implied leading 1: $M = 1.xxx…x_2$
  - xxx…x: bits of frac field
  - Minimum when frac=000…0 (M = 1.0)
  - Maximum when frac=111…1 (M = 2.0 – ε)
  - Get extra leading bit for "free"

Normalized Encoding Example

$v = (-1)^s \, M \, 2^E$
$E = Exp - Bias$

- **Value:** `float F = 15213.0;`
  - $15213_{10} = 11101101101101_2$
    $= 1.1101101101101_2 \times 2^{13}$

- **Significand**

  $M = 1.\underline{1101101101101}_2$

  $\texttt{frac} = \underline{1101101101101}0000000000_2$

- **Exponent**

  $E = 13$

  $Bias = 127$

  $Exp = 140 = 10001100_2$

- **Result:**

s	exp	frac
0	10001100	11011011011010000000000

Denormalized Values

$v = (-1)^s M 2^E$
$E = 1 - \text{Bias}$

- Condition: exp = 000…0

- Exponent value: E = 1 – Bias (instead of 0 – Bias)
- Significand coded with implied leading 0: $M = 0.xxx\ldots x_2$
  - `xxx…x`: bits of `frac`
- Cases
  - `exp` = **000…0**, `frac` = **000…0**
    - Represents zero value
    - Note distinct values: +0 and –0 (why?)
  - `exp` = **000…0**, `frac` ≠ **000…0**
    - Numbers closest to 0.0
    - Equispaced

Special Values

- Condition: `exp` = **111…1**

- Case: `exp` = **111…1**, `frac` = **000…0**
  - **Represents value ∞ (infinity)**
  - Operation that overflows
  - Both positive and negative
  - E.g., 1.0/0.0 = −1.0/−0.0 = +∞, 1.0/−0.0 = −∞

- Case: `exp` = **111…1**, `frac` ≠ **000…0**
  - **Not-a-Number (NaN)**
  - Represents case when no numeric value can be determined
  - E.g., sqrt(–1), ∞ − ∞, ∞ × 0

C float Decoding Example

$v = (-1)^s\ M\ 2^E$

$E\ =\ Exp - Bias$

float: **`0xC0A00000`**

Bias = $2^{k-1} - 1 = 127$

binary:



E = -> Exp = (decimal)

S =

M =

v = $(-1)^s$ M 2^E =

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

C float Decoding Example

$v = (-1)^s M\ 2^E$
$E = Exp - Bias$

float: **0xC0A00000**

binary: 1100 0000 1010 0000 0000 0000 0000 0000

1	1000 0001	010 0000 0000 0000 0000 0000
1	8-bits	23-bits

E = -> Exp = (decimal)

S =

M = 1 .

v = $(-1)^s$ M 2^E =

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

C float Decoding Example

$v = (-1)^s\ M\ 2^E$
$E = \text{Exp} - \text{Bias}$

float: **0xC0A00000**

Bias = $2^{k-1} - 1 = 127$

binary: 1100 0000 1010 0000 0000 0000 0000 0000

1	1000 0001	010 0000 0000 0000 0000 0000
1	8-bits	23-bits

E = 129 -> Exp = 129 – 127 = 2 (decimal)

S = 1 -> negative number

M = 1.010 0000 0000 0000 0000 0000

= 1 + 1/4 = 1.25

v = $(-1)^s$ M 2^E = $(-1)^1$ * 1.25 * 2^2 = -5

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

Visualization: Floating Point Encodings



Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Tiny Floating Point Example



- 8-bit Floating Point Representation
  - the sign bit is in the most significant bit
  - the next four bits are the exponent, with a bias of 7
  - the last three bits are the `frac`

- Same general form as IEEE Format
  - normalized, denormalized
  - representation of 0, NaN, infinity

Dynamic Range (Positive Only)

$v = (-1)^s M\ 2^E$
n: $E = \text{Exp} - \text{Bias}$
d: $E = 1 - \text{Bias}$

	s	exp	frac	E	Value	
Denormalized numbers	0	0000	000	-6	0	
	0	0000	001	-6	1/8*1/64 = 1/512	closest to zero
	0	0000	010	-6	2/8*1/64 = 2/512	(-1)^0(0+1/4)*2^-6
	…					
	0	0000	110	-6	6/8*1/64 = 6/512	
	0	0000	111	-6	7/8*1/64 = 7/512	largest denorm
Normalized numbers	0	0001	000	-6	8/8*1/64 = 8/512	smallest norm
	0	0001	001	-6	9/8*1/64 = 9/512	(-1)^0(1+1/8)*2^-6
	…					
	0	0110	110	-1	14/8*1/2 = 14/16	
	0	0110	111	-1	15/8*1/2 = 15/16	closest to 1 below
	0	0111	000	0	8/8*1 = 1	
	0	0111	001	0	9/8*1 = 9/8	closest to 1 above
	0	0111	010	0	10/8*1 = 10/8	
	…					
	0	1110	110	7	14/8*128 = 224	
	0	1110	111	7	15/8*128 = 240	largest norm
	0	1111	000	n/a	inf	

Distribution of Values

- 6-bit IEEE-like format
  - e = 3 exponent bits
  - f = 2 fraction bits
  - Bias is $2^{3-1}-1 = 3$



- Notice how the distribution gets denser toward zero.



Distribution of Values (close-up view)

- 6-bit IEEE-like format
  - e = 3 exponent bits
  - f = 2 fraction bits
  - Bias is 3





Special Properties of the IEEE Encoding

- FP Zero Same as Integer Zero
  - All bits = 0
- Can (Almost) Use Unsigned Integer Comparison
  - Must first compare sign bits
  - Must consider −0 = 0
  - NaNs problematic
    - Will be greater than any other values
    - What should comparison yield? The answer is complicated.
  - Otherwise OK
    - Denorm vs. normalized
    - Normalized vs. infinity

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Floating Point Operations: Basic Idea

- $x +_f y = \text{Round}(x + y)$

- $x \times_f y = \text{Round}(x \times y)$

- Basic idea
  - First compute exact result
  - Make it fit into desired precision
    - Possibly overflow if exponent too large
    - Possibly round to fit into `frac`

Rounding

- Rounding Modes (illustrate with $ rounding)

-

	$1.40	$1.60	$1.50	$2.50	–$1.50
Towards zero	$1 ↓	$1 ↓	$1 ↓	$2 ↓	–$1 ↑
Round down (−∞)	$1 ↓	$1 ↓	$1 ↓	$2 ↓	–$2 ↓
Round up (+∞)	$2 ↑	$2 ↑	$2 ↑	$3 ↑	–$1 ↑
Nearest Even (default)	$1 ↓	$2 ↑	$2 ↑	$2 ↓	–$2 ↓

Closer Look at Round-To-Even

- Default Rounding Mode
  - Hard to get any other kind without dropping into assembly
  - C99 has support for rounding mode management
  - All others are statistically biased
    - Sum of set of positive numbers will consistently be over- or under-estimated
- Applying to Other Decimal Places / Bit Positions
  - When exactly halfway between two possible values
    - Round so that least significant digit is even
  - E.g., round to nearest hundredth

7.8949999	7.89	(Less than half way)
7.8950001	7.90	(Greater than half way)
7.8950000	7.90	(Half way—round up)
7.8850000	7.88	(Half way—round down)

Rounding Binary Numbers

- Binary Fractional Numbers
  - "Even" when least significant bit is `0`
  - "Half way" when bits to right of rounding position = $100\ldots_2$

- Examples
  - Round to nearest 1/4 (2 bits right of binary point)

Value	Binary	Rounded	Action	Rounded Value
2 3/32	10.00011_2	10.00_2	(<1/2—down)	2
2 3/16	10.00110_2	10.01_2	(>1/2—up)	2 1/4
2 7/8	10.11100_2	11.00_2	(1/2—up)	3
2 5/8	10.10100_2	10.10_2	(1/2—down)	2 1/2

FP Multiplication

- $(-1)^{s1}$ M1 2^{E1} x $(-1)^{s2}$ M2 2^{E2}
- Exact Result: $(-1)^{s}$ M 2^{E}
  - Sign s: s1 ^ s2
  - Significand M: M1 x M2
  - Exponent E: E1 + E2
- Fixing
  - If M ≥ 2, shift M right, increment E
  - If E out of range, overflow
  - Round M to fit `frac` precision
- Implementation
  - Biggest chore is multiplying significands

4 bit mantissa: $1.010 * 2^{2} \times 1.110 * 2^{3} = 10.0011 * 2^{5}$

$= 1.00011 * 2^{6} = 1.001 * 2^{6}$

Floating Point Addition

- $(-1)^{s1}\ M1\ \ 2^{E1}\ \ +\ \ (-1)^{s2}\ M2\ \ 2^{E2}$
  - Assume E1 > E2
- Exact Result: $(-1)^{s}\ M\ \ 2^{E}$
  - Sign s, significand M:
    - Result of signed align & add
  - Exponent E: E1
- Fixing
  - If M ≥ 2, shift M right, increment E
  - if M < 1, shift M left k positions, decrement E by k
  - Overflow if E out of range
  - Round M to fit `frac` precision

Get binary points lined up



$$1.010*2^2 + 1.110*2^3 = (0.1010 + 1.1100)*2^3$$
$$= 10.0110 * 2^3 = 1.00110 * 2^4 = 1.010 * 2^4$$

Mathematical Properties of FP Add

- Compare to those of Abelian Group
  - Closed under addition? Yes
    - But may generate infinity or NaN
  - Commutative? Yes
  - Associative? No
    - Overflow and inexactness of rounding
    - `(3.14+1e10)-1e10 = 0, 3.14+(1e10-1e10) = 3.14`
  - 0 is additive identity? Yes
  - Every element has additive inverse? Almost
    - Yes, except for infinities & NaNs
- Monotonicity
  - $a \geq b \Rightarrow a+c \geq b+c$? Almost
    - Except for infinities & NaNs

Mathematical Properties of FP Mult

- Compare to Commutative Ring
  - Closed under multiplication? Yes
    - But may generate infinity or NaN
  - Multiplication Commutative? Yes
  - Multiplication is Associative? No
    - Possibility of overflow, inexactness of rounding
    - Ex: `(1e20*1e20)*1e-20= inf, 1e20*(1e20*1e-20)= 1e20`
  - 1 is multiplicative identity? Yes
  - Multiplication distributes over addition? No
    - Possibility of overflow, inexactness of rounding
    - `1e20*(1e20-1e20)= 0.0, 1e20*1e20 – 1e20*1e20 = NaN`
- Monotonicity
  - $a \geq b$ & $c \geq 0 \Rightarrow a * c \geq b * c$? Almost
    - Except for infinities & NaNs

Today: Floating Point

- Background: Fractional binary numbers
- IEEE floating point standard: Definition
- Example and properties
- Rounding, addition, multiplication
- Floating point in C
- Summary

Floating Point in C

- C Guarantees Two Levels
  - `float` single precision
  - `double` double precision
- Conversions/Casting
  - Casting between `int`, `float`, and `double` changes bit representation
  - `double`/`float` → `int`
    - Truncates fractional part
    - Like rounding toward zero
    - Not defined when out of range or NaN: Generally sets to TMin
  - `int` → `double`
    - Exact conversion, as long as `int` has ≤ 53 bit word size
  - `int` → `float`
    - Will round according to rounding mode

Floating Point Puzzles

- For each of the following C expressions, either:
  - Argue that it is true for all argument values
  - Explain why not true

```
int x = …;
float f = …;
double d = …;
```

Assume neither `d` nor `f` is NaN

- `x == (int)(float) x` ✗
- `x == (int)(double) x` ✓
- `f == (float)(double) f` ✓
- `d == (double)(float) d` ✗
- `f == -(-f);` ✓
- `2/3 == 2/3.0` ✗
- `d < 0.0     ⇒   ((d*2) < 0.0)` ✓
- `d > f       ⇒   -f > -d` ✓
- `d * d >= 0.0` ✓
- `(d+f)-d == f` ✗

Summary

- IEEE Floating Point has clear mathematical properties
- Represents numbers of form M x 2^E
- One can reason about operations independent of implementation
  - As if computed with perfect precision and then rounded
- Not the same as real arithmetic
  - Violates associativity/distributivity
  - Makes life difficult for compilers & serious numerical applications programmers



HOW ROUNDING WORKS

Creating Floating Point Number

s	exp	frac
1	4-bits	3-bits

- Steps
  - Normalize to have leading 1
  - Round to fit within fraction
  - Postnormalize to deal with effects of rounding

- Case Study
  - Convert 8-bit unsigned numbers to tiny floating point format

Example Numbers

`128`	`10000000`
`15`	`00001101`
`33`	`00010001`
`35`	`00010011`
`138`	`10001010`
`63`	`00111111`

Normalize



- Requirement
  - Set binary point so that numbers of form 1.xxxxx
  - Adjust all to have leading one
    - Decrement exponent as shift left

Value	Binary	Fraction	Exponent
`128`	`10000000`	`1.0000000`	`7`
`15`	`00001101`	`1.1010000`	`3`
`17`	`00010001`	`1.0001000`	`4`
`19`	`00010011`	`1.0011000`	`4`
`138`	`10001010`	`1.0001010`	`7`
`63`	`00111111`	`1.1111100`	`5`

Rounding

1.BBGRXXX

Guard bit: LSB of result

Round bit: 1st bit removed

Sticky bit: OR of remaining bits

- Round up conditions
  - Round = 1, Sticky = 1 ➙ > 0.5
  - Guard = 1, Round = 1, Sticky = 0 ➙ Round to even

Value	Fraction	GRS	Incr?	Rounded
128	1.0000000	000	N	1.000
15	1.1010000	100	N	1.101
17	1.0001000	010	N	1.000
19	1.0011000	110	Y	1.010
138	1.0001010	011	Y	1.001
63	1.1111100	111	Y	10.000

Postnormalize

- Issue
  - Rounding may have caused overflow
  - Handle by shifting right once & incrementing exponent

Value	Rounded	Exp	Adjusted	Numeric Result
128	1.000	7		128
15	1.101	3		15
17	1.000	4		16
19	1.010	4		20
138	1.001	7		134
63	10.000	5	1.000/6	64

Additional Slides

Interesting Numbers

{single,double}

Description	*exp*	*frac*	*Numeric Value*
■ Zero	00…00	00…00	0.0
■ Smallest Pos. Denorm.	00…00	00…01	$2^{-\{23,52\}} \times 2^{-\{126,1022\}}$
▪ Single ≈ 1.4×10^{-45}			
▪ Double ≈ 4.9×10^{-324}			
■ Largest Denormalized	00…00	11…11	$(1.0 - \varepsilon) \times 2^{-\{126,1022\}}$
▪ Single ≈ 1.18×10^{-38}			
▪ Double ≈ 2.2×10^{-308}			
■ Smallest Pos. Normalized	00…01	00…00	$1.0 \times 2^{-\{126,1022\}}$
▪ Just larger than largest denormalized			
■ One	01…11	00…00	1.0
■ Largest Normalized	11…10	11…11	$(2.0 - \varepsilon) \times 2^{\{127,1023\}}$
▪ Single ≈ 3.4×10^{38}			
▪ Double ≈ 1.8×10^{308}			