


50001 (NV) CONNECTOR

间距: 5.00mm
(Pitch) (.197")




■ 技术参数 (SPECIFICATIONS)

- 线数 (poles): 2、3、4
- 适用线规 (Applicable wires): AWG24#~18#
- 适应基板厚度 (Applicable PC board thickness): 1.6mm
- 温度范围 (Temperature range): -25℃~85℃
- 额定电压 (Voltage rating): 250V.AC/DC
- 额定电流 (Current rating): 3A
- 接触电阻 (Contact resistance): $\leq 0.015\Omega$
- 绝缘电阻 (Insulation resistance): $\geq 1000M\Omega$
- 耐压 (Withstand voltage): 1500V.AC/1min
- 材料 (Material):
 - 孔座 (Housing): 尼龙 (PA66) UL94V-2/0
 - 针座 (Wafer): 尼龙 (PA66) UL94V-2/0
 - 端子 (Terminal): 磷青铜 (C5191)

端子 (Terminal)


型号 Part no.	适用线规 Applicable wires		电线外径 O.D of wire ins mm
	mm ²	AWG#	
39600-PT	0.33~0.83	22~18	1.7~3.0




针座 (wafer)/孔座 (Housing)

线数 Poles	型号 Part no.	尺寸 Dimensions(mm)	
		A	B
02	50001-02Y	5.00	10.00
03	50001-03Y	10.00	15.00
04	50001-04Y	15.00	20.00
02	50001-02A	5.00	10.00
03	50001-02A	10.00	15.00
04	50001-02A	15.00	20.00

针座 (wafer)



孔座 (Housing)



■ 安装尺寸 (Mounting Measurement)

