

~moller/doc/runtemplate_new1.pdf

Date	Begin time	End time	Crew				Comments	

Energy	Linac	Injector	Pass	Wien Angle	HWP	Slit	Attenuat	Raster

	Q1	Q2	Q3	Dipole
Amps				

N	Time	I _{beam} curr	Run Number	Targ et	H _{coil} sign	Polarization %	FADC	Comments
1	19:23	0.3	14336	4	+3	89.71 ± 0.62	1276.7	Right
2	19:29	0.3	14337	4	+3	89.68 ± 0.62	1277-1279	left
3	19:40	0.3	14338	4	+3	90.55 ± 0.61	1280	Right
4						<P> =		
5	19:55	1.3	Target 3					
6	19:59	1.3	14339 - 14341	3	all	JUNKS		beam current 1.3
7	20:08	1.3						
8			Target 2					
9	20:15	1.3	14342 - 14344	2		JUNKS, beam current 1.3		
10	20:20	1.3						
11	20:40	3.0	14345	2		JUNK	1283	
12	20:59	1.0	14346	2	+3		1284	
13	20:39	1.0	14347	2	+3			
14								
15								
16	19:55	1.3	14339	3	+3		1281	
17	19:59	1.3	14340	3	+3		1281	
18	20:08	1.3	14341	3	+3		1281	
19	20:15	1.3	14342	2	+3		1282	
20	20:20	1.3	14343	2	+3		1283	
21	20:25	1.3	14344	2	+3		1283	
22								
23								
24								
25								
26								

Date	Begin time	End time	Crew				Comments	
04/17/10	9:20		O. Glamazdina, R. Pomatsalyuk, J. Zhang					
Energy	Linac	Injector	Pass	Wien Angle	HWP	Slit	Attenuat	Raste
1063.186	503.25	56.62	1	-52.0	Out			2.5x
			Q1	Q2	Q3	Dipole		
Amps			82.32	1.332	21.49	68.007	1.0x	

N	Time	I _{beam} curr	Run Number	Targ et	H _{coil} sign	Polarization %	FADC	Comments Target position
1	15:28	2.0	14315	1	+	HV off.		1.722 / 48.0
2	15:32	3.1	14316	1		89.13 ± 0.73	1238	Left trigger (CL)
3	15:43	3.0	14317	1		89.79 ± 0.73	1240	Right trigger (CR)
4	15:52	3.0	14318	1		88.25 ± 0.64	1241	Left.
5	16:04	3.0	14319	1		88.73 ± 0.64	1242- 1247	Right.
6	16:16	3.0	14320	1		87.91 ± 0.64	1248- 1250	Left
7	16:26	3	14321	1		88.52 ± 0.74	1251- 1252	Right
8				$\langle P \rangle = +88.70 \pm 0.29$			$\chi^2 = 0.9$	
9	16:42		14322	2		89.97 ± 0.68	1253- 1254	Left
10	16:53		14323	2		88.40 ± 0.68	1255	Right.
11	SC HV test runs							
12	17:07		14324	2		88.90 ± 0.68	1256- 1257	Right
13	17:20		14325	2			1258	Right.
14	17:26		14326	2			1259	Left
15	switch back to normal HV setting							
16	17:29		14327	2		89.42 ± 0.67	1260 1261	Left.
17	17:38		14328	2		89.08 ± 0.67	1262- 1264	Right
18	17:49		14329	2		89.80 ± 0.67	1265- 1267	Left
19	17:59		14330	2		89.47 ± 0.67	1268- 1269	Right
20	switch to target 3, Beam=1.5, $\langle P \rangle = 89.32 \pm 0.27$ $\chi^2 =$							
21	18:14	1.5	14331	3		90.76 ± 0.53	1269 1270	Left.
22	18:25	1.5	14332	3		89.20 ± 0.53	1271	Right
23	18:35	1.3	14333	3	+3T	91.16 ± 0.58	1272	Left
24	18:47	1.3	14334	3		89.25 ± 0.57	1273	Right
25	switch to target 4 $\langle P \rangle = 90.09 \pm 0.28$							
26	19:02	0.3	14335	4	+3T	90.90 ± 0.61	1274 1275	Left

Cris

→ B field dropped ^{to 1.1} then increase
~~0.067~~ 0.03
~~0.543~~ 0.257
~~0.633~~

B (T)	1H01	1H04A	1H04B
0	0.09, -0.006	0.06, 0.135	-0.007, -0.03
0.5	0.08, -0.008	1.83, 0.52	2.004, 0.65
1.0	0.07, 0.001	3.43, 0.91	3.82, 1.33
* 1.5	0.06, -0.010	5.00, 1.24	5.45, 1.93
2.0	0.011, -0.024	6.53, 1.67	6.95, 2.63
2.5	try to go to $B=2.5T$, but beam tripped		
2.0	go back to 2.0T, found 1H01 position changed		
2.0	-0.355, -0.183	6.31, 1.54	7.07, 2.44

called MCC and find out the beam go through the chicane!!!
 now we need to redo the measurement again.