

Digitally Fabricated Sole-Attached Textures for Haptic Walking in Virtual Reality

Donald Degraen
donald.degraen@canterbury.ac.nz
HIT Lab NZ
University of Canterbury
Christchurch, New Zealand

Stephan Lukosch
stephan.lokusch@canterbury.ac.nz
HIT Lab NZ
University of Canterbury
Christchurch, New Zealand

Abstract

Haptic feedback is essential for creating immersive and realistic Virtual Reality (VR) experiences, yet current foot-based haptic systems often rely on bulky and expensive hardware. Our previous work explored sole-attached textures to simulate different ground surfaces, allowing users to perceive changes in terrain through passive haptic feedback. To enable controlled variations in friction, we propose to enhance our approach by leveraging digital fabrication techniques. Digitally fabricated sole-attached textures present an accessible, lightweight, and cost-effective method for enhancing foot-based interactions. We discuss the potential of this technique for different applications, as well as future directions for optimizing fabrication of materials, design approaches, and multimodal integration. Our work contributes to the growing field of haptic design by demonstrating how customized, 3D-printed artifacts can enrich virtual experiences.

CCS Concepts

• **Human-centered computing** → **Human computer interaction (HCI)**; *Haptic devices*; *Virtual reality*.

Keywords

haptic walking, haptic feedback, virtual reality, personal fabrication, digital fabrication, 3D printing

ACM Reference Format:

Donald Degraen and Stephan Lukosch. 2025. Digitally Fabricated Sole-Attached Textures for Haptic Walking in Virtual Reality. In *Workshop on Walking the Future (WTF '25)*, April 27, 2025, Yokohama, Japan. ACM, New York, NY, USA, 3 pages.

1 Introduction

Virtual Reality (VR) enables users to experience a wide range of simulated environments, such as snowy or muddy landscapes. While walking in such virtual experiences, generating realistic and plausible foot-based haptic feedback is crucial to ensure users feel present and act accordingly [26]. However, communicating the diverse tactile features of different ground surfaces remains challenging.

In recent years, a wide range of foot interfaces have been proposed to simulate haptic walking. These systems can broadly be




Figure 1: Fabricated sole-attached textures. Here, the texture applied underneath the shoe sole was 3D-printed using an infill-based additive manufacturing method, while the bottom textures illustrate different potential surface features that can be designed to control surface roughness [8].

categorized into *tactile*, for simulating detailed sensations, such as stepping on crackling leaves [28], and *kinesthetic* approaches, for simulating changes in terrain, such as inclines or stairs [23]. Sadly such interfaces often require bulky actuators and sophisticated hardware to impose the required forces onto the human body, making them inaccessible to end-users of off-the-shelf VR setups.

Our work addresses the need for inexpensive and accessible approaches to allow users to deliberately perceive differences in ground surfaces during haptic walking. Our initial investigation proposed physical surface textures attached underneath users' soles to translate mechanical friction into perceptual slipperiness during foot-based locomotion [6]. While this enabled us to enrich foot-based haptic feedback, our method remained dependent on the physical friction properties of commercially available textures. Informed by research on designing tactile experiences that users can fabricate on demand [8, 11, 13, 14, 31], we aim to create surfaces with desired features using digital fabrication technologies. This will enable us to extend the gamut of 3D-printed friction by creating controlled foot-based tactile experiences for virtual environments.

2 Digitally Fabricated Foot Augmentations

Sole-attached textures provide a lightweight approach to augment foot-based interfaces. The strength of this approach lies with controlled fabrication of surface textures to vary physical friction. We discuss several pathways to enhance our approach in future work.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

WTF '25, April 27, 2025, Yokohama, Japan

© 2025 Copyright held by the owner/author(s).

2.1 Sole-Attached Textures

Our recent work pointed out that sole-attached textures can be used to simulate ground features in virtual environments [6]. To do so, we used commercially available textures from a wide range of sources, including fabric sample books. Using these samples, we took physical measurements to determine their coefficient of friction. In human-factor experiments, we related physical friction to perceptual slipperiness. By attaching our textures to the sole of users' shoes, we showed that perceived slipperiness during haptic walking in VR corresponded well to the visual slipperiness of different simulated environments.

Our work was motivated by passive haptic feedback for VR [15]. The feedback provided by passive interfaces, e.g., physical materials [9] or everyday objects [4, 5, 19], has been shown to significantly enhance the realism of virtual experiences. A key part lies with successful integration of visuo-haptic stimuli [30], i.e., a combination of visual ground textures to communicate varying levels of visual friction and foot-based feedback to provide haptic friction.

2.2 Fabricating Slipperiness

An exciting route for future work lies with investigating different materials to control sole-based friction. One example includes the use of digital fabrication methods to create textures with controlled surface features. As pointed out by related work [8, 11–14, 31], the design of such objects can support tactile experiences which can be fabricated by the user on demand. As illustrated in Figure 1, applying these methods to foot-based interfaces can enable controlled fabrication for foot-based tactile experiences.

The tactile response of an object depends on its geometry, material, and the manufacturing process. Therefore, we need to carefully select physical features to haptically convey surface features and ensure designs remain inclusive and accessible for all users. To achieve desired experiences, computational design can be implemented to model physical interactions [2], haptic reproduction can be used to reproduce real world impressions [16], and perceptual modeling techniques can predict users' touch perception [21]. The latter approach will be essential to understand how a given design will be perceived prior to fabrication.

2.3 Haptic Aesthetics

To support designers in creating custom experiences through controlled fabrication of underfoot materials, haptic designers require intuitive approaches to support them in their design workflows [24]. While recent work has investigated different design approaches for vibrotactile feedback [7, 33, 34], design approaches for enhancing virtual experiences with physical materials remain underexplored [9]. Therefore, an open challenge lies with design tools for creating 3D-printed objects with desired haptics. These tools should take desired tactile qualities as input and generate the corresponding design and printing parameters as output to enable designers to design haptic aesthetics (cfr. visual aesthetics).

Furthermore, digital fabrication of sole-attached materials supports end-user customization and personalization, both crucial aspects of haptic experience design [25]. By modifying digital designs to users' individual sensitivities prior to fabrication, haptic experiences can be optimized to the user in question. Future research

could explore different parameters of haptic personalization tools to provide intuitive ways for users to calibrate the feedback provided and enable them to define their own interactions [10].

2.4 Multimodal Integration

Sole-attached textures for haptic walking provide a lightweight and affordable approach to vary the perception of surface slipperiness. As this does not use any active mechanisms, and the used material textures can be applied to any existing shoe, this approach can easily complement other methods, such as omnidirectional treadmills for body-centric walking in VR. Moreover, by integrating vibrotactile actuation inside the shoe sole, different feedback mechanisms can be combined during the entire walking movement [28], enabling the simulation of more complex surface interactions. Considering recent advancements in vibrotactile actuation, sole-attached materials can be enhanced with simulated forces [22] or sensory substitution approaches providing directional cues [32]. Analogously, during the footstep experience, auditive feedback can be used to generate multimodal surface experiences [29].

2.5 Applications

The history of sports goes back several thousands of years. Sports started off as preparation for war or training as hunter. Virtual reality is, e.g., used for sensorimotor training [1], improving motor performance [3], or mental imagery training [35]. Augmented reality is, e.g., used to provide augmented feedback [20] and various training and education scenarios [27]. Superhuman Sports [17, 18] relies on these technologies and focuses on augmenting sports to enhance a player's senses, to extend a player's body, augment the sports field, create new sports or enhance the training while making us experience superhuman capabilities. Following up on the multimodal integration with treadmills, such foot-based haptic feedback could be used to create superhuman sports that make athletes experience realistic sensations of different terrains, such as snowy or muddy landscapes, when training on a treadmill while preparing for diverse environments. Further, being able to simulate different haptic sensations, e.g., stepping on crackling leaves or changes with regard to the slipperiness of terrain, in combination with visuo-haptic experiences [30] could make virtual training sessions on a treadmill more engaging and effective.

3 Conclusion

Our work explores the potential of digitally fabricated sole-attached textures to enhance foot-based experiences. By leveraging 3D printing, custom surface textures can be created to modulate friction and simulate ground conditions, offering an accessible and lightweight alternative to traditional haptic feedback during haptic walking. We proposed directions for future research, including refinements of the design and fabrication processes to improve user customization and personalization and ensuring a wider range of tactile sensations. Additionally, integration with multimodal feedback mechanisms, such as vibrotactile actuation and auditory cues, could further enhance realism in virtual environments. Continued exploration of fabrication methods, material properties, and user-centered design principles will be essential in realizing the full potential of our approach.

References

- [1] Sergei V Adamovich, Gerard G Fluet, Eugene Tunik, and Alma S Merians. 2009. Sensorimotor training in virtual reality: a review. *NeuroRehabilitation* 25, 1 (2009), 29–44.
- [2] Bernd Bickel, Moritz Bäcker, Miguel A. Otaduy, Hyunho Richard Lee, Hanspeter Pfister, Markus Gross, and Wojciech Matusik. 2010. Design and Fabrication of Materials with Desired Deformation Behavior. *ACM Trans. Graph.* 29, 4, Article 63 (July 2010), 10 pages. <https://doi.org/10.1145/1778765.1778800>
- [3] Rocco Salvatore Calabrò, Antonino Naro, Margherita Russo, Antonino Leo, Rosaria De Luca, Tina Balletta, Antonio Buda, Gianluca La Rosa, Alessia Bramanti, and Placido Bramanti. 2017. The role of virtual reality in improving motor performance as revealed by EEG: a randomized clinical trial. *Journal of neuroengineering and rehabilitation* 14, 1 (2017), 1–16.
- [4] Florian Daiber, Donald Degraen, André Zenner, Tanja Döring, Frank Steinicke, Oscar Javier Ariza Nunez, and Adalberto L. Simeone. 2021. Everyday Proxy Objects for Virtual Reality. In *Extended Abstracts of the 2021 CHI Conference on Human Factors in Computing Systems* (Yokohama, Japan) (CHI EA '21). ACM, Article 101, 6 pages. <https://doi.org/10.1145/3411763.3441343>
- [5] Florian Daiber, Donald Degraen, André Zenner, Frank Steinicke, Oscar Javier Ariza Núñez, and Adalberto L. Simeone. 2020. Everyday Proxy Objects for Virtual Reality. In *Extended Abstracts of the 2020 CHI Conference on Human Factors in Computing Systems* (Honolulu, HI, USA) (CHI EA '20). ACM, 1–8. <https://doi.org/10.1145/3334480.3375165>
- [6] Donald Degraen, Martin Feick, Serdar Durdyev, and Antonio Krüger. 2024. Prototyping Surface Slipperiness using Sole-Attached Textures during Haptic Walking in Virtual Reality. In *Proceedings of the International Conference on Mobile and Ubiquitous Multimedia (MUM '24)*. ACM, 95–105. <https://doi.org/10.1145/3701571.3701589>
- [7] Donald Degraen, Bruno Fruchard, Frederik Smolders, Emmanouil Potetsianakis, Seref Güngör, Antonio Krüger, and Jürgen Steimle. 2021. Weiriding Haptics: In-Situ Prototyping of Vibrotactile Feedback in Virtual Reality through Vocalization. In *The 34th Annual ACM Symposium on User Interface Software and Technology* (Virtual Event, USA) (UIST '21). ACM, 936–953. <https://doi.org/10.1145/3472749.3474797>
- [8] Donald Degraen, Michal Piovarči, Bernd Bickel, and Antonio Krüger. 2021. Capturing Tactile Properties of Real Surfaces for Haptic Reproduction. In *The 34th Annual ACM Symposium on User Interface Software and Technology* (Virtual Event, USA) (UIST '21). ACM, 954–971. <https://doi.org/10.1145/3472749.3474798>
- [9] Donald Degraen, Anna Reindl, Akhmajon Makhvadov, André Zenner, and Antonio Krüger. 2020. Envisioning Haptic Design for Immersive Virtual Environments. In *Companion Publication of the 2020 ACM Designing Interactive Systems Conference* (Eindhoven, Netherlands) (DIS '20 Companion). ACM, 287–291. <https://doi.org/10.1145/3393914.3395870>
- [10] Donald Degraen, Marco Speicher, André Zenner, and Antonio Krüger. 2024. Exploring User-Defined Interactions for Virtual Reality. In *Proceedings of the 2024 ACM Symposium on Spatial User Interaction* (Trier, Germany) (SUI '24). ACM, Article 42, 3 pages. <https://doi.org/10.1145/3677386.3688882>
- [11] Donald Degraen, André Zenner, and Antonio Krüger. 2019. Enhancing Texture Perception in Virtual Reality Using 3D-Printed Hair Structures. In *Proceedings of the 2019 CHI Conference on Human Factors in Computing Systems* (Glasgow, Scotland UK) (CHI '19). ACM, 1–12. <https://doi.org/10.1145/3290605.3300479>
- [12] Faraz Faruqi, Maxine Perroni-Scharf, Jaskaran Singh Walia, Yuniy Zhu, Shuyue Feng, Donald Degraen, and Stefanie Mueller. 2025. TactStyle: Generating Tactile Textures with Generative AI for Digital Fabrication. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems* (Yokohama, Japan) (CHI '25). ACM, 1–16. <https://doi.org/10.1145/3706598.3713740>
- [13] Martin Feick, Donald Degraen, Fabian Hupperich, and Antonio Krüger. 2023. MetaReality: enhancing tactile experiences using actuated 3D-printed meta-materials in Virtual Reality. *Frontiers in Virtual Reality* 4 (June 2023). <https://doi.org/10.3389/frvir.2023.1172381>
- [14] Jess Hartcher-O'Brien, Jeremy Evers, and Erik Tempelman. 2019. Surface roughness of 3D printed materials: Comparing physical measurements and human perception. *Materials Today Communications* 19 (Jun 2019), 300–305. <https://doi.org/10.1016/j.mtcomm.2019.01.008>
- [15] Brent Edward Insko. 2001. *Passive Haptics Significantly Enhances Virtual Environments*. Ph.D. Dissertation. University of North Carolina at Chapel Hill, USA. Advisor(s) Frederick P. Brooks Jr. <http://www.cs.unc.edu/techreports/01-017.pdf>
- [16] Katherine J. Kuchenbecker, Joseph Romano, and William McMahan. 2011. *Haptography: Capturing and Recreating the Rich Feel of Real Surfaces*. Springer Tracts in Advanced Robotics, Vol. 70. Springer Berlin Heidelberg, Berlin, Heidelberg, 245–260. https://doi.org/10.1007/978-3-642-19457-3_15
- [17] Kai Kunze and Stephan Lukosch. 2019. Superhuman Sports – A Testing Ground for Augmenting Our Senses. *XRDS* 25, 4 (July 2019), 38–43. <https://doi.org/10.1145/3331069>
- [18] Kai Kunze, Kouta Minamizawa, Stephan Lukosch, Masahiko Inami, and Jun Rekimoto. 2017. Superhuman Sports: Applying Human Augmentation to Physical Exercise. *IEEE Pervasive Computing* 16, 2 (April-June 2017), 14–17. <https://doi.org/10.1109/MPRV.2017.35>
- [19] Akhmajon Makhvadov, Donald Degraen, André Zenner, Felix Kosmalla, Kamila Mushkina, and Antonio Krüger. 2022. VRySmart: a Framework for Embedding Smart Devices in Virtual Reality. In *Extended Abstracts of the 2022 CHI Conference on Human Factors in Computing Systems* (New Orleans, LA, USA) (CHI EA '22). ACM, Article 358, 8 pages. <https://doi.org/10.1145/3491101.3519717>
- [20] Emma Louise Petancevski, Joshua Inns, Job Fransen, and Franco Milko Impellerizzi. 2022. The effect of augmented feedback on the performance and learning of gross motor and sport-specific skills: A systematic review. *Psychology of Sport and Exercise* 63 (2022), 102277. <https://doi.org/10.1016/j.psychsport.2022.102277>
- [21] Michal Piovarči, David I. W. Levin, Jason Rebello, Desai Chen, Roman Đuriković, Hanspeter Pfister, Wojciech Matusik, and Piotr Didyk. 2016. An interaction-aware, perceptual model for non-linear elastic objects. *ACM Transactions on Graphics* 35, 4 (July 2016), 1–13. <https://doi.org/10.1145/2897824.2925885>
- [22] Nihar Sabnis, Maelle Roche, Dennis Wittchen, Donald Degraen, and Paul Strohmeier. 2025. Motion-Coupled Asymmetric Vibration for Pseudo Force Rendering in Virtual Reality. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems* (Yokohama, Japan) (CHI '25). ACM, 1–22. <https://doi.org/10.1145/3706598.3713358>
- [23] Dominik Schmidt, Rob Kovacs, Vikram Mehta, Udayan Umapathi, Sven Köhler, Lung-Pan Cheng, and Patrick Baudisch. 2015. Level-Ups: Motorized Stilts That Simulate Stair Steps in Virtual Reality. In *Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems* (Seoul, Republic of Korea) (CHI '15). ACM, 2157–2160. <https://doi.org/10.1145/2702123.2702253>
- [24] Oliver Schneider, Bruno Fruchard, Dennis Wittchen, Bibhushan Raj Joshi, Georg Freitag, Donald Degraen, and Paul Strohmeier. 2022. Sustainable Haptic Design: Improving Collaboration, Sharing, and Reuse in Haptic Design Research. In *Extended Abstracts of the 2022 CHI Conference on Human Factors in Computing Systems* (New Orleans, LA, USA) (CHI EA '22). ACM, Article 79, 5 pages. <https://doi.org/10.1145/3491101.3503734>
- [25] Hasti Seifi. 2019. *Personalizing Haptics: From Individuals' Sense-Making Schemas to End-User Haptic Tools*. Springer International Publishing. <https://doi.org/10.1007/978-3-030-11379-7>
- [26] Mel Slater. 2009. Place illusion and plausibility can lead to realistic behaviour in immersive virtual environments. *Philosophical Transactions of the Royal Society B: Biological Sciences* 364, 1535 (Dec 2009). <https://doi.org/10.1098/rstb.2009.0138>
- [27] Pooya Soltani and Antoine H.P. Morice. 2020. Augmented reality tools for sports education and training. *Computers & Education* 155 (2020), 103923. <https://doi.org/10.1016/j.compedu.2020.103923>
- [28] Paul Strohmeier, Seref Güngör, Luis Herres, Dennis Gudea, Bruno Fruchard, and Jürgen Steimle. 2020. BARefoot: Generating Virtual Materials Using Motion Coupled Vibration in Shoes. In *Proceedings of the 33rd Annual ACM Symposium on User Interface Software and Technology* (Virtual Event, USA) (UIST '20). ACM, 579–593. <https://doi.org/10.1145/3379337.3415828>
- [29] Ana Tajadura-Jiménez, Maria Basia, Ophelia Deroy, Merle Fairhurst, Nicolai Marquardt, and Nadia Bianchi-Berthouze. 2015. As Light as your Footsteps: Altering Walking Sounds to Change Perceived Body Weight, Emotional State and Gait. In *Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems*. ACM, Seoul Republic of Korea, 2943–2952. <https://doi.org/10.1145/2702123.2702374>
- [30] Jack Topliss, Stephan Lukosch, Euan Coutts, and Tham Piumsomboon. 2023. Manipulating Underfoot Tactile Perceptions of Flooring Materials in Augmented Virtuality. *Applied Sciences* 13, 24 (2023). <https://doi.org/10.3390/app132413106>
- [31] Chelsea Tymms, Denis Zorin, and Esther P. Gardner. 2018. Tactile perception of the roughness of 3D-printed textures. *Journal of Neurophysiology* 119, 3 (Mar 2018), 862–876. <https://doi.org/10.1152/jn.00564.2017>
- [32] Iddo Yehoshua Wald, Donald Degraen, Amber Maimon, Jonas Keppel, Stefan Schneegass, and Rainer Malaka. 2025. Spatial Haptics: A Sensory Substitution Method for Distal Object Detection Using Tactile Cues. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems* (Yokohama, Japan) (CHI '25). ACM, 1–12. <https://doi.org/10.1145/3706598.3714083>
- [33] Dennis Wittchen, Alexander Ramian, Nihar Sabnis, Christopher Chlebowsky, Richard Böhme, Georg Freitag, Bruno Fruchard, and Donald Degraen. 2025. CollabJam: Studying Collaborative Haptic Experience Design for On-Body Vibrotactile Patterns. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems* (Yokohama, Japan) (CHI '25). ACM, 1–20. <https://doi.org/10.1145/3706598.3713469>
- [34] Dennis Wittchen, Katta Spiel, Bruno Fruchard, Donald Degraen, Oliver Schneider, Georg Freitag, and Paul Strohmeier. 2022. TactJam: An End-to-End Prototyping Suite for Collaborative Design of On-Body Vibrotactile Feedback. In *Proceedings of the Sixteenth International Conference on Tangible, Embedded, and Embodied Interaction* (Daejeon, Republic of Korea) (TEI '22). ACM, Article 1, 13 pages. <https://doi.org/10.1145/3490149.3501307>
- [35] Yuanjie Wu, Stephan Lukosch, Heide Lukosch, Robert W. Lindeman, Ryan Douglas McKee, Shunsuke Fukuden, Cameron Ross, and Dave Collins. 2023. Training mental imagery skills of elite athletes in virtual reality. *Frontiers in Virtual Reality* 4 (2023). <https://doi.org/10.3389/frvir.2023.1189717>