



Difference Between Multithreading vs Multiprocessing in Python

In this article, we will learn the what, why, and how of multithreading and multiprocessing in Python. Before we dive into the code, let us understand what these terms mean.

- A **program** is an executable file which consists of a set of instructions to perform some task and is usually stored on the disk of your computer.
- A **process** is what we call a program that has been loaded into memory along with all the resources it needs to operate. It has its own memory space.
- A **thread** is the unit of execution within a process. A process can have multiple threads running as a part of it, where each thread uses the process's memory space and shares it with other threads.
- **Multithreading** is a technique where multiple threads are spawned by a process to do different tasks, at about the same time, just one after the other. This gives you the illusion that the threads are running in parallel, but they are actually run in a concurrent manner. In Python, the Global Interpreter Lock (GIL) prevents the threads from running simultaneously.
- **Multiprocessing** is a technique where parallelism in its truest form is achieved. Multiple processes are run across multiple CPU cores, which do not share the resources among them. Each process can have many threads running in its own memory space. In Python, each process has its own instance of Python interpreter doing the job of executing the instructions.

Now, let's jump into the program where we try to execute two different types of functions: **IO-bound** and **CPU-bound** in six different ways. Inside the IO-bound function, we ask the CPU to sit idle and pass time whereas, inside the CPU-bound function, the CPU is going to be busy churning out a few numbers.

Requirements:

- A Windows computer (My machine has 6 cores).

Free Python 3 Tutorial Data Types Control Flow Functions List String Set Tuple Dictionary Oops Exception Handling Python Programs

Note: Below is the structure of our program, which will be common across all the six parts. In the place where it is mentioned # YOUR CODE SNIPPET HERE, replace it with the code snippet of each part as you go.

AD

Python3

```
import time, os
from threading import Thread, current_thread
from multiprocessing import Process, current_process
```

```
COUNT = 2000000000
SLEEP = 10
```

```
def io_bound(sec):
```

```
    pid = os.getpid()
```

```

print(f"{pid} * {processName} * {threadName} \
    ---> Start sleeping...")
time.sleep(sec)
print(f"{pid} * {processName} * {threadName} \
    ---> Finished sleeping...")

def cpu_bound(n):

    pid = os.getpid()
    threadName = current_thread().name
    processName = current_process().name

    print(f"{pid} * {processName} * {threadName} \
        ---> Start counting...")

    while n>0:
        n -= 1

    print(f"{pid} * {processName} * {threadName} \
        ---> Finished counting...")

if __name__=="__main__":
    start = time.time()

    # YOUR CODE SNIPPET HERE

    end = time.time()
    print('Time taken in seconds -', end - start)

```

Part 1: Running IO-bound task twice, one after the other...

Python3

```

# Code snippet for Part 1
io_bound(SLEEP)
io_bound(SLEEP)

```

Here, we ask our CPU to execute the function `io_bound()`, which takes in an integer (10, here) as a parameter and asks the CPU to sleep for that many seconds. This execution takes a total of 20 seconds, as each function execution takes 10 seconds to complete. Note that, it is the same MainProcess that calls our function twice, one after the other, using its default thread, MainThread.

```

40416 * MainProcess * MainThread ---> Start sleeping...
40416 * MainProcess * MainThread ---> Finished sleeping...
40416 * MainProcess * MainThread ---> Start sleeping...
40416 * MainProcess * MainThread ---> Finished sleeping...
Time taken in seconds - 20.0010244846344

```

Python3

```
# Code snippet for Part 2
t1 = Thread(target = io_bound, args =(SLEEP, ))
t2 = Thread(target = io_bound, args =(SLEEP, ))
t1.start()
t2.start()
t1.join()
t2.join()
```

Here, let's use threading in Python to speed up the execution of the functions. The threads Thread-1 and Thread-2 are started by our MainProcess, each of which calls our function, at almost the same time. Both the threads complete their job of sleeping for 10 seconds, concurrently. This reduced the total execution time of our whole program by a significant 50%. Hence, multithreading is the go-to solution for executing tasks wherein the idle time of our CPU can be utilized to perform other tasks. Hence, saving time by making use of the wait time.

```
24272 * MainProcess * Thread-1 ---> Start sleeping...
24272 * MainProcess * Thread-2 ---> Start sleeping...
24272 * MainProcess * Thread-1 ---> Finished sleeping...
24272 * MainProcess * Thread-2 ---> Finished sleeping...
Time taken in seconds - 10.002389907836914
```

Part 3: Running CPU-bound task twice, one after the other...

Python3

```
# Code snippet for Part 3
cpu_bound(COUNT)
cpu_bound(COUNT)
```

Here, we shall call our function `cpu_bound()`, which takes in a big number (200000000, here) as a parameter and decrements it at each step until it is zero. Our CPU is asked to do the countdown at each function call, which roughly takes around 12 seconds (this number might differ on your machine). Hence, the execution of the whole program took me about 26 seconds to complete. Note that it is once again our MainProcess calling the function twice, one after the other, in its default thread, MainThread.

```
2992 * MainProcess * MainThread ---> Start counting...
2992 * MainProcess * MainThread ---> Finished counting...
2992 * MainProcess * MainThread ---> Start counting...
2992 * MainProcess * MainThread ---> Finished counting...
Time taken in seconds - 26.805074214935303
```

Part 4: Can threading speed up our CPU-bound tasks?

Python3

```
# Code snippet for Part 4
t1 = Thread(target = cpu_bound, args =(COUNT, ))
t2 = Thread(target = cpu_bound, args =(COUNT, ))
t1.start()
t2.start()
t1.join()
t2.join()
```

Okay, we just proved that threading worked amazingly well for multiple IO-bound tasks. Let's use the same approach for executing our CPU-bound tasks. Well, it did kick off our threads at the same time initially, but in the end, we see that the whole program execution took about a whopping 40 seconds! What just happened? This is because when Thread-1 started, it acquired the Global Interpreter Lock (GIL) which prevented Thread-2 to make use of the CPU. Hence, Thread-2 had to wait for Thread-1 to finish its task and release the lock so that it can acquire the lock and perform its task. This acquisition and release of the lock added overhead to the total execution time. Therefore, we can safely say that threading is not an ideal solution for tasks that requires CPU to work on something.

```
18060 * MainProcess * Thread-1 ---> Start counting...
18060 * MainProcess * Thread-2 ---> Start counting...
18060 * MainProcess * Thread-2 ---> Finished counting...
18060 * MainProcess * Thread-1 ---> Finished counting...
Time taken in seconds - 40.78663516044617
```

Part 5: So, does splitting the tasks as separate processes work?

Python3

```
# Code snippet for Part 5
p1 = Process(target = cpu_bound, args =(COUNT, ))
```

```
p1.join()
p2.join()
```

Let's cut to the chase. Multiprocessing is the answer. Here the MainProcess spins up two subprocesses, having different PIDs, each of which does the job of decreasing the number to zero. Each process runs in parallel, making use of separate CPU core and its own instance of the Python interpreter, therefore the whole program execution took only 12 seconds. Note that the output might be printed in unordered fashion as the processes are independent of each other. Each process executes the function in its own default thread, MainThread. Open your Task Manager during the execution of your program. You can see 3 instances of the Python interpreter, one each for MainProcess, Process-1, and Process-2. You can also see that during the program execution, the Power Usage of the two subprocesses is "Very High", as the task they are performing is actually taking a toll on their own CPU cores, as shown by the spikes in the CPU Performance graph.

```
26224 * Process-2 * MainThread ---> Start counting...
26224 * Process-2 * MainThread ---> Finished counting...
17916 * Process-1 * MainThread ---> Start counting...
17916 * Process-1 * MainThread ---> Finished counting...
Time taken in seconds - 12.198703289031982
```

Sublime Text (7)		18.6%	49.9 MB	0 MB/s	0 Mbps	0%	Very high
Console Window Host	conhost.exe	0%	6.8 MB	0 MB/s	0 Mbps	0%	Very low
plugin_host	plugin_host.exe	0%	11.0 MB	0 MB/s	0 Mbps	0%	Very low
Python	python.exe	9.3%	6.3 MB	0 MB/s	0 Mbps	0%	Very high
Python	python.exe	9.3%	6.3 MB	0 MB/s	0 Mbps	0%	Very high
Python	python.exe	0%	6.1 MB	0 MB/s	0 Mbps	0%	Very low
Sublime Text	sublime_text.exe	0%	12.1 MB	0 MB/s	0 Mbps	0%	Very low
Windows Command Processor	cmd.exe	0%	1.4 MB	0 MB/s	0 Mbps	0%	Very low



Part 6: Hey, lets use multiprocessing for our IO-bound tasks

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).


```

# Code snippet for Part 6
p1 = Process(target = io_bound, args =(SLEEP, ))
p2 = Process(target = io_bound, args =(SLEEP, ))
p1.start()
p2.start()
p1.join()
p2.join()

```

Now that we got a fair idea about multiprocessing helping us achieve parallelism, we shall try to use this technique for running our IO-bound tasks. We do observe that the results are extraordinary, just as in the case of multithreading. Since the processes Process-1 and Process-2 are performing the task of asking their own CPU core to sit idle for a few seconds, we don't find high Power Usage. But the creation of processes itself is a CPU heavy task and requires more time than the creation of threads. Also, processes require more resources than threads. Hence, it is always better to have multiprocessing as the second option for IO-bound tasks, with multithreading being the first.

```

16960 * Process-1 * MainThread ---> Start sleeping...
16960 * Process-1 * MainThread ---> Finished sleeping...
38588 * Process-2 * MainThread ---> Start sleeping...
38588 * Process-2 * MainThread ---> Finished sleeping...
Time taken in seconds - 10.299973011016846

```

Sublime Text (7)		0.1%	51.0 MB	0 MB/s	0 Mbps	0%	Very low	Very low
Console Window Host	conhost.exe	0%	6.8 MB	0 MB/s	0 Mbps	0%	Very low	
mp.py (lockdown_classes) - Su...	sublime_text.exe	0.1%	13.3 MB	0 MB/s	0 Mbps	0%	Very low	Very low
plugin_host	plugin_host.exe	0%	10.8 MB	0 MB/s	0 Mbps	0%	Very low	Very low
Python	python.exe	0%	6.1 MB	0 MB/s	0 Mbps	0%	Very low	
Python	python.exe	0%	6.3 MB	0 MB/s	0 Mbps	0%	Very low	
Python	python.exe	0%	6.3 MB	0 MB/s	0 Mbps	0%	Very low	
Windows Command Processor	cmd.exe	0%	1.4 MB	0 MB/s	0 Mbps	0%	Very low	



Well, that was quite a ride. We saw six different approaches to perform a task, that roughly took about 10 seconds, based on whether the task is light or heavy on the CPU.

Bottomline: Multithreading for IO-bound tasks. Multiprocessing for CPU-bound tasks.

Multithreading in Python	Multiprocessing in Python
It Implements the Concurrency.	It Implements the Parallelism.
Python does not support multithreading in the case of parallel computing.	Python supports multiprocessing in the case of parallel computing.
In multithreading, multiple threads at the same time are generated by a single process.	In multiprocessing, multiple threads at the same time run across multiple cores.
Multithreading can not be classified.	Multiprocessing can be classified such as symmetric or asymmetric.

Unlock the Power of Placement Preparation!

Feeling lost in OS, DBMS, CN, SQL, and DSA chaos? Our [Complete Interview Preparation](#) Course is the ultimate guide to conquer placements. Trusted by over 100,000+ geeks, this course is your roadmap to interview triumph. Ready to dive in? Explore our Free Demo Content and join our [Complete Interview Preparation](#) course.

Last Updated : 31 Mar, 2023

55

[Previous](#)

[Next](#)

[Matplotlib.colors.Normalize class in Python](#)

[Deconstructing Interpreter: Understanding Behind the Python Bytecode](#)

[Share your thoughts in the comments](#)

[Add Your Comment](#)

Similar Reads

[Python multiprocessing.Queue vs multiprocessing.manager\(\).Queue\(\)](#)

[Difference between Multiprogramming, multitasking, multithreading and multiprocessing](#)

[Difference between Multiprocessing and Multithreading](#)

[Multithreading or Multiprocessing with Python and Selenium](#)

[Difference between Asymmetric and Symmetric Multiprocessing](#)

[Difference between Multitasking and Multiprocessing](#)

Running Queries in Python Using Multiprocessing

Multiprocessing in Python and PyTorch

V varunkum...

Follow

Article Tags : [Python-multithreading](#) , [Difference Between](#) , [Operating Systems](#) , [Python](#) , [Write From Home](#)

Practice Tags : [python](#)



Sanchhaya Education Private Limited
A-143, 9th Floor, Sovereign Corporate
Tower, Sector-136, Noida, Uttar Pradesh -
201305



Company

About Us
Legal
Careers
In Media
Contact Us
Advertise with us
GFG Corporate Solution
Placement Training
Program

Explore

Hack-A-Thons
GfG Weekly Contest
DSA in JAVA/C++
Master System Design
Master CP
GeeksforGeeks Videos
Geeks Community

Languages

Python
Java
C++
PHP
GoLang
SQL
R Language
Android Tutorial
Tutorials Archive

DSA

Data Structures
Algorithms
DSA for Beginners
Basic DSA Problems
DSA Roadmap
Top 100 DSA Interview
Problems
DSA Roadmap by
Sandeep Jain
All Cheat Sheets

Data Science & ML

Data Science With
Python
Data Science For
Beginner
Machine Learning
Tutorial
ML Maths
Data Visualisation
Tutorial
Pandas Tutorial
NumPy Tutorial
NLP Tutorial
Deep Learning Tutorial

HTML & CSS

HTML
CSS
Web Templates
CSS Frameworks
Bootstrap
Tailwind CSS
SASS
LESS
Web Design
Django Tutorial

Python Tutorial

Python Programming Examples
Python Projects
Python Tkinter
Web Scraping
OpenCV Tutorial
Python Interview Question

Computer Science

Operating Systems
Computer Network
Database Management
System
Software Engineering
Digital Logic Design
Engineering Maths

DevOps

Git
AWS
Docker
Kubernetes
Azure
GCP
DevOps Roadmap

Competitive Programming

Top DS or Algo for CP
Top 50 Tree
Top 50 Graph
Top 50 Array
Top 50 String
Top 50 DP
Top 15 Websites for CP

System Design

High Level Design
Low Level Design
UML Diagrams
Interview Guide
Design Patterns
OOAD
System Design
Bootcamp
Interview Questions

JavaScript

JavaScript Examples
TypeScript
ReactJS
NextJS
AngularJS
NodeJS
Lodash
Web Browser

Preparation Corner

Company-Wise
Recruitment Process
Resume Templates
Aptitude Preparation
Puzzles
Company-Wise Preparation

School Subjects

Mathematics
Physics
Chemistry
Biology
Social Science
English Grammar
World GK

Management & Finance

Management
HR Management
Finance
Income Tax
Organisational Behaviour
Marketing

Free Online Tools

Typing Test
Image Editor
Code Formatters
Code Converters
Currency Converter
Random Number Generator
Random Password Generator

More Tutorials

Software Development
Software Testing
Product Management
SAP
SEO - Search Engine Optimization
Linux
Excel

GeeksforGeeks Videos

DSA
Python
Java
C++
Data Science
CS Subjects

@GeeksforGeeks, Sanchhaya Education Private Limited, All rights reserved