

Alu 3-Core Waveform Cu cne, with Flame Retardant Outer Sheath type LS-OH

Conductor:	35 mm ² : 70-300 mm ² :	Circular solid aluminium conductor Sector shaped solid aluminium conductor
Insulation:	XLPE	
Colour marking of cores:	Brown, black, grey	
Inner sheath:	Thermoplastic compound, for flame retardant cable	
Concentric conductor:	Copper wires in waveconal execution with a copper tape applied.	
Oversheath:	Thermoplastic compound	
Colour of sheath:	Orange	
Rated voltage:	0,6/1 kV	
Guaranteed test voltage:	3.5 kV AC between conductor and screen for 5 minutes	
Maximum conductor temperature:	90°C	
Maximum short circuit temperature:	250°C	
Minimum laying temperature:	0°C	



Alu 3-Core Waveform Cu cne, with Flame Retardant Outer Sheath type LS-OH

Standard: BS 7870 – 3.50

Tested according to:

Fire conditions: EN 50265-2-1
EN 50266-2-2 (Category A)
EN 50266-2-4 (Category C)
(IEC 60332-1,
IEC 60332-3-22 + 24)

Smoke density: EN 50268 (IEC 61034)

Emission of corrosive gases: EN 50267-1 (IEC 60754-1)

Conductivity – ph change: EN 50267-2 (IEC 60754-2)

Application: Low voltage installations, that requires fire protection.

Number of cores and cross section	Number and diameter of wires in concentric conductor	Insulation thickness	Thickness of sheath	Outer diameter	Approx. weight per km	Standard length	Diameter of drum
mm ²	nom. mm	nom. mm	nom. mm	nom. mm	kg	m	m
3 x 35	30 x 1.13	0.9	1.8	26.5	1,350	250 m	1.2
3 x 70	30 x 1.35	1.1	1.9	31.2	1,850	250 m	1.2
3 x 95	30 x 1.58	1.1	2.1	34.6	2,600	250 m	1.5
3 x 120	30 x 1,78	1.2	2.2	38.6	3,250	250 m	1.5
3 x 150	42 x 1.87	1.4	2.3	41.3	4,100	250 m	1.5
3 x 185	42 x 1.87	1.6	2.5	45.8	5,000	250 m	1.8
3 x 300	42 x 1.87	1.8	2.8	54.7	6,000	250 m	2.0

