

Alu 4-core Waveform Cu sne With Flame Retardant Outer Sheath Type LS-OH

Conductor:	Sector shaped solid aluminium conductor
Insulation:	XLPE
Colour marking of cores:	Brown, black, grey, blue
Inner sheath:	Thermoplastic compound, for flame retardant cable
Concentric conductor:	Copper wires in waveconal execution with a copper tape applied.
Oversheath:	Thermoplastic compound
Colour of sheath:	Orange
Rated voltage:	0,6/1 kV
Guaranteed test voltage:	3.5 kV AC between conductor and screen for 5 minutes
Maximum conductor temperature:	90°C
Maximum short circuit temperature:	250°C
Minimum laying temperature:	0°C

2006-04-12 FKI P035.601	Issued by: DEN	Approved by: <i>JON</i> 12-04-06	Edition: 0	Page 1 of 2
----------------------------	----------------	-------------------------------------	------------	-------------



Alu 4-core Waveform Cu sne With Flame Retardant Outer Sheath Type LS-OH

Standard: BS 7870 – 3.50

Tested according to:

Fire conditions: EN 50265-2-1
EN 50266-2-2 (Category A)
EN 50266-2-4 (Category C)
(IEC 60332-1,
IEC 60332-3-22 + 24)

Smoke density: EN 50268 (IEC 61034)

Emission of corrosive gases: EN 50267-1 (IEC 60754-1)

Conductivity – ph change: EN 50267-2 (IEC 60754-2)

Application: Low voltage installations, that requires fire protection.

Number of cores and cross section mm ²	Number and diameter of wires in con- centric con- ductor nom. mm	Insulation thickness nom. mm	Thickness of sheath nom. mm	Outer diameter	Approx. weight per km kg	Standard length m	Diameter of drum m
				Nom. mm			
4 x 95	30 x 1.58	1.1	2.2	38.3	2,500	250 m	1.5
4 x 185	42 x 1.87	1.6	2.6	53.2	4,400	250 m	1.8
4 x 240	42 x 1.87	1.7	2.8	57.8	5,400	250 m	2.0
4 x 300	42 x 1.87	1.8	3.1	63.0	6,500	250 m	2.2

2006-04-12 FKI P035.601	Issued by: DEN	Approved by: <i>TDR</i> 12-04-06	Edition: 0	Page 2 of 2
----------------------------	----------------	-------------------------------------	------------	-------------

