

c. 25mm?

ANGLED CUT 30° TO LOGITUDINAL AXIS?

TOP MIN DIAMETER (mm)

Ø 18mm HOLE

FOR REVIEW PURPOSES ONLY

POLE BUTT MARKINGS (IMPRESSED INTO THE WOOD FIBRES)

INSPECTOR'S STAMP

10 S — SIZE & CLASS OF POLE

20 — YEAR OF TREATMENT

CG — PURCHASER INITIALS

NBI — PURCHASER INITIALS

CE DISK

LENGTH & CLASS — 10 S

SPECIES & COUNTRY OF ORIGIN — PS FI

YEAR OF TREATMENT — 20

TREATMENT (if other than creosote) — AC

MANUFACTURER — CG

TREATMENT BATCH NUMBER — N107

NOTES:

- ALL CHARACTERS HAVE A MINIMUM HEIGHT OF 25mm AND ARE GOUGED 5mm WIDE 3mm DEEP MINIMUM.
- WOOD POLE INFORMATION AND SERIAL NUMBER BRAND MARKINGS AS SHOWN.
- ALL DIMENSIONS ARE IN mm.

	Rev.	DATE	INITIAL	DETAIL
	A	17-2-2020	D.L.	ORIGINAL DRAWING FOR CUSTOMER APPROVAL.
	TITLE :			
	NBI/NBID STOCK WOOD POLE			
DRAWN: D.L.	APPROVED: NBI			
CHECKED: R.L.	SHEET(S) IN SET: 1			
DATE: 17-2-2020	ISSUER: C&G, BOSTON			
	DRG. NO.	CG NBI PD A 01		
	ASSOC. NBI DRG.			

NOTE: THIS DRAWING IS FOR ILLUSTRATION PURPOSES ONLY AND MUST NOT BE USED FOR FABRICATION OF POLES.
'DESIGN' IS A SPECIFIC EXCLUSION FROM THE SCOPE OF CALDERS & GRANDIDGE'S ISO CERTIFICATION.