

DRILLINGS 22mm DIA.

POSITION OF ANTI-SPLIT BOLTS IF
REQUIRED

ANTI SPLIT
BOLT HOLES
REQ'D

CHAMFER TO 340mm FROM TOP ONLY
BOTTOM HOLE NOT REQUIRED

**GOUGE
MARK**

8.5	LENGTH OF POLE IN METRES
S	GRADE OF POLE (L, M, S)
SPFI	TIMBER SPECIES AND COUNTRY OF ORIGIN
90	YEAR OF CREOSOTING (1990)
ABC	SUPPLIER'S MARK

UNLESS OTHERWISE SPECIFIED POLES TO
BE NOTCHED FOR BLOCKS AS FOLLOWS:-
MEDIUM POLE - TOP BLOCK ONLY
STOUT POLE - BOTH BLOCKS
DRILLING FOR BLOCK BOLT TO BE
CARRIED OUT ON SITE AS REQUIRED

POLE LENGTH (m)	'A' (m)
8.5 – 11	1.9
11.5 – 12	1.7
13 – 15	1.4
16 – 18	1.1
20	0.5

ALL DIMENSIONS IN MILLIMETRES
UNLESS OTHERWISE SHOWN

POLE SIZE TO BE IMPRESSED
ON THE POLE BUTT

Date	12.09.91	Title SINGLE POLE DRILLING, SCARFING & MARKING				 PERTH				
Drawn	W.J.B.									
Checked										
Approved		Project	11 & 33KV WOOD POLE OVERHEAD LINE SPECIFICATION	Drawing Number	501/1109/0205		Sht. No.	EP	Rev.	1
Scale										