



POLE SCARFED ON BOTH SIDES
DRILLINGS 22mm DIA

NOTES:—

1. ALL DIMENSIONS ARE IN MILLIMETRES, UNLESS OTHERWISE SHOWN.
2. ALL POLE DRILLINGS ABOVE GROUND LEVEL WHICH ARE NOT USED, MUST BE PLUGGED WITH APPROVED WOOD POLE PLUGS



MARKING GENERALLY AS BS1990

- 1. LENGTH AND DIAMETER OR CLASS AT 1500mm
2. CHARACTERS TO BE GOUGED OR BRANDED
5mm WIDE, 3mm DEEP AND 25mm HIGH
AS A MINIMUM
- 3. POLE TOP DIAMETER
- 4. TIMBER SPECIES, COUNTRY OF ORIGIN
- 5. YEAR OF PRESERVATION AND CHARGE No.
- 6. INITIALS OF SUPPLIER

POLE LENGTH (m)	DIM 'A' (m)
8.5 – 11.0	1.3
11.5 – 14.0	1.1
15.0 – 17.0	0.7
18.0 – 24.0	0.5



System Design, Drawing Office, 3 Prenton Way , Prenton , CH43 3ET
Telephone 0151 6092491

Drawn TA	Date 27/04/06
Checked LC	Date 09/05/09
Approved LC	Date 09/05/06

Title

DELTA 'H' POLE MEMBER DRILLING, SCARFING AND MARKING

	Location
--	----------

	Status
--	--------

FOR ISSUE

Drq. No.

SP4000875

Rev.

Rev.
2.0

© Copyright property of SP PowerSystems Ltd.

Scale

Size	A4
------	----