




# MTA

## AUDIO EDITOR

### User Manual

English Version

**Version: 0.2.0-103**

**Build: 20261004-04:18:00**

Alessandro De Salvo

braket71@gmail.com

<https://github.com/desalvo/mta-audio-editor>

License: EUPL-1.2

A real Digital Audio Workstation with full support for MTA and multitrack formats.



Digital Audio Workstation with MTA support



Windows



macOS



Linux



Android



iOS

MTA Audio Editor is a true **multitrack Digital Audio Workstation (DAW)** and does not require a project to be constrained to an MTA format. The **Multitrack DAW** project format is intended for unrestricted editing, mixing, effects and mastering; MTA8 and MTA16 remain available as dedicated project formats and export targets.

**MTA** means **Multi Track Audio**: a multitrack container that keeps musical parts separately addressable during playback. MTA Audio Editor can import and edit existing files, but it can also **create new MTA8/MTA16 files** from tracks or stems and export the completed project as **MTA, WAV, MP3 or FLAC**; individual tracks can be exported separately as WAV, MP3 or FLAC.

This manual covers the complete MTA Audio Editor workflow: access and platforms, projects, import, waveforms, editing, synchronization, mixing, effects, musical metadata, stem separation, MTA8/MTA16 export, desktop clients and mobile apps. Procedures include screenshots, diagrams and practical examples.

## Contents

- |                                          |                                           |
|------------------------------------------|-------------------------------------------|
| 1. Quick start                           | 13. Lyrics, Chords and Markers            |
| 2. Platforms and operating modes         | 14. Stem separation                       |
| 3. DAW workspace                         | 15. MTA8/MTA16 and device profiles        |
| 4. Projects, archives and autosave       | 16. MTA creation, export and slot mapping |
| 5. MTA and audio import                  | 17. Android and iOS/iPadOS                |
| 6. Waveforms and cache                   | 18. Windows and macOS                     |
| 7. Transport, buffering, sync and Follow | 19. Accounts, TOTP, security and sharing  |
| 8. Non-destructive editing               | 20. End-to-end examples                   |
| 9. Tracks, roles and MTA slots           | 21. Quick controls                        |
| 10. Live mixer and meters                | 22. Troubleshooting                       |
| 11. Insert FX, presets and controls      | 23. Glossary                              |
| 12. Auto Mix and master                  |                                           |

## 1. Quick start

Start by choosing how the project is created: empty, imported from an existing MTA, built from individual audio files, or generated from a stereo mix through stem separation. If the final destination is MTA, also choose MTA8/MTA16 and the target device profile.



Figure 1 - Project lifecycle. Source audio remains available while clips, events and processing are edited non-destructively.

- 1 **Open or create.** Use New project, Import MTA or Open project.
- 2 **Inspect tracks.** Check names, roles, synchronization, channels and waveforms.
- 3 **Edit and mix.** Work with the timeline, faders, pan, mute/solo and inserts while playing.
- 4 **Check Render.** Compare dynamic preview with the rendered master.
- 5 **Export.** Select the device profile and verify Click/Melody and slot mapping.

## 2. Platforms and operating modes

The project model and editor are shared across platforms; file handling differs by client.

| Platform               | Scenario                             | Files                                         | Processing                                       |
|------------------------|--------------------------------------|-----------------------------------------------|--------------------------------------------------|
| Browser / server       | Centralized and multi-user operation | Server workspace                              | Server-side FFmpeg, waveforms, stems and renders |
| Docker / Kubernetes    | Production and team deployments      | Persistent volume / PVC                       | Server-side                                      |
| Windows / macOS        | Local desktop workflow               | Native file pickers and bound project archive | Integrated local backend                         |
| Android / iOS / iPadOS | Mobile access to a server            | System file pickers and sharing               | Heavy operations remain on the server            |

**Mobile first launch:** the apps automatically use their preconfigured service. They do not ask for a server address and never display the built-in default address. Server settings can later store a custom address; only a user-configured custom value may be displayed and edited.

### 3. DAW workspace


The main screen follows a DAW layout: transport at the top, timeline and waveforms in the center, inspector on the right, mixer at the bottom, and musical event/import/export functions around the workspace.



Figure 2 - Real application workstation captured from the current build.



Real application view - Transport: start, rewind, Play/Pause, tempo, Render, Follow and zoom.



Real application view - Inspector: track properties, level, pan, type, MTA slot and insert chain.

### 3.1 Main panels

The **Timeline** manages clips and time selection. The **Inspector** edits the selected track. The **Mixer** provides a compact view of tracks and master. The larger vertical fader is the volume control; adjacent meters are reserved for realtime signal level, so no redundant static level bar is shown. **Lyrics/Chords/Markers** manage timed musical events.

### 3.2 Selection and state

The selected track provides context for insert editing, import/replace, split and single-track export. Mute, Solo, level, pan and FX state remain available in the mixer.

## 4. Projects, archives and autosave

---

The **Multitrack DAW** format is the recommended default for general editing and mixing: it does not constrain the project to 8 or 16 tracks. WAV, MP3 and FLAC export directly; when MTA export is selected, MTA8 or MTA16 is chosen and slot mapping is applied only for that output.

A project stores tracks, clips, waveform previews, events, inserts, mix settings, target format, MTA profile, view state and metadata. Source files and required attachments remain in the project workspace.

- 1 New desktop project.** Choose a name and save destination; the local archive is bound to the project.
- 2 Desktop MTA import.** A project destination is selected before import starts. Cancelling the dialog cancels the import.
- 3 Autosave.** Changes are automatically persisted when enabled; manual Save remains available.
- 4 Project Info.** Project/File - Project Info shows name, project ID, home/workspace, location, target, duration, track count, artist, BPM, key and MTA profile.

**Project archive versus MTA export:** the project archive contains editing information that does not necessarily belong in the final MTA.

## 5. MTA and audio import

---

MTA import creates editor tracks from the available audio streams, reads usable names/roles and supported attachments, and keeps the original source. Audio import can add a new track or replace the selected track.

| Operation          | Use                                              | Result                                      |
|--------------------|--------------------------------------------------|---------------------------------------------|
| Import MTA         | Start from an existing MTA                       | Project with available streams and metadata |
| Import Audio Track | Add a stem or part                               | New project track                           |
| Import & Replace   | Replace one part while preserving role/structure | New source on the selected track            |
| Import & Separate  | Start from a stereo mix                          | Demucs job and generated stems              |


**Example:** select Guitar, choose Import & Replace, check the entry point and Solo it with drums and bass. Fine-tune any offset by moving the track or editing its clip.

## 6. Waveforms and cache

Waveforms are graphical previews, not the audio source. They are calculated when required, stored in the project with a revision and loaded immediately when a project is reopened. Changes that invalidate the preview trigger recalculation.

**Important:** playback does not depend on waveform availability. Audio can play while waveform generation is still in progress.

## 7. Transport, buffering, synchronization and Follow



The |◀ control returns the transport and active sources to 00:00.000. Rewind/forward change position; Play starts or resumes; Pause keeps the current position; Stop closes the current preview session.

### 7.1 Dynamic preview

Before playback, all tracks are prepared and buffered. The UI reports **Buffering audio... please wait** and then synchronization. Playback starts only when sources are ready. A reference clock monitors drift and realigns active sources when necessary.

### 7.2 Render mode

Render plays a backend-generated master preview. Browser-live parameters remain immediate; changes that are baked into the master trigger an automatic refresh at the current position without a manual Stop/Play cycle.

### 7.3 Follow

Follow keeps the playhead visible in both dynamic and Render modes. In Render mode the rendered master explicitly acts as the transport clock.

## 8. Non-destructive editing




Figure 4 - Timeline and range selection.

Editing changes clip ranges and positions without rewriting the immutable source audio.

| Command             | Effect                                   | Typical use                 |
|---------------------|------------------------------------------|-----------------------------|
| Split               | Split a clip at the chosen point         | Create independent sections |
| Remove              | Remove a selected interval               | Delete noise or a part      |
| Ripple              | Close the gap by shifting later material | Shorten a section           |
| Delete song segment | Global cut plus event realignment        | Remove a verse/section      |
| Move track          | Apply a global time offset               | Correct alignment           |

## 9. Tracks, roles and MTA slots

Each track contains name, role/type, source, clips, channel information, volume, pan, mute/solo, inserts, waveform state and an **assigned MTA slot**. The Inspector exposes an editable **MTA Slot** field: **Auto** delegates placement to the device profile, while 1...8 or 1...16 stores the preferred output slot. The value is reused as the initial export mapping and is updated when the user confirms a mapping. Multiple tracks may share a slot when they must be mixed into one MTA output stream. Track roles remain important to Auto Mix and mapping; **click** identifies the metronome and melody the guide melody.

**Click identification:** explicit metadata and track name/role are preferred. Stream position alone is not sufficient because MTA8 device families use different Click/Melody orders.

## 10. Live mixer and VU meters




Figure 5 - Mixer and meters.

Track level, pan, mute/unmute, solo/unsolo and FX state can be changed while playback continues. Global Mute/Unmute, Solo/Unsolo and FX Bypass/Enable controls simplify mix comparisons.

RealTime meters monitor both tracks and master. In Render mode the per-track analyser path is separated from speaker output, so the master can remain the only audible stream while track meters still receive the real signal.

**Balancing example:** start playback, establish drums as a reference, balance bass and instruments, use Pan to create space, then check the master. No Stop/Play cycle is required for these changes.

## 11. Insert FX, presets and controls

Tracks and master support chains of up to 16 inserts. Available processors include normalization, compression, limiting, Delay, Lexicon-style Reverb, Room/Ambience, 32-band Graphic EQ, Amplify, Stereo Imager, Maximizer/Loudness, Mastering Wizard, De-Noise and Crackling Cleaner.

| Operation           | While playing                              |
|---------------------|--------------------------------------------|
| Bypass / Enable     | Applied automatically                      |
| Preset change       | The affected preview is refreshed          |
| Custom parameters   | Persisted and applied                      |
| Add / remove insert | The chain updates without manual Stop/Play |

Reverb Lexicon configuration

Presetlexicon-large-hall

Il preset selezionato viene applicato realmente alla catena audio. I controlli sotto servono per creare una configurazione custom.  
Custom values are validated server-side.

Size

0.72

0.1 ... 1

Mix

0.24

0.01 ... 0.7

Damping Hz

12000

3000 ... 18000

Custom preset name

My preset

Apply custom

Figure 6 - Real plugin editor: preset selection immediately refreshes the visible parameters and continuous values expose synchronized knob and numeric controls.

Changing a preset updates the plugin's visible parameters **immediately** to values appropriate for that preset: for example Slapback selects a short delay, Large Hall increases reverb size/mix, Wide increases stereo width and Strong raises noise/crackle reduction. Continuous parameters use a synchronized **rotary knob plus numeric input**;

MTA Audio Editor - 11 / 20

moving either control updates the other. A knob commits the value when the adjustment is released; a numeric input commits directly when **Enter** is pressed or when focus leaves the field. The 32-band graphic EQ keeps its dedicated faders. Factory presets can be complemented by user presets, and all parameters are validated by the backend.

## 12. Auto Mix and master

---

Auto Mix applies deterministic, role-aware balancing rules to track gains, pan and processing. It is reversible: enabling it stores a snapshot and disabling it restores that previous state.

**Recommended workflow:** use Auto Mix as a starting point, then manually refine the result while checking guide vocal/melody, Click, master dynamics and the densest sections of the song.

## 13. Lyrics, Chords and Markers

---

Lyrics, Chords and Markers are timed events independent of waveform previews. They can be populated from supported MTA data, edited in the project and shifted by global editing operations.

**Example:** add Intro, Verse, Chorus and Solo markers, timed chord symbols and lyric lines. A global song cut shifts later events together with the audio.


## 14. Stem separation

---

Import & Separate uses Demucs on the server. Long-running jobs continue server-side even if a mobile client is temporarily suspended. Results can create a new project or be added to the current project.

- 1 Select the stereo source.
- 2 Choose Multitrack DAW, MTA8, MTA16 or the current project.
- 3 Wait for server progress.
- 4 Rename and classify generated stems.
- 5 Add Click/Melody if available and synchronize.

# 15. MTA8/MTA16 and device profiles



**MTA (Multi Track Audio)** is a multitrack format containing audio streams plus metadata/ attachments. Device-specific export must preserve the real stream position, not only an internal logical slot label.

| Profile                                          | Click  | Melody | Behavior                      |
|--------------------------------------------------|--------|--------|-------------------------------|
| Merish5 / Xynthia2 - MTA8                        | 8      | 7      | Physical positions preserved  |
| B.Beat / B.Beat Plus / Evo / Pro16 / DIVO - MTA8 | 7      | 8      | Physical positions preserved  |
| M-Live MTA16 - corpus default                    | 1      | 9      | Suggested and always editable |
| Generic MTA                                      | Manual |        | No device-specific assumption |

**MTA16:** the available MTA16 samples consistently place Metronome in stream 1. Explicit Melody Track appears most often in stream 9 and in one sample in stream 10, so slot 9 is a practical default rather than a universal requirement.

## 16. MTA creation, export and slot mapping




Figure 8 - Real Export panel.

The application can **create a new MTA8 or MTA16 from scratch** as well as modify an imported MTA. A completed project can be exported as MTA, WAV, MP3 or FLAC, while each individual track can be exported separately as WAV, MP3 or FLAC. For MTA, select the device profile and verify slot mapping. When a project contains more tracks than the MTA capacity, multiple project tracks can be assigned to one output slot and mixed before container generation.

- 1 Choose MTA8 or MTA16.
- 2 Select the target device profile.
- 3 Check Click and Melody roles.
- 4 Review or customize slot mapping.
- 5 Export and test the result on the target device/firmware before live use.

**Silent slots:** when needed, export creates silent intermediate streams to preserve a physical position. Without them, an item assigned to slot 9 could become the fourth real stream.

## 17. Android and iOS/iPadOS




Figure 9 - Mobile connection and optional custom server configuration.

The mobile apps are native shells for the server UI. On first launch they connect automatically to the preconfigured service: installation and first launch never ask for a URL, and the built-in default address is never displayed.

Open **Server settings** only when using a different server. The input can display the custom value chosen by the user; selecting **Use default** removes that custom value and returns to the built-in service without exposing its address.

| Function | Android                  | iOS/iPadOS              |
|----------|--------------------------|-------------------------|
| Import   | Storage Access Framework | Document Picker / Files |
| Export   | Create Document          | Files / Document Picker |
| Sharing  | Sharesheet               | Share Sheet             |
| Session  | WebView cookies          | WKHTTPCookieStore       |

**Offline mode:** the mobile clients do not bundle full FFmpeg/PyTorch/Demucs runtimes. Rendering, stem separation and MTA generation require a reachable server.

## 18. Windows and macOS

---

Desktop clients run the local backend and native WebView. File choosers are provided by the operating system. macOS packages target both Intel and Apple Silicon; Windows can be packaged with an installer.

A local project archive binding is persisted across restarts. Save As can change its path. Native import/upload limits are configurable in Settings.

## 19. Accounts, TOTP, security and sharing

---

**Users, passwords, TOTP, email verification, roles and sharing apply to the online/server edition and to mobile apps.** Mobile apps connect to a cloud/remote server because heavy operations - FFmpeg rendering, MTA generation, waveform work and Demucs separation - run server-side; therefore they use the server account. In local native/desktop single-user mode authentication features are unnecessary and hidden, and processing/files stay on the user's computer.

**Recommendation:** public servers should use HTTPS, strong passwords, TOTP where appropriate, regular persistent-volume backups and upgrades validated through the production gate.

## 20. End-to-end examples

---

### 20.1 Prepare an MTA for a show

- 1 Import the MTA and save the project.
- 2 Check tracks, roles, Click/Melody and the device profile.
- 3 Start Play, wait for buffering, and adjust mixer/pan/FX live.
- 4 Enable Render and compare the master while keeping Follow and meters active.
- 5 Review Lyrics, Chords and Markers.
- 6 Export the MTA and validate it on the target device.

## 20.2 Build an MTA from a stereo mix

- 1 Create a project and run Import & Separate.
- 2 Classify the generated stems.
- 3 Import or create Click and Melody.
- 4 Correct offsets, then mix and process.
- 5 Choose MTA8/MTA16 and the device profile.
- 6 Review slot mapping and export.

## 20.3 Correct a track while the song plays

Solo the target track, change pan/level, bypass an insert and compare presets, then restore Solo. These operations are applied without a manual Stop/Play cycle; Render mode refreshes the required preview automatically.

## 21. Quick controls

| Action                  | Control                     |
|-------------------------|-----------------------------|
| Return to start         | ◀ transport button          |
| Play / Pause            | Transport Play/Pause        |
| Undo / Redo             | Standard platform shortcuts |
| Global Mute/Solo        | All controls in mixer       |
| Global FX bypass/enable | Global FX controls          |
| Project information     | Project/File - Project Info |

## 22. Troubleshooting

| Issue                                   | Check / action                                                                                    |
|-----------------------------------------|---------------------------------------------------------------------------------------------------|
| Play does not start immediately         | Wait for buffering/synchronization; the delay is intentional to keep tracks aligned.              |
| Tracks appear out of sync               | Seek, Resume or use  ◀; active sources are also continuously drift-corrected.                     |
| Follow does not scroll                  | Ensure Follow is enabled. It is supported in Render mode.                                         |
| Meters inactive in Render               | Enable RealTime meters; rendered metering is supported.                                           |
| Click routed to the wrong device output | Check track role, MTA profile and physical slot mapping.                                          |
| Waveform missing                        | Wait for waveform generation; playback remains available.                                         |
| Mobile app cannot connect               | If a custom server was configured, review it in Server settings or return to the default service. |
| MTA rejected by hardware                | Check MTA8/MTA16 target, profile, slot capacity and target firmware validation.                   |

## 23. Glossary

| Term            | Meaning                                                             |
|-----------------|---------------------------------------------------------------------|
| Clip            | A non-destructive time range referencing source audio.              |
| Track role      | Musical function used by Auto Mix and MTA mapping.                  |
| Click           | Metronome track.                                                    |
| Melody          | Guide melody track.                                                 |
| Dynamic preview | Separate client-side track playback with buffering/synchronization. |
| Render preview  | Backend-generated master preview.                                   |
| MTA slot        | Logical and, for profiles, physical stream position in the MTA.     |
| Stem            | Separated component of a mix.                                       |
| Attachment      | Embedded MTA data such as metadata or timed sections.               |

## Stem count

---

Stem separation offers **Auto / 2 / 4 / 6 / 8**. Auto is the default. The current iPhone/iPad build performs Demucs on the server; 8 stems requires a compatible extended backend model.

**On-device Demucs on iPhone/iPad.** Auto mode uses Core ML on the device when a compatible local model is available and falls back to the server otherwise. Models can be downloaded once from the server and reused offline. The current conservative on-device limit is 12 minutes per source file; longer material is processed by the server in Auto mode.

## Native updates and Demucs models

---

Native Windows, macOS, Android, iPhone and iPad applications check GitHub for newer versions. The **Stable** channel uses tagged releases only, while **Early release** also includes the rolling early-main prerelease produced by the latest successful main build.

On iPhone/iPad the app automatically provisions a default 4-stem Demucs Core ML model: it prefers a bundled validated model and otherwise downloads it from the configured server. SHA-256 fingerprints are compared with the server inventory and installed models are refreshed when the fingerprint changes. Once installed, the local model remains available offline.

On iOS/iPadOS application updates must still use TestFlight/App Store or another operating-system-authorized distribution mechanism.

## Automatic mobile Demucs model updates

---

The Docker/Kubernetes server periodically refreshes Core ML (iPhone/iPad) and ONNX (Android) model repositories from an HTTPS manifest, verifies SHA-256 and replaces files atomically. Mobile clients check the catalogue every six hours and at startup. **Update on Wi-Fi only** is enabled by default, so periodic model updates download only over Wi-Fi unless the switch is explicitly disabled. The baseline 4-stem model is provisioned at the first available network opportunity.

## Model-driven stem separation

---

Stem counts are no longer limited to 2/4/6/8. The list is generated from models actually available on the server or installed on the device and may include 10, 12, 16, or more stems. Multitrack DAW projects keep all tracks; MTA8/MTA16 constraints are handled only during export.

## Dynamic Demucs model management

---

The server periodically refreshes the full configured model catalogue, including official Demucs models available in the runtime and Core ML/ONNX artifacts published by the manifest. Mobile and desktop clients download the selected model on demand when splitting is requested. Local options can delete, re-download, or force-update one or more models. Administrators can blacklist a model: managed server artifacts are deleted and the model disappears from the web/client catalogue until it is removed from the blacklist.