Quorivio

Quorivio

ILLUSTRATED OPERATIONAL GUIDE · ADMINISTRATOR

Administrator guide

0.1.0-dev • RC283 · commit not recorded • Technical documentation | 9 November 2026



Quorivio · 0.1.0-dev · Build RC283 · commit not recorded
Alessandro De Salvo · braket71@gmail.com
2026-11-09 · EUPL-1.2 · https://github.com/desalvo/quorivio
Linux amd64/arm64 server (Docker, Podman, Kubernetes). Web clients on Windows, macOS, Linux, iOS and Android.
Indicative evaluation minimum: 2 vCPU, 4 GiB RAM, 20 GiB disk plus persistent data; benchmark production sizing.

> FIGURES: labelled reconstructions; live screenshots only with verified evidence
> RC283 edition; security and real infrastructure certifications remain separate.

Contents

32 chapters · Edition RC283

1. Architecture and responsibilities 3
2. Pre-installation checklist 4
3. Docker Compose deployment 5
4. Kubernetes and Helm 6
5. Standalone Kubernetes wizard 7
6. PostgreSQL 18, migrations and consistency 8
7. Full-instance backup 9
8. Helm backup configuration 10
9. Restore and disaster recovery 12
10. Local identity and account approval 13
11. LDAP/LDAPS and Active Directory 14
12. SMTP, OAuth/OIDC and MFA 15
13. Operation audit and retention 16
14. Advanced server settings 17
15. Monitoring, capacity and HA 18
16. Security and GDPR by design 19
17. Upgrades, CI and image publication 20
18. Administrator troubleshooting 21
19. Operational acceptance checklist 22
20. Technical references and outstanding work 23
Appendix A. Backup storage decision matrix 24
Appendix B. Monthly backup verification workflow 25
Appendix C. NFS and S3 setup checks 26
Appendix D. LDAP approval: from valid password to authorized access 27
Appendix E. Audit search and purge procedure 28
Appendix F. Credential lifecycle 29
Appendix G. Multi-replica ingress acceptance 30
Appendix H. Release-candidate change-management workflow 31
Appendix I. Authentic screenshots and quick reference 32
Appendix L. Kubernetes horizontal scaling: operator runbook 33
Appendix M. Disaster Recovery: stepwise operational runbook 34
Compatibility and indicative hardware planning sheet 35

1. Architecture and responsibilities

Quorivio 0.1.0-dev · Documentation build RC283 · 9 November 2026

Technical and operational manual for installation, configuration, identity management, backups, monitoring, audit logging, maintenance and disaster recovery. Procedures reflect the RC276 source and deployment charts; they do **not** certify a production environment. **Explanatory UI illustrations in earlier chapters are reconstructions**, labelled as such. When the CI-produced PDF includes the final gallery, it contains genuine screenshots of the disposable live application, verified against hashes and commit. Independent D5 editorial review remains required.

Quorivio combines a React/Vite frontend, Node/Express API, PostgreSQL 18 as the authoritative data store, WebSocket and PostgreSQL LISTEN/NOTIFY for live synchronization, persistent asset storage, an isolated PDF/PPTX converter and ClamAV for uploaded-file scanning. Deployment options include Compose, Helm and a standalone Kubernetes wizard. Multiple replicas require explicit validation of RWX storage, ingress, session continuity and data synchronization.

Component	Purpose	Operator check
API + frontend	Authentication, session editor, responses, exports	Readiness, HTTPS, version parity, audit.
PostgreSQL 18	Users, sessions, answers and configuration	TLS, backup, migrations, disk and restore.
Assets volume	Media, backgrounds, portraits and uploads	Persistence, ownership, quota and replication.
ClamAV	Upload malware scanning	Health, signature updates, production fail-closed behavior.
Converter	PDF/PPTX page import	Worker image, shared mount, private token, limits and logs.
Backup engine	Custom PostgreSQL dump + asset archive	Scratch space, destination, credentials, off-system retention.
SMTP/LDAP/OIDC	Identity and notifications	TLS, mapping, authorization and credential lifecycle.

Responsibility model: the instance operator determines infrastructure, legal basis, authorization, retention, backups and incident handling. A session owner manages that session; ownership does not imply cross-organization administrator rights.

2. Pre-installation checklist

1. Choose the external DNS name and provision a valid TLS certificate.
2. Decide between internal and external PostgreSQL and document upgrade responsibility.
3. Plan persistent asset storage (RWO for a suitable single replica; genuine RWX support for multiple replicas).
4. Generate unique secrets and keep them outside Git and unencrypted Helm values.
5. Provision a platform administrator and validate MFA and recovery procedures.
6. Set up SMTP, ClamAV and any LDAP/LDAPS or OAuth/OIDC providers to be used.
7. Enable only backup backends that can be reached and tested; perform an isolated restore drill.
8. Verify public ingress, service logs, disk alerts, account approval and retention policies.

A `0.1.0-dev` build must not be promoted to production on the strength of this manual alone. Review the current gate matrix and actual CI evidence separately.

3. Docker Compose deployment

The repository provides `compose.yaml`, `.env.compose.example`, `.env.example` and Dockerfiles. Create an environment file outside version control, separate database passwords from administrator credentials and provide durable volumes for PostgreSQL, the private `assets` directory and backups. Persistent records must never depend on an ephemeral container filesystem.

3.1 Important environment variables

Variable	Meaning and caution
`DATABASE_URL`	PostgreSQL endpoint and credentials; protect connections where appropriate.
`PUBLIC_BASE_URL`	External HTTPS URL used to generate join links and QR codes.
`ADMIN_EMAIL`, `ADMIN_PASSWORD`	Bootstrap administrator identity; rotate password and restrict exposure.
`NODE_ENV=production`	Production restrictions including mandatory antivirus scanning.
`SMTP_HOST/PORT/SECURE/USER/PASSWORD/FROM`	Outgoing notifications; implicit TLS for SMTPS when enabled.
`QUORIVIO_WORKER_TOKEN`	Strong private converter authentication token.
`QUORIVIO_AV_REQUIRED`	Antivirus requirement; not a production bypass switch.

3.2 Basic smoke test

Confirm API and DB readiness, ClamAV health and converter health when enabled. Sign in as administrator, create a disposable session, submit an answer from a separate browser and inspect authorized results. Restrict log access and avoid recording cookies, passwords, tokens or personal answer payloads.

4. Kubernetes and Helm

The chart lives in `helm/quorivio`. Use an environment-specific values file and an existing Kubernetes Secret for credentials. Inspect `helm template` output before deployment: ingress, mounts and resource requests must match the cluster. Helm cannot automatically supply a missing NFS service or CSI driver.

4.1 Principal chart options

Values key	Function
`image.repository`, `image.tag`, `image.pullPolicy`	Application image (`desalvo/quorivio`; `latest` on main).
`replicaCount`	Number of API pods, subject to state and storage constraints.
`existingSecret`	Name of the application's Kubernetes Secret.
`publicBaseUrl`	External public HTTPS URL.
`assets.existingClaim`	Existing PVC for durable assets.
`assets.accessMode/size/storageClassName`	Storage access mode, size and class.
`ingress.className/host/tlsSecret`	Routing and TLS termination.
`antivirus.image`	ClamAV pod sidecar image.
`converter.image`	Isolated conversion worker image.

4.2 NGINX and HAProxy ingress

Choose the ingress class actually installed in the cluster. NGINX and HAProxy Technologies have different conventions, including legacy HAProxy annotations in some deployments. Check request-size limits against the API, as well as timeouts and WebSocket upgrade handling. A correct ingress class alone does not prove public TLS reachability.

4.3 Persistent volumes and multiple replicas

`ReadWriteOnce` is not proof that several pods on different nodes can share writable assets. Use a genuinely RWX-capable storage backend when multiple API replicas need shared media. Test UID/GID, permissions, file locking, graceful termination, simultaneous migrations and reconnection after pod replacement. Do not raise `replicaCount` before completing these tests.

5. Standalone Kubernetes wizard

`tools/k8s_wizard.py` configures new or revised Kubernetes manifests for PostgreSQL, ingress, volumes, converter, LDAP and backups. **Never commit** generated Secrets or private overrides. For an installed cluster, generate into a separate directory, compare with the live desired state and retain custom converter and database patches.

Example with non-sensitive values:

```
python3 tools/k8s_wizard.py --no-self-update --unattended \
  --output ./k8s-generated \
  --set host=quorivio.example.org
kubectl kustomize ./k8s-generated > /tmp/quorivio-rendered.yaml
```

Do not supply `ldap_bind_password`, S3 secret keys or API tokens in command-line history. Rotate secrets in a controlled change window, review `kubectl diff`, and maintain a tested rollback procedure.

6. PostgreSQL 18, migrations and consistency

PostgreSQL stores identities, sessions, answers, audit and backup settings. Install `pg_dump`/`pg_restore` clients compatible with the server. A major version upgrade requires a supported upgrade or dump/restore procedure: changing the database image tag alone is not sufficient.

For an external database, verify host, port, `DATABASE_URL`, TLS certificate trust and server identity, SQL privileges, latency and availability. Do not disable certificate verification merely to silence connection errors. Internal deployments require durable PostgreSQL volumes and monitoring of WAL, indexes, tables, connection capacity and disk usage.

Test schema migrations on representative staging data. A successful SQL migration does not prove that referenced external asset files are present; validate an end-to-end session workflow afterward.

7. Full-instance backup

RC270 introduced **administrator full export**: PostgreSQL custom-format dump, persistent asset files, manifest and SHA-256 checksums in a compressed archive. In **Server configuration → Full backup**, an administrator can start a job or download a browser-delivered archive. The archive contains sensitive information; store it securely and apply appropriate encryption and access policies.

<figure>
<figcaption>Figure 1 — Reconstructed backup configuration: selected backend, schedule, manual execution, browser download and recent runs.</figcaption></figure>

7.1 Destinations and schedule

The current implementation supports **one active destination** for manual and scheduled operations, with a recurring interval of **1 to 720 hours**. The database coordinates scheduled claims across replicas. Recent run history records execution state; creating a job does not mean that a backup has succeeded. Browser download is independent of the stored remote destination.

Backend	Configuration	Prerequisites and risks
POSIX	Path beneath a deployment-mounted root	Writable PVC, permissions and capacity.
NFS	Existing PVC or direct NFS server/export mount	UID 1000 permission, node connectivity, RWX when needed.
S3 compatible	HTTPS endpoint, bucket, region, credentials	SigV4, multipart, minimal IAM scope and bucket lifecycle.
WebDAV	HTTPS URL, account and destination path	Verified TLS, writable remote service and quota policy.

7.2 Manual backup and browser download

Open Full backup, configure an authorized backend, verify that it is enabled in the deployment and choose **Run now**. Check the run history until completion; a returned job ID is only an acknowledgement. Use the administrator browser export for a local archive. Validate the manifest, SHA-256 values and the archive contents before considering the copy usable.

7.3 Scheduler operations

Enable scheduling, choose an interval suited to database size and temporary storage and monitor timestamps, sizes and error codes. A green backup status is not a recovery guarantee until a restore drill succeeds. Separate source database retention from off-site archive lifecycle and deletion rules.

8. Helm backup configuration

Deployment controls decide which storage backends can be mounted and used; administrators can manage only authorized targets in the UI.

Values path	Purpose
`backup.allowedBackends`	Remote backends enabled by deployment (initially S3/ WebDAV).
`backup.tmpSize`	Disk-backed scratch space for dump and compressed archive.
`backup.posix.enabled`	POSIX storage support.
`backup.posix.existingClaim`	Reuse a provisioned PVC.
`backup.posix.accessMode/size/storageClassName`	Define a new claim and its properties.
`backup.nfs.enabled`	NFS backend support.
`backup.nfs.existingClaim`	NFS storage exposed through an existing PVC.
`backup.nfs.server/path`	Direct remote NFS mount details.
`backup.bootstrap.enabled`	One-time initial target import if none exists.
`backup.bootstrap.intervalHours`	Initial scheduler interval.
`backup.bootstrap.existingSecret`	Secret holding `BACKUP_TARGET_JSON`.

Example containing **no credentials**:

```
backup:
  tmpSize: 20Gi
  allowedBackends: [s3, webdav]
  posix:
    enabled: true
    existingClaim: quorivio-backups
  nfs:
    enabled: false
  bootstrap:
    enabled: false
```

For a direct NFS mount provide `backup.nfs.server` and `backup.nfs.path`, then test visibility and write permission from inside the pod. Ensure scratch space can hold both the dump and the archive during construction; a disk-backed `emptyDir` also competes with node storage.

8.1 Secrets and encryption

Prefer a Kubernetes Secret containing the `BACKUP_TARGET_JSON` key, not plaintext credentials stored in Helm values or the shell. Once imported, backend configuration is encrypted at the application layer with AES-256-GCM using a key derived from the authentication secret. Application encryption does not replace Kubernetes RBAC, encrypted persistent volumes or encryption of exported archives.

9. Restore and disaster recovery

Full restore is offline and manual, not a dashboard restore button. Rehearse it in isolated staging before any production recovery.

1. Preserve the source environment and suspend writes or coordinate consistent database-and-asset snapshots.
2. Retrieve the archive from trusted storage and verify its manifest, contents and SHA-256 checksums.
3. Create an isolated replacement deployment with an empty PostgreSQL database and empty assets volume.
4. Extract the archive in a secured administrative environment and use a PostgreSQL-18-compatible `pg_restore` against the replacement database, not an active production database.
5. Restore asset files with appropriate ownership and permissions, start services and check schema, file references, account logins, sessions, answers and APIs.
6. Measure actual data loss and elapsed restore time against organizational RPO/RTO; record observations, deviations and remediation.

Recovery limitations: database dumping and asset collection do not form a simultaneous atomic snapshot; multiple schedules, automatic remote archive retention and dashboard restore are not implemented. Remote storage lifecycle and archive encryption need separate operational controls. Never run destructive `pg_restore --clean` against a live instance without approval, rollback and an independent rehearsal.

10. Local identity and account approval

The server administrator manages users in the **server settings/user administration** area. A new local or LDAP registration remains **pending** until approved. Valid credentials do not bypass this gate. Assign the least privileged role needed for the person's job and reserve platform administrator rights for explicitly authorized operators.

With SMTP configured, new requests notify approved platform administrators. If email is unavailable, the pending account must remain pending; the administration UI remains the authoritative review queue.

11. LDAP/LDAPS and Active Directory

11.1 Secure configuration

An optional service bind supports scoped directory search; an end-user bind validates the user's real password. Prefer validated `ldaps://` or STARTTLS over `ldap://`. Use a carefully scoped lookup filter, stable external identifier and appropriate base DN. Never link an external identity to a local account simply because email strings match.

Wizard setting	Meaning
`ldap_enabled`, `ldap_url`	Enable provider and specify LDAP/LDAPS endpoint.
`ldap_bind_dn`, `ldap_bind_password`	Service bind identity and secret.
`ldap_base_dn`, `ldap_user_filter`	Base DN and filtered lookup using `{login}`.
`ldap_id_attribute`	Stable identifier (`entryUUID`; `objectGUID` often for AD).
`ldap_email_attribute`, `ldap_group_attribute`	Email and group information.
`ldap_admin_group_dn`, `ldap_presenter_group_dn`	Group hints; do not override Quorivio approval.
`ldap_auto_provision`, `ldap_organization_id`	Optional creation of pending accounts and associated organization.
`ldap_starttls`, `ldap_tls_ca_file`	STARTTLS and a private CA file actually mounted in the pod.

11.2 LDAP self-registration

A user provides directory credentials; Quorivio performs a secure bind and creates a linked identity with `approved=false`. The administrator reviews the request, validates ownership and grants or denies access. LDAP group changes do not silently upgrade a manually approved Quorivio role.

11.3 Administrative lookup and approval

In user administration, choose **Search LDAP**, find the account using the service bind, verify the unique directory identifier, assign a role and authorize the linked user. An identity already linked to a Quorivio account must not be auto-reassigned or duplicated. Review the audit record for the decision.

<figure><figcaption>Figure 2 — Reconstructed LDAP lookup and approval; no real directory identities are displayed.</figcaption></figure>

12. SMTP, OAuth/OIDC and MFA

SMTP supports approval notices, recovery and operational alerts. Configure host, port, TLS, sender identity and authentication; test actual delivery and failure handling without logging secrets.

Cross-replica authorization state (security and HA). OAuth state is stored in PostgreSQL and consumed once across replicas. For both OIDC and social OAuth, the server inserts only a hash of the random `state` in the `auth_flows` table, with an expiration time of five minutes and the provider identity. A callback consumes the record atomically using `DELETE FROM auth_flows ... RETURNING`, checks the matching browser state cookie and provider, and rejects expired, missing or reused state. Never store this state only in a worker's memory: callbacks can reach any API replica through the ingress. Confirm during a rolling restart/failover drill that an OAuth/OIDC flow can complete through another replica, while replaying the same callback is rejected. Keep the PostgreSQL connection available on every replica, HTTPS callbacks and secure cookies enabled, and never record authorization codes, secrets or state values in logs. This is an implementation contract, not evidence that a particular external identity provider has been certified.

OAuth/OIDC supports configured providers such as Google, GitHub, Facebook or generic identity providers, subject to HTTPS callbacks and provider-specific credentials. Validate `state`, redirect URIs and explicit account linking: matching email addresses is not evidence of identity ownership. TOTP MFA and recovery codes must follow the deployment's security policy. Administrative MFA reset must include strong authorization and relevant session revocation.

13. Operation audit and retention

The operation audit includes actor, timestamp, action, resource and outcome without storing passwords, cookies, tokens, IP addresses or full participant answer contents. Authorized administrators may search by user, resource/UUID and action, paginate records, and configure retention from **7 to 3650 days**.

Manual purge removes rows older than the selected threshold; automatic periodic purging follows the configured policy. Before shortening retention, reconcile incident-response requirements, legal obligations and any external log storage. The audit log is not an SIEM replacement nor, by itself, proof of GDPR compliance.

14. Advanced server settings

Area	Main operator action	Recommended check
Public URL and QR	Configure `PUBLIC_BASE_URL` / server setting	Regenerate previously exported QR and test invitations.
PDF/PPTX converter	Worker enablement, image, token and mount	Real import, 413/415/503 responses and cleanup.
ClamAV	Sidecar health and scan policy	Benign file and safe EICAR test in an isolated environment.
Storage	PVC, quotas, cleanup and disk state	Simulated low space and notification delivery.
Email	SMTP and operational notices	Successful and failed deliveries; pending approvals unaffected.
Profiles	Pictures, Gravatar and replacement	HTTPS sources, image rights and private asset permissions.
Users	Approve, role assignment, revoke, external link	Session revocation and least privilege.
Backup	Target, schedule, run log and export	Isolated restore, integrity and archive lifecycle.

15. Monitoring, capacity and HA

Monitor `/api/health/live` and `/api/health/ready`, PostgreSQL health, asset/conversion volume utilization, node capacity, ingress reachability and replica restarts. The logical `pg_database_size` value does **not** include all physical PostgreSQL files, including WAL; do not use it as the sole disk-capacity signal.

Disk alerts can be emailed to administrators if SMTP works. Test multi-pod behavior, single-replica failure, converter restart and certificate renewal. Use the project's load-testing tools but do not treat a single laboratory result as a production SLA.

16. Security and GDPR by design

Enforce TLS, protected Secrets, organizational isolation, least privileges, session controls, audited operations and appropriate retention. Disable demo credentials and unused providers. Uploads must be scanned; do not bypass antivirus in production. Review archive privacy, backup access, retention and erasure procedures.

The controller must provide notices, lawful basis, retention policies, appropriate contracts with processors/subprocessors and any required DPIA. Software controls can assist but are **not GDPR or AGID certification**. Regularly review `npm audit`, Trivy scans and security test results.

Authorized 500-participant load exercise (staging only). Use `tools/live_500_answers.py` only against an installation that you administer and have explicitly approved for load testing. Prerequisites: a dedicated owner's demo session, a valid presenter login cookie supplied through `QUORIVIO_LOAD_PRESENTER_COOKIE`, sufficient capacity, a test window and an agreed rollback plan. The CLI requires `--base-url`, the exact `--confirm-host` and `--confirm-run`; outside loopback, HTTPS is mandatory. Optionally `--open-test-question` starts the designated demo question. The destructive `--reset-before` flag is allowed **only together with** `--open-test-question` and clears old demo votes/rotates the demo invitation: never use it on production participant data. A typical controlled exercise is:

```
# Run on your authorized staging host only; do not paste the presenter cookie here.
python3 tools/live_500_answers.py --base-url https://staging.example.org \
  --confirm-host staging.example.org --confirm-run --users 500 \
  --open-test-question --ramp-seconds 900 --json-out load-summary.json
```

Review success by comparing server-confirmed submissions to the expected 500 responses, watching presenter-visible counters, error rate and latency. Never interpret HTTP attempts alone as successful votes. Use `tools/load_500.py` separately for simultaneous WebSocket presence. Store only the sanitized aggregate report; **do not** include credentials, join tokens, names or session IDs in archived evidence. Optional Gravatar profile photos remain subject to user permissions, retention and image rights; avoid using real profile photos in synthetic load scenarios.

17. Upgrades, CI and image publication

The main branch uses the container tag **`latest`**; tagged versions use their corresponding tag names. Building an image is not the same as authorized publication, which is controlled by CI gates and workflow permissions. Do not push, tag or publish images outside a documented change procedure.

Before upgrading: produce and verify a backup, use reproducible `npm ci`, check Helm and schema changes, test on staging, prepare rollback and then update replicas. Historical SHA-256 inventories remain immutable; each new cycle gets a fresh current manifest matching the files actually committed.

18. Administrator troubleshooting

Issue	Likely area	Controlled action
LDAP login fails	Certificate, base DN, filter, bind, approval	Check TLS, lookup and user state without recording passwords.
No approval email	SMTP unavailable or delivery failure	Review private logs and pending account queue.
Backup failed	Credentials, quota, network, read-only mount, full scratch	Inspect run state, permissions and remote policy; retry safely.
Partial restore	Uncoordinated database and assets	Restart from clean staging targets and validated archive.
Converter returns 503	Worker missing or unhealthy	Health, token, shared mount and pod logs.
Upload denied	ClamAV down or scanner error	Restore scanner instead of bypassing it.
Results not propagated	WebSocket/DB/ingress or rejected answer	Check LISTEN/NOTIFY, activity state and live connections.
Wrong result data	Incorrect linked source or changed options	Verify IDs; do not rewrite historic votes casually.
CI inventory mismatch	File changed after manifest creation	Verify lockfile and hashes before install; use `npm ci`.

19. Operational acceptance checklist

- ☐ Image tags and application versions recorded across all pods.
- ☐ DNS, external HTTPS, ingress and WebSocket tested from outside the cluster.
- ☐ PostgreSQL 18 migrations and recovery tested, not just a ready probe.
- ☐ ClamAV fail-closed scanning and isolated converter both exercised.
- ☐ Real local/LDAP registration, administrator approval and SMTP notices validated.
- ☐ Administrator/presenter/user permissions and session revocation verified.
- ☐ Enabled POSIX/NFS/S3/WebDAV targets actually backed up and restored.
- ☐ Audit search, deletion and automatic retention reviewed.
- ☐ Live pages, editor and participant displays checked on real desktops and phones.
- ☐ Privacy, hardening, vulnerability scans and incident response reviewed independently.

20. Technical references and outstanding work

Source files: `helm/quorivio/values.yaml`, `tools/k8s_wizard.py`, `apps/api/src/schema.sql`, `apps/api/src/server.ts`, `docs/RC_CYCLE270_FULL_BACKUP_LDAP_AUDIT_RESULTS.it.md`, `docs/RC_CYCLE269_LDAP_OWNERSHIP_HOUSEKEEPING.it.md`, `docs/SECURITY.md`, `docs/DEVELOPMENT_STATUS.md`.

PVC: PersistentVolumeClaim. **RWX:** multi-node/pod writable storage when actually supported by the driver. **RPO/RTO:** data-loss and recovery-time objectives. **LDAP bind:** directory authentication. **MFA:** second authentication factor. **SigV4:** S3-compatible request signature. **Fail closed:** reject operation if a required security service is unavailable. **DR drill:** rehearsed disaster recovery.

Outstanding: automatic restore, multiple backup schedules, remote archive retention and real integrated acceptance with all external providers are not certified complete. The overall project baseline remains **85.25%** until independent gates are passed. UI illustrations are not evidence of a working deployment.

Appendix A. Backup storage decision matrix

Before selecting a backend, record database and asset sizes, desired interval, transfer costs, availability and encryption/retention requirements. Scratch capacity must handle intermediate files and the compressed archive. A multi-pod application must not perform concurrent full exports to a shared target without proper coordination.

Requirement	POSIX/PVC	NFS	S3	WebDAV
Mounted as a local path inside the pod	Yes	Yes	No	No
Requires a remote network service	Depends on CSI	Yes	Yes	Yes
Typical archive lifecycle support	Operator-managed	Server policy	Bucket lifecycle	Server-specific
API credentials stored by Quorivio	No	Generally no	Yes	Yes
Mandatory restore drill	Database + assets	Database + assets	Database + assets	Database + assets

<figure>
<figcaption>Figure 3 — Conceptual backup process. DB and assets are not captured atomically and full restore remains operator-driven.</figcaption></figure>

Appendix B. Monthly backup verification workflow

1. Sign in as an authorized administrator and inspect the recent execution history.
2. Check the destination's write permission, free capacity, credential expiry, network reachability and versioning/lifecycle policy.
3. Trigger a manual backup and wait for its final state, not just HTTP acceptance.
4. Compare file size, checksum and presence of the archive in the target storage.
5. Restore into a new isolated staging installation without concurrent writes.
6. Confirm a representative session, linked files, login behavior and results; record times, defects and the responsible operator.
7. Repeat after major DB, chart, storage or application version changes.

Maintain a recovery drill log outside the Quorivio database itself, since the database may be unavailable during an actual recovery.

Appendix C. NFS and S3 setup checks

A direct NFS mount needs a worker-reachable server/export and permissions for the actual application UID. Example **non-secret** Helm configuration:

```
backup:
  nfs:
    enabled: true
    server: nfs.example.org
    path: /exports/quorivio-backups
  posix:
    enabled: false
```

For S3, include `s3` in `backup.allowedBackends` and configure endpoint, bucket, region and credentials through the authorized UI or a Kubernetes bootstrap Secret. IAM should limit access to the required backup prefix. Verify multipart uploads, interrupted-upload cleanup and credential rotation. Avoid binding long-lived storage credentials to a personal employee account.

Appendix D. LDAP approval: from valid password to authorized access

1. The user selects LDAP self-registration and supplies directory credentials.
2. Quorivio uses validated LDAPS or STARTTLS, searches for a stable identity and checks the password with a user bind.
3. The linked Quorivio account is created with `approved=false`, even if directory authentication succeeds.
4. Configured SMTP notifies administrators; the account remains visible as pending.
5. An administrator checks identity and role need against organizational policy.
6. Only after approval may the user log in through LDAP; group changes do not override Quorivio authorization.

<figure>

Appendix E. Audit search and purge procedure

Open **Server configuration → Audit**, filter by actor, action or resource and constrain the time period. For an access-control incident, gather only the relevant entries and follow the incident evidence policy. Set approved retention between 7 and 3650 days; check legal holds, active investigations and log-backup policy before a manual purge.

Acceptance exercise: change one non-secret server setting under a test administrator, then locate timestamp, actor, normalized route and status in the audit log. Verify that password, cookie, body payload and participant answer content are absent. Shortening retention may trigger irreversible deletion and requires explicit review.

Appendix F. Credential lifecycle

Store passwords and API keys in Kubernetes Secrets or a dedicated secret manager, never in Git, public CI artifacts, tutorial manifests or shell history. Maintain a rotation register with credential type, owner, expiry and service impact. After rotating S3/WebDAV secrets, test a real backup. Preserve the knowledge needed to decrypt previously sealed backup configuration when changing application authentication secrets.

In a suspected compromise, revoke sessions and credentials, inspect relevant audit events, preserve minimal authorized evidence and activate incident response. Do not attempt remediation by making logs public or disabling TLS certificate verification.

Appendix G. Multi-replica ingress acceptance

A meaningful test uses at least two replicas on nodes supporting the declared RWX storage, HTTPS ingress, a running session, WebSocket-connected participants and a submitted answer while one replica is gracefully stopped. Check result convergence, reconnect behavior and ongoing access to attachments. Repeat using NGINX and HAProxy if both controllers are part of the supported deployment.

A successfully parsed Kubernetes manifest is not evidence of a functioning cluster. A valid YAML file may still fail because of absent CSI support, inaccessible NFS exports, invalid certificates or file permission errors.

Appendix H. Release-candidate change-management workflow

For every cumulative package: start from verified source, record changes since the latest acknowledged commit, regenerate docs, promote the current SHA-256 inventory, verify public manual copies, run preflight/TypeScript checks and then full CI. Distinguish **locally passed tests**, **GitHub Actions gates** and **real infrastructure acceptance evidence**.

When CI fails, identify the first failed step rather than only the summary job. Never disable meaningful safety tests to obtain a green status. A documentation cycle does not certify the runtime behavior it describes; a reconstructed UI screenshot is not live browser proof.

Appendix I. Authentic screenshots and quick reference

This gallery includes only genuine Chromium captures of a running Quorivio CI instance using disposable database records and synthetic identities. SHA-256 evidence ties them to the source commit. They are not illustration composites and do not imply production security or functional certification.

Authentic screenshots are generated by CI on a disposable server and published as job artifacts; this local edition embeds no unverified images.

Editorial note: initial rewritten edition RC277; live screenshot/metadata workflow updated in RC278.

Appendix L. Kubernetes horizontal scaling: operator runbook

Prerequisites: two schedulable nodes, an actually functional RWX CSI backend for media, a shared PostgreSQL service, WebSocket-capable ingress and a sound backup destination. Declaring RWX in Helm cannot by itself provision RWX storage.

1. Take a verified full backup and perform a staging restore, recording the source commit, image tag and backup checksum.
2. Measure application, ClamAV and converter CPU/memory, WebSocket churn, PostgreSQL connections, p95 latency, media volume and scratch usage.
3. Prove read/write access on shared assets across **different** nodes with disposable test pods.
4. Review staging values, for example:

```
replicaCount: 2
enforceNodeDiversity: true
assets:
  existingClaim: quorivio-assets-rwx
  accessMode: ReadWriteMany
backup:
  allowedBackends: [s3, webdav]
  posix:
    enabled: false
```

1. Render the manifests with `helm template quorivio ./helm/quorivio -f values-staging.yaml`, review secrets and storage, then deploy using `helm upgrade --install quorivio ./helm/quorivio -n quorivio -f values-staging.yaml`.
2. Check `kubectl -n quorivio rollout status deployment/quorivio-quorivio` and `kubectl -n quorivio get pods -o wide`; inspect the PodDisruptionBudget and node placement.
3. Drive a live sample session from two browsers, terminate one replica in a controlled fashion, and measure reconnect time, media access, correct results and error rate. Roll back when any hard requirement is unmet.

The chart currently exposes `replicaCount` and resource requests/limits; this does **not** certify an HPA policy. Calibrate any autoscaler against database limits, WebSocket churn, throughput and a capacity test. Helm CPU/memory defaults are not production hardware minima.

Appendix M. Disaster Recovery: stepwise operational runbook

Stage	Operator action	Acceptance evidence
Plan	Define RPO/RTO, owner, clean latest backup and required secrets	Signed DR rehearsal log
Contain	Stop writes on the compromised site; preserve minimum incident evidence	Incident timeline
Rebuild	Provision clean PostgreSQL 18, media storage, application and secret services	Staging environment with least-privilege access
Restore database	Check archive SHA-256; apply `pg_restore` to a **new empty** test database	Expected tables and sample records
Restore media	Extract and validate assets with correct ownership/permissions	Uploaded pictures, backgrounds and files load
Qualify	Exercise login, MFA/LDAP, editor, QR, WebSocket, AV, converter and backup	Browser and API checklist
Cut over	Change ingress/DNS only with operator approval and rollback plan	Actual RTO and data-loss measurement

A full application archive is **not** an atomic snapshot of database plus asset files. Reconcile time boundaries. Keep off-site encrypted backup retention outside the app, and preserve a protected backup of historic encryption keys if required for restoring encrypted configuration. Never run destructive `pg_restore` flags against live production. Use `pg_restore --list dump.backup` for inventory first and `pg_restore --no-owner --no-privileges --dbname=quorivio_test dump.backup` only against a prepared disposable database.

Compatibility and indicative hardware planning sheet

Component	Deployment/client platforms	Indicative evaluation resources (verify on site)
Standalone/test server	Linux amd64/arm64 with Docker/ Podman and PostgreSQL 18	2 vCPU, 4 GiB RAM, 20 GiB system disk **plus** database, media and backup volumes
Multi-node Kubernetes/HA	Linux Kubernetes nodes with NGINX/ HAProxy ingress and actual RWX storage	At least 2 independent nodes for HA rehearsals; consider 4 vCPU/8 GiB per node as a benchmark starting point
Desktop browser	Current Chrome/Chromium, Firefox, Edge, Safari on Windows/macOS/ Linux	Modern CPU, approximately 2 GiB free for the browser and an appropriate screen; presentation requires higher resolution
Smartphone/tablet	Current Android/iOS/iPadOS browsers	Approximately 2 GiB available RAM and a viewport of at least 360 CSS px recommended, reliable network

These are **planning assumptions for evaluation**, not officially certified hardware minimums. Size production according to a documented concurrency/media/bandwidth benchmark. Antivirus, conversion services and backup jobs add substantial CPU, memory and storage requirements. Validate browser/mobile compatibility against the real same-build CI matrix before deployment.