

Academic year
2025 - 2026

Exam Programming: PINN

Using Physics Informed Neural Networks to solve nonlinear Partial Differential Equations

Des De Borger



University of Antwerp
| Faculty of Science

Contents

1	Introduction	1
2	Damped Harmonic Oscillator	3
2.1	Analytic solution	3
2.2	Understanding the PINN example	5
2.2.1	Questions on the method	5
2.2.2	Questions on the code	10
2.3	Improving the example code	15
2.3.1	Code improvements	15
2.3.2	Code demonstration	18
2.3.3	Comparison between blind and physics informed extrapolation	21
2.3.4	Comparison with traditional ML model	22
2.3.5	Hyperparameter optimisation	23
2.4	Inverse problem	23
2.4.1	Overdamped case	23
2.4.2	Critically damped case	24
2.4.3	Underdamped case	25
2.4.4	Statistical analysis	26
2.4.5	Discussion	27
3	Burger's Equation	29
3.1	Ground truth solving strategies	29
3.1.1	Numerical PDE solvers	29
3.1.2	Cole-Hopf Transformation	29
3.2	PINNs for the Burger's equation	29
3.2.1	Code implementation	29
3.2.2	Code demonstration	29
3.2.3	Comparison between blind and physics informed extrapolation	29
3.2.4	Comparison with traditional ML model	29
3.2.5	Hyperparameter optimisation	29
3.3	Inverse problem	29
3.3.1	Underdamped case	29
3.3.2	Critically damped case	29
3.3.3	Overdamped case	29
3.3.4	Statistical analysis	29
3.3.5	Discussion	29
4	Conclusion	31

1 Introduction

2 Damped Harmonic Oscillator

In this chapter, we will apply PINNs to solve the damped harmonic oscillator, a secondary order ODE which describes oscillatory motion with friction. The code for this chapter can be found in the `Damped_Oscillator` directory.

2.1 Analytic solution

The central equation we are trying to solve is given by:

$$my''(t) + cy'(t) + ky(t) = 0 \quad (2.1)$$

This is a second order linear ordinary differential equation. The formal solution of this equation can be found by substituting $y(t) = e^{rt}$ and solving the characteristic equation:

$$mr^2 + cr + k = 0 \quad (2.2)$$

The roots of this equation are given by:

$$r_{1,2} = \frac{-c \pm \sqrt{c^2 - 4mk}}{2m} \quad (2.3)$$

It can be useful to introduce the parameters $\omega_0 = \sqrt{k/m}$ and $\zeta = c/(2\sqrt{mk})$, in which case the roots of the equation become:

$$r_{1,2} = -\zeta\omega_0 \pm \omega_0\sqrt{\zeta^2 - 1} \quad (2.4)$$

We can distinguish three cases based on the value of the discriminant $D = c^2 - 4mk$ and ζ . Figures 2.1 to 2.3 illustrate these cases.

Overdamped If $D > 0$ ($\zeta > 1$), the roots are real and the solution is given by:

$$y(t) = Ae^{r_1 t} + Be^{r_2 t} \quad (2.5)$$

Where $r_1, r_2 < 0$ are real and A and B are constants determined by the initial conditions $y(0) = y_0$ and $y'(0) = dy_0$:

$$\begin{aligned} A &= \frac{dy_0 - r_2 y_0}{r_1 - r_2} \\ B &= \frac{-dy_0 + r_1 y_0}{r_1 - r_2} \end{aligned} \quad (2.6)$$

Critically damped if $D = 0$ ($\zeta = 1$), the roots $r_1 = r_2 = r = -\zeta\omega_0$ are negative, real and equal. A second linearly independent solution is then given by te^{rt} , so the general solution is given by:

$$y(t) = (A + Bt)e^{rt} \quad (2.7)$$

The constants A and B are again determined by the initial conditions:

$$\begin{aligned} A &= y_0 \\ B &= dy_0 - ry_0 \end{aligned} \quad (2.8)$$

Underdamped if $D < 0$ ($\zeta < 1$), the roots r_1 and r_2 are complex conjugates, whose complex parts are conventionally expressed as $\omega_d = \omega_0 \sqrt{1 - \zeta^2}$, so that the roots can be expressed as $r_{1,2} = -\zeta \omega_0 \pm i \omega_d$. The solution is then given by:

$$y(t) = e^{-\zeta \omega_0 t} (A \cos(\omega_d t) + B \sin(\omega_d t)) \quad (2.9)$$

The constants A and B are again determined by the initial conditions:

$$\begin{aligned} A &= y_0 \\ B &= \frac{dy_0 + \zeta \omega_0 y_0}{\omega_d} \end{aligned} \quad (2.10)$$




Figure 2.1: Analytic solution for the overdamped harmonic oscillator.




Figure 2.2: Analytic solution for the critically damped harmonic oscillator.




Figure 2.3: Analytic solution for the underdamped harmonic oscillator.

2.2 Understanding the PINN example

In this section, we will study the provided code `pinn_spring_damper.py` and attempt to respond to the questions about the method and the code. The provided example trains a standard ML model and a PINN to solve the underdamped case of the damped harmonic oscillator. The models in question are trained on 15 noisy observation points, which are supplemented with the initial conditions and the physics residual at 200 evenly spaced collocation points in the case for the PINN.

2.2.1 Questions on the method

Question 1

Identify the total loss function in the code and write its expression down in your report. Identify the different contributions to the loss function.

The total loss function has three terms and is displayed below:

$$\mathcal{L}_{tot} = \mathcal{L}_{data} + \lambda_{physics} \mathcal{L}_{physics} + \lambda_{i.c.} \mathcal{L}_{i.c.} \quad (2.11)$$

The first term is the mean squared error of the predicted data compared to the 15 noisy observation points:

$$\mathcal{L}_{data} = \frac{1}{M} \sum_{j=1}^M (\hat{y}(t_j) - y_j)^2 \quad (2.12)$$

with $j = 1, 2, \dots, 15$. This term is the total loss function of a standard, non-PI NN and gives the model direct information about the correct solution of the equation with the relevant boundary conditions, but doesn't check for any non-physical behavior.

The second term is the mean squared residual of the ODE (see equation 2.1) at the 200 evenly spaced collocation points:

$$\mathcal{L}_{physics} = \frac{1}{N} \sum_{i=1}^N (m\hat{y}''(t_i) + c\hat{y}'(t_i) + k\hat{y}(t_i))^2 \quad (2.13)$$

with $i = 1, 2, \dots, 200$. This term gives the model information about how much the predicted solution violates the mechanics of the system, without checking if the predicted solution matches the observed data.

The third term is the sum of squared errors of the two initial conditions:

$$\mathcal{L}_{i.c.} = (\hat{y}(0) - y_0)^2 + (\hat{y}'(0) - dy_0)^2 \quad (2.14)$$

This term enforces the initial conditions and applies only to the very first point $t = 0$.

The constants $\lambda_{physics}$ and $\lambda_{i.c.}$ determine the relative weight of every term in the loss function. Because it is important that the initial conditions are met, $\lambda_{i.c.}$ is chosen at a much larger value than $\lambda_{physics}$. This is why in the given program, the values are set at $\lambda_{physics} = 0.01$ and $\lambda_{i.c.} = 10$.

Question 2

Is the inclusion of the initial condition loss essential for this particular example? When would it be essential?

To investigate the effect of the initial condition term, the term can be dropped out of the loss function to compare the results. Figure 2.4 shows the predicted solutions of the ODE if the $\mathcal{L}_{i.c.}$ is included and excluded. In this specific case, there does not seem to be a big difference which indicated that the initial condition loss is not essential. This is because the noisy observations point, which also contribute to the loss function, are close enough to $t = 0$ to give enough information for the model to accurately predict the initial conditions.




Figure 2.4: Predicted solutions to the ODE of the $\mathcal{L}_{i.c.}$ is included and excluded. In this specific case, the $\mathcal{L}_{i.c.}$ is not absolutely necessary, because the noisy observation points give enough information for the model to accurately predict the initial conditions.

We do not always have access to observations close to the initial time t_0 . However, if the initial conditions are known and need to be enforced, $\mathcal{L}_{i.c.}$ is a crucial term in the total loss function.

Question 3

The loss function used here is based on the mean squared errors (MSE) between predictions and data points or initial condition, and on the mean squared residual (MSR) of the PDE for the collocation points. Why are these specific functional forms used, and would there be alternative functions that could replace the MSE or MSR?

The mean square error and mean square residuals are the most commonly used loss functions for regression models. Any loss function has to be symmetrical and positive for all possible values, so that errors cannot cancel each other out. Furthermore, it is desired that the loss function is differentiable so that its gradient can be computed.

The MSE and MSR check both of these boxes. However, since the errors are squared before averaging, these functions heavily punish and are sensitive to large outliers. This can lead to problems when very noisy data points are included in the calculation for the loss function. However, this effect is good for the residuals since it is essential that the predicted solution does not break the laws of physics. There are alternative loss functions with different (dis)advantages [1]:

Mean Absolute Error The Mean Absolute Error (MAE) does not average the squares, but the absolute distances:

$$\mathcal{L}_{MAE} = \frac{1}{M} \sum_{j=1}^M |\hat{y}(t_j) - y_j| \quad (2.15)$$

Because the errors are not squared, this loss function is less sensitive to large outliers, which can make it more robust. However, it is not differentiable at zero, which can lead to problems for some optimisation algorithms.

Huber Loss The Huber Loss is a hybrid of the MAE and the MSE which is differentiable, but less sensitive to outliers than the MSE. It is defined as follows:

$$L_{\delta}(x) = \begin{cases} \frac{1}{2}x^2 & \text{if } |x| \leq \delta \\ \delta(|x| - \frac{1}{2}\delta) & \text{if } |x| \geq \delta \end{cases} \quad (2.16)$$

The Huber Loss behaves like the MSE for $|x| < \delta$ and like the MAE for $|x| > \delta$. The hyperparameter δ can be tuned to make the loss function more or less sensitive to outliers.

Question 4

What is the type of neural network used in this example? How many input nodes, output nodes and hidden layers does it have? How many parameters are then being optimized? What type of activation function is used and why? What quantity or quantities are provided at the input, and what quantity or quantities do we extract from the output of the network? Are the dimensions of this Neural Network architecture adequate, too small or too large for this example? How would you determine this?

We are trying to solve an ODE, which means to solve for a function $y(t)$. This function takes one input and returns one output, which means the network will also need to have one input and one output, representing the time and the function value respectively.

A dense network is used in this specific case. The parameters for the hidden layers can be given as inputs, in the example script there are 4 hidden layers of 32 nodes. For every connection between nodes has a weight, and every node (except the input) has a bias. From this we can calculate the total parameter count:

$$\begin{aligned} n &= \text{First layer weights} + \text{First layer bias} \\ &\quad + \text{Hidden layer weights} + \text{Hidden layer bias} \\ &\quad + \text{Last layer weights} + \text{Last layer bias} \\ &= (1 \cdot 32 + 32) + 3(32 \cdot 32 + 32) + (1 \cdot 32 + 1) = 3265 \text{ parameters} \end{aligned} \quad (2.17)$$

The dimensions of the network (the depth and layer size) are hyperparameters which should be tuned according to the specific problem needs to be solved by the model. Defining the optimal value for hyperparameters such as the dimensions is a relatively subjective and empirical process, since there are no general formulas that give the optimal hyperparameter set for every problem.

The activation function used is a tanh function. This choice is important; we will be calculating the first and second derivatives of the output y with respect to the input t , which means the activation function needs to be differentiable at least twice. for this reason, ex. ReLu is not suitable for this network.

Judging from the predicted solution, the model is large enough to make an accurate prediction for the solution to the equation. To optimise the network dimensions further, one can choose to implement an optimising algorithm which tunes the hyperparameters based on a validation set. This way, the accuracy and training time can be optimised in a reproducible way [5]. Examples possible methods include:

- Random search: for every hyperparameter, a range of evenly spaced values is defined. A model is trained for every single possible combination and their performances are compared.
- Random search: hyperparameter sets are chosen at random with user-defined ranges, and the best performing model is chosen from the resulting set of models.
- Bayesian optimization: a probabilistic sequential algorithm that optimises an unknown, computationally heavy function (such as the model performance).

Question 5

How many input samples are provided to the neural network model during each of its training cycles or epochs? What kind of samples are provided? Does the network receive again for each epoch the same exact samples? Would there be a better way to provide samples to this network for training over the various epochs?

The model receives the same 15 noisy observation points every single epoch. These points are used to calculate $\mathcal{L}_{data}$. Furthermore, the model receives the initial conditions to calculate $\mathcal{L}_{i.c.}$. The $\mathcal{L}_{physics}$ is calculated only using the residual of equation 2.1, for which no inputs are needed.

This is a suboptimal approach, since the model could simply memorize the 15 given points. A better approach would be to randomize the 15 points every epoch to avoid overtraining on a specific dataset. Furthermore, it would also be good practise to stop the inputting of datapoints after a defined number of epochs, so that the model is solely trained based on the equation residuals. This is even an even safer approach to avoid overtraining and is known as *curriculum training*. [6]

Question 6

The example uses the Adam algorithm as the so-called optimizer. What is the purpose of this optimizer? What is specific about the Adam algorithm, and what are its main hyper-parameters? Are there viable alternatives for the Adam optimizer?

An optimizer is a tool to accelerate the gradient descent by taking previously calculated gradients into account [2]. This way, the optimizer can avoid oscillations and avoid local minima. Adam is actually a combination of two alternative optimisers:

1. Momentum-based optimising [3]: this technishe incorporates the gradients of previous epochs by calculating an exponentially weighted moving average. If the gradient at epoch t is given by w_t , the momentum-based gradient m_t is calculated iteratively as follows:

$$m_t = \beta m_{t-1} + (1 - \beta) \nabla_{w_t} \mathcal{L}_{tot} \quad (2.18)$$

where β is the momentum factor, typically chosen as 0.9. This parameter determines how much the previous gradients need to be taken into account. The weights are then updated:

$$w_t = w_{t-1} - \alpha m_t \quad (2.19)$$

2. Root Mean Square Propagation [4]: this technique uses an exponentially weighted moving average of squared gradients to optimise the learning rate α . The learning rate is divided by a factor $\sqrt{v_t}$, the root (weighted)mean square of the gradients. This is also calculated iteratively:

$$v_t = \gamma v_{t-1} + (1 - \gamma) (\nabla_{w_t} \mathcal{L}_{tot})^2 \quad (2.20)$$

The weights are then updated:

$$w_t = w_{t-1} - \frac{\alpha}{\sqrt{v_t} + \epsilon} \nabla_{w_t} \mathcal{L}_{tot} \quad (2.21)$$

A small value is added in the denominator to avoid division by zero.

Both m and v are biased towards zero since they are initialized at zero. They need to be corrected:

$$\begin{aligned} \hat{m}_t &= \frac{m_t}{1 - \beta^t} \\ \hat{v}_t &= \frac{v_t}{1 - \gamma^t} \end{aligned} \quad (2.22)$$

The Adam optimiser combines these two techniques and updates the weights as follows:

$$w_t = w_{t-1} - \frac{\alpha}{\sqrt{\hat{v}_t} + \epsilon} \hat{m}_t \quad (2.23)$$

The Adam optimiser is widely used since it generally has an efficient performance with relative little hyperparameters; only α , β , and γ need to be defined. Both the learning rate and the gradient itself are made adaptive which helps to find the global minimum of the loss function more effectively. Alternative optimisers include the momentum-based and RMSprop techniques as discussed above, or Adamax (a variant of Adam based on the infinity norm) and Adagrad (which accumulated the gradients instead of using the weighted average).

Question 7

The example also uses an additional optimizer: a learning rate scheduler. What does this scheduler do? Is it a necessary ingredient for training a neural network? What are its main hyperparameters? Are there alternatives that can be usefully applied in this example?

The learning rate scheduler StepRL reduces the the learning rate with a factor γ after every n epochs, which are tunable hyperparameters. This adds a global decay, which can optimize the convergence in the different stages of optimisation. When the number of epochs is still small and the parameter set is still far from the optimum, the learning rate is big, but as the number of epochs gets bigger and the network converges towards the best set of parameters, the learning rate has to decrease as well in order to avoid oscillations around the minimum. This approach lead to a further acceleration of the gradient descent.

There exist many different alternative learning rate schedulers, such as:

1. ExponentialLR: similar to StepRL but applies a small decay factor γ after every epoch, leading to an exponentially decreasing learning rate.

2. CosineAnnealingLR: the learning rate follows a cosine curve which converges to a minimum value.
3. ReduceLROnPlateau: adaptive scheduler which applies a decay factor γ when improvement stagnates.
4. CyclicalLR: non-traditional learning rate scheduler which periodically increases and decreases the learning rate in order to avoid local minima.

In this specific case, StepLR or ExponentialLR are good choices to effectively train the model.

Question 8

How many epochs is the network trained for? How would you determine whether you have trained for too little or too many epochs?

The model is trained for 8000 epochs. In order to determine if this is too many/too little, we need to compare the test and training loss function curves as a function of the number of epochs. When these two curves start to diverge, it means the model is overfitting on the training set. The model is then learning meaningless details in the test set. In the provided script no validation dataset is implemented, which makes it impossible to detect overfitting in this way. A proper implementation would reserve a separate set of points, unseen during training, against which the loss is evaluated each epoch.

Question 9

Would it make sense to have a set of validation points? How would these look like? How would you use them?

This script does not have a set of validation points, which makes it difficult to gauge the accuracy of the model while taking the possibility of overtraining into account. The most representative way to determine the accuracy of the solution is to compare it directly to the analytic, exact solution. This can be done by defining a set of many evenly spaced values for t and calculating the analytic solution $y(t)$ at these points. This acts as the ground truth of the model. Then, the MSR between the predicted and ground truth datapoints can be calculated to give an idea of the accuracy of the model.

It could also be wise to split the validation points into two sets in order to more specifically investigate the model's ability to extrapolate beyond the range in which observation points were supplied. The set would then be split up into a set of extrapolated and non-extrapolated points. Then, the mean squared errors of both sets can be compared to analyse how much worse the predictions for the extrapolated region are.

2.2.2 Questions on the code

Question 1

Why are these two lines of code good, or bad, for:

```
torch.manual_seed(42)
np.random.seed(42)
```

These lines of code set the seed for the random number generation in the script. Using the same seed every time makes it so that the noisy observation points are exactly the same when the script is ran. This can make it easier to debug the script when a specific combination of observation points causes a bug.

It is however also important to occasionally test the script with different seeds. The model architecture and the script could become optimised for this specific seed if other seeds are never tested.

Question 2

What is the purpose of the `np.ndarray` statements in this function definition:

```
def analytic(t: np.ndarray) -> np.ndarray:
```

This is Python's type annotation syntax, as prescribed by PEP484 [9]. It tells the user which datatypes the input and output need to be. No typechecking happens at runtime, so this statement doesn't explicitly raise a `TypeError` if an object of the wrong type is passed. It serves as documentation and can help the developer to keep track of the precise definitions of every variable.

Question 3

The data points are created randomly and then sorted before being offered to the neural net, using this statement:

```
t_obs = np.sort(np.random.uniform(0.1, T_TRAIN, N_OBS))
```

Is this good or bad?

Randomizing the datapoints is good practise. A periodic set of points could lead the model to memorize specific patterns, instead of predicting the general solution to the initial condition. However, as said before, this script always passes the same set of random points which negates the advantage of randomizing the points in the first place.

The sorting of the points has no effect, since we are taking the MSE between the observation points and predicted points. The order in which the errors are summed has no effect on the loss function.

Question 4

The collocation points are created uniformly on a fixed grid, using this statement:

```
t_col = np.linspace(0.0, T_EXTRAP, N_COL)
```

Is this good or bad?

Using a uniform grid for the collocation points is not optimal, the model can fine-tune to the specific spacing of the collocation grid which is not desirable. It is better practise to generate the collocation points randomly at every epoch. By constantly regenerating a set of collocation points, any bias towards one region is also avoided.

Questions 5 and 6

What is this statement doing? Is it necessary?

```
optimiser.zero_grad()
```

What are these statements doing in the training cycle? Is their order important?

```
loss_total.backward()
optimiser.step()
scheduler.step()
```

This sequence of commands updates the model weights by calculating the gradients through back-propagation. `loss_total` is a 0-dimensional PyTorch tensor representing the loss function. The `loss_total.backward()` command will do a backward pass to see how the loss function changes with the model parameters (weights and biases), and apply the chain rule at every step in the calculation of `loss_total`. This results in a gradient which is *added* to the `.grad` attribute of every parameter. In other words, `loss_total.backward()` does not *save* the gradient, but *accumulates* the gradient. This means that the `.grad` attributes need to be set to zero before every backwards pass, which is exactly what `optimiser.zero_grad()` accomplishes. This statement is absolutely necessary, without it the gradients would be accumulated in the `.grad` attributes which causes the weights and biases to be updated incorrectly.

`optimiser.step()` will read the `.grad` attributes and update the m_t and v_t values for every parameter and update the parameters accordingly (see eq. 2.23). m_t and v_t are not zeroed by the `optimiser.zero_grad()` command, because otherwise it would be impossible to implement the Adam optimiser since the gradients at previous epochs are needed.

`scheduler.step()` changes the learning rate according to the specific scheduler used. In this case, an internal counter of the number of epochs is kept, and once this counter reaches a multiple of 3000, the learning rate is halved.

The order of these commands are crucial. The gradients must be set to zero first to avoid accumulation of gradients. The gradients must then be calculated to avoid using the gradients of the previous epoch to update the parameters. Finally, the fresh gradients are used to update the parameters. [7]

Question 7

Why do the collocation time input tensor and the initial condition time input tensor require the gradient option, while the input data tensors do not require a gradient?

```
t_obs_t = to_tensor(t_obs)
y_obs_t = to_tensor(y_obs)
t_col_t = to_tensor(t_col, requires_grad=True)
t_ic_t = to_tensor(t_ic, requires_grad=True)
```

The collocation points are used to calculate the MSR of the ODE as shown in equation 2.13, and the initial conditions are used to calculate the deviation from the predicted initial conditions as shown in equation 2.14. In both expressions of the loss function, the derivatives of $y(t)$ show up, so these need to be calculated.

Rather than using finite differences to calculate the derivatives at the collocation points and at $t = 0$, we can calculate the gradients during the forward pass through the model using `torch.autograd.grad`. This is more efficient since it allows for the simultaneous prediction of $y(t)$ and the calculation of the derivatives. However, we need to tell the model which derivatives with respect to t are required, which is done by the `requires_grad=True` statement. For the calculation of the MSE of the noisy observation points as in equation 2.12, no derivatives are needed, so the statement is omitted and `requires_grad` is set to the standard value `False`. [7]

Question 8

When presenting arrays of time points to the input of my neural network, I need to convert them into a pytorch tensor, using this helper function:

```
def to_tensor(arr, requires_grad=False):
    return torch.tensor(arr, dtype=torch.float32,
                        requires_grad=requires_grad).unsqueeze(1)
```

What does the `unsqueeze(1)` method of the `torch.tensor` class do, and why do I need to do this?

The `unsqueeze()` method takes a pytorch tensor of rank n and adds a dimension of depth 1 at a specified index, as shown on Figure 2.5. In this case, the helper function takes in a one-dimensional array of length n and returns a $(n, 1)$ `torch.tensor` class. This is necessary for two different reasons:

1. The time arrays (`t_obs_t` and `t_col_t`) which are used as inputs for forward passes through the network need to be $(n, 1)$ shaped in order to do matrix multiplication. The first `nn.Linear(1, 32)` layer of the network performs the following matrix multiplication:

$$y = xW^T + b \quad (2.24)$$

where x is the $n \times 1$ input of the first layer, consisting of n samples with 1 feature, which is the time value t . W and b are (32×1) column matrices containing the weights and biases¹ of the layer and y is the $n \times 32$ output. If we do not unsqueeze the time arrays, which correspond to x in this case, `nn.Linear(1, 32)` will interpret the $(n,)$ tensors as $(1, n)$ tensors, consisting of 1 sample with n features. This makes the matrix multiplication xW^T , which is $(1, n) \times (1, n)$ impossible. Note that the `t_ic_t` tensor does not need to be unsqueezed, since it is a $(1,)$ shaped tensor which cannot be interpreted incorrectly by the `nn.Linear(1, 32)` layer.

2. The `y_obs_t` unsqueezed tensor is not passed through the network, but rather is used to calculate the data loss $\mathcal{L}_{data}$ (see equation 2.12). When predicting the y values for the `t_obs_t` values, the model returns a $(n, 1)$ tensor (`y_pred`). In the code, the residual is calculated as `l_data = torch.mean((y_pred - y_obs_t) ** 2)`. If `y_obs_t` is not unsqueezed ($(n,)$ tensor), the $(n, 1) - (n,)$ operation will return a (n, n) tensor, containing *all* differences $\hat{y}_i - y_j$, instead of only the relevant errors $\hat{y}_i - y_i$. When averaging over these elements using `torch.mean`, it is averaging over differences and returns a loss which is not correct.

¹ b cannot actually be added directly to xW^T since the dimensions do not match. b is actually added to each row of the xW^T matrix.




Figure 2.5: Unsqueezing of a 2×2 tensor into $1 \times 2 \times 2$, $2 \times 1 \times 2$, and $2 \times 2 \times 1$ tensors by using the `unsqueeze()` method of the `torch.tensor` class. [8]

Question 9

When computing the first and second derivatives of $y(t)$ we use the `torch.autograd` method. Explain why the `grad_outputs` are set to ones and why we need to take the zero-th element `[0]` of this output in the statements below:

```
dy = torch.autograd.grad(
    y_hat, t,
    grad_outputs=torch.ones_like(y_hat),
    create_graph=True) [0]
```

The `torch.autograd.grad` differentiates an output vector $y = (y_1, \dots, y_n)$ with respect to an input vector $t = (t_1, \dots, t_n)$ and returns a vector-Jacobian product:

$$v^T J = v^T \begin{pmatrix} \frac{\partial y_1}{\partial t_1} & \dots & \frac{\partial y_1}{\partial t_n} \\ \vdots & \ddots & \vdots \\ \frac{\partial y_n}{\partial t_1} & \dots & \frac{\partial y_n}{\partial t_n} \end{pmatrix} \quad (2.25)$$

where v is set by `grad_outputs`. In our specific case, every value y_i only depends on the corresponding time value t_i , which makes the Jacobian a diagonal matrix. In order to contract the Jacobian to a column vector, v can be set to a row vector of ones with `grad_outputs=torch.ones_like(y_hat)`. The `torch.autograd.grad` actually returns a tuple $(dy,)$ per input, so to unpack it we can simply select the first and only element using `[0]`.

2.3 Improving the example code

Now that we have a good understanding of the code and have a better idea of how to improve the code, we will restart from scratch and make a new implementation of the code based on the provided example. In this section, I will discuss the improvements I have made, demonstrate the code for the three different damping cases, and discuss the results and effects of different factors. Finally, we will adapt the code to solve the inverse problem, where I attempt to extract the physical parameters of the system without passing them as explicit inputs to the model.

2.3.1 Code improvements

To begin, I will give a thorough overview of the improvements I have made to the code. These range from fundamental changes to the training process and code structure, to more minor changes to the plotting methods and helper functions.

2.3.1.1 File structure

While the original code was implemented in a single script, I have decided to split the different functionalities and steps into multiple files. The file structure is as follows:

Damped harmonic oscillator file structure	
Damped_Oscillator/	
-- config.py	- dataclass holding all physical constants, hyperparameters, runtime settings
-- data.py	- analytic solution and data generation for collocation points, observation points, and initial conditions
-- model.py	- FCNet architecture and predictor functions
-- losses.py	- loss functions for the training of the model
-- trainer.py	- training loop
-- plot.py	- all plotting functions
-- utils.py	- helper file for small functions

This file structure allows for a more modular code, which makes it more accessible and easier to maintain or debug. This also allows me to make multiple scripts for different experiments easily, since the necessary functionalities can simply be imported from the relevant files. The config.py file is especially useful, since it provides a dataclass that allows for the user to specify all parameters at once. This class can then be passed to the different functions and classes which automatically sets the correct parameters. Splitting the trainer script and the model architecture is also a flexible approach, since it allows for modular implementation of new models (ex. a model for the inverse problem, see section 2.4) or new training strategies (ex. curriculum training).

In order to train a model using these files, a separate script needs to be created. The workflow is as follows:

1. We check if there is a GPU available and set the device accordingly using the get_device helper from the utils.py file.
2. A Config object with user-defined parameters is created.
3. Data is generated based on the ground truth solution through the generate_data function from the data.py file. This includes the collocation points, observation points, and initial conditions.

4. A FCNet model, from the `model.py` file, is created based on the parameters in the `Config` object.
5. The model is trained using the `train` function from the `trainer.py` file, which takes the model, data and `Config` object as inputs.

In the rest of this report, we will design multiple of scripts like this to do different experiments. The code for these scripts can be found along with the rest of the aforementioned files in the `Damped_Oscillator` directory.

2.3.1.2 Randomising training data

In the provided example, the model is trained on a training set of 15 noisy observation points. The same training points are used at every single epoch, which could lead to the model overfitting or bias towards one region of the time domain as explained previously. To avoid this, I have chosen to randomise the observation points at every epoch. This gives the model more spread-out information about the entire time domain of the equation. I have chosen to keep these observation points noisy for two reasons:

1. Noisy observation points is more representative of real-world data, which is never perfectly clean. We are essentially producing 'fake' observation data for the model to train on, which is a technique that is widely used in the field of machine learning when the amount of real data is limited.
2. The noise can also be seen as a way of forcing the model to learn the physics of the system, rather than only memorising the numerical value of the provided observation points. This can avoid overfitting and lead to better results when extrapolating the model beyond the training domain.

Just like the observation points, the collocation points are also randomised. In the provided example the same dense evenly spaced grid of collocation points is used, in my code the set of collocation points is randomly chosen at every epoch. Since there are way more collocation points than observation points, this is more to avoid the model to fine-tune to the specific spacing of the collocation grid, which is not desirable.

2.3.1.3 Early stopping

In the provided example, the model is trained for a pre-set number of epochs. This is not optimal, since it could be possible that the model has already converged to an optimal set of parameters before all epochs have passed. To account for this, we need to implement an early stopping strategy which stops the training when the model has converged. For this, we need to choose a performance metric to monitor during the training, so that the training will stop when the metric has minimalised and the improvement has stalled.

The most representative way to determine the accuracy of the model is to compare the predicted solution to the exact analytic solution. The metric which we want to use is the mean squared error between the predicted and exact solution over the interval:

$$MSE = \int_0^{t_{end}} (y(t) - \hat{y}(t))^2 dt \quad (2.26)$$

In our case, this integral can be approximated by choosing a dense, evenly spaced grid and approximating the integral by the Riemann-sum over the interval:

$$MSE = \sum_{i=0}^N (y_i - \hat{y}(t_i))^2 \Delta t \quad (2.27)$$

This metric will be called the *validation loss*, annotated by $\mathcal{L}_{val.}$. The training will stop when the validation loss has stopped decreasing. We need to define two more parameters to get an efficient early stopping strategy:

1. The patience is defined as the number of epochs to wait after the last improvement (decrease of the validation loss) before stopping the training. This is necessary to avoid stopping too early, since it is possible that the validation fluctuates around (local) minima and further improvements can be made after more training epochs. If the patience is ran out, it means the model has not improved for a while and training can be safely stopped.
2. The patience threshold is defined as the minimum improvement in the validation loss to be considered a *notable* improvement. only if the improvement is large enough and notable, the patience counter will be reset. This avoids resetting the patience counter for minimal, insignificant improvements and makes the early stopping strategy more efficient.

Both of these parameters can be set in the `Config` class.

2.3.1.4 Model saving

Another improvement is the saving of the best model weights after every training run. This allows us to load the trained model later instead of retraining the model every time we want to make or show a prediction. Throughout the training loop, the weights that give the lowest validation loss are saved as a variable `best_state`. After the training has completed, these weights are passed as an output of the function along with the history of the different loss terms as a function of the epochs, and the prediction snapshots after a pre-set number of epochs. I have then created a helper function called `save_model` that saves these the relevant outputs to a folder. The model weights and snapshots are saved as `.pt` files, the history is saved as a `.csv` file, and the `Config` parameters are saved as a `.json` file.

A second helper function, `load_model`, is implemented to reload the best model weights from a specific training run and do predictions using those weights. This is done by creating a new `FCNet` using the saved `Config` parameters, after which the best weights are loaded into the model using the `load_state_dict` method. The loaded model is then returned along with the training history, snapshots and `Config` parameters. This model is then ready to be used to make predictions and plot results.

2.3.1.5 Plotting improvements

The plotting methods from the provided example are more or less reused with some small improvements. The following plotting methods are implemented in the `plot.py` file:

- A plot of the analytic ground truth solution of the differential equation (`plot_analytic`). This function is entirely implemented by me.
- A plot of the predicted solution using the best weights of the model, along with the analytic ground truth solution (`plot_predicted`). This function is entirely implemented by me.
- A plot of the saved snapshots, showing the predicted solution at different stages of the training process (`plot_epoch_figure`). This function is taken from the provided example.
- A plot of the different loss terms as a function of the epochs (`plot_loss_history`). This function is entirely implemented by me.
- A summary plot with six panels (`plot_summary`). This plot shows:
 1. The analytic solution with noisy observation points and the position of the collocation points².
 2. The analytic and predicted solutions on the training interval.

²These points are actually never used in training, but are generated after training has already finished. They do however give an intuitive idea of what the training set looks like, which is why I have chosen to plot these as well.

3. The training loss $\mathcal{L}_{tot}$ (logarithmic scale) as a function of the epochs.
4. The analytic and predicted solutions on the training and extrapolated interval.
5. The pointwise data residual, in other words the squared error between the predicted and observed values $(y_i - \hat{y}(t_i))^2$, as a function of time.
6. The squared ODE residual $|r(t)|^2$ as a function of time.

Panels 1, 2, 3, and 4 are copied from the provided example, while panels 5 and 6 are made by me (based on the original fifth panel, which showed the *absolute* error between the predicted and observed values).

These plotting methods are then wrapped in a single function called `save_model_plots`, which generated all of the above plots and saves them to a specified output folder. This function can be called at the end of a training loop with the model, training history, epoch snapshots, data, and Config parameters as inputs.

Alternatively, one can choose to save the outputs of the training loop to a folder and then call the `save_plots_from_file` function, which loads the saved model weights and saves all relevant plots to the same folder. This is my preferred approach, since the best model weights need to be saved in this way, which can be useful in the future for ex. comparing model performances.

2.3.2 Code demonstration

In this section, I will give a quick demonstration of three PINNs, used to predict the solution to each of the three damped cases. In all three examples, we will use the following hyperparameters:

Table 2.1: PINN Hyperparameters

Parameter	Description	Value
hidden	Hidden units per layer	64
n_layers	Number of hidden layers	5
n_epochs	Maximum training epochs	30000
lr	Initial learning rate	5×10^{-3}
patience	Early stopping patience	1000
patience_threshold	Min improvement to reset patience	1×10^{-5}

For now, these hyperparameters are chosen because they are observed to give good results. Section 2.3.5 will give a more quantitative analysis of the effect of the hyperparameters. Furthermore, the collocation points are chosen in the training *and* extrapolated domain. In this way, we are not actually making a fully blind prediction about the extrapolated domain, rather a physics informed prediction. This distinction will be further analysed in section 2.3.3. For brevity, I will only show the summary plots. All generated plots can be found in the `outputs` directory. Below, I will discuss each case separately.

2.3.2.1 Overdamped demonstration

For the overdamped case, I chose the following parameters:

Table 2.2: Overdamped parameters

Parameter	Value
ζ	1.5
ω_0	2

2.3. IMPROVING THE EXAMPLE CODE

The training was stopped early after ~ 1600 epochs and the final prediction yields $RMSE = 0.00485$. The results of the training are shown on Figure 2.6.




Figure 2.6: Summary plot for the overdamped case.

2.3.2.2 Critically damped demonstration

For the critically damped case, I chose the following parameters:

Table 2.3: Overdamped parameters

Parameter	Value
ζ	1
ω_0	2

The training was stopped early after ~ 1400 epochs and the final prediction yields $RMSE = 0.00480$. The results of the training are shown on Figure 2.7.




Figure 2.7: Summary plot for the critically damped case.

2.3.2.3 Underdamped demonstration

For the overdamped case, I chose the following parameters:

Table 2.4: Overdamped parameters

Parameter	Value
ζ	0.125
ω_0	2

The training was stopped early after ~ 4700 epochs and the final prediction yields $RMSE = 0.00562$. The results of the training are shown on Figure 2.8.

2.3. IMPROVING THE EXAMPLE CODE




Figure 2.8: Summary plot for the underdamped case.

2.3.3 Comparison between blind and physics informed extrapolation




Figure 2.9: Summary plot for a PINN without collocation points in the extrapolated domain. This leads to a fully blind prediction for $t > t_{dom}$.

2.3.4 Comparison with traditional ML model




Figure 2.10: Summary plot for a non-physics informed neural network.

2.3.5 Hyperparameter optimisation

2.4 Inverse problem

2.4.1 Overdamped case




Figure 2.11: Predicted solution and parameters for an overdamped harmonic oscillator with randomised parameters.




Figure 2.12: Parameter convergence to true values for an overdamped harmonic oscillator with randomised parameters.

2.4.2 Critically damped case




Figure 2.13: Predicted solution and parameters for a critically damped harmonic oscillator with randomised parameters.




Figure 2.14: Parameter convergence to true values for a critically damped harmonic oscillator with randomised parameters.

2.4.3 Underdamped case




Figure 2.15: Predicted solution and parameters for an underdamped harmonic oscillator with randomised parameters.




Figure 2.16: Parameter convergence to true values for an underdamped harmonic oscillator with randomised parameters.

2.4.4 Statistical analysis




Figure 2.17: Scatter plot of 2402 true and predicted ζ pairs for the damped harmonic oscillator.




Figure 2.18: Scatter plot of 2402 true and predicted ω_0 pairs for the damped harmonic oscillator.




Figure 2.19: Parameter space of 2402 true (ζ, ω_0) pairs and the $RMSE$ compared to the predicted values..

2.4.5 Discussion

3 Burger's Equation

3.1 Ground truth solving strategies

3.1.1 Numerical PDE solvers

3.1.2 Cole-Hopf Transformation

3.2 PINNs for the Burger's equation

3.2.1 Code implementation

3.2.2 Code demonstration

3.2.3 Comparison between blind and physics informed extrapolation

3.2.4 Comparison with traditional ML model

3.2.5 Hyperparameter optimisation

3.3 Inverse problem

3.3.1 Underdamped case

3.3.2 Critically damped case

3.3.3 Overdamped case

3.3.4 Statistical analysis

3.3.5 Discussion

4 Conclusion

Bibliography

- [1] GeeksforGeeks. Loss function for linear regression in machine learning, 2024. Accessed: 2026-05-06. 7
- [2] GeeksforGeeks. Adam optimizer, 2025. Accessed: 2026-05-07. 8
- [3] GeeksforGeeks. Momentum-based gradient optimizer, 2025. Accessed: 2026-05-07. 8
- [4] GeeksforGeeks. Rmsprop optimizer in deep learning, 2025. Accessed: 2026-05-07. 9
- [5] GeeksforGeeks. Hyperparameter tuning, 2026. Accessed: 2026-05-07. 8
- [6] Y. Guo, Z. Fu, J. Min, S. Lin, X. Liu, Y. F. Rashed, and X. Zhuang. Long-term simulation of physical and mechanical behaviors using curriculum-transfer-learning based physics-informed neural networks. 2025. Accessed: 2026-05-07. 8
- [7] PyTorch Contributors. *PyTorch Documentation, Version 2.11*. PyTorch, 2025. Accessed: 2026-05-12. 12, 13
- [8] Stack Overflow contributors. What does unsqueeze do in PyTorch?, 2019. Accessed: 2026-05-12. 14
- [9] G. van Rossum, J. Lehtosalo, and Ł. Langa. PEP 484 – type hints. Python Enhancement Proposal 484, Python Software Foundation, 2015. Status: Final. Python version: 3.5. 11