


Defending Your SQL Server Against Ransomware

Jeff Iannucci

Download all slides and scripts



Who in the world is Jeff Iannucci?




Consultant at Straight Path Solutions



Content Author at Pluralsight



Author of “Learn SQL in a Month of Lunches”











OpenAI agents hacked Hugging Face in 700-strong swarm, tried to cover tracks, investigations find

Gemini Hacked Three Companies in First Known Breakout by Google's AI

Three researchers, three days and about \$3,000 landed OpenAI's crown code jewels

What are we discussing today?

What exactly is ransomware?

Where are your biggest SQL Server vulnerabilities?

How can you prepare for ransomware?

What are we NOT discussing today?

Other cyber attacks

- Other malware
- Dedicated Denial of Service (DDoS)

Other data breaches

- Stolen data
- Publicly available data

Why should you care about ransomware?

“While half of organizations feel ‘very prepared’ to face ransomware, 78% experienced ransomware attacks last year...”

“...and fewer than 25% achieved recovery within a day...”

“...83% of organizations that paid ransoms were attacked again...”

“...93% lost data regardless of payment.”

– CrowdStrike State of Ransomware 2025 survey results

<https://go.crowdstrike.com/State-of-Ransomware-Survey.html>

SQL Server?

“The researchers note that the ransomware infection starts with the MS-SQL process on the compromised machine downloading a .NET file using cmd.exe and powershell.exe.”

Microsoft SQL servers hacked in TargetCompany ransomware attacks

By Bill Toulas

September 24, 2022 11:12 AM 1



Vulnerable Microsoft SQL servers are being targeted in a new wave of attacks with FARGO ransomware, security researchers are warning.

<https://www.bleepingcomputer.com/news/security/microsoft-sql-servers-hacked-in-targetcompany-ransomware-attacks/>

SQL Server?

“Once they gain access to the endpoint, the attackers will first install a piece of malware the researchers named CLR Shell. This malware picks up system information, changes the compromised account’s configuration, and escalates privileges to LocalSystem through a vulnerability in the Windows Secondary Logon Service.”

<https://www.techradar.com/news/microsoft-sql-servers-hacked-to-spread-ransomware>

Microsoft SQL servers hacked to spread ransomware

News

By Sead Fadilpašić published April 20, 2023

Hackers are after poorly configured Microsoft SQL servers



SQL Server?

“The attacks start with threat actors scanning for servers with an open TCP port 1433, which are likely public-facing MS-SQL servers. The attacker then carries out brute-forcing and dictionary attacks to crack the password. For the attack to work with either method, the target password has to be weak.”

<https://www.bleepingcomputer.com/news/security/vulnerable-microsoft-sql-servers-targeted-with-cobalt-strike/>

Vulnerable Microsoft SQL Servers targeted with Cobalt Strike

By **Bill Toulas**

February 22, 2022 01:08 PM 0



Threat analysts have observed a new wave of attacks installing Cobalt Strike beacons on vulnerable Microsoft SQL Servers, leading to deeper infiltration and subsequent malware infections.

Phase 1: Access

Login vulnerabilities



Principle of Zero Trust

Verify explicitly

- Always authenticate and authorize based on all available data points.

Assume breach

- Minimize blast radius and segment access. Verify end-to-end encryption and use analytics to get visibility, drive threat detection, and improve defenses.
- **Think “detect and contain”** – Andreas Wolter

<https://learn.microsoft.com/en-us/security/zero-trust/zero-trust-overview>

Is your SQL Server
public facing?


Should it be?

Is your firewall configured?

Do you know your IP?

Can you ping your server?

Can I ping your server?

A screenshot of a Windows Command Prompt window. The title bar reads "Command Prompt" with standard window controls. The text inside the window shows the Windows version and copyright information, followed by a command prompt where the user has entered the command "ping 10.20.101.202".

```
Microsoft Windows [Version 10.0.22631.3296]  
(c) Microsoft Corporation. All rights reserved.  
  
C:\Users\JeffIannucci>ping 10.20.101.202
```

The sa login is enabled

Every instance has/needs sa
...and it's in the sysadmin role
Most common attack point
Disabling = no connections
You can use sa when disabled

```
/* check to see if sa is disabled */  
SELECT
```

```
    name
```

```
    , is_disabled
```

```
FROM sys.server_principals
```

```
WHERE sid = 0x01;
```

```
/* disabled sa */
```

```
ALTER LOGIN [sa] DISABLE;
```

SQL Server logins

No MFA

Not identity specific

Limit permissions for logins

Create “secure” passwords



What is a “secure” password?

Number of Characters	Numbers Only	Lowercase Letters	Upper and Lowercase Letters	Numbers, Upper and Lowercase Letters	Numbers, Upper and Lowercase Letters, Symbols
4	Instantly	Instantly	Instantly	Instantly	Instantly
5	Instantly	Instantly	Instantly	Instantly	Instantly
6	Instantly	Instantly	Instantly	Instantly	Instantly
7	Instantly	Instantly	1 sec	2 secs	4 secs
8	Instantly	Instantly	28 secs	2 mins	5 mins
9	Instantly	3 secs	24 mins	2 hours	6 hours
10	Instantly	1 min	21 hours	5 days	2 weeks
11	Instantly	32 mins	1 month	10 months	3 years
12	1 sec	14 hours	6 years	53 years	226 years
13	5 secs	2 weeks	332 years	3k years	15k years
14	52 secs	1 year	17k years	202k years	1m years
15	9 mins	27 years	898k years	12m years	77m years
16	1 hour	713 years	46m years	779m years	5bn years
17	14 hours	18k years	2bn years	48bn years	380bn years
18	6 days	481k years	126bn years	2tn years	26tn years

<https://tech.co/password-managers/how-long-hacker-crack-password>

Password issues

Password is blank

Password is same as the login

Password is “password”

Yes, you can find these!

```
/* blank passwords */  
SELECT name  
FROM sys.sql_logins  
WHERE PWDCOMPARE('',password_hash)=1;
```

```
/* password same as login */  
SELECT name  
FROM sys.sql_logins  
WHERE PWDCOMPARE(name,password_hash)=1;
```

```
/* passwords is password */  
SELECT name  
FROM sys.sql_logins  
WHERE PWDCOMPARE('password',password_hash)=1;
```

SQL Login Audit should include failed logins

This IS the default.

Auditing failed logins can reveal hacking attempts

...and more!

Check your SQL Server logs

sp_readerrorlog

Server authentication

- ☐ Windows Authentication mode
- ☒ SQL Server and Windows Authentication mode

Login auditing

- ☐ None
- ☒ Failed logins only
- ☐ Successful logins only
- ☐ Both failed and successful logins

Server proxy account

☐ Enable server proxy account

Proxy account:

Password:

Options

But even if you do your best...

According to Sophos' "The State of Ransomware 2026" report, the leading causes of exploited vulnerabilities are:

- Malicious email (26%)
- Phishing (24%)
- Compromised credentials (23%)

Overall, 79% of attacks started with compromised identities.

(This includes other exploited vulnerabilities)

Phase 2: Infection

The quest for Privilege Escalation.



Principle of Least Privilege

Grant users account or processes only those privileges which are essentially vital to perform its intended functions.

- Database roles
- Instance roles
- Server roles

“Know your role...” – Dwayne “The Rock” Johnson

https://en.wikipedia.org/wiki/Principle_of_least_privilege

sysadmin role members

Members of sysadmin can do anything in SQL Server

Have you reviewed your current sysadmins?

Avoid SQL Server logins in this group

```
/* find members of sysadmin role */  
SELECT  
    name  
    ,type_desc  
    ,is_disabled  
FROM sys.server_principals  
WHERE IS_SRVROLEMEMBER ('sysadmin',name) = 1  
ORDER BY name
```

CONTROL SERVER permissions

Virtually identical to sysadmin
permissions

Can impersonate sysadmin
members

Often unnoticed

Why are you using this?

```
/* find logins with CONTROL SERVER */  
SELECT  
    name  
    ,type_desc  
    ,is_disabled  
FROM sys.server_principals AS pri  
WHERE pri.[principal_id] IN (  
    SELECT p.[grantee_principal_id]  
    FROM sys.server_permissions AS p  
    WHERE p.[state] IN ( 'G', 'W' )  
    AND p.[class] = 100  
    AND p.[type] = 'CL'  
    )  
AND pri.[name] NOT LIKE '###%###';
```

securityadmin role members

Members of securityadmin can NOT create or alter permissions for members of the sysadmin role

Can create logins with CONTROL SERVER permissions

Do you even need this role?

```
/* find members of securityadmin role */  
SELECT  
    name  
    ,type_desc  
    ,is_disabled  
FROM sys.server_principals  
WHERE IS_SRVROLEMEMBER ('securityadmin',name) = 1  
ORDER BY name
```


Local Administrators group members

Windows group

May already be in sysadmin role

Can add themselves to sysadmin role

<https://straightpathsql.com/archives/2023/08/adding-sql-server-access-when-youre-locked-out/>



Database roles and privilege escalation

- **db_owner** – can create objects that EXECUTE AS OWNER
- **CONTROL DATABASE*** – functionally equivalent to db_owner
- **db_securityadmin** – can add themselves to custom roles
- **db_accessadmin** – can grant access to other logins
- **db_ddladmin** – can create triggers to EXECUTE AS OWNER

TRUSTWORTHY database

Allows code in the database to execute in other databases.

Code is executed using the database owner's permissions.

Allows db_owner role members to execute as sysadmin.

Are your databases owned by sysadmin role members?

```
/* find TRUSTWORTHY databases owned by a sysadmin */  
SELECT  
    name  
    ,SUSER_SNAME(owner_sid) AS DatabaseOwner  
FROM sys.databases  
WHERE is_trustworthy_on = 1  
AND name <> 'msdb'  
AND IS_SRVROLEMEMBER ('sysadmin',SUSER_SNAME(owner_sid)) = 1  
ORDER BY name;
```

But...msdb is TRUSTWORTHY?

- Yes, and it's owned by sa
- Yes, you should leave it TRUSTWORTHY or your jobs may fail
- **Changing this “might result in unexpected behavior by SQL Server components that use the msdb database.”**

[TRUSTWORTHY database property - SQL Server | Microsoft Learn](#)

Cumulative updates

Contain vulnerability fixes

Apply GDRs too

Who do you think knows about these vulnerabilities?

<https://sqlserverupdates.com>

SQL Server 2017 Updates

Here's the release history for Microsoft SQL Server 2017. Each update is linked to its Microsoft knowledge base article with the download and the list of hotfixes included. Starting with SQL Server 2017, we only get Cumulative Updates and GDRs (security fixes), not Service Packs. That makes support end dates a little simpler:

- Mainstream support ended 2022/10/11
- Extended support ends 2027/10/12

Cumulative Update	Release Date	Build	Support Ends
GDR	2026/07/14	14.0.2120.1	2027/10/12
CU31 + GDR	2026/07/14	14.0.3540.1	2027/10/12
CU31 GDR	2026/05/12	14.0.3530.2	2027/10/12
CU31 GDR	2026/04/14	14.0.3525.1	2027/10/12
CU31 GDR	2026/03/10	14.0.3520.4	2027/10/12
CU31 GDR	2025/11/11	14.0.3515.1	2027/10/12
CU31 GDR	2025/09/09	14.0.3505.1	2027/10/12
CU31 GDR	2025/08/12	14.0.3500.1	2027/10/12
CU31 GDR	2025/07/09	14.0.3495.9	2027/10/12
CU31 GDR	2024/11/12	14.0.3485.1	2027/10/12
CU31 GDR	2024/10/08	14.0.3480.1	2027/10/12
CU31 GDR	2024/09/10	14.0.3475.1	2027/10/12
CU31 GDR	2024/07/09	14.0.3471.2	2027/10/12
CU31 GDR	2023/10/12	14.0.3465.1	2027/10/12

Linked servers

What security context?

PLEASE NOT sa!

...or another sysadmin!

Local server login to remote server login mappings:

Local Login	Impersonate	Remote User	Remote Password
-------------	-------------	-------------	-----------------

Add Remove

For a login not defined in the list above, connections will:

- ☐ Not be made
- ☐ Be made without using a security context
- ☐ Be made using the login's current security context
- ☒ Be made using this security context:

Remote login:

With password:

xp_cmdshell enabled

This is NOT a default

Shell for external commands

Only members of sysadmin
can use

Only members of sysadmin
can enable

The real issue: Who is a
sysadmin?

```
/* is xp_cmdshell enabled? */  
SELECT *  
FROM master.sys.configurations  
WHERE [name] = 'xp_cmdshell';
```

We made sp_CheckSecurity!

	VulnerabilityLevel	Vulnerability	Issue	DatabaseName	Details	ActionStep	ReadMoreURL
1	0	Information only	SQL Server name and version	NULL	NC-PRODSQL-SV2\ (default instance), SQL Server 201...	(Information captured on 04/07/2024)	
2	0	Information only	Communication protocol	NULL	The instance is using the TCP communication protocol ...	If using the TCP protocol, port 1433 is the default.	
3	0	Information only	Remote admin connections	NULL	Remote admin connections are currently ENABLED.	We recommend 'remote admin connections' be ENABLE...	https://straightpathsql.com
4	0	Information only	SQL Agent service account	NULL	The SQL Agent service is running with the following ac...	We recommend using managed service accounts if possi...	https://straightpathsql.com
5	0	Information only	SQL Server service account	NULL	The SQL Server service is running with the following ac...	We recommend using managed service accounts if possi...	https://straightpathsql.com
6	0	Information only	Unencrypted database	NULL	This instance has 13 unencrypted databases.	Having unencrypted databases isn't necessarily bad, but...	https://straightpathsql.com
7	1	High - action required	Password is same as login	NULL	Login [adsuser] has a password that is the same as the l...	Change the password to something more secure. Logins...	https://straightpathsql.com
8	2	High - review required	clr enabled	NULL	Having the 'clr enabled' setting enabled allows for the e...	Starting with SQL Server 2017, use the configuration opt...	https://straightpathsql.com
9	2	High - review required	Failed logins	NULL	There have been at least 2 failed logins recently.	Review the SQL Server error log for patterns of login fail...	https://straightpathsql.com
10	2	High - review required	Public permissions	ADSMaster	The [public] role has been granted the permission [CRE...	Because these permissions are available to anyone who...	https://straightpathsql.com
11	2	High - review required	Public permissions	ADSMaster	The [public] role has been granted the permission [CRE...	Because these permissions are available to anyone who...	https://straightpathsql.com
12	2	High - review required	Public permissions	ADSMaster	The [public] role has been granted the permission [CRE...	Because these permissions are available to anyone who...	https://straightpathsql.com
13	2	High - review required	Public permissions	ADSMaster	The [public] role has been granted the permission [CRE...	Because these permissions are available to anyone who...	https://straightpathsql.com
14	2	High - review required	Public permissions	ADSMaster	The [public] role has been granted the permission [CRE...	Because these permissions are available to anyone who...	https://straightpathsql.com
15	2	High - review required	Public permissions	ADSMaster	The [public] role has been granted the permission [CRE...	Because these permissions are available to anyone who...	https://straightpathsql.com
16	2	High - review required	Public permissions	SSISDB	The [public] role has been granted the permission [EXE...	Because these permissions are available to anyone who...	https://straightpathsql.com
17	2	High - review required	Public permissions	SSISDB	The [public] role has been granted the permission [EXE...	Because these permissions are available to anyone who...	https://straightpathsql.com
18	2	High - review required	Public permissions	SSISDB	The [public] role has been granted the permission [EXE...	Because these permissions are available to anyone who...	https://straightpathsql.com
19	2	High - review required	Public permissions	SSISDB	The [public] role has been granted the permission [EXE...	Because these permissions are available to anyone who...	https://straightpathsql.com
20	2	High - review required	sysadmin role members	NULL	Login [ADSCORP\Administrator] is a sysadmin. They ca...	Review the list of logins and groups in the sysadmin role ...	https://straightpathsql.com

https://github.com/Straight-Path-Solutions/sp_Check/

Phase 3: Encryption

It's already too late.











Options for responding to ransomware

Pay the ransom

- Typically paid by insurance
- May or may not provide the decryption key
- Could take days/weeks to recover all files ...if ever

Ignore the ransomware demand

- Completely rebuild your environment somewhere else
- Restore all your data from the last available recovery point in time

Go out of business

- ˘_(\ツ)_/˘

You can pay the ransom, but...

“...93% lost data regardless of payment.”

“...83% of organizations that paid ransoms were attacked again.”

Your only hope is
backups

Have you been taking care of
your eggs?



Do you have database backups

Native backups are great!

Enable compression,
checksum

VM snapshot backups do not
count!

Is your backup software
application-aware?

System databases?

Offsite?

Have you tested restoring?

```
/* Check for full backups */
SELECT
    s.server_name AS InstanceName
    , s.database_name AS DatabaseName
    , s.recovery_model AS RecoveryModel
    , s.is_copy_only
    , s.is_snapshot
    , s.has_backup_checksums
    , s.backup_start_date AS BackupStartDate
    , s.backup_finish_date AS BackupFinishDate
    , CAST(DATEDIFF(second, s.backup_start_date, s.backup_finish_date) AS VARCHAR(4))
      + ' ' + 'Seconds' AS Duration
    , CAST(CAST(s.backup_size / 1000000 AS INT) AS VARCHAR(14)) + ' ' + 'MB' AS SizeInMB
    , m.physical_device_name AS PhysicalDevice
    , m.logical_device_name AS LogicalDevice
    , CASE m.device_type
        WHEN 2 THEN 'Disk'
        WHEN 5 THEN 'Tape'
        WHEN 7 THEN 'Virtual Device'
        WHEN 9 THEN 'Azure Storage'
        WHEN 2 THEN 'A permanent Backup Device'
        ELSE 'UNKNOWN'
    END AS DeviceType
    , s.[user_name] AS UserName
FROM msdb.dbo.backupset s
INNER JOIN msdb.dbo.backupmediafamily m
    ON s.media_set_id = m.media_set_id
WHERE s.[Type] = 'D' /* Full backups */
ORDER BY s.backup_start_date DESC
```

Do you have log backups

Native log backups are great!

Compression and checksum help with these too

Is your backup software backing up the log...to NUL?

Have you tested restoring to a point in time?

```
/* Check for log backups */
SELECT
    s.server_name AS InstanceName
  , s.database_name AS DatabaseName
  , s.recovery_model AS RecoveryModel
  , s.is_copy_only
  , s.is_snapshot
  , s.has_backup_checksums
  , s.backup_start_date AS BackupStartDate
  , s.backup_finish_date AS BackupFinishDate
  , CAST(DATEDIFF(second, s.backup_start_date, s.backup_finish_date) AS VARCHAR(4))
    + ' ' + 'Seconds' AS Duration
  , CAST(CAST(s.backup_size / 1000000 AS INT) AS VARCHAR(14)) + ' ' + 'MB' AS SizeInMB
  , m.physical_device_name AS PhysicalDevice
  , m.logical_device_name AS LogicalDevice
  , CASE m.device_type
      WHEN 2 THEN 'Disk'
      WHEN 5 THEN 'Tape'
      WHEN 7 THEN 'Virtual Device'
      WHEN 9 THEN 'Azure Storage'
      WHEN 2 THEN 'A permanent Backup Device'
      ELSE 'UNKNOWN'
    END AS DeviceType
  , s.[user_name] AS UserName
FROM msdb.dbo.backupset s
INNER JOIN msdb.dbo.backupmediafamily m
    ON s.media_set_id = m.media_set_id
WHERE s.[Type] = 'L' /* Log backups */
ORDER BY s.backup_start_date DESC
```

Is your backup chain consistent?

Multiple backups in different places

Do you have copy-only backups?

...have you tested restoring?

<https://straightpathsql.com/archives/2023/10/audit-your-database-backup-chain/>

Audit Your Database Backup Chain!

October 30, 2023 by David Seis

All database administrators know that safeguarding data is paramount and having a strong restore strategy is crucial. In this post, I would like to add another tool to your arsenal that I have found helpful in auditing server health and configurations as it pertains to backups and the backup chain.

A backup chain is important when it comes to recovery. If you have full, diff, and log backups going to different backup locations, non-copy-only off-cycle backups from developers or testers, or other strangeness in your server's backup history, you could be in a world of hurt should you need to restore to a specific time.

The script below will look through msdb and add up the number of each type of backup found and count how many are going to different locations, separated by native to a network share, third party via GUID, or native to a local disk location.

```
1.  /*****
2.  /*#          Created by David Seis          #*/
3.  /*#          4/18/2023                      #*/
4.  /*#          #*/
5.  /*#          Straight Path IT Solutions, LLC. #*/
6.  *****/
7.
8.  /*
9.  Description:
10. - This identifies the number of sql server backups detected in the time period from the backup history log in
    msdb, breaks it down by distinct locations found, how many native share, native local, and third party guid
    backups found. the second result set outputs each found unique backup location per database and backup type.
11.
12. - 4/19/2023 - counting third party tools as 1 location
13. */
--
```

We also made sp_CheckBackup!

	InstanceName	DatabaseName	AvailabilityGroupName	RecoveryModel	BackupType	BackupSetID	IsCopyOnly	IsSnapshot	IsPasswordProtected	HasBackupChecksum	BackupStartDate	BackupFinishDate
1	LAPTOP-9K06NS8T	Dummy	NULL	Full	Full	23	No	No	No	No	2024-08-01 10:42:38.000	2024-08-01 10:42:38.000
2	LAPTOP-9K06NS8T	Dummy	NULL	Full	Full	22	No	No	No	Yes	2024-07-11 13:23:55.000	2024-07-11 13:23:55.000
3	LAPTOP-9K06NS8T	Dummy	NULL	Full	Transaction Log	21	No	No	No	No	2024-07-11 13:15:59.000	2024-07-11 13:15:59.000
4	LAPTOP-9K06NS8T	Dummy	NULL	Full	Full	20	No	No	No	Yes	2024-07-11 13:13:05.000	2024-07-11 13:13:05.000
5	LAPTOP-9K06NS8T	Dummy	NULL	Full	Full	20	No	No	No	Yes	2024-07-11 13:13:05.000	2024-07-11 13:13:05.000
6	LAPTOP-9K06NS8T	Dummy	NULL	Full	Full	20	No	No	No	Yes	2024-07-11 13:13:05.000	2024-07-11 13:13:05.000
7	LAPTOP-9K06NS8T	Dummy	NULL	Full	Full	20	No	No	No	Yes	2024-07-11 13:13:05.000	2024-07-11 13:13:05.000
8	LAPTOP-9K06NS8T	DB_Administration	NULL	Full	Full	19	No	No	No	No	2024-04-21 10:26:12.000	2024-04-21 10:26:12.000
9	LAPTOP-9K06NS8T	DB_Administration	NULL	Full	Full	14	No	No	No	No	2024-04-21 10:26:11.000	2024-04-21 10:26:11.000
10	LAPTOP-9K06NS8T	DB_Administration	NULL	Full	Full	15	No	No	No	No	2024-04-21 10:26:11.000	2024-04-21 10:26:11.000
11	LAPTOP-9K06NS8T	DB_Administration	NULL	Full	Full	16	No	No	No	No	2024-04-21 10:26:11.000	2024-04-21 10:26:11.000
12	LAPTOP-9K06NS8T	DB_Administration	NULL	Full	Full	17	No	No	No	No	2024-04-21 10:26:11.000	2024-04-21 10:26:11.000
13	LAPTOP-9K06NS8T	DB_Administration	NULL	Full	Full	18	No	No	No	No	2024-04-21 10:26:11.000	2024-04-21 10:26:12.000
14	LAPTOP-9K06NS8T	master	NULL	Simple	Full	11	No	No	No	Yes	2024-04-21 09:05:13.000	2024-04-21 09:05:13.000
15	LAPTOP-9K06NS8T	model	NULL	Full	Full	12	No	No	No	Yes	2024-04-21 09:05:13.000	2024-04-21 09:05:13.000
16	LAPTOP-9K06NS8T	msdb	NULL	Simple	Full	13	No	No	No	Yes	2024-04-21 09:05:13.000	2024-04-21 09:05:13.000
17	LAPTOP-9K06NS8T	master	NULL	Simple	Full	8	No	No	No	Yes	2024-04-21 08:17:00.000	2024-04-21 08:17:00.000
18	LAPTOP-9K06NS8T	model	NULL	Full	Full	9	No	No	No	Yes	2024-04-21 08:17:00.000	2024-04-21 08:17:00.000
19	LAPTOP-9K06NS8T	msdb	NULL	Simple	Full	10	No	No	No	Yes	2024-04-21 08:17:00.000	2024-04-21 08:17:01.000
20	LAPTOP-9K06NS8T	DB_Administration	NULL	Full	Transaction Log	7	No	No	No	Yes	2024-04-19 19:48:28.000	2024-04-19 19:48:28.000

https://github.com/Straight-Path-Solutions/sp_Check/

How can you prepare?

In so far as it depends on you...protect the nest with this [checklist](#) of Action Items!



1. Identify all instances

Document all your instances

- Server and instance name
- Communication protocols and ports used
- Resources assigned including drives
- IP addresses

Are they external facing?

Did you find them all?

- Find-DbalInstance
- <https://docs.dbatools.io/Find-DbalInstance.html>

2. Review your instances

Apply Cumulative Updates and GDRs

- <https://sqlserverupdates.com/>
- Develop an updating schedule

Check your linked server credentials

Check for TRUSTWORTHY databases

Capture failed login attempts

3. Review failed logins

Review the SQL Server log

- Check the IP addresses
- Use Extended Events of SQL Server Audit for more info

sp_readerrorlog

- <https://learn.microsoft.com/en-us/sql/relational-databases/system-stored-procedures/sp-readerrorlog-transact-sql?view=sql-server-ver16>

4. Limit SQL Server permissions

Disable the sa login

Check for password vulnerabilities

- Blank
- Same as login
- “password”

Principle of Least Privilege (a.k.a. Know your role!)

- Instance level: sysadmin, CONTROL SERVER, securityadmin, local Administrators group
- Database level: db_owner, CONTROL DATABASE, db_securityadmin, db_accessadmin, db_ddladmin

5. Use strong passwords for SQL Server logins

Number of Characters	Numbers Only	Lowercase Letters	Upper and Lowercase Letters	Numbers, Upper and Lowercase Letters	Numbers, Upper and Lowercase Letters, Symbols
4	Instantly	Instantly	Instantly	Instantly	Instantly
5	Instantly	Instantly	Instantly	Instantly	Instantly
6	Instantly	Instantly	Instantly	Instantly	Instantly
7	Instantly	Instantly	1 sec	2 secs	4 secs
8	Instantly	Instantly	28 secs	2 mins	5 mins
9	Instantly	3 secs	24 mins	2 hours	6 hours
10	Instantly	1 min	21 hours	5 days	2 weeks
11	Instantly	32 mins	1 month	10 months	3 years
12	1 sec	14 hours	6 years	53 years	226 years
13	5 secs	2 weeks	332 years	3k years	15k years
14	52 secs	1 year	17k years	202k years	1m years
15	9 mins	27 years	898k years	12m years	77m years
16	1 hour	713 years	46m years	779m years	5bn years
17	14 hours	18k years	2bn years	48bn years	380bn years
18	6 days	481k years	126bn years	2tn years	26tn years

...or better yet – don't use logins at all!

6. Verify your schedule of backups

Do you have database backups?

- How often?
- Is the restore chain broken?

Do you have log backups?

- How often?
- Are they to NUL?

Do you have backups of encryption keys and certificates?

Are your backups offsite?

What is your Recovery Point Objective (RPO)?

7. Test “recover from zero”

Assume a breach has occurred or will occur

Have you restored...

- A database from a backup?
- Your **largest** database from backup?
- An entire server from backup?
- Multiple servers from backup?

How long do these operations this take?

What is your Recovery Time Objective (RTO)?

8. Check with your colleagues

Principle of Zero Trust

Your systems & network administrators

- Use Antivirus software according to Microsoft recommendations
- <https://learn.microsoft.com/en-us/troubleshoot/sql/database-engine/security/antivirus-and-sql-server>
- Use MFA

Stop clicking on stupid emails and attachments

- Haha! Right?
- Seriously though, compromised identities are the most common entry point for ransomware

You have Action Items

Your organization can survive this if YOU prevent and prepare!




Ransomware is inevitable

“While half of organizations feel ‘very prepared’ to face ransomware, 78% experienced ransomware attacks last year...”

Assume a breach has occurred



Your feedback is appreciated!



Defending Your SQL Server: Practical Strategies against
Ransomware

Event Evaluation

Win a \$100 Gift Card

Scan the QR code with your phone camera.

Share what worked and what we should improve.

Submit the form to enter the \$100 gift card drawing.



Boston Data and AI Saturday 2026
Event Feedback



Or visit
forms.cloud.microsoft/r/NWSD6jJd93

Be Prepared!



<https://bit.ly/3TpjwuE> (session materials)



www.linkedin.com/in/jeff-iannucci



https://github.com/Straight-Path-Solutions/sp_Check/

