Verilog Size Checking

Expressions

- A is the set of atoms in an expression. In the AST, they correspond to leaves. In System-Verilog, they refer to what the standard calls an "operand" (variables, integers, function calls, slices of a variable, etc.).
- \mathcal{R} is the set of resizable expressions. It corresponds to the expression whose top level is one of: atom, cast, comparisons, logic operation, reduction, assignments, shift assignments, concatenation, replication and inside operation.
- \mathcal{E} is the set of System-Verilog expressions. We have $\mathcal{A} \subset \mathcal{E}$. An expression either contains an expression or is an atom.

Rules

We use the following notations:

- Γ maps atoms to their size,
- Φ maps l
values to their size,
- The statement $e \Rightarrow t$ means "e has a size t",
- The statement $e \Leftarrow t$ means "e can be resized to t".

Base case

$$\frac{\Gamma(e) = s \quad e \in \mathcal{A}}{e \Rightarrow s} \text{ Atom} \Rightarrow$$

Resize case

$$\frac{e \Rightarrow s \quad s \leqslant t \quad e \in \mathcal{R}}{e \Leftarrow t} \text{ Resize} \Leftarrow$$

Operators

• ⊕ ∈ {+, -, *, /, %, &, |, ^, ^~, ~^}:

$$\frac{a\Rightarrow t \quad b\Leftarrow t}{a\oplus b\Rightarrow t} \text{ LBinOp} \Rightarrow \qquad \qquad \frac{a\Leftarrow t \quad b\Rightarrow t}{a\oplus b\Rightarrow t} \text{ RBinOp} \Rightarrow \qquad \qquad \frac{a\Leftarrow t \quad b\Leftarrow t}{a\oplus b\Leftarrow t} \text{ BinOp} \Leftarrow$$

⊕ ∈ {+, -, ++, --, ~}:

$$\frac{e\Rightarrow t}{\oplus e\Rightarrow t} \text{ UnOp} \Rightarrow \qquad \qquad \frac{e \Leftarrow t}{\oplus e \Leftarrow t} \text{ UnOp} \Leftarrow$$

• $\oplus \in \{$ \$signed, \$unsigned $\}$:

$$\frac{e \Rightarrow t}{\oplus (e) \Rightarrow t}$$
 Cast \Rightarrow

• ⊕ ∈ {===, !==, ==?, !=?, ==, !=, >, >=, <, <=}:

$$\frac{a\Rightarrow t \quad b\Leftarrow t}{a\oplus b\Rightarrow 1} \text{ LCmp} \Rightarrow \qquad \qquad \frac{a\Leftarrow t \quad b\Rightarrow t}{a\oplus b\Rightarrow 1} \text{ RCmp} \Rightarrow$$

⊕ ∈ {&&, | |, ->, <->}:

$$\frac{a \Rightarrow t_a \quad b \Rightarrow t_b}{a \oplus b \Rightarrow 1} \text{ Logic} \Rightarrow$$

• $\oplus \in \{\&, \&, |, |, |, \hat{}, \hat{}, \hat{}, \hat{}, \hat{}, |\}$:

$$\frac{e\Rightarrow t}{\oplus e\Rightarrow 1} \ \operatorname{Red} \Rightarrow$$

⊕ ∈ {>>, <<, **, >>>, <<<}:

$$\frac{a\Rightarrow t \quad b\Rightarrow t_b}{a\oplus b\Rightarrow t} \text{ Shift} \Rightarrow \qquad \qquad \frac{a\Leftarrow t \quad b\Rightarrow t_b}{a\oplus b\Leftarrow t} \text{ Shift} \Leftarrow$$

 $\bullet \ \oplus \in \{\texttt{=}, \texttt{+=}, \texttt{-=}, \texttt{*=}, \texttt{/=}, \texttt{\%=}, \texttt{\&=}, \texttt{|=}, \texttt{^=}\}:$

$$\frac{\phi(l) = t \quad e \Leftarrow t}{l \oplus e \Rightarrow t} \text{ LAssign} \Rightarrow \qquad \qquad \frac{\phi(l) = t \quad e \Rightarrow t_e \quad t < t_e}{l \oplus e \Rightarrow t} \text{ RAssign} \Rightarrow$$

• $\oplus \in \{ <<=, >>=, <<<=, >>>= \}:$

$$\frac{\phi(l) = t \quad e \Rightarrow t_e}{l \oplus e \Rightarrow t} \text{ AssignShift} \Rightarrow$$

• If expression:

• Concatenation:

$$\frac{e_1 \Rightarrow t_1 \quad \dots \quad e_k \Rightarrow t_k \quad t = t_1 + \dots + t_k}{\{e_1, \dots, e_k\} \Rightarrow t} \quad \text{Concat} \Rightarrow$$

• Replication:

$$\frac{i \in \mathbb{N} \quad e \Rightarrow t_e \quad t = i \times t_e}{\{i e\} \Rightarrow t} \text{ Repl} \Rightarrow$$

• Inside:

$$\frac{a\Rightarrow t \quad e_1 \Leftarrow t \quad \dots \quad e_k \Leftarrow t}{a \text{ inside } \{e_1, \dots, e_k\} \Rightarrow 1} \text{ LInside} \Rightarrow$$

$$\frac{i \in \{1, \dots, k\} \quad a \Leftarrow t \quad e_1 \Leftarrow t \quad \dots \quad e_{i-1} \Leftarrow t \quad e_i \Rightarrow t \quad e_{i+1} \Leftarrow t \quad \dots \quad e_k \Leftarrow t}{a \text{ inside } \{e_1, \dots, e_k\} \Rightarrow 1} \text{ RInside} \Rightarrow$$