

RR KABEL FR HSF / FR-LSH / LSOH-FR



Single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC/FR-LSH PVC/ Thermoplastic Halogen free Flame Retardant (HFFR) 70° Insulated Industrial Cables in voltage grade upto and including 1100 Volts (HSN Code : 8544)

RATE / 100 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR HSF FR PVC INSULATION As Per IS 694	RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694	RR KABEL LSOH-FR Thermoplastic Halogen Free Flame Retardant (HFFR) 70° C Insulation As Per IS 17048
10.0	140/0.3	52	22634	23423	24868
16.0	126/0.4	70	35827	37077	39163
25.0	196/0.4	88	57860	60176	64808
35.0	276/0.4	112	80938	84175	90649
50.0	396/0.4	146	115426	120040	129274
70.0	360/0.5	216	163577	170120	183204
95.0	480/0.5	262	220048	228850	246453
120.0	608/0.5	310	284725	296117	318895
150.0	750/0.5	355	352953	367075	395307
185.0	931/0.5	415	429259	446431	480767
240.0	1200/0.5	500	564726	587315	632494
300.0	1500/0.5	550	705005	733208	789606
400.0 *	2013/0.5	590	958007	996328	1072967
500.0 *	2562/0.5	660	1241804	1291473	1390818
630.0 *	3416/0.5	725	1650719	1716747	1848805

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

** RR Kabel LSOH-FR: Insulation conforming to HFI TP 70 as per IS 17048

RR KABEL FR HSF SINGLE CORE



Multistrand bright electrolytic annealed bare copper conductor, FR PVC Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts as per IS 694 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Rate Per 100 Mtr
0.5	16/0.2	5	1298
0.75	24/0.2	8	1825
1.0	32/0.2	13	2377
1.5	30/0.25	17	3438
2.5	50/0.25	24	5600
4.0	56/0.3	30	8560
6.0	84/0.3	38	12736

RATNA FLEX MULTICORE CABLES

RR KABEL

Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

Rate per 100 meter											
Size (Sq.mm)	CONFIG.	AMPS	2 CORE	3 CORE	4 CORE	Size (Sq.mm)	CONFIG.	AMPS	2 CORE	3 CORE	4 CORE
0.5	16/0.2	5	3674	4848	6096	25.0	196/0.4	88	131091	185843	244847
0.75	24/0.2	8	4838	6517	8328	35.0	276/0.4	112	-	259524	343906
1.0	32/0.2	13	5929	8280	10601	50.0	396/0.4	146	-	370466	482451
1.5	30/0.25	17	8193	11323	14742	70.0	360/0.5	216	-	521217	687119
2.5	50/0.25	24	12970	18164	23625	95.0	480/0.5	262	-	703109	921927
4.0	56/0.3	30	19925	27947	36613	120.0	608/0.5	310	-	887644	1175589
6.0	84/0.3	38	28724	40971	53911	150.0	750/0.5	355	-	1126738	1477830
10.0	140/0.3	52	51007	73087	95240	185.0	931/0.5	415	-	1384523	1797903
16.0	126/0.4	70	79690	112546	148297	240.0	1200/0.5	500	-	1799382	2431519
						300.0	1500/0.5	550	-	2244529	3037191

CONTROL CABLES

RR KABEL

Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Control Cables (JZ-500), Voltages Grade 300/500 V. (HSN CODE : 8544)

Rate per 100 meter												
Size (Sq.mm)	CONFIG.	AMPS	5 CORE *	6 CORE *	7 CORE *	8 CORE *	10 CORE *	12 CORE *	14 CORE *	16 CORE *	19 CORE *	24 CORE *
0.5	16/0.2	5	8218	9591	10796	12691	15742	18490	21633	24027	29203	36291
0.75	24/0.2	8	11212	13485	15263	18125	22380	26618	30915	34918	43372	53257
1.0	32/0.2	13	14317	16948	19684	23448	29222	34341	40224	45100	55604	68433
1.5	30/0.25	17	20223	24487	28015	32855	41136	48555	56532	64298	76078	97476
2.5	50/0.25	24	32231	39078	45670	52960	66728	78582	90371	105367	126544	158855
4.0	56/0.3	30	50057	60940	70407	84574	105703	125213	145831	166204	196346	250862
6.0	84/0.3	38	74593	90270	105202	121703	155511	184335	213672	243370	287183	366421
10.0	140/0.3	52	127449	-	-	-	-	-	-	-	-	-
16.0	126/0.4	70	200828	-	-	-	-	-	-	-	-	-

Loading factor for Different Insulation / Sheath * -

FR Insulation	FR Sheath	FR-LSH / HR Insulation	FR-LSH / HR Sheath	LSOH Insulation	LSZH Sheath
5%	5%	10%	10%	35%	25%

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.