AQUEN FLUID TECHNOLOGIES LLP

Complete Water & Wastewater Treatment Solutions

AQUEN — FLUID BY NATURE

Design | Manufacturing | Supply | Installation | Commissioning | AMC

Clean Water Healthy Life Better Tomorrow

ACTIVATED CARBON FILTER (ACF)

REMOVES COLOUR, ODOUR, ORGANIC IMPURITIES, CHLORINE AND IMPROVES TASTE & QUALITY OF WATER

Colour Removal | Odour Control | Chlorine Removal | Organic Matter Removal | Improved Taste | Suitable for Multiple Industries

FRP VESSEL

(FIBREGLASS REINFORCED PLASTIC)





- Light weight
- Corrosion resistant
- Suitable for low to medium pressure
- Long service life
- Easy installation
- Economical

Model	Vessel Size (Dia. × Ht.) (mm)	Flow Rate (m^3/hr)	Carbon Media Quantity (kg)	Inlet Parameters (Typical)	Outlet Parameters (Typical)
ACF-500	500 × 1750	1 – 2	80 – 100	Turbidity: < 50 NTU Colour: 10 – 300 TCU Free Chlorine: 0.1 – 5.0 mg/L COD: < 50 mg/L	Turbidity: < 1 NTU Colour: < 5 TCU Free Chlorine: < 0.1 mg/L Odour: Absent Improved Taste
ACF-750	750 × 1950	3 – 5	180 – 220		
ACF-900	900 × 2100	6 – 10	300 – 350		
ACF-1200	1200 × 2400	10 – 15	550 – 600		
ACF-1500	1500 × 2600	15 – 25	850 – 900		
ACF-1800	1800 × 2850	25 – 40	1200 – 1400		
ACF-2000	2000 × 3000	40 – 60	1700 – 2000		

MSEP VESSEL

(MILD STEEL EPOXY PAINTED)





- High strength
- Epoxy coated for long life
- Suitable for industrial application
- Cost effective
- Available in custom sizes
- Good corrosion resistance (indoor)

Model	Vessel Size (Dia. × Ht.) (mm)	Flow Rate (m^3/hr)	Carbon Media Quantity (kg)	Inlet Parameters (Typical)	Outlet Parameters (Typical)
ACF-MSEP-500	500 × 1750	1 – 2	80 – 100	Turbidity: < 50 NTU Colour: 10 – 300 TCU Free Chlorine: 0.1 – 5.0 mg/L COD: < 50 mg/L	Turbidity: < 1 NTU Colour: < 5 TCU Free Chlorine: < 0.1 mg/L Odour: Absent Improved Taste
ACF-MSEP-750	750 × 1950	3 – 5	180 – 220		
ACF-MSEP-900	900 × 2100	6 – 10	300 – 350		
ACF-MSEP-1200	1200 × 2400	10 – 15	550 – 600		
ACF-MSEP-1500	1500 × 2600	15 – 25	850 – 900		
ACF-MSEP-1800	1800 × 2850	25 – 40	1200 – 1400		
ACF-MSEP-2000	2000 × 3000	40 – 60	1700 – 2000		

MSRL VESSEL

(MILD STEEL RUBBER LINED)





- Rubber lining for better corrosion resistance
- Suitable for high chlorine and aggressive water
- Long service life
- Suitable for industrial & municipal applications
- Available in custom sizes

Model	Vessel Size (Dia. × Ht.) (mm)	Flow Rate (m^3/hr)	Carbon Media Quantity (kg)	Inlet Parameters (Typical)	Outlet Parameters (Typical)
ACF-MSRL-500	500 × 1750	1 – 2	80 – 100	Turbidity: < 50 NTU Colour: 10 – 300 TCU Free Chlorine: 0.1 – 5.0 mg/L COD: < 50 mg/L	Turbidity: < 1 NTU Colour: < 5 TCU Free Chlorine: < 0.1 mg/L Odour: Absent Improved Taste
ACF-MSRL-750	750 × 1950	3 – 5	180 – 220		
ACF-MSRL-900	900 × 2100	6 – 10	300 – 350		
ACF-MSRL-1200	1200 × 2400	10 – 15	550 – 600		
ACF-MSRL-1500	1500 × 2600	15 – 25	850 – 900		
ACF-MSRL-1800	1800 × 2850	25 – 40	1200 – 1400		
ACF-MSRL-2000	2000 × 3000	40 – 60	1700 – 2000		

ACTIVATED CARBON MEDIA



- High adsorption capacity
- Effective removal of colour, odour, organics and chlorine
- 8 × 30 mesh (standard)
- High mechanical strength
- Low ash content
- Available in bulk supply

TYPICAL INLET & OUTLET PARAMETERS

Parameter	Inlet (Typical)	Outlet (Typical)
Turbidity (NTU)	5 – 50	< 1
Colour (TCU)	10 – 300	< 5
Free Chlorine (mg/L)	0.1 – 5.0	< 0.1
Odour Taste	Noticeable	Absent
COD (mg/L)	< 50	< 10
BOD (mg/L)	< 20	< 5
TDS (mg/L)	No significant change	No significant change
pH	6.5 – 8.5	No significant change

APPLICATIONS

- Drinking Water Treatment Plants (WTP)
- Industrial Process Water
- RO Pre-Treatment
- Municipal Water Supply
- Commercial & Institutional Buildings
- Food & Beverage Industry
- Pharmaceutical Industry
- Cooling Tower Make-up

ACTUAL SITE INSTALLATION



AQUEN FLUID TECHNOLOGIES LLP

Complete Water & Wastewater Treatment Solutions

WTP | STP | ETP | ZLD | FABRICATION | SPARES | AMC | RETROFIT | AUTOMATION

Office & Factory:
Sr. No. 165/2/9, Alankapuram Road,
Opposite Yashobhumi Society, Adarsha Nagar,
Charholi Budruk, Pimpri-Chinchwad, Maharashtra – 412105, India.

+91 9096645119 / +91 9622554445
ceo@aquenfluid.com
www.aquenfluid.com


MULTI GRADE FILTER (MGF)
ACTIVATED CARBON FILTER (ACF)
RAW WATER PUMPS
BACKWASH PUMPS


MGF
ACF
RAW WATER PUMPS
BACKWASH PUMPS


MULTI GRADE FILTER (MGF)
ACTIVATED CARBON FILTER (ACF)
RAW WATER PUMPS
BACKWASH PUMPS


MGF
ACF
RAW WATER PUMPS
BACKWASH PUMPS


ACF
RAW WATER PUMPS
BACKWASH PUMPS


MGF
ACF
RAW WATER PUMPS
BACKWASH PUMPS


MGF
ACF
RAW WATER PUMP


MGF (MSRL)
ACF (MSRL)
RAW WATER PUMP