AQUEN FLUID TECHNOLOGIES LLP

Complete Water & Wastewater Treatment Solutions

Design | Manufacturing | Supply | Installation | AMC

Reliable Cooling Solutions for Process and Industry

INDUSTRIAL WATER CHILLER

Energy Efficient Reliable Compact Customizable

Precise Temperature Control for Process, Machines & Comfort Applications



- Temperature Range 5°C to 30°C
- Energy Efficient
- Reliable Performance
- Easy Installation
- Robust Design
- Customizable Options

TYPES OF WATER CHILLERS



Air Cooled Water Chiller

Compact design, no cooling tower required. Suitable for small to medium capacities.



Water Cooled Water Chiller

High efficiency and suitable for large capacities. Requires cooling tower.



Compact Chiller (Integrated)

Chiller with built-in pump, tank and controls. Plug & play solution.



Screw Chiller (High Capacity)

Suitable for large industrial applications with high cooling demand.

APPLICATIONS



Pharmaceutical Industry | Plastic & PET Industry | Food & Beverage Industry | Machine Tools & CNC | Chemical & Process Industry | Injection Molding | HVAC Applications

AQUEN FLUID TECHNOLOGIES LLP
Complete Water & Wastewater Treatment Solutions
WTP | STP | ETP | ZLD | FABRICATION | SPARES | AMC | RETROFIT | AUTOMATION

Office & Factory : Sr. No. 165/2/9, Alankapuram Road, Opposite Vaishnavi Society, Adarsha Nagar, Chartoli Budruk, Pimpri-Chinchwad, Maharashtra – 412105, India.

+91-9822654461 / +91-9284544150 / +91-9226197281
eec@aquenfluid.com / sales@aquenfluid.com
www.aquenfluid.com

AQUEN FLUID TECHNOLOGIES LLP
Complete Water & Wastewater Treatment Solutions
Design | Manufacturing | Supply | Installation | AMC

Custom Engineered Chillers for Your Cooling Needs

TECHNICAL SPECIFICATIONS

Model	Cooling Capacity (TR)	Cooling Capacity (kW)	Chilled Water Flow Rate (m³/hr)	Compressor Type	Condenser Type	Refrigerant	Power Consumption (kW)	Power Supply	Approx. Dimensions L x W x H (mm)	Approx. Weight (kg)
ACW-01	1	3.5	0.6	Scroll	Air Cooled	R-410A	1.2	230 V / 1 Ph / 50 Hz	900 x 700 x 900	120
ACW-02	2	7	1.2	Scroll	Air Cooled	R-410A	2.0	230 V / 1 Ph / 50 Hz	1000 x 750 x 1100	160
ACW-03	3	10.5	1.8	Scroll	Air Cooled	R-410A	3.0	230 V / 1 Ph / 50 Hz	1200 x 800 x 1200	200
ACW-05	5	17.5	3.0	Scroll	Air Cooled	R-410A	5.0	415 V / 3 Ph / 50 Hz	1500 x 900 x 1400	280
ACW-08	8	28	4.8	Scroll	Air Cooled	R-410A	7.5	415 V / 3 Ph / 50 Hz	1800 x 1000 x 1600	400
ACW-10	10	35	6.0	Scroll	Air Cooled	R-410A	10.0	415 V / 3 Ph / 50 Hz	2000 x 1100 x 1700	500
ACW-15	15	52	9.0	Scroll	Air Cooled	R-410A	15.0	415 V / 3 Ph / 50 Hz	2200 x 1200 x 1800	700
ACW-20	20	70	12.0	Scroll	Air Cooled	R-410A	20.0	415 V / 3 Ph / 50 Hz	2500 x 1500 x 2000	900
ACW-25	25	88	15.0	Screw	Air Cooled	R-410A	25.0	415 V / 3 Ph / 50 Hz	3000 x 1700 x 2100	1200
ACW-30	30	105	18.0	Screw	Air Cooled	R-410A	30.0	415 V / 3 Ph / 50 Hz	3200 x 1800 x 2200	1500
ACW-40	40	140	24.0	Screw	Air/Water Cooled	R-134a	40.0	415 V / 3 Ph / 50 Hz	3500 x 2000 x 2200	2000
ACW-50	50	175	30.0	Screw	Water Cooled	R-134a	50.0	415 V / 3 Ph / 50 Hz	3600 x 2000 x 2300	2500
ACW-75	75	263	45.0	Screw	Water Cooled	R-134a	75.0	415 V / 3 Ph / 50 Hz	4200 x 2200 x 2400	3500
ACW-100	100	350	60.0	Screw	Water Cooled	R-134a	100.0	415 V / 3 Ph / 50 Hz	5000 x 2200 x 2500	4500

Note: Above specifications are standard models. Custom capacities, temperatures and configurations are available on request.

STANDARD FEATURES

- High efficiency hermetic scroll / screw compressor
- Stainless steel brazed plate / shell & tube evaporator
- Air cooled fin & tube / water cooled condenser
- Digital temperature controller with display
- Built-in safety protections (HP/LP, overload, flow switch)
- SS-304 chilled water tank (optional)
- Built-in chilled water pump (optional)
- Low noise operation
- Powder coated MS / SS enclosure
- Environment friendly refrigerant (R-410A / R-134a)
- Easy operation and maintenance


OPTIONAL FEATURES

- SS-304 insulated storage tank (100 L – 2000 L)
- Built-in circulation pump (duty/standby)
- Flow meter and pressure gauge
- PLC based control panel with HMI
- Data logging and remote monitoring (IoT)
- Dual pump system (duty + standby)
- Variable frequency drive (VFD)
- Special temperature range (-5°C to 30°C)
- Weatherproof enclosure for outdoor installation
- Customization as per client requirement

GENERAL TECHNICAL DETAILS

Chilled Water Temperature	5°C to 30°C (Standard 7°C – 12°C)
Ambient Temperature	Upto 45°C (Air Cooled)
Refrigerant	R-410A / R-134a (Environment Friendly)
Compressor	Hermetic Scroll / Semi Hermetic Screw
Evaporator	Stainless Steel Brazed Plate / Shell & Tube
Condenser	Air Cooled Fin & Tube / Water Cooled Shell & Tube
Control Panel	Microprocessor / PLC Based with Safety Interlocks
Power Supply	230 V / 1 Phase / 50 Hz (1–3 TR) 415 V / 3 Phase / 50 Hz (5 TR and above)
Construction Material	MS Powder Coated / SS-304 (Optional)

DIMENSION REFERENCE (TYPICAL)



AQUEN FLUID TECHNOLOGIES LLP
Complete Water & Wastewater Treatment Solutions
WTP | STP | ETP | ZLD | FABRICATION | SPARES | AMC | RETROFIT | AUTOMATION

Office & Factory : Sr. No. 165/2/9, Alankapuram Road, Opposite Vaishnavi Society, Adarsha Nagar, Chartoli Budruk, Pimpri-Chinchwad, Maharashtra – 412105, India.

+91-9822654461 / +91-9284544150 / +91-9226197281
eec@aquenfluid.com / sales@aquenfluid.com
www.aquenfluid.com