AQUEN FLUID TECHNOLOGIES LLP

Complete Water & Wastewater Treatment Solutions

IRON REMOVAL PLANT
Site Execution Across India

Guwahati, Assam



SITE IN PROGRESS

FRP Iron Removal Plant – 20 m³/hr
Location: Guwahati, Assam

Silchar, Assam



SITE COMPLETED

FRP Iron Removal Plant – 10 m³/hr
Location: Silchar, Assam

Patna, Bihar



SITE IN PROGRESS

MSEP Iron Removal Plant – 25 m³/hr
Location: Patna, Bihar

Muzaffarpur, Bihar



SITE COMPLETED

MSRL Iron Removal Plant – 15 m³/hr
Location: Muzaffarpur, Bihar

Srinagar, Kashmir



SITE IN PROGRESS

FRP Iron Removal Plant – 10 m³/hr
Location: Srinagar, Kashmir

Anantnag, Kashmir



SITE COMPLETED

MSEP Iron Removal Plant – 20 m³/hr
Location: Anantnag, Kashmir

Dibrugarh, Assam



SITE COMPLETED

FRP Iron Removal Plant – 30 m³/hr
Location: Dibrugarh, Assam

Gaya, Bihar



SITE COMPLETED

MSRL Iron Removal Plant – 50 m³/hr
Location: Gaya, Bihar

AQUEN FLUID TECHNOLOGIES LLP
Complete Water & Wastewater Treatment Solutions

Office & Factory :
Sr. No. 165/2/9, Alankapuram Road, Opposite Yashobhumi Society, Adarsha Nagar, Charholi Budruk, Pimpri-Chinchwad, Maharashtra – 412105, India.

+91- 9622554445 / +91 - 9284544150 / +91 - 9226197281

ceo@aquenfluid.com / sales@aquenfluid.com

www.aquenfluid.com

AQUEN FLUID TECHNOLOGIES LLP

Complete Water & Wastewater Treatment Solutions

Design | Manufacturing | Supply | Installation | AMC

Clean Water
Iron Free Water
Healthy Life
For a Better
Tomorrow

IRON REMOVAL PLANT

Efficient Solution for Iron, Manganese & H_2S Removal

Removes Iron (Fe) | Removes Manganese (Mn) | Removes Hydrogen Sulphide (H_2S) | Improves Taste, Colour & Odour | Automatic Operation | Low Maintenance



AVAILABLE IN THREE CONSTRUCTIONS

FRP IRON REMOVAL PLANT



- Corrosion resistant FRP vessels
- Compact and lightweight
- Suitable for small to medium capacities
- Easy installation
- Cost effective solution

MSEP IRON REMOVAL PLANT (Mild Steel Epoxy Painted)



- Mild Steel Epoxy Painted (MSEP) vessels
- Suitable for medium to large capacities
- High strength and long life
- Epoxy internal coating for corrosion protection
- Custom design as per site requirement

MSRL IRON REMOVAL PLANT (Mild Steel Rubber Lined)



- Mild Steel Rubber Lined (MSRL) vessels
- Suitable for high iron and aggressive water
- Rubber lining for superior corrosion resistance
- Ideal for industrial applications
- Long service life

PROCESS FLOW DIAGRAM (WITH COMPRESSOR & BLOWER)



APPLICATIONS



AQUEN FLUID TECHNOLOGIES LLP
Complete Water & Wastewater Treatment Solutions
WTP | STP | ETP | ZLD | FABRICATION | SPARES | AMC | RETROFIT | AUTOMATION

Office & Factory :
Sr. No. 183/2/8, Alankapuram Road, Opposite Vashubhumi Society, Adarsha Nagar, Charholi Budruk, Pimpri-Chinchwad, Maharashtra – 412105, India.

+91-9822554445 / +91-9284544910 / +91-9226857281
ceo@aquenfluid.com / sales@aquenfluid.com
www.aquenfluid.com

AQUEN FLUID TECHNOLOGIES LLP
Complete Water & Wastewater Treatment Solutions
Design | Manufacturing | Supply | Installation | AMC

Sustainable Water Solutions for Homes, Industries & Communities

TECHNICAL SPECIFICATIONS & STANDARD MODELS

Model	Capacity (m^3/hr)	Vessel Type (FRP / MSEP / MSRL)	Vessel Size (Dia × Ht in mm) (Per Vessel)	Media Quantity (Per Vessel) (Manganese Greensand/Birm) (kg)	Compressor Capacity (m^3/min)	Blower Capacity (m^3/min)	Service Flow (m^3/hr)	Backwash Flow (m^3/hr)	Inlet/Outlet Pipe Size (NB)
IRP-0.5	0.5	FRP	350 × 1650	50	0.1	0.3	0.5	1.0	25
IRP-1	1	FRP / MSEP	400 × 1800	75	0.1	0.5	1.0	2.0	25
IRP-2	2	FRP / MSEP	500 × 2000	125	0.2	0.5	2.0	4.0	40
IRP-3	3	FRP / MSEP	600 × 2000	175	0.3	0.7	3.0	6.0	50
IRP-5	5	FRP / MSEP / MSRL	750 × 2000	300	0.5	1.0	5.0	10.0	65
IRP-10	10	MSEP / MSRL	1000 × 2200	550	0.7	1.5	10.0	20.0	80
IRP-15	15	MSEP / MSRL	1200 × 2200	800	1.0	2.0	15.0	30.0	100
IRP-20	20	MSEP / MSRL	1400 × 2400	1100	1.5	2.5	20.0	40.0	100
IRP-30	30	MSEP / MSRL	1600 × 2400	1500	2.0	3.5	30.0	60.0	150
IRP-50	50	MSEP / MSRL	2000 × 2500	2300	3.0	5.0	50.0	100.0	200

Note: 1. Above models are standard. Custom capacities and configurations available on request. 2. Media: Manganese Greensand / Birm / Catalytic Media. 3. Compressor and blower capacity may vary based on raw water quality and system design.

INLET & OUTLET WATER QUALITY (TYPICAL)

Parameter	Typical Inlet	Typical Outlet
Iron (Fe)	0.5 – 10.0 mg/L	< 0.3 mg/L
Manganese (Mn)	0.1 – 5.0 mg/L	< 0.1 mg/L
Hydrogen Sulphide (H_2S)	0.1 – 2.0 mg/L	< 0.05 mg/L
pH	6.5 – 8.5	6.5 – 8.5
Turbidity	Up to 10 NTU	< 1 NTU

KEY FEATURES

- Complete solution with compressor and blower
- FRP / MSEP / MSRL pressure vessels
- Manganese Greensand / Birm / Catalytic media
- Automatic multiport / pneumatic / motorized valve options
- PLC based control panel with HMI (optional)
- Online monitoring (Iron, pH, Flow, Pressure) (optional)
- Low power consumption & high efficiency
- Suitable for borewell / surface water
- Compact design with skid mounting
- Easy installation, commissioning & low maintenance

ONGOING SITE INSTALLATION



Ongoing Installation (MSEP Iron Removal Plant 10 m^3/hr)



Ongoing Installation (FRP Iron Removal Plant 5 m^3/hr)



Ongoing Installation (MSRL Iron Removal Plant) 20 m^3/hr)

COMPLETED PROJECTS



Completed Project Residential Society - 5 m^3/hr



Completed Project Commercial Building - 10 m^3/hr



Completed Project Industrial Unit - 30 m^3/hr



Completed Project School - 2 m^3/hr

AQUEN FLUID TECHNOLOGIES LLP
Complete Water & Wastewater Treatment Solutions
WTP | STP | ETP | ZLD | FABRICATION | SPARES | AMC | RETROFIT | AUTOMATION

Office & Factory :
Sr. No. 183/2/8, Alankapuram Road, Opposite Vashubhumi Society, Adarsha Nagar, Charholi Budruk, Pimpri-Chinchwad, Maharashtra – 412105, India.

+91-9822554445 / +91-9284544910 / +91-9226857281
ceo@aquenfluid.com / sales@aquenfluid.com
www.aquenfluid.com