AQUEN FLUID TECHNOLOGIES LLP

Complete Water & Wastewater Treatment Solutions

Design | Manufacturing | Supply | Installation | Commissioning | AMC

Clean Water Healthy Life Better Tomorrow

PRESSURE SAND FILTER (PSF) | MULTI GRADE FILTER (MGF) | DUAL MEDIA FILTER (DMF)

Reliable Filtration Solutions for Clean & Clear Water

- Removes Suspended Solids & Turbidity
- Improves Water Quality
- Suitable for Industrial, Commercial & Institutional Use
- Available in FRP, MSEP & MSRL Vessels

PRESSURE SAND FILTER (PSF)

Removes suspended solids, turbidity, silt and fine particles from raw water.



Model	Vessel Size (Dia. × Ht.) (mm)	Flow Rate (m³/hr)
PSF-500	500 × 1750	1 – 2
PSF-750	750 × 1950	3 – 5
PSF-900	900 × 2100	6 – 10
PSF-1200	1200 × 2400	10 – 15
PSF-1500	1500 × 2600	15 – 25
PSF-1800	1800 × 2850	25 – 40
PSF-2000	2000 × 3000	40 – 60

TYPICAL INLET & OUTLET PARAMETERS

Parameter	Inlet (Typical)	Outlet (Typical)
Turbidity (NTU)	5 – 100	< 1
TSS (mg/L)	10 – 200	< 5
Colour (TCU)	10 – 100	< 5

MULTI GRADE FILTER (MGF)

Uses multiple layers of media to remove a wide range of particle sizes and provides higher filtration efficiency.



Model	Vessel Size (Dia. × Ht.) (mm)	Flow Rate (m³/hr)
MGF-500	500 × 1750	1 – 2
MGF-750	750 × 1950	3 – 5
MGF-900	900 × 2100	6 – 10
MGF-1200	1200 × 2400	10 – 15
MGF-1500	1500 × 2600	15 – 25
MGF-1800	1800 × 2850	25 – 40
MGF-2000	2000 × 3000	40 – 60

TYPICAL INLET & OUTLET PARAMETERS

Parameter	Inlet (Typical)	Outlet (Typical)
Turbidity (NTU)	10 – 100	< 1
TSS (mg/L)	20 – 200	< 5
Colour (TCU)	10 – 100	< 5
SDI	5 – 20	< 3

DUAL MEDIA FILTER (DMF)

Combination of Anthracite and Sand for improved depth filtration and longer run time.



Model	Vessel Size (Dia. × Ht.) (mm)	Flow Rate (m³/hr)
DMF-500	500 × 1750	1 – 2
DMF-750	750 × 1950	3 – 5
DMF-900	900 × 2100	6 – 10
DMF-1200	1200 × 2400	10 – 15
DMF-1500	1500 × 2600	15 – 25
DMF-1800	1800 × 2850	25 – 40
DMF-2000	2000 × 3000	40 – 60

TYPICAL INLET & OUTLET PARAMETERS

Parameter	Inlet (Typical)	Outlet (Typical)
Turbidity (NTU)	10 – 100	< 1
TSS (mg/L)	20 – 200	< 5
Colour (TCU)	10 – 100	< 5
Fe (Iron) (mg/L)	Up to 1.0	< 0.3
Mn (Manganese) (mg/L)	Up to 0.5	< 0.1

Applications: Industrial Process Water | RO Pre-Treatment | Commercial & Institutional | Municipal Water Supply | Cooling Tower Make-up

AQUEN FLUID TECHNOLOGIES LLP

Complete Water & Wastewater Treatment Solutions

Sustainable Water Solutions for a Cleaner Tomorrow

WTP | STP | ETP | ZLD | Fabrication | Spares | AMC | Retrofit | Automation

PRESSURE SAND FILTER (PSF) | MULTI GRADE FILTER (MGF) | DUAL MEDIA FILTER (DMF)

Available in FRP, MSEP and MSRL Vessels

FRP VESSEL
(FIBREGLASS REINFORCED PLASTIC)



- Light weight
- Corrosion resistant
- Suitable for low to medium pressure
- Long service life
- Economical
- Quick installation

Typical FRP Vessel with Multiport Valve

MSEP VESSEL
(MILD STEEL EPOXY PAINTED)



- High strength with epoxy coating
- Suitable for industrial applications
- Cost effective
- Good corrosion resistance (indoors)
- Available in custom sizes
- Suitable for higher flow capacities

Typical MSEP Vessel with Piping

MSRL VESSEL
(MILD STEEL RUBBER LINED)



- Mild steel with rubber lining
- Excellent corrosion resistance
- Suitable for high pressure and harsh water conditions
- Durable and long life
- Suitable for industrial & municipal applications
- Available in custom sizes

Typical MSRL Vessel with Piping

DESIGN & OPERATING PARAMETERS

Parameter	Typical Range
Operating Pressure	2 – 6 kg/cm² (Standard)
Maximum Pressure	8 – 10 kg/cm² (As per design)
Operating Temperature	5 – 50 °C
Filtration Velocity	10 – 15 m³/m²/hr
Backwash Velocity	30 – 40 m³/m²/hr
Inlet / Outlet Connection	Flanged / Screwed (as per requirement)
Control Valve	Manual / Auto (Multiport / Butterfly)
Underdrain	Lateral with gravel support
Media	Silica Sand / Anthracite / Garnet (as applicable)

FILTRATION MEDIA



Silica Sand (0.6 – 1.2 mm)



Anthracite (0.8 – 1.6 mm)



Garnet (0.2 – 0.4 mm)



Gravel Support Media (2 – 6 mm)



Underdrain System (Lateral Type)



Multiport Valve (Manual / Automatic)

AQUEN FLUID TECHNOLOGIES LLP

Office & Factory:
Sr. No. 165/2/9, Alankapuram Road, Opposite Yashobhumi Society, Adarsha Nagar, Charholi Budruk, Pimpri-Chinchwad, Maharashtra – 412105, India.

+91 9096645119 / +91 9822554445
ceo@aquenfluid.com
www.aquenfluid.com

Scan for Website


PRESSURE SAND FILTER (PSF)
MULTI GRADE FILTER (MGF)
DUAL MEDIA FILTER (DMF)
RAW WATER PUMPS
BACKWASH PUMPS


PSF
MGF
DMF


PRESSURE SAND FILTER (PSF)
MULTI GRADE FILTER (MGF)
DUAL MEDIA FILTER (DMF)



AQUEN FLUID TECHNOLOGIES LLP

Complete Water & Wastewater Treatment Solutions

Design | Manufacturing | Supply | Installation | Commissioning | AMC

SITE IN PROGRESS

WATER TREATMENT PLANT

PRESSURE SAND FILTER | MULTI GRADE FILTER | DUAL MEDIA FILTER
with Raw Water Pumps & Backwash Pumps




PSF – SAND MEDIA


MGF – MULTI LAYER MEDIA


DMF – ANTHRACITE + SAND


FRONTAL PIPING WITH MULTIPORT VALVE


RAW WATER PUMP SET


BACKWASH PUMP SET


ON-GOING INSTALLATION AT SITE

AQUEN FLUID TECHNOLOGIES LLP

+91 9096645119 / +91 9622554445

ceo@aquenfluid.com

www.aquenfluid.com

Office & Factory:
Sr. No. 165/2/9, Alankapuram Road,
Opposite Yashobhumi Society, Adarsha Nagar,
Charholi Budruk, Pimpri-Chinchwad, Maharashtra – 412105, India.

Clean Water Healthy Life Better Tomorrow