

This **Restease Design System (RDS)** is built on the philosophy of **"Tactical Minimalism."** In a landslide rescue, every extra pixel is a distraction. The system is designed for high-stress environments, ensuring the Admin can make life-saving decisions with zero cognitive friction.

1. Visual Foundation (The Core)

Color Palette (The Safety Spectrum)

We use high-contrast colors that remain distinguishable under glare or low-light conditions.

Name	Hex	Usage	Role
SOS Orange	#FF4F00	Critical actions, SOS alerts, SOS button.	Signal/Alert
Command Black	#0D0D0D	Backgrounds, primary UI housing.	Grounding
Kinetic Green	#00E676	Moving units, safe status, battery healthy.	Progress
Static Grey	#8E8E93	Stationary units, inactive hardware.	Passive
Signal White	#FFFFFF	Primary text, high-contrast icons.	Legibility

Typography (The Data-Driven Type)

- **Primary Typeface: Inter** (Variable).
 - *Why:* Exceptional legibility at small sizes and high-speed scanning.
 - *Scale:*
 - H1: 32pt (Mission Status)
 - H2: 20pt (Unit Headers)
 - Body: 16pt (General Data)
 - Caption: 12pt (Secondary Telemetry)
- **Secondary Typeface: JetBrains Mono.**
 - *Why:* To display GPS coordinates and Unit IDs. The fixed width prevents "jittering" when numbers update in real-time.

2. Iconography & Symbols (Universal Logic)

All icons follow a **2px stroke** weight for a technical, precise feel.

- **Stretcher Icon:** A rectangle with four handle extensions (Top-down view).
 - **Personnel Icon:** A bold triangle (representing direction/vector).
 - **Signal Strength:** Traditional stepped bars but with a "Node" dot at the base to represent the chipset.
 - **Battery:** Vertical tank style (easier to read at a glance).
-

3. UI Components (The Building Blocks)

A. Tactical Unit Cards

Small, modular containers that float on the map or live in the sidebar.

- **Header:** Unit ID (e.g., UNIT-07) in JetBrains Mono.
- **Visual Pulse:** A subtle outer glow in **SOS Orange** (if alert) or **Kinetic Green** (if moving).
- **Telemetry:** Micro-stats (Speed: 2km/h | Batt: 88%).

B. The "Action Bar" (Bottom Dock)

- **Visuals:** Anchored to the bottom of the screen.
- **The SOS Override:** When active, the bar expands to cover 50% of the screen in flashing Orange.
- **Buttons:** Must be **minimum 48px to 64px** touch targets to allow for thumb-only operation or gloved hands.

C. The Map Layer

- **Base:** Dark-themed topographic map (low saturation to let Orange/Green icons "pop").
 - **The "Breadcrumb" Trail:** A 2px dashed line showing the path of each unit.
-

4. Interaction Design (Motion & Sound)

Micro-Interactions

- **The Pulse:** Active units have a slow "breathing" animation (4s cycle) to indicate the system is still receiving data.
- **The Alert:** SOS units have a rapid "flash" (0.5s cycle) to demand immediate attention.
- **Transition:** Moving from Dashboard to SOS View should be an "Instant Cut," not a fade. Speed is the priority.

Sonic Brand (Audio Cues)

- **The SOS Alert:** A high-frequency, dissonant "staccato" beep (Safe Zone Admin only).
 - **The A&R Chime:** The "Two-Note" harmonic (Do-Sol) — smooth, sine-wave tone to evoke calm.
-

5. Information Architecture Patterns

- **Z-Pattern Scanning:** Most critical data (Mission Name, SOS Count) Top Left; Health stats (Battery, Signal) Top Right.
- **The "No-Go" Rule:** No nested menus. All critical functions (Acknowledge, Map, Comms) must be visible on the top layer. No "hidden" features.

6. Design System Tokens (For Developers)

Token Name	Value	Description
radius-ui	8px	For buttons and cards (Professional/Ergonomic).
border-thick	2px	For all UI borders to maintain "Gear" aesthetic.
elev-high	0px 8px 16px rgba(0,0,0,0.5)	For SOS modals to pull forward.
haptic-heavy	250ms burst	For hardware SOS trigger.

Implementation Priority

1. **High Contrast:** Always maintain a minimum **7:1 contrast ratio**.
2. **State Logic:** Every component must have a "Disconnected" state (Greyed out) so the Admin knows immediately if a signal is lost.