

Explosive proof telephone KNEX1

Features

IECEx certified

Zone 1&2, type Exib.

Analogue telephone matching with most PABX, PBX and PAX system Telephone line powered. No external power or battery required Robust SMC 2600 glassfibre reinforced polyester die-cast body LCD display, SUS Metal keypad 24digit, Magnetic reed hook-switch Busy tone detection for auto release the line if line busy

High temperature approval, Auto answer auto release line.

Full Soft lock: only dial out from phone book 50 memory address number Half soft lock: limit to dial out starting number, e.g. "00852" area code

Ring sound 95 dB dfd in 1 m and 10 ringing tone melodies selectable

Listening by loudspeaker: 70dB in 1m

Phone book memory: 50 address (name & number) programmable

Dry contact for external control automation (Option)





LCD display include

Manual setting

Welcome text programmable e.g. welcome to koontech telephone

Full soft lock or half soft lock

Phone book up to 50 address number selectable

Ring speaker up to 4 level selectable

Hands free talking sound up to 4 level selectable

Handset receiver sound up to 4 level selectable

Up to 9 Ring tone melodies selectable

Back light up to 4 level selectable

The dialing number

Calling time counting

Order number: KNEX1

Certificate:



Explosion-proof Telephone

Model: KNEx1 Ex e ib mb IIC T6 Gb Ex tb IIIC T80°C Db -25°C≤Ta≤+60°C COM XXX **IECEX XXXX** CE 14 XXXXXX ShenZhen Xijun Technology Ltd

6/F 268# Nanchang ind. park Gushu Baoan Shenzhen China

2012 s/n 001





















Specification

Unit dimension	227 x 293 x 135mm
Unit Weight	5.8kg
LCD Display:	2 line alphanumerical display ICON or number or letter
	Up to 4 level back light selectable
Keypad	stainless steel flash mount Waterproof IP66. Ice protection
	21 keys with number and ACE letter for program
Handset:	dynamic receiver with inductive coupling for hearing aids
	Electret type microphone with noice cancelling
	Stainless steel armoured handset hold over 170kg
Waterproof protection	IP66
Impact protection:	IK09
Call Flash transfer:	max:120ms
Dialling procedure:	DTMF
External function	external louder speaker
(Option):	additional earpiece
	headset
	ringl sounder
operation temperature:	-25°C to 60°C
Storage temperature:	-30°C to +70°C





Factory Photo

Regular Customer -













www.koontech.com Email: mrkt26@koontech.com Whatsapp: +86 135 3042 8923 Skype / Wechat ID: knsales06