# SMALL IS THE NEW BIG.

# E SERIES

Amazingly big on features, yet surprisingly small in size.

# E SERIES

Available in single and two-line, analog, VoIP, corded, and cordless configurations, micro-footprint Teledex E Series phones have created an entirely new hotel guestroom telephone category. Originally designed to meet the limited space requirements aboard cruise ships, E Series phones require less room on the hotel guestroom desk and nightstand, and consume less energy in the manufacturing process, so the impact on the environment is smaller as well.

Small is the new big.

E Series VoIP RediDock

E Series Lobby

E Series Trimline

E Series Analog Corded

E Series Basic

E Series Analog Cordless

E Series VoIP Cordless

E Series VoIP Corded

## E Series VoIP Corded

- Single or two-line speakerphones
- Up to seven (7) configurable Guest Service Keys
- LCD display with digital clock screen
- Patented OneTouch voice mail retrieval
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Dual Neon/LED message-waiting light
- Electronic 3-way conference*
- Dual Port (10/100) for HSIA
- Available in Ash or Black
- ETrim available

*Two-line only

## E Series VoIP Cordless

- Available Frequencies: 1.8 GHz and 1.9 GHz
- Single or two-line speakerphones
- Supports up to four handsets, including one on the base and three remotes
- Up to seven (7) configurable Guest Service Keys
- Patented OneTouch voice mail retrieval
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Dual Neon/LED message-waiting light
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference*
- Dual Port (10/100) for HSIA
- RediDock available
- Available in Ash or Black

*Two-line only

## E Series Analog Corded

- Single or two-line speakerphones
- Eight (8) configurable Guest Service Keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Electronic 3-way conference*
- EasyAccess™ data port
- Available in Ash or Black
- ETrim available

*Two-line only

## E Series Analog Cordless

- Available frequencies: 1.8 GHz and 1.9 GHz
- Single or two-line speakerphones
- Supports up to four handsets, including one on the base and three remotes
- Eight (8) configurable Guest Service Keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- HAC/VCH (ADA) complient handset volume boost
- Electronic 3-way conference*
- EasyAccess™ data port
- RediDock available
- Available in Ash or Black

*Two-line only

# E SERIES VoIP

## SPECIFICATIONS

| | |
|---|---|
| **Standard Color:** | Ash and Black |
| **Footprint (Desk):** | 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 3.63" (9.22cm) (d) (max height with desk stand) |
| **Footprint (Wall):** | 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 1.5" (3.81cm) (d) (depth from wall mount) |
| **Footprint (ETrim/RediDock):** | Same as above |
| **Weight:** | 2.0 lbs. (0.9kg) |
| **Weight (ETrim/Redidock):** | 12 oz. (0.34kg) |
| **Frequency:** | 1.9 GHz or 1.8 GHz |
| **Power:** | Power over Ethernet (POE) 802.3af Compliant |
| **Power (Cordless):** | Remote Charging Station includes Handset with Battery & A/C adaptor |
| **Standby Time (Cordless):** | 10 days |
| **Talk Time (Cordless):** | 6 hours |
| **Range (Cordless):** | 100ft (30m) |
| **Humidity:** | 65% ± 20% |
| **Temperature:** | 77°F ± 50° (25°C ± 10°C) |
| **Packaging:** | 10 per carton |
| **Packaging (RediDock):** | 20 per carton |
| **Faceplate Size:** | Full length |
| **FCC Specifications:** | FCC Part 15 Subpart B: 2009 |
| **Safety Standard:** | UL - 60950–1 2nd edition ADA/HAC |
| **Handset:** | 10 ft (3.048m) |
| **Line Cord:** | RJ14 line cord - 15 ft (4.5m) |
| **Line Cord (Cordless):** | RJ45 line cord - 15 ft (4.5m) |

RFCs: 3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)

## PART NUMBERS

### SINGLE-LINE VoIP CORDED

**E100IP - Basic**
| | | |
|---|---|---|
| EV021000S00T | | Ash |
| EV011000S00T | | Black |

**E100IP - 7 GSK**
| | | |
|---|---|---|
| EV021000S07D | | Ash |
| EV011000S07D | | Black |

**E100IPTrim**
| | | |
|---|---|---|
| EV210N0T | | Ash |
| EV110N0T | | Black |

**E100IPLBY - Lobby**
| | | |
|---|---|---|
| EV021000N00L | | Ash |
| EV011000N00L | | Black |

### TWO-LINE VoIP CORDED

**E200IP - Basic**
| | | |
|---|---|---|
| EV022000S00T | | Ash |
| EV012000S00T | | Black |

**E200IP - 7 GSK**
| | | |
|---|---|---|
| EV022000S07D | | Ash |
| EV012000S07D | | Black |

**E200IPTrim**
| | | |
|---|---|---|
| EV220N0T | | Ash |
| EV120N0T | | Black |

### SINGLE-LINE VoIP CORDLESS

**E103IP - 4 GSK**
| | | |
|---|---|---|
| EV021319S04D | | Ash |
| EV011319S04D | | Black |

**E103IP - 7 GSK**
| | | |
|---|---|---|
| EV021319S07D | | Ash |
| EV011319S07D | | Black |

**E103IP-RediDock**
| | | |
|---|---|---|
| EV021319S00H | | Ash |
| EV011319S00H | | Black |

### TWO-LINE VoIP CORDLESS

**E203IP - 4 GSK**
| | | |
|---|---|---|
| EV022319S04D | | Ash |
| EV012319S04D | | Black |

**E203IP - 7 GSK**
| | | |
|---|---|---|
| EV022319S07D | | Ash |
| EV012319S07D | | Black |

**E203IP-RediDock**
| | | |
|---|---|---|
| EV022319S00H | | Ash |
| EV012319S00H | | Black |

---

# E SERIES ANALOG

## SPECIFICATIONS

| | |
|---|---|
| **Standard Color:** | Ash and Black |
| **Footprint (Desk):** | 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 3.63" (9.22cm) (d) (max height with desk stand) |
| **Footprint (Wall):** | 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 1.5" (3.81cm) (d) (depth from wall mount) |
| **Footprint (RediDock):** | Same as above |
| **Weight:** | 1.4 lbs. (0.64kg) |
| **Weight (Redidock):** | 10 oz. (0.29kg) |
| **Frequency:** | 1.9 GHz or 1.8 GHz |
| **Power:** | Adapter |
| **Power (Cordless):** | Remote Charging Station includes Handset with Battery & A/C adaptor |
| **Standby Time (Cordless):** | 10 days |
| **Talk Time (Cordless):** | 6 hours |
| **Range (Cordless):** | 100ft (30m) |
| **Humidity:** | 65% ± 20% |
| **Temperature:** | 77°F ± 50° (25°C ± 10°C) |
| **Packaging:** | 10 per carton |
| **Packaging (RediDock):** | 20 per carton |
| **Faceplate Size:** | Full length |
| **FCC Specifications:** | Meets or exceeds Part 68, FCC Part 15 & UL 1459 Ref. |
| **Safety Standard:** | UL - 60950–1 2nd edition ADA/HAC |
| **Operating Voltage:** | 24 to 56 VDC Non-Polarity |
| **Flash Timing:** | 600 ms |
| **Ringer Equivalence:** | Z (Use only behind PBX) |
| **Handset:** | 10 ft (3.048m) |
| **Line Cord:** | RJ14 line cord - 15 ft (4.5m) |
| **Line Cord (Cordless):** | RJ45 line cord - 15 ft (4.5m) |

## PART NUMBERS

### SINGLE-LINE ANALOG CORDED

**E100 - Basic**
| | | |
|---|---|---|
| EA021000S00T | | Ash |
| EA011000S00T | | Black |

**E100 - 4 GSK**
| | | |
|---|---|---|
| EA021000S04D | | Ash |
| EA011000S04D | | Black |

**E100 - 8 GSK**
| | | |
|---|---|---|
| EA021000S08D | | Ash |
| EA011000S08D | | Black |

**E100Trim**
| | | |
|---|---|---|
| EA210N0T | | Ash |
| EA110N0T | | Black |

**E100LBY - Lobby**
| | | |
|---|---|---|
| EA021000N00L | | Ash |
| EA011000N00L | | Black |

### TWO-LINE ANALOG CORDED

**E200 - Basic**
| | | |
|---|---|---|
| EA022000S00T | | Ash |
| EA012000S00T | | Black |

**E200 - 4 GSK**
| | | |
|---|---|---|
| EA022000S04D | | Ash |
| EA012000S04D | | Black |

**E200 - 8 GSK**
| | | |
|---|---|---|
| EA022000S08D | | Ash |
| EA012000S08D | | Black |

**E200Trim**
| | | |
|---|---|---|
| EA220N0T | | Ash |
| EA120N0T | | Black |

### SINGLE-LINE ANALOG CORDLESS

**E103 - 4 GSK**
| | | |
|---|---|---|
| EA021319S04D | | Ash |
| EA011319S04D | | Black |

**E103 - 8 GSK**
| | | |
|---|---|---|
| EA021319S08D | | Ash |
| EA011319S08D | | Black |

**E103-RediDock**
| | | |
|---|---|---|
| EA021319S00H | | Ash |
| EA011319S00H | | Black |

### TWO-LINE ANALOG CORDLESS

**E203 - 4 GSK**
| | | |
|---|---|---|
| EA022319S04D | | Ash |
| EA012319S04D | | Black |

**E203 - 8 GSK**
| | | |
|---|---|---|
| EA022319S08D | | Ash |
| EA012319S08D | | Black |

**E203-RediDock**
| | | |
|---|---|---|
| EA022319S00H | | Ash |
| EA012319S00H | | Black |

U.S. Toll Free 1 800 794 8353
Telephone +1 719 638 8821
Fax +1 719 638 8815

info@teledex.com
teledex.com