

M200 SC

Single-cell DECT base station



M200 SC



Key features

- Up to 6 cordless handsets
- Up to 4 simultaneous calls
- Cordless localisation key
- Powered via PoE or power adaptor
- GAP compatible



Directory



Power over Ethernet



IPv6 & IPv4



OpenVPN



Security (TLS & SRTP)



GAP compatible



OTA Updates

The M200 SC base station provides everything you need to create an economic, high performance and scalable DECT telephone solution. This modern DECT base not only provides excellent coverage but also various phone functions such as direct access to the company directory and excellent HD audio quality.

Its high performance enables the M200 SC base station to connect up to six Snom single-cell (SC) cordless handsets. In addition, the M200 SC can manage up to six different SIP identities and four simultaneous calls.

To facilitate integration of the M200 SC base station, it can be powered easily using Power-over-Ethernet (PoE). The M200 SC can provide software updates to connected handsets over the air.

Hardware

- Network connection: 10/100 BASE-T
- PoE (Class 2) or optional power adaptor
- Cordless handset localisation key
- Reset button
- LED status light
- Wall mountable

Features

- Up to 6 SIP accounts (used in common or individually for cordless phones)
- Up to 4 simultaneous calls
- Compatible with GAP devices
- Over-the-air cordless software updates
- Range up to 50 m indoors
- Local directory and network
- Up to 200 numbers in the voice phone book
- Import/export phone book
- Up to 200 numbers in the call history lists
- Intercom function
- Three way conference call per base
- Caller ID
- Call plan
- Hold function
- Call forwarding
- Call divert
- Do not disturb function (DND)

Interoperability

- Broadsoft® BroadWorks
- Asterisk based platforms
- Metaswitch networks
- Genband™

Audio

- Codecs:
 - G.711 a-law, u-law
 - G.722
 - G.726
 - G.729
 - iLBC

Set-up

- Configurable via web interface (Admin and User)
- Provisioning:
 - DHCP Options 66/159/160
 - Plug & Play
 - Snom redirection service
 - TR-69

Protocols

- SIP (RFC3261)
- HTTP/HTTPS/TFTP/FTP
- DHCP, NTP, SNTP, STUN, VLAN
- RTP/SRTP
- IPv4/IPv6
- LDAP

Security

- Transport Layer Security (TLS)
- Provisioning file with AES encryption
- OpenVPN
- 802.1x
- 802.1pq
- LLDP-MED
- Password protected web interface
- DECT encryption

Specifications

- Dimensions: 116 x 42.4 x 151 mm
- Input voltage: 5V DC
- Environmental conditions:
 - Operating temperature: from -5°C to 45°C
 - Non-operating temperature: from -5°C to 60°C
 - Humidity: up to 95% (non-condensing)
- Included in the package:
 - Base
 - Network cable
 - Quick start guide
 - Color: Black
- Manufacturer's warranty: 2 years
- Product code: 00004359 Snom M200 SC
00004365 Snom M215 SC EU

Compliance

- CE Marking
- IEC 60950

Product codes of compatible devices

- Snom M15SC Handset EU: 00004363

Product codes of accessories:

00004373 Power supply with EU clip for Snom M200SC/M215SC EU

00004374 Power supply with UK clip for Snom M200SC/M215SC UK

00004325 A6 Adapter with EU clip

M15 SC

Cost-effective handset for Snom SC base stations



M15 SC



Key features

- Battery life up to 7 days in stand-by and 7 hours talk time
- Voicemail LED notification light
- Illuminated keypad
- Integrated belt clip
- 2.5 mm headphone jack
- GAP compatible



Long Stand-by Time



Belt Clip



GAP compatible

The Snom M15 SC is a high performance cordless DECT VoIP phone to be used with single-cell bases. This modern DECT telephone is easy to use and perfect for everyday business needs. With a wide 1.7" panoramic display, illuminated keypad and excellent voice transmission, the Snom M15 SC is the right tool for a variety of applications.

An integrated belt clip makes it easy to carry the M15 SC everywhere you go. A set of powerful batteries ensure up to 7 hours of talk time and up to a week on stand-by so you never miss a call.

The M15 SC is the perfect choice: both in the office and at home the Snom M15 SC meets all the requirements of the modern day working environment.

With the M200 SC base station, which can connect up to six M15 SC handsets, it is possible to make up to four concurrent phone calls. This perfect combination provides maximum productivity at an excellent price.

Hardware

- Backlit graphic LCD with 90 x 65 pixels
- 2.5 mm headphone jack
- Speakerphone
- Up to 7 days battery life in stand-by
- Up to 7 hours talk time
- Voicemail notification LED
- Illuminated keypad
- Integrated belt clip

Features

- Call history lists
- Local directory and network
- Call transfer
- Call forwarding
- Hold function
- Intercom function between cordless devices connected to the M200 SC base
- Mute function
- Up to 10 numbers with speed dial
- Range up to 50 m indoors
- Compatible with GAP bases
- Over-the-air software updates

Specifications

- Dimensions: 174 x 49 x 31 mm
- Batteries: 2.4 V / 550 mAh Ni-MH
- Input voltage: 6V
- Wall mountable charger base
- Hearing Aid Compatibility (HAC)
- Environmental conditions:
 - Operating temperature: from -5°C to 45°C
 - Non-operating temperature: from -5°C to 60°C
 - Humidity: up to 95% (non-condensing)

Included in the package:

- Cordless M15 SC
- Charging cradle
- Power supply for charging cradle
- Batteries
- Quick start guide (QIG)
- Color: Black

- Manufacturer's warranty: 2 years
- Product code: 00004363 Snom M15SC Handset EU

Compliance

- CE Marking
- IEC60950 safety

Compatibility

- Comprehensive features only in conjunction with the M200 SC base station (PN 00004359)
- Available accessories:
 - Headphone adapter ACPJ25 (PN 00004371)
 - A100M (PN 00004341), A100D (PN 00004342)
Only in conjunction with the ACPJ25 adapter
 - Handset charger PSU for the UK (PN 00004379)