Hotel Phone H2S

Company Profile:

Fanvil Technology Co., Ltd. is a professional developer and manufacturer of VoIP products. Fanvil provides VoIP communication devices solutions for small and medium sized businesses, as well as large mission-critical enterprise environments.

Features

✓ Wall-mount

✓ Call hold, redial, transfer, release

✓ Call transfer (bland or consultative)

✓ Do not disturb

✓ Paging/intercom

✓ Configurable dial plan

Enterprise Functionality

● 802.3af power over Ethernet

● VLAN and DSCP

● VPN

Vertical market Opportunities

✧ Hospitality: second guestroom phone or lobby phone

✧ Education: classroom phones

✧ Retail: point of sale phone

✧ Healthcare: patient room phones

✧ General business: entry-level, single-port IP phone

Networking

● 10/100Mbps Ethernet

● IP Configuration: Static / DHCP / PPPoE

● Support basic NAT and NAPT

● Support PPPoE for xDSL

● Support DHCP client on WAN

● Support DNS relay, SNTP client, firewall

Protocols Supported

● SIP (RFC3261, RFC3262)

● SDP (RFC2327)

● (SIP) subscribe/ notify (RFC3265)

● (SIP) offer/answer model (RFC3264)

● (SIP) refer method (RFC3515)

● SIP INFO and in-band DTMF transport

● RTP/RTCP (RFC3550, 3551)

● (SIP)DNS SRV (RFC2781)

● Peer to peer calling

QoS

● DiffServ /IP precedence; IEEE 802.3p

Audio/Codec

● G.711 A law and G.711 U law 64K

● G.729

● G.723.1

● Acoustic echo cancellation

● Built-in audio mixer

User level configuration and status

● Brower based configuration interface and status page

● Edit the programmable keys using web interface

Configuration and Management

● Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR069

● Web Management Portal

● Web-based Packet-dump

● Configuration Export / Import

● Recover firmware and factory reset through POST mode

● Upgrade firmware via FTP or TFTP

● syslog

Physical Features

● Keypad: 17 keys, including
  12 Standard Phone Digits keys
  4 Function keys
  1 DSS key

● Power supply mode: PoE (802.3af) or DC 12V/500mA

● RJ45 Ethernet Port x1: Network x1 (Support 802.3AF POE Class 1)

● Power Consumption: Idle: 1.6~2.3W Peak: 2.5~3.3W

● Working Temperature: 0~40℃

● Working Humidity: 10~65%

● Main Chipset: Broadcom

● SDRAM: 16MB

● FLASH: 8MB

● Color: Black

● Gift Box Dimensions: 302x105x167mm (L x W x H)

● Outer CTN Dimensions: 445x355x325 (20 PCS)